

PAVEMENT MARKING SCHEDULE													
STATION TO STATION	LOCATION	SIDE	DESCRIPTION	PREFORMED PLASTIC, TYPE B-INLAID					URETHANE PAVEMENT MARKING				
				LETTER SYMBOLS	5" WHITE	6" WHITE	8" WHITE	12" WHITE	24" WHITE	5" WHITE	5" YELLOW	6" WHITE	8" WHITE
				SQ. FT.	FOOT								
STA 249+57.25 TO 249+93.31	SBL	CL	SKIP DASH		36.1								
STA 249+61 TO 249+93.31	SBL	LT	SOLID							32.3			
STA 249+53 TO 249+93.31	SBL	RT	SOLID								40.3		
STA 249+93.31 = 1+53.03	EQUATION												
STA 1+53.03 TO 105+89.34	SBL	CL	SKIP DASH		2410.0								
STA 1+53.03 TO 19+10	SBL	LT	SOLID							1757.0			
STA 1+53.03 TO 54+21	SBL	RT	SOLID								5268.0		
STA 19+10 TO 22+50	SBL	LT	SOLID				340.0						
STA 19+10 TO 21+70	SBL/RAMP C		CHEVRONS					160.0					
STA 22+50 TO 25+71	SBL	LT	SKIP DASH			102.0							
STA 25+71.00 TO 54+49	SBL	LT	SOLID							2878.0			
STA 54+21 TO 54+71	SBL	RT	SOLID								55.0		
STA 54+49 TO 54+91	SBL		SOLID							87.0			
STA 54+89 TO 55+05.5	SBL	RT	STOP BAR					16.0					
STA 55+17 TO 55+60	SBL	LT	SOLID							74.0			
STA 55+39 TO 55+72	SBL	RT	SOLID								35.0		
STA 55+72 TO 57+90	SBL	RT	SOLID									218.0	
STA 55+72 TO 57+90	SBL	RT	SOLID								218.0		
STA 57+90 TO 60+10	SBL	RT	SKIP DASH			56.0							
STA 57+90 TO 60+10	SBL	RT	SOLID								220.3		
STA 55+60 TO 58+58	SBL	LT	SOLID							298.0			
STA 55+60 TO 58+58	SBL	LT	SOLID									298.0	
STA 58+58 TO 60+42	SBL	LT	SOLID							285.3			
STA 60+10 TO 105+89.34	SBL	RT	SOLID								4579.3		
STA 60+42 TO 105+89.34	SBL	LT	SOLID							4547.3			
STA 55+97 TO 57+90	SBL	RT	LT TURN ARROW(4)	62.4									
STA 55+85 TO 58+58	SBL	LT	RT TURN ARROW(5)	78.0									
STA 105+89.34 TO 108+89.34	SBL	LT	SOLID							300.0			
STA 105+89.34 TO 108+89.34	SBL	RT	SOLID								300.0		
STA 105+89.34 TO 108+89.34	SBL	CL	SKIP DASH							75.0			
STA 108+89.34 TO 344+00	SBL	CL	SKIP DASH		5880.0								
STA 108+89.34 TO 139+28	SBL	LT	SOLID							3038.7			
STA 139+28 TO 139+73	SBL	LT	SOLID							71.0			
STA 139+86 TO 140+52	SBL	LT	SOLID							105.0			
STA 140+52 TO 143+43	SBL	LT	SOLID							291.0			
STA 143+43 TO 145+38	SBL	LT	SOLID							199.3			
STA 140+52 TO 143+43	SBL	LT	SOLID									291.0	
STA 143+43 TO 145+38	SBL	LT	SKIP DASH			50.0							
STA 108+89.34 TO 139+81	SBL	RT	SOLID								3091.7		
STA 139+62 TO 139+81	SBL	RT	SOLID								31.0		
STA 140+35 TO 141+81	SBL	RT	SOLID								48.0		
STA 141+81 TO 143+83	SBL	RT	SOLID								202.0		
TOTAL				140.4	8326.1	208.0	340.0	160.0	16.0	14038.9	14088.6	807.0	
USE				141	8327	208	340	160	16	14039	14089	807.0	