

PAVEMENT MARKING SCHEDULE													
STATION TO STATION	LOCATION	SIDE	DESCRIPTION	PREFORMED PLASTIC, TYPE B-INLAID					URETHANE PAVEMENT MARKING				
				LETTER SYMBOLS	5" WHITE	6" WHITE	8" WHITE	12" WHITE	24" WHITE	5" WHITE	5" YELLOW	6" WHITE	8" WHITE
				SQ. FT.	FOOT								
STA 143+83 TO 145+90	SBL	RT	SKIP DASH			52.0							
STA 143+83 TO 145+90	SBL	RT	SOLID								207.3		
STA 141+81 TO 143+83	SBL	RT	SOLID									202.0	
STA 142+06 TO 143+83	SBL	RT	LT TURN ARROW(4)	62.4									
STA 140+77 TO 143+43	SBL	LT	RT TURN ARROW(5)	78.0									
STA 139+63 TO 140+13	SBL	LT	STOP BAR						50.0				
STA 145+38 TO 169+70	SBL	LT	SOLID							2432.0			
STA 169+70 TO 170+51	SBL	LT	SOLID							125.0			
STA 170+59 TO 171+10	SBL	LT	SOLID							104.0			
STA 171+10 TO 173+97	SBL	LT	SOLID							287.0			
STA 173+97 TO 176+97	SBL	LT	SOLID							300.3			
STA 171+10 TO 173+97	SBL	LT	SOLID									287.0	
STA 173+97 TO 176+97	SBL	LT	SKIP DASH			76.0							
STA 145+90 TO 168+47	SBL	RT	SOLID								2257.0		
STA 168+47 TO 169+00	SBL	RT	SOLID								60.0		
STA 170+51 TO 170+59	SBL	RT	SOLID								20.0		
STA 170+51 TO 172+66	SBL	RT	SOLID								215.0		
STA 172+66 TO 175+09	SBL	RT	SOLID								243.3		
STA 170+51 TO 172+66	SBL	RT	SOLID									215.0	
STA 172+66 TO 175+09	SBL	RT	SKIP DASH			62.0							
STA 170+04 TO 170+14	SBL	LT	STOP BAR						14.0				
STA 170+76 TO 172+66	SBL	RT	LT TURN ARROW(4)	62.4									
STA 171+35 TO 173+97	SBL	LT	RT TURN ARROW(5)	78.0									
STA 176+97 TO 292+85	SBL	LT	SOLID							11588.0			
STA 175+09 TO 213+27	SBL	RT	SOLID								3818.0		
STA 213+27 TO 213+75	SBL	RT	SOLID								53.0		
STA 214+45 TO 214+81	SBL	RT	SOLID								40.0		
STA 214+81 TO 218+04	SBL	RT	SOLID								323.0		
STA 218+04 TO 220+38	SBL	RT	SOLID								234.3		
STA 214+81 TO 218+04	SBL	RT	SOLID									323.0	
STA 218+04 TO 220+38	SBL	RT	SKIP DASH			60.0							
STA 215+06 TO 218+04	SBL		LT TURN ARROW(5)	78.0									
STA 220+38 TO 239+69	SBL	RT	SOLID								1931.0		
STA 239+69 TO 239+89	SBL	RT	SOLID								31.4		
STA 240+22 TO 240+42	SBL	RT	SOLID								31.4		
STA 240+42 TO 242+45	SBL	RT	SOLID								203.0		
STA 242+45 TO 244+54	SBL	RT	SOLID								209.3		
STA 240+42 TO 242+45	SBL	RT	SOLID									203.0	
STA 242+45 TO 244+54	SBL	RT	SKIP DASH			54.0							
STA 240+67 TO 242+45	SBL		LT TURN ARROW(4)	62.4									
STA 244+54 TO 255+58	SBL	RT	SOLID								1104.0		
STA 255+58 TO 255+78	SBL	RT	SOLID								31.4		
STA 255+98 TO 256+18	SBL	RT	SOLID								31.4		
STA 256+18 TO 258+22	SBL	RT	SOLID								204.0		
TOTAL				421.2		304.0			64.0	14836.3	11040.5	1230.0	
USE				422		304			64.0	14836	11041	1230	