

PAVEMENT MARKING SCHEDULE													
STATION TO STATION	LOCATION	SIDE	DESCRIPTION	PREFORMED PLASTIC, TYPE B-INLAID					URETHANE PAVEMENT MARKING				
				LETTER SYMBOLS	5" WHITE	6" WHITE	8" WHITE	12" WHITE	24" WHITE	5" WHITE	5" YELLOW	6" WHITE	8" WHITE
				SQ. FT.	FOOT								
STA 51+59 TO 54+24	NBL		RT TURN ARROW(5)	78.0									
STA 1+53.03 TO 49+94	NBL	LT	SOLID								4841.0		
STA 49+94 TO 52+20	NBL	LT	SOLID								226.3		
STA 52+20 TO 54+21	NBL	LT	SOLID								201.0		
STA 54+21 TO 54+71	NBL	LT	SOLID								55.0		
STA 52+20 TO 54+21	NBL	LT	SOLID									201.0	
STA 52+20 TO 53+96	NBL		LT TURN ARROW(3)	46.8									
STA 54+49 TO 54+95	NBL	RT	SOLID							70.0			
STA 55+05 TO 55+26	NBL	RT	STOP BAR SOLID						14.0				
STA 55+17 TO 55+61	NBL	RT	SOLID							82.0			
STA 55+39 TO 55+86	NBL	LT	SOLID								57.0		
STA 55+86 TO 105+89.34	NBL	LT	SOLID								5003.3		
STA 55+61 TO 105+89.34	NBL	RT	SOLID							5028.3			
STA 105+89.34 TO 108+89.34	NBL	RT	SOLID							300.0			
STA 105+89.34 TO 108+89.34	NBL	CL	SKIP DASH							70.0			
STA 105+89.34 TO 108+89.34	NBL	LT	SOLID								300.0		
STA 108+89.34 TO 344+00	NBL	CL	SKIP DASH		5870.0								
STA 108+89.34 TO 134+70	NBL	RT	SOLID							2580.7			
STA 134+70 TO 137+56	NBL	RT	SOLID							286.3			
STA 134+70 TO 137+56	NBL	RT	SKIP DASH			76.0							
STA 137+56 TO 140+52	NBL	RT	SOLID							296.0			
STA 140+52 TO 141+12	NBL	RT	SOLID							100.0			
STA 141+31 TO 141+81	NBL	RT	SOLID							100.0			
STA 108+89.34 TO 134+88	NBL	LT	SOLID								2598.7		
STA 134+88 TO 137+14	NBL	LT	SOLID								226.3		
STA 137+14 TO 139+17	NBL	LT	SOLID								203.0		
STA 137+56 TO 140+52	NBL	RT	SOLID									296.0	
STA 134+88 TO 137+14	NBL	LT	SKIP DASH			60.0							
STA 139+17 TO 139+62	NBL	LT	SOLID								50.0		
STA 137+14 TO 139+17	NBL	LT	SOLID			203.0							
STA 137+14 TO 138+92	NBL		LT TURN ARROW(4)	62.4									
STA 137+56 TO 140+27	NBL		RT TURN ARROW(5)	78.0									
STA 140+85 TO 141+31	NBL	RT	STOP BAR SOLID						54.0				
STA 141+18 TO 141+35	NBL	LT	SOLID								32.0		
STA 141+69 TO 162+64	NBL	RT	SOLID							2095.0			
STA 162+64 TO 165+62	NBL	RT	SOLID							298.3			
STA 165+62 TO 168+52	NBL	RT	SOLID							290.0			
STA 165+62 TO 168+52	NBL	RT	SOLID									290.0	
STA 162+64 TO 165+82	NBL	RT	SKIP DASH			76.0							
STA 168+52 TO 168+89	NBL	RT	SOLID							110.0			
STA 165+62 TO 168+27	NBL		RT TURN ARROW(5)	78.0									
STA 141+18 TO 164+71	NBL	LT	SOLID								2353.0		
STA 164+71 TO 166+98	NBL	LT	SOLID								227.3		
STA 166+98 TO 169+10	NBL	LT	SOLID								212.0		
STA 166+98 TO 169+10	NBL	LT	SOLID									212.0	
TOTAL				343.2	5870.0	415.0			68.0	11706.6	16585.9	999.0	
USE				344	5870	415			68	11707	16586	999	