

EARTHWORK SCHEDULE

LOCATION	EARTH EXCAVATION	EARTH EXCAVATION ADJ FOR SHRINKAGE (25%)	CHANNEL EXCAVATION	FURNISHED EXCAVATION	EARTHWORK BALANCE WASTE (+) OR SHORTAGE (-)
STATION TO STATION	CU YD	CU YD	CU YD	CU YD	CU YD
SECTION 1BR					
234+37.5 TO 235+00	3.0	2.3		138.4	-136.2
235+00 TO 235+50	4.3	3.2		257.6	-254.4
235+50 TO 236+00	3.9	2.9		244.2	-241.3
236+00 TO 236+50	14.9	11.2		102.1	-90.9
236+50 TO 236+50	6.8	5.1		32.4	-27.3
236+50 TO 236+55	0.7	0.5		11.9	-11.4
236+55 TO 237+45			940		0.0
237+45 TO 237+50	0.7	0.5		8.5	-8.0
237+50 TO 237+65	5.5	4.1		33.5	-29.3
237+65 TO 238+00	11.7	8.8		133.5	-124.7
238+00 TO 238+50	4.1	3.1		234.7	-231.7
238+50 TO 239+00	5.0	3.8		202.3	-198.6
239+00 TO 239+50	6.1	4.6		171.3	-166.7
239+50 TO 239+62.5	0.9	0.7		20.5	-19.8
TOTAL =	68	51	940	1591	-1540

PAVEMENT MARKING SCHEDULE

LOCATION	THERMOPLASTIC PAVEMENT MARKING SKIP-DASH CENTERLINE YELLOW - 4"	POLYUREA PAVEMENT MARKING TYPE I SKIP-DASH CENTERLINE YELLOW - 4"	TEMPORARY PAVEMENT MARKING - LINE 4"	PAVEMENT MARKING REMOVAL
STATION TO STATION	FOOT	FOOT	FOOT	SQ FT
233+15 TO 236+35	80		80	27
236+35 TO 237+65		30	30	10
237+65 TO 241+35	90		90	30
TOTAL =	170	30	200	67

SEE STANDARDS 781001 AND 780001 FOR PAVEMENT MARKING DETAILS.

TREE REMOVAL SCHEDULE

LOCATION			DIAMETER	
STATION	OFFSET (FT)	RT/LT	6" TO 15" (UNITS)	OVER 15" (UNITS)
234+85	30.4	LT	4	
234+89	30.4	LT		46
234+93	30.4	LT	8	
TOTAL =			12	46

EROSION CONTROL SCHEDULE

LOCATION	PERIMETER EROSION BARRIER	POTASSIUM FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	NITROGEN FERTILIZER NUTRIENT	MULCH, METHOD 2	SEEDING CLASS 2	STONE RIPRAP, CLASS A3 (SPECIAL)	FILTER FABRIC	TEMPORARY EROSION CONTROL SEEDING
	FOOT	POUND	POUND	POUND	ACRE	ACRE	SQ YD	SQ YD	POUND
NW QUADRANT							22	22	
NE QUADRANT							18	18	
SW QUADRANT							10	10	
SE QUADRANT							19	19	
STA 233+50 TO STA 234+37.5 LT	93	1	1	1	0.04	0.01			3
STA 233+50 TO STA 234+37.5 RT	90	1	1	1	0.04	0.01			3
STA 234+37.5 TO STA 235+00 LT	63	3	3	3	0.12	0.03			9
STA 234+37.5 TO STA 235+00 RT	63	2	2	2	0.08	0.02			6
STA 235+00 TO STA 235+50 LT	50	4	4	4	0.16	0.04			12
STA 235+00 TO STA 235+50 RT	50	3	3	3	0.12	0.03			9
STA 235+50 TO STA 236+00 LT	50	3	3	3	0.12	0.03			9
STA 235+50 TO STA 236+00 RT	50	3	3	3	0.12	0.03			9
STA 236+00 TO STA 236+55 LT	74	2	2	2	0.08	0.02			6
STA 236+00 TO STA 236+55 RT	86	3	3	3	0.12	0.03			9
STA 237+45 TO STA 238+00 LT	89	4	4	4	0.16	0.04			12
STA 237+45 TO STA 238+00 RT	84	3	3	3	0.12	0.03			9
STA 238+00 TO STA 238+50 LT	50	3	3	3	0.12	0.03			9
STA 238+00 TO STA 238+50 RT	50	3	3	3	0.12	0.03			9
STA 238+50 TO STA 239+00 LT	50	3	3	3	0.12	0.03			9
STA 238+50 TO STA 239+00 RT	50	4	4	4	0.16	0.04			12
STA 239+00 TO STA 239+50 LT	50	3	3	3	0.12	0.03			9
STA 239+00 TO STA 239+50 RT	50	3	3	3	0.12	0.03			9
STA 239+50 TO STA 239+62.5 LT	13	0	0	0	0.00	0.00			0
STA 239+50 TO STA 239+62.5 RT	13	0	0	0	0.00	0.00			0
STA 239+62.5 TO STA 240+50 LT	91	1	1	1	0.04	0.01			3
STA 239+62.5 TO STA 240+50 RT	91	1	1	1	0.04	0.01			3
TOTAL =	1350	50	50	50	2.00	0.50	69	69	150

ROW MARKERS SCHEDULE

LOCATION			FURNISHING & ERECTING RIGHT-OF-WAY MARKERS
STATION	OFFSET (FT)	RT/LT	EACH
232+75	44.79	LT	1
233+00	45.17	RT	1
233+75	59.95	LT	1
236+00	59.69	RT	1
240+00	60.96	LT	1
240+00	59.04	RT	1
241+00	46.12	LT	1
241+00	43.88	RT	1
TOTAL =			8

REMOVAL SCHEDULE

LOCATION	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	REMOVE SIGN PANEL TYPE 1	PAVEMENT REMOVAL
STATION TO STATION	SQ YD	SQ FT	SQ YD
234+37.5 TO 234+67.5	74		
		3	
		3	
236+35 TO 236+83.5			119
237+16.5 TO 237+65			119
		3	
		3	
126+92.5 TO 127+60	74		
TOTAL =	148	12	238