PA052 TOTAL SHEETS = 66

### CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS

CONSTRUCTION PLANS FOR

CHICAGO EXECUTIVE AIRPORT

PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS INCLUDING EXTENDING TAXIWAY L AND ADDITIVE ALTERNATE 1: CONSTRUCT BYPASS TAXIWAY L1

LOCAL AGENCY CONTACT INFORMATION

VILLAGE OF WHEELING - 847.459.2600 CITY OF PROSPECT HEIGHTS - 847.398.6700

CHICAGO EXECUTIVE AIRPORT


PROJECT PERMIT LOG


NPDES # VILLAGE PERMIT #

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

**APRIL 16, 2010** 







LOCATION MAP

SITE PLAN

### **IDOT STANDARDS**

602301-02 602411-01 602306-02 602601-02 602401-02 602701-02 602406-03 604001 - 03



JOINT UTILITY LOCATING

CALL J.U.L.I.E. FOR UTILITY INFORMATION AT 811

\09290-07\DRAW\SHEETS\COVER

65
5
£ 8
62
3 0
2 0
8
50
58
57
56
55
54
: 8
23
52
51
50
49
5 8
48
47
46
45
: 1
44
43
42
41
1 6
40
39
38
37
S
36
35
34
33
32
31
30
22
3 8
28
27
26
25
1
24
23
22
21
2 2
20
19
18
17
16
Ö
ì :
14
13
12
11
0.
5
9
8
7
6
5
4
ω
1 0
s
1
NUMBER
SHEE
\

2		AR800194
AS		AR800053
LS		AR800040
EACH	_	AR800026
EACH	REMOVE END SECTION	AR752900
EACH	RECONSTRUCT MANHOLE	AR751983
EACH	ADUST MANHOLE	AR751943
EACH	REMOVE IN ET	AR751900
HOVE	MANHOLE 6	AR751560
EACH	MANHOLE 5	AR751550
EACH	4	AR751540
1	REMOVE I NDERDRAIN	AR705000
F 5		AR705526
5 5		AR/01530
		AR701524
7		AR/UIDIO
; F		AR701512
1 4		AR620900
7	TAVEMENT MARKING-BLACK BOKUER	AR620525
2 2	PAVEMENT MARKING - WATERBORNE	AR020520
200	BAVEMENT MARKING - WA	A DE 20520
2 i	BILIMINIOUS TACK COA	A B603510
TAĐ	S PRIME CO	AR602510
ΥS	OVE PCC PAVEME	AR501900
EACH	TEST	AR501530
YS	PCC P	AR501510
NO	OMINO	AK403610
1	ZEWOVE	AD400010
۸5	DEMOVE	ABA01010
ΥS	REMOVE BITUMINOUS PAVEMENT	AR401900
ΛS	BITUMINOUS PAVEMENT MILLING	AR401650
TON	BITUMINOUS SURFACE COURSE	AR401610
SY	CRUSHED AGG. BASE COURSE - 18"	AR209618
2	07.001.000.000.000.000.000.000.000.000.0	A D200646
\ \ \	CRUSHED AGG BASE COURSE - 6"	AR209606
СХ	POROUS GRANULAR EMBANKMENT	AR208515
EACH	REMOVE ELECTRIC GATE	AR162908
EACH	REMOVE GATE	AR162905
7	CLASS E FENC	AKI 62900
1 2	0 00 1 11 10	A DA COCOCO
HOVE		Δ <b>R</b> 162720
두		AR162506
EACH		AR156520
EACH	DIICH CHECK	AK156511
2 5		A D4 50544
-		A D4 E6E40
YS	SOIL STABILIZATION FABRIC	AR152540
CY	UNCLASSIFIED EXCAVATION	AR152410
LS		AR150520
S		AR150510
MAA		AK125947
200		A D4 DE0 47
HOAR		AR125942
HOAB	ADJUST STAKE MOUNTED LIGHT	AR125941
EACH	REMOVE SPLICE CAN	AR125906
EACH	REMOVE TAXI GUIDANCE SIGN	AR125904
2 2	SENOVE GLOVE MODIFIED FIGURE	AD405004
HOAR	BEMOVE STAKE MOLINTED LIGHT	AR125901
EACH	E CA	AR125565
EACH	INPA)	AR125525
EACH	HIRL, BASE MOUNTED	AR125515
EACH	TAXI GUIDANCE SIGN, 7 CHARACTER	AR125447
EACH	TAX GUIDANCE SIGN, 6 CHARACTER	AR125446
FACH	IAX GUIDANCE SIGN, 5 CHARACTER	AK125445
2 2	TAX OCIDANCE GIGIN, 4 CIRCACCIER	77125444
T (	TAY CHIDANCE SIGN 4 CHARACTER	V D4 3E 444
HOA	TAXI GUIDANCE SIGN 2 CHARACTER	AR125442
HOAH	MITI - BASE MOLINTED	AR125415
EACH		AR1 10907
EACH		AR1 10906
-TF		AR1 10900
HOAH		AR1 10610
LF	_	AR1 10550
F	CONCRETE ENCASED DUC	AK110504
; F	CONCRETE ENCASED DUC	AKI 1050Z
, c	CONCETE O	A D4 4 0 E 0 2
, n	STREET DIGT INCKED	A D4 4 0 3 4 3
n	- 1	AB440343
ЭĪ		AR1 10204
나	2" PVC DUCT, DIRECT BURY	AR1 10202
EACH	30 KW REGULATOR, STYLE 1	AR109361
ᄕ	50 PAIR CONTROL CABLE	AR108850
5		AKIU88Ub
		A D4 00000
F		AR108758
뉴		AR108108
Л		AR108084
UNIT	DESCRIPTION	TEM NO.
	!	
SE BID	유	
!	2	
	### ### ### ### ### ### ### ### ### ##	DESCRIPTION  10.24 ALP-JISE  10.24 SERVIJG CABLE 10.24 SERVIJG CABLE 20 AWA REGULATOR, STYLE 1 27 PVC DUCT, DIRECT BURY 27 STEEL DUCT, DIRECT BURY 28 SECONDER SIGN, 5 CHARACTER 29 LUCE CAN 29 SECONDER SIGN, 5 CHARACTER 29 LUCE CAN 20 SECONDER SIGN, 5 CHARACTER 20 SECONDER SIGN,

2	D C C	MULCHING	A.S908510
2	ACRE	SEEDING	AS901510
2	EACH	L-804 RGL ELEVATED, BASE MOUNTED	AS800816
1,100	SY	SOIL GUARD	AS800053
460	LF	REMOVE UNDERDRAIN	AS705900
780	두	6" PERFORATED UNDERDRAIN W/ SOCK	AS705526
25	LF	REMOVE PIPE	AS701900
25	LF	18" RCP, CLASS IV	AS701518
1,450	SF	PAVEMENT MARKING REMOVAL	AS620900
2,760	SF	PAVEMENT MARKING-BLACK BORDER	AS620525
3,300	SF	PAVEMENT MARKING - WATERBORNE	AS620520
295	GAL	BITUMINOUS TACK COAT	AS603510
485	GAL	BITUMINOUS PRIME COAT	AS602510
1,465	SY	10" PCC PAVEMENT	AS501510
305	TON	BITUMINOUS BASE COURSE	AS403610
30	SY	REMOVE & REPLACE BIT. PAVEMENT	AS401910
305	TON	BITUMINOUS SURFACE COURSE	AS401610
1,385	SY	CRUSHED AGG. BASE COURSE - 18"	AS209618
1,565	SY	CRUSHED AGG. BASE COURSE - 6"	AS209606
990	CY	POROUS GRANULAR EMBANKMENT	AS208515
4	EACH	INLET PROTECTION	AS156520
1,400	LF	SILT FENCE	AS156510
2,950	SY	SOIL STABILIZATION FABRIC	AS152540
2,210	CY	UNCLASSIFIED EXCAVATION	AS152410
	EACH	RELOCATE TAXI GUIDANCE SIGN	AS125964
	EACH	REMOVE TAXI GUIDANCE SIGN	AS125904
	EACH	REMOVE BASE MOUNTED LIGHT	AS125902
	EACH	SPLICE CAN	AS125565
	EACH	HIRL, INPAVEMENT	AS125525
	EACH	TAXI GUIDANCE SIGN, 7 CHARACTER	AS125447
	EACH	TAXI GUIDANCE SIGN, 5 CHARACTER	AS125445
2	EACH	TAXI GUIDANCE SIGN, 4 CHARACTER	AS125444
2	EACH	TAXI GUIDANCE SIGN, 3 CHARACTER	AS125443
22	EACH	MITL - BASE MOUNTED	AS125415
2	EACH	ELECTRICAL HANDHOLE	AS110610
70	ᄕ	4WAY CONCRETE ENCASED DUCT	AS110504
255	ᄕ	2" STEEL DUCT, DIRECT BURY	AS110212
1,950	LF	2" PVC DUCT, DIRECT BURY	AS110202
2,805	두	1/C #8 5KV UG CABLE	AS108108
QUANTITY	UNIT	DESCRIPTION	ITEM NO.

SHEET	ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44	JOB No:	DATE:	APPROVED BY:	CHECKED BY:	DRAWN BY:	DESIGN BY:
2	S PRO			BY:	BY:	r:	∺
OF	DUECT:						_
66	PWK	09290-07	04/16/10	MLK	SMS	СМТ	MLK / SMS
SHEETS	–3991 118–B44	)—07	5/10	.K	1S	4T	' SMS

DESIGN BY:	© Copyright CMT,  CMT  CRAWFORD, MURPHY & TILLY, II  CONSULTING ENGINEERS  License No. 184-000613
_	


CHICAGO EXECUTIVE AIRPORT
WHEELING/PROSPECT HEIGHTS, ILLINOIS
PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS
AND EXTEND TAXIWAY LIMA


	INDEX TO	SH	HEETS
AND	SUMMARY	OF	QUANTITIES


THIS B. AT FU	0			NUMBER	
THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).	1			ВҮ	REVISIONS
TO 2" 4X22).	2			DATE	0,

¥	DAT	SL	Ç	5	FIL	
XREF DWG: tbcInt-con2.dwg	DATE: Friday, April 16, 2010 11:53:32 AM	SURVEY BOOK #	UPDATE BY: Marc Katz	LAYOUT: Layout1	FILE: Index.dwg	7

INDEX TO SHEETS







### PHASING NOTES (ALL PHASES)

- THE INTENT OF THE PHASING PLANS IS TO MINIMIZE THE IMPACT OF CONSTRUCTION ON THE OPERATION OF THE AIRPORT. THE CONTRACTOR SHALL CONSTRUCT THE PROJECT IN CONSECUTIVE PHASES AS OUTLINED IN THE PLANS
- PRIOR TO REOPENING A CLOSED RUNWAY THE ENTIRE RUNWAY SAFETY AREA (200 FEET FROM CENTERLINE) MUST MEET FAA CRITERIA. FAA CRITERIA REQUIRES THAT THERE BE NO OPEN EXCAVATIONS OR TRENCHES, THE MAXIMUM PAVEMENT DROPOFF BE 3 INCHES, AND ALL GRADES IN ANY DIRECTION BE LESS THAN 5 PERCENT. TEMPORARY WEDGING OF BASE COURSE AND BITUMINOUS CONCRETE WILL BE REQUIRED TO MEET CRITERIA.
- THE CONTRACTOR SHALL SUBMIT A CONSTRUCTION SCHEDULE. STRICT ADHERENCE TO THE APPROVED SCHEDULE WILL BE ENFORCED TO AVOID CONFLICTS WITH OTHER CONSTRUCTION ACTIVITIES ON THE AIRPORT AND THE ADVERSE EFFECTS THEY COULD HAVE ON AIRPORT OPERATIONS.
- THE CONTRACTOR SHALL COORDINATE CLOSELY WITH THE AIRPORT STAFF TO SCHEDULE THE RUNWAY/TAXIWAY CLOSURES. ITEMS SUCH AS THE EXTENDED WEATHER FORECAST, MATERIAL AVAILABILITY, EQUIPMENT DEPENDABILITY AND MANPOWER AVAILABILITY SHALL BE DISCUSSED PRIOR TO SCHEDULING THESE CRITICAL CLOSURES. THE ACTING AIRPORT MANAGER AND THE CONTRACTOR SHALL MUTUALLY AGREE ON THE EXACT DATE OF THE CLOSURE.
- CONTRACTOR MUST MAINTAIN ACCESS TO ALL APRON/HANGAR AREAS AT ALL TIMES. CONTRACTOR SHALL RELOCATE EQUIPMENT AT NO ADDITIONAL COST TO THE CONTRACT TO ALLOW AIRCRAFT TO PASS. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION OPERATIONS AT ALL APRON/HANGAR AREAS TO

### LIQUIDATED DAMAGES (ALL PHASES)

- BECAUSE OF THE CRITICAL LIMITATIONS WHICH THE CLOSURE OF RUNWAY 16/34 OF \$2500 WILL BE DEDUCTED FROM THE MONIES OWED THE CONTRACTOR FOR EACH HALF HOUR OVER 6:00 AM UNTIL SPECIFIED WORK IS COMPLETED AND THE RUNWAY IS REOPENED TO AIRCRAFT TRAFFIC. DAMAGES MAY STARTING AT 6:01 AM ON ANY DAY THE RUNWAY IS NOT REOPENED. DAMAGES MAY BE ASSESSED
- A MAXIMUM OF FIVE (5) CLOSURES ON RUNWAY 16/34 WILL BE ALLOWED. RUNWAY CLOSURES, NIGHTIME (10 PM - 6 AM). SEE SEQUENCE OF CONSTRUCTION GENERAL NOTES FOR DETAILS ON RUNWAY CLOSURES. FOR EVERY ADDITIONAL RUNWAY 16/34 CLOSURE REQUIRED BY THE CONTRACTOR LIQUIDATED DAMAGES IN THE AMOUNT OF \$2,500 WILL BE ASSESSED.

### PHASE 1A: SUGGESTED SEQUENCE OF CONSTRUCTION

- AIR OPERATIONS AREA (A.O.A.) WITH LATHE AND RIBBON AND PLACE BARRICADES AS SHOWN OR AS DIRECTED BY THE ENGINEER
- COORDINATE CLOSURE OF RUNWAY 6/24 WITH RESIDENT ENGINEER, PLACE CLOSED RUNWAY MARKERS AND BARRICADES.
- REMOVE EXISTING PAVEMENTS AND BUILDINGS WITHIN LIMIT SHOWN.
- CONSTRUCT PROPOSED IMPROVEMENTS. INCLUDING PAVING. JOINT SEALING. PAVEMENT MARKING, ELECTRICAL AND SAFETY GRADING FOR PHASE 1A LIMITS.
- · CLEAN PAVEMENTS AND REMOVE BARRICADES.
- OPEN RUNWAY 6/24.

### PHASE 1B: SUGGESTED SEQUENCE OF CONSTRUCTION

- PHASE 1B SHALL NOT COMMENCE UNTIL THE COMPLETION OF TAXIWAY B WITHIN THE PHASE 1A AND PHASE 3 LIMITS.
- COORDINATE CLOSURE OF RUNWAY 6/24 WITH RESIDENT ENGINEER; MARK AIR OPERATIONS AREA (A.O.A.) WITH LATHE AND RIBBON. PLACE CLOSED RUNWAY MARKER AND BARRICADES AS SHOWN OR AS DIRECTED BY THE RESIDENT
- REMOVE ENTRANCE AND TEMPORARY PAVEMENT TO HANGAR 4. CONSTRUCT NORTH FILLET OF TAXIWAY L WITH RUNWAY 6/24, INCLUDING PAVING, PAVEMENT MARKING, ELECTRICAL AND SAFETY AREA GRADING.
- . MILL AND OVERLAY HANGAR 4 APRON. WORK TO BE COMPLETED OVERNIGHT ONLY
- · CLEAN PAVEMENTS AND REMOVE BARRICADES. OPEN RUNWAY 6/24.

### PHASE 2: SUGGESTED SEQUENCE OF CONSTRUCTION

- COORDINATE PARTIAL CLOSURE OF TAXIWAY L WITH RESIDENT ENGINEER.
- AIR OPERATIONS AREA (A.O.A.) WITH LATHE AND RIBBON AND PLACE BARRICADES AS SHOWN OR AS DIRECTED BY THE ENGINEER.
- CONSTRUCT PROPOSED IMPROVEMENTS, INCLUDING PAVING, JOINT SE PAVEMENT MARKING, ELECTRICAL AND SAFETY GRADING FOR PHASE 2 LIMITS.
- · CLEAN PAVEMENTS AND REMOVE BARRICADES.

### **DETAIL "A" NOTES**

- EXPAND ENTRANCE TAXIWAY AND EXTEND EXISTING CULVERT AS REQUIRED PRIOR TO BEGINNING WORK IN PHASE 1A. PAYMENT FOR TEMPORARY BITUMINOUS PAVEMENT SHALL BE MADE AT THE UNIT PRICES FOR LIKE ITEMS. THE CULVERT EXTENSION SHALL BE INCIDENTAL TO THE CONTRACT.
- THE TEMPORARY PAVEMENT STRUCTURE SHALL CONSIST OF 2-INCH BITUMINOUS SURFACE COURSE (AR401), 2-INCH BITUMINOUS BASE COURSE (AR403) AND 7-INCH CRUSHED AGGREGATE BASE COURSE (AR209607). FILL REQUIRED UNDER PAVEMENT SHALL BE PGE (AR208515). GRADE SHOULDER FILL TO MEET EXISTING GRADE AT 5% MAXIMUM SLOPE. THE PAVEMENT SLOPE SHALL NOT EXCEED 1.5% IN THE DIRECTION OF DRAINAGE.

PHASE 1A WORK AREA PHASE 1B WORK AREA PHASE 2 WORK AREA AIRCRAFT MOVEMENT AREA BARRICADE WITH FLASHING LIGHTS AND SIGNS PHASE 1 ("DO NOT ENTER" AND "AIRCRAFT MOVEMENT AREA") BARRICADE WITH FLASHING LIGHTS AND SIGNS PHASE 2 ("DO NOT ENTER" AND "AIRCRAFT MOVEMENT AREA") AIR OPERATIONS AREA (A.O.A.) ACTIVE RUNWAYS 200' CENTERLINE TO A.O.A. ACTIVE TAXIWAYS 72' CENTERLINE TO A.O.A. TEMPORARY CLOSED RUNWAY MARKER

### REVISIONS BY NUMBER DATE ARM 8/02/06

PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheet

LAYOUT: Lavout1 UPDATE BY: iohse SURVEY BOOK #

FILE: phasing-1&2.dwg

DATE: Thu 4/15/10 1:20pm

XREF DWG: taxiway-base-con2.dwa

topo-txy-L.DWG

HIS BAR IS EQUAL TO 2 AT FULL SCALE (34X22)

OVEN

ō

шε

CHICAC ELING/F RUNWA

2

ш

AIRP(GHTS,

EXECUTIVE

SE

Z

20

NST /537 PHA

<u>0</u>60.

a

Ш

S

ES

ΩĞ

### PHASE 1 NOTES

**LEGEND** 


AIRCRAFT SHALL NOT USE NEW P.C. CONCRETE PAVEMENTS UNTIL 3,500 PSI COMPRESSIVE STRENGTH HAS BEEN OBTAINED.

CONTRACTOR'S ACCESS/HAUL ROAD

- 2. THE REMOVAL OF THE EXISTING ENTRANCE TO HANGAR 4 SHALL NOT OCCUR UNTIL THE COMPLETION OF THE NEW TAXIWAY B FROM RUNWAY 16/34 TO THE HANGAR 4 APRON AND THE PCC PAVEMENT HAS REACHED SUFFICIENT CONTROLL FOR TAXEFOCKING.
- 3. THE CONTRACTOR SHALL ENSURE THAT ADEQUATE ACCESS TO HANGAR 4 IS AVAILABLE AT ALL TIMES.
- 4. PRIOR TO BEGINNING CONSTRUCTION OF PHASE 1A. REMOVE THE EXISTING TAXIWAY CENTERLINE STRIPE INCLUDING TANGENT SECTIONS ON RUNWAY 6/24 AND PAINT A NEW 12" WIDE, REFLECTIVE YELLOW TAXIWAY CENTERLINE STRIPE N ACCORDANCE WITH DETAIL "A", THIS SHEET.
- 5. THE MILL AND OVERLAY OF THE HANGAR 4 APRON SHALL OCCUR AT NIGHT ONLY. THE CONTRACTOR SHALL BE REQUIRED TO REPLACE ALL AREAS MILLED BEFORE REOPENING THE PAVEMENT IN THE MORNING TO AIRCRAFT TRAFFIC. WORK SHALL BE COORDINATED A MINIMUM OF 5 WORKING DAYS IN ADVANCE WITH HANGAR TENANTS.
- 6. AT THE CONTRACTOR'S OPTION, PHASES 1 AND 3 MAY BE CONCURRENT. PHASES 1 AND 2 SHALL NOT BE CONCURRENT WITHOUT THE APPROVAL OF

### PHASE 2 NOTES

- AIRCRAFT SHALL NOT USE NEW P.C. CONCRETE PAVEMENTS UNTIL 3,500 PSI COMPRESSIVE STRENGTH HAS BEEN OBTAINED.
- THE CONTRACTOR SHALL CONSTRUCT A HAUL ROUTE OF HIS OWN DESIGN TO ACCESS THE SITE FROM WOLF ROAD. CONSTRUCTION OF THE HAUL ROUTE INCLUDING CULVERTS FOR DITCH CROSSINGS SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. THE LOCATION OF THE HAUL ROUTE SHALL BE
- 3. AT TIMES, AIRCRAFT MAY BE REQUIRED TO EXECUTE A TURNAROUND ON TAXIWAY LIMA. THE CONTRACTOR SHALL ENSURE THAT HIS PERSONNEL ARE CLEAR OF TAXIWAY LIMA AT ALL TIMES.
- AT THE CONTRACTOR'S OPTION, PHASES 2 AND 3 MAY BE CONCURRENT. PHASES 1 AND 2 SHALL NOT BE CONSTRUCTED CONCURRENTLY WITHOUT THE APPROVAL OF THE AIRPORT MANAGER



DETAIL "A" - NOT TO SCALE

DRAWN BY

DATE:

CHECKED BY

8 CRAWFO 25 SMS

APPROVED BY: 04/16/10


CMT

SMS

MLK

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 5 OF 66 SHEETS



### PHASING NOTES (ALL PHASES)

- 1. THE INTENT OF THE PHASING PLANS IS TO MINIMIZE THE IMPACT OF CONSTRUCTION ON THE OPERATION OF THE AIRPORT. THE CONTRACTOR SHALL CONSTRUCT THE PROJECT IN CONSECUTIVE PHASES AS OUTLINED IN THE PLANS UNLESS OTHERWISE APPROVED BY THE ENGINEER.
- 2. PRIOR TO REOPENING A CLOSED RUNWAY, THE ENTIRE RUNWAY SAFETY AREA (200 PRIOR TO REOPENING A CLOSED RUNWAY, THE ENTIRE RUNWAY SAFELY AREA (2200 FEET FROM CENTERLINE) MUST MEET FAA CRITERIA, FAA CRITERIA FAO LITERIA REQUIRES THAT THERE BE NO OPEN EXCAVATIONS OR TRENCHES, THE MAXIMUM PAVEMENT DROPOFF BE 3 INCHES, AND ALL GRADES IN ANY DIRECTION BE LESS THAN 5 PERCENT. TEMPORARY WEDGING OF BASE COURSE AND BITUMINOUS CONCRETE WILL BE REQUIRED TO MEET CRITERIA.
- 3. THE CONTRACTOR SHALL SUBMIT A CONSTRUCTION SCHEDULE. STRICT ADHERENCE TO THE APPROVED SCHEDULE WILL BE ENFORCED TO AVOID CONFLICTS WITH OTHER CONSTRUCTION ACTIVITIES ON THE AIRPORT AND THE ADVERSE EFFECTS THEY COULD HAVE ON AIRPORT OPERATIONS.
- THE CONTRACTOR SHALL COORDINATE CLOSELY WITH THE AIRPORT STAFF TO SCHEDULE THE RUNWAY/TAXIWAY CLOSURES. ITEMS SUCH AS THE EXTENDED WEATHER FORECAST, MATERIAL AVAILABILITY, EQUIPMENT DEPENDABILITY AND MANPOWER AVAILABILITY SHALL BE DISCUSSED PRIOR TO SCHEDULING THESE CRITICAL CLOSURES. THE ACTING AIRPORT MANAGER AND THE CONTRACTOR SHALL MUTUALLY AGREE ON THE EXACT DATE OF THE CLOSURE.
- 5. CONTRACTOR MUST MAINTAIN ACCESS TO ALL APRON/HANGAR AREAS AT ALL TIMES. CONTRACTOR SHALL RELOCATE EQUIPMENT AT NO ADDITIONAL COST TO THE CONTRACT TO ALLOW AIRCRAFT TO PASS. THE CONTRACTOR SHALL COORDINATE CONSTRUCTION OPERATIONS AT ALL APRON/HANGAR AREAS TO PROVIDE MINIMAL DISRUPTIONS TO AIRCRAFT MOVEMENT IN THAT AREA.

### LIQUIDATED DAMAGES (ALL PHASES)


- BECAUSE OF THE CRITICAL LIMITATIONS WHICH THE CLOSURE OF RUNWAY 16/34 PLACES ON THE USERS OF THE AIRPORT, LIQUIDATED DAMAGES IN THE AMOUNT OF \$2500 WILL BE DEDUCTED FROM THE MONIES OWED THE CONTRACTOR FOR EACH HALF HOUR OVER 6:00 AM UNTIL SPECIFIED WORK IS COMPLETED AND THE RUNWAY IS REOPENED TO AIRCRAFT TRAFFIC. DAMAGES MAY BE ASSESSED STARTING AT 6:01 AM ON ANY DAY THE RUNWAY IS NOT REOPENED.
- 2. A MAXIMUM OF FIVE (5) CLOSURES ON RUNWAY 16/34 WILL BE ALLOWED. RUNWAY CLOSURES, NIGHTIME (10 PM — 6 AM). SEE SEQUENCE OF CONSTRUCTION GENERAL NOTES FOR DETAILS ON RUNWAY CLOSURES. FOR EVERY ADDITIONAL RUNWAY 16/34 CLOSURE REQUIRED BY THE CONTRACTOR LIQUIDATED DAMAGES IN THE AMOUNT OF \$2,500 WILL BE ASSESSED.

### PHASE 3: SUGGESTED SEQUENCE OF CONSTRUCTION

- COORDINATE TEMPORARY NIGHTTIME CLOSURE OF RUNWAY 16/34 WITH THE ENGINEER AND PLACE CLOSED RUNWAY MARKERS.
- PLACE BARRICADES AS SHOWN OR AS DIRECTED BY THE RESIDENT ENGINEER FOR PHASE 3 LIMITS.
- CONSTRUCT PROPOSED IMPROVEMENTS WITHIN PHASE 3 LIMITS, INCLUDING BITUMINOUS PAVEMENT CONSTRUCTION, GRADING, PAVEMENT MARKING, ELECTRICAL AND TURFING
- CLEAN ALL PAVEMENTS AND REMOVE PHASE 3 BARRICADES
- OPEN RUNWAY 16/34

### PHASE 3 NOTES

- THE CONTRACTOR SHALL CONSTRUCT A HAUL ROUTE OF HIS OWN DESIGN TO ACCESS THE SITE FROM WOLF ROAD. CONSTRUCTION OF THE HAUL ROUTE INCLUDING CULVERTS FOR DITCH CROSSINGS SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT THE LOCATION OF THE HAUL ROUTE SHALL BE APPROVED BY THE RESIDENT ENGINEER PRIOR TO CONSTRUCTING THE HAUL ROTE.
- 2. AT THE CONTRACTOR'S OPTION, PHASE 3 MAY BE CONCURRENT WITH PHASES 1 OR 2.
- 3. AT THE COMPLETION OF WORK EACH MORNING, THE BARRICADES NOT REQUIRED BY OTHER PHASES UNDER CONSTRUCTION AT THE SAME TIME SHALL BE REMOVED AND THE PAVEMENTS SWEPT AND REOPENED. BARRICADES REQUIRED IN THE NEAR FUTURE MAY BE PLACED OFF TO THE SIDE PROVIDED THEY ARE STACKED NEATLY OUTSIDE OF THE AOA AT A LOCATION APPROVED BY THE RESIDENT ENGINEER. THE HEIGHT OF THE STACK OF BARRICADES SHALL NOT EXCEED TWO
- 4. THE CONTRACTOR SHALL ENTER AND EXIT THE FIELD AT THE LOCATIONS SHOWN DEPENDING ON THE WORK AREA. AT NO TIME SHALL HE USE RUNWAY 16/34 AS
- 5. ANY DAMAGE CAUSED BY CONTRACTOR HAUL OPERATIONS OVER EXISTING AIRFIELD PAVEMENTS SHALL BE REPAIRED BY THE CONTRACTOR AT NO COST TO THE



ITS, ILLINOIS SA IMPROVEMENT: Y LIMA IRUCTION 70-2E PHASE 3 STI 377 EXECUTIVE OSPECT HEIG T HEIGOFA/I E OF CONS AC 150/5( EDITION) CHICAGO EXECUT WHEELING/PROSPECT E 2 - RUNWAY 16/34 O AND EXTEND TA ENCE PER 'EST 回回 ō Ш SE S MURPHY & ENGINEERS CRAWFORT DESIGN BY: MJS DRAWN BY JRO CHECKED BY SMS APPROVED BY MLK DATE 04/16/10 JOB No

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44 SHEET 6 OF 66 SHEETS

CLA

tbcInt-con2.dwg topo-txy-L.DWG

REVISIONS

BY

ARM

DATE

8/02/06

### **GENERAL NOTES**

- THE SUGGESTED SEQUENCE OF CONSTRUCTION SHOWN IS INTENDED TO ALLOW FOR THE ORDERLY CONSTRUCTION OF THE PROPOSED IMPROVEMENTS WHILE MAINTAINING AIRCRAFT ACCESS AT ALL TIMES. THE PHASING SHOWN IS A SUGGESTED SEQUENCE OF CONSTRUCTION ONLY. THIS SEQUENCE MAY BE MODIFIED HOWEVER, ALTERNATE STAGING PLANS MUST MAINTAIN AIRPORT OPERATIONS TO THE SATISFACTION OF THE AIRPORT MANAGER AND RESIDENT ENGINEER AND BE APPROVED BY THE DIVISION OF AERONAUTICS AND FEDERAL AVIATION ADMINISTRATION.
- 2. ALL OPERATIONS SHALL BE IN CONFORMANCE WITH AC 150/5370-2E (LATEST EDITION) SAFETY DURING CONSTRUCTION.
- 3. CONTRACTOR'S EQUIPMENT SHALL BE STORED IN THE EQUIPMENT AND MATERIAL STORAGE/STAGING AREA WHEN CONSTRUCTION IS NOT IN PROGRESS.
- 4. THE AIRPORT MANAGER IN CONSULTATION WITH THE RESIDENT ENGINEER SHALL HAVE FINAL THE APPROVAL OF THE CONSTRUCTION OPERATING SEQUENCE AS IT RELATES TO PEDESTRIAN. VEHICULAR AND AIRCRAFT SAFFTY
- 5. ALL EXISTING PAVEMENTS, DRIVES OR ANY OTHER AREAS USED AS A HAUL ROAD OR STORAGE AREA BY THE CONTRACTOR SHALL BE RESTORED IN KIND TO THEIR PRE—CONSTRUCTION CONDITION OR TO THE SATISFACTION OF THE RESIDENT ENGINEER, AIRPORT MANAGER AND VILLAGE OF WHEELING DIRECTOR OF PUBLIC WORKS. THE COST OF MAINTAINING, REPAIRING OR CONSTRUCTING THESE PAVEMENTS AND AREAS SHALL BE INCIDENTAL TO THE CONTRACT. EXISTING AREAS OUTSIDE THE PROJECT LIMITS WHICH ARE DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED BY HIM AT HIS EXPENSE TO THE SATISFACTION OF THE RESIDENT ENGINEER AND THE AIRPORT MANAGER.
- 6. THE CONTRACTOR SHALL KEEP ALL TRUCKS, EQUIPMENT AND MATERIALS OFF OF THE EXISTING TAXIMAYS, APRONS AND RUNWAYS OUTSIDE OF THE PROJECT LIMITS EXCEPT AS SHOWN OR WITH THE PRIOR PERMISSION OF THE ENGINEER.
- WORK PERFORMED BY THE CONTRACTOR OUTSIDE OF DAYLIGHT HOURS SHALL BE DONE UNDER SUFFICIENT ARTIFICIAL LIGHTING TO ALLOW FOR PROPER CONSTRUCTION METHODS AND INSPECTIONS. LIGHT SHALL CONSIST OF MOVABLE POLE MOUNTED FLOODLIGHTS AND/OR SPOTLIGHTS OF SUFFICIENT NUMBER TO ILLUMINATE THE WORK AREA. VEHICLE HEADLIGHTS WILL BE ALLOWED ONLY IN ADDITION TO OTHER LIGHTS MENTIONED ABOVE. LIGHTING SHALL BE AS APPROVED BY THE ENGINEER AND SHALL NOT BE USED IF THEY AFFECT FLIGHT SAFETY. CONTRACTOR'S WORK HOURS SHALL BE IN
- 8 THE CONTRACTOR SHALL PROVIDE PORTABLE FLOOD LIGHTING FOR NIGHTTIME CONSTRUCTION SUFFICIENT UNITS SHALL BE PROVIDED SO THAT WORK AREAS ARE ILLUMINATED TO A LEVEL OF FIVE HORIZONTAL FOOT CANDLES. THE LIGHTING LEVELS SHALL BE CALCULATED AND MEASURED IN ACCORDANCE WITH THE CURRENT STANDARDS OF THE ILLUMINATION ENGINEERING SOCIETY. LIGHTS SHALL BE POSITIONED SO AS NOT TO INTERFERE WITH AIRPORT OPERATIONS.
- THE CONTRACTOR WILL BE REQUIRED TO HAVE A SWEEPER AVAILABLE FOR USE AT ALL TIMES. WHEN ACTIVE AIRFIELD PAVEMENTS ARE UTILIZED AS HAUL ROADS BY THE CONTRACTOR, MATERIAL TRACKED ON TO THE PAVEMENT SHALL BE CONTINUALLY REMOVED WITH SAID SWEEPER. THIS SWEEPING SHALL NOT BE PAID FOR SEPERATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.
- 10. MATERIALS REMOVED FROM THE PROJECT WILL BE DISPOSED OF OFF AIRPORT PROPERTY UNLESS
- 11. PAYMENT FOR TRAFFIC CONTROL INCLUDING, BUT NOT LIMITED TO BARRICADES, SIGNING, RUNWAY CLOSED MARKERS, AIR OPERATIONS AREA (A.O.A.) LATHE AND RIBBON, ETC. SHALL NOT BE PAID SEPARATELY, BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. BARRICADES AT 10-FOOT CENTERS WITH ONE ORANGE FLAG (24" x 24") BETWEEN EACH SET OF BARRICADES SHALL BE PLACED AT THE LOCATIONS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER. BARRICADES SHALL BE WEIGHTED TO PREVENT BLOWING OVER. BARRICADES SHALL HAVE A FLASHING RED LICHT AND CONFORM TO IDOT STANDARD 702001, TYPE II. BARRICADE INSTALLATION WILL BE REQUIRED PRIOR TO ACCESS TO THE A.O.A. BY CONTRACTOR'S WORKERS, EQUIPMENT OR MATERIAL. SIGNS SHALL BE PLACED AT EACH TAXIWAY/RUNWAY CLOSURE LOCATION AND SHALL BE ATTACHED TO THE BARRICADES. EACH BARRICADE LOCATION SHALL CONSIST OF ONE "DO NOT ENTER" SIGN AND ONE "AIRCRAFT MOVEMENT AREA" SIGN. SIGNS SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. IN CONJUNCTION WITH IDOT TYPE II BARRICADES, THE CONTRACTOR SHALL SUPPLY AND USE AS DIRECTED BY THE AIRPORT, REFLECTIVE LOW PROFILE BARREL TYPE BARRICADES.
- 12. THE CONTRACTOR SHALL CONTACT THE AIRPORT MANAGER TEN (10) WORKING DAYS IN ADVANCE OF THE START OF CONSTRUCTION SO THAT THE APPROPRIATE NOTAMS MAY BE ISSUED.
- 13. THE CONTRACTOR SHALL BE RESPONSIBLE FOR KEEPING ALL CONSTRUCTION ACCESS GATES CLOSED DURING NON WORKING HOURS. THE CONTRACTOR SHALL PROVIDE A SIGN AT THE ACCESS GATE SAYING "AUTHORIZED PERSONNEL ONLY". THE CONTRACTOR SHALL CLOSE AND LOCK THE ACCESS GATE UPON LEAVING THE SITE. THROUGHOUT THE DURATION OF THE CONTRACT, ANY DAMAGES TO THE ACCESS ROAD, ACCESS GATE OR FENCING ADJACENT TO THE PROJECT SHALL BE REPAIRED BY THE CONTRACTOR TO THE SATISFACTION OF THE RESIDENT ENGINEER. ALL COST RELATING TO CONTRACTOR'S ACCESS AND SECURITY SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR
- 14. CONTRACTOR WILL BE REQUIRED TO PUT AIRPORT FLAGS AND HAVE BEACON LIGHTS ON ALL EQUIPMENT AT ALL TIMES DURING CONSTRUCTION, SEE FLAG DETAIL, THIS SHEET
- 15. IN THE CASE OF AN EMERGENCY, CONTRACTOR SHALL NOTIFY AIRPORT MANAGER AND THE ENGINEER
- 16. DURING ADVERSE WEATHER, THE CONTRACTOR SHALL MAKE PROVISIONS FOR ACCESS TO THE WORK AT NO ADDITIONAL COST TO THE CONTRACT. NO EXTENSION OF CONTRACT TIME WILL BE CONSIDERED FOR DELAYS DUE TO LACK OF ADEQUATE ACCESS TO THE WORK
- 17. THE TALLEST PIECE OF CONSTRUCTION EQUIPMENT IS ANTICIPATED TO BE AN ASPHALT/STONE TRUCK WHICH HAS A MAXIMUM HEIGHT OF 25 FEET IN A DUMP POSITION.
- 18. IF RUNWAY NUMERALS ARE PRESENT DURING CONSTRUCTION THEN CONTRACTOR SHALL PLACE CLOSED RUNWAY MARKER OVER NUMERALS AS DETAILED, OTHERWISE PLACE RUNWAY CLOSED MARKER IN TURE AT ENDS OF RUNWAY AS DETAILED
- 19. CHICAGO EXECUTIVE AIRPORT WILL BE IN OPERATION DURING THE CONSTRUCTION OF THIS PROJECT COORDINATION OF WORK WITH THE AIRPORT IS MANDATORY SO AS TO MINIMIZE IMPACTS ON AIRPORT
- 20. APPROXIMATE LOCATION OF HAUL ROUTES ON THE AIRPORT SITE ARE SHOWN ON THE GENERAL PROJECT LAYOUT AND THE PHASING PLANS. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO COORDINATE OFF-SITE HAUL ROUTES (STATE HIGHWAYS, COUNTY ROADS OR CITY STREETS) WITH THE APPROPRIATE OWNER WHO HAS JURISDICTION OVER THE AFFECTED ROUTE. ON—SITE ROADS USED AS HAUL ROUTES SHALL BE MAINTAINED BY THE CONTRACTOR AND SHALL BE RESTORED AT THE CONTRACTOR'S EXPENSE TO THEIR ORIGINAL CONDITION UPON COMPLETION OF BEING USED AS A HAUL ROUTE. THE BEFORE AND AFTER CONDITION OF ON—SITE HAUL ROUTES SHALL BE JOINTLY INSPECTED AND DETERMINED BY THE CONTRACTOR AND THE ENGINEER. FENCING, DRAINAGE, GRADING AND OTHER MISCELLANEOUS CONSTRUCTION REQUIRED TO CONSTRUCT TEMPORARY HAUL ROUTES OR ACCESS POINTS ON THE AIRPORT WILL BE THE CONTRACTOR'S TOTAL RESPONSIBILITY AND SHALL BE APPROVED BY THE ENGINEER PRIOR TO THE WORK. ALL ON-SITE ACCESS ROADS TO AIRPORT FACILITIES SHALL REMAIN OPEN AND MAINTAINED AT ALL TIMES.
- 21. MOBILIZATION/EQUIPMENT STORAGE AREA WILL BE MADE AVAILABLE FOR CONTRACTOR'S MOBILIZATION AND STORAGE AS SHOWN ON THE PLANS. THIS AREA SHALL BE RESTORED TO THE ORIGINAL CONDITION UPON COMPLETION OF THE PROJECT AT THE CONTRACTOR'S EXPENSE.

ALL EXISTING TAXIWAY AND RUNWAY AIRFIELD LIGHTING CIRCUITS, FAA CABLES AND OTHER AIRPORT ELECTRICAL CABLES SHALL REMAIN IN SERVICE UNTIL REPLACED AS ACCEPTABLE TO THE RESIDENT ENGINEER. ALL TEMPORARY CABLING AND SPLICING NECESSARY TO KEEP THE CIRCUITS IN OPERATION SHALL BE CONSIDERED INCIDENTAL TO CONTRACT.

- 22. LOCATION OF KNOWN EXISTING AIRPORT UNDERGROUND CABLES ARE SHOWN ON THE PLANS AND MUST BE VERIFIED BY THE CONTRACTOR. REPAIR OF DAMAGED CABLE MUST BE STARTED IMMEDIATELY MUST BE VERTIFIED BY THE CONTRACTOR. REPAIR OF DAMAGED CABLE MUST BE STARTED IMMEDIATELY AND CONTINUED UNTIL COMPLETED. ALL SUCH REPAIRS SHALL BE IN ACCORDANCE WITH THE SPECIFICATIONS, OR AS DIRECTED BY THE OWNER OF THE CABLE, AND SHALL BE AT THE CONTRACTOR'S EXPENSE. IF FAA CABLES ARE DAMAGED, REPAIRS SHALL BE DONE FROM POINT TO POINT IN ACCORDANCE WITH FAA REQUIREMENTS AND IN THE PRESENCE OF A FAA REPRESENTATIVE. THE OWNER MAY ELECT TO HAVE THE REPAIR PERFORMED BY OTHERS IN WHICH CASE THE CONTRACTOR SHALL BE RESPONSIBLE FOR PAYING THE INCURRED COSTS OF REPAIRS.
- 23. COORDINATION MEETINGS THE CONTRACTOR SHALL CONDUCT WEEKLY COORDINATION MEETINGS TO DISCUSS WORK AREAS AND SCHEDULING, ETC. WITH THE ENGINEER, AIRPORT OPERATIONS, FAA, AND OTHER APPROPRIATE OFFICIALS. MINUTES FROM THE WEEKLY MEETINGS SHALL BE PREPARED BY THE CONTRACTOR, FURNISHED TO ALL ATTENDESS PRIOR TO THE SUBSEQUENT MEETING, AND KEPT ON FILE AT THE FIELD OFFICE. THE COORDINATION MEETING COSTS SHALL BE CONSIDERED
- 24 THE CONTRACTOR SHALL PROVIDE THE PHONE NUMBERS OF THREE PERSONNEL INCLUDING THE PROJECT SUPERINTENDENT, WHO MAY BE CONTACTED IN AN EMERGENCY, PERSONNEL SHALL BE ON CALL 24 HOURS PER DAY FOR MAINTAINING AIRPORT HAZARD LIGHTING AND BARRICADES.
- 25. DRAINAGE MODIFICATIONS SHALL BE SEQUENCED TO PROVIDE POSITIVE DRAINAGE AT ALL TIMES AT NO
- 26. VEHICLES AND EQUIPMENT SHALL NOT BE ALLOWED WITHIN 72' FROM ACTIVE TAXIWAYS AND 200' FROM ACTIVE RUNWAYS UNLESS OTHERWISE APPROVED BY THE AIRPORT MANAGER.
- 27. CONTRACTOR SHALL STORE EQUIPMENT AND MATERIALS IN SUCH A MANNER AS NOT TO VIOLATE FEDERAL AVIATION ADMINISTRATION PART 77 IMAGINARY SURFACES OR RUNWAY AND TAXIWAY SAFETY
- 28. ALL EXISTING TAXIWAY AND RUNWAY AIRFIELD LIGHTING CIRCUITS, FAA CABLES AND OTHER ELECTRICAL CABLES SHALL REMAIN IN SERVICE AT ALL TIMES. ALL EXISTING LIGHTING AND VAULT EQUIPMENT SHALL REMAIN IN SERVICE UNTIL PROPOSED IMPROVEMENTS ARE INSTALLED AND OPERATIONAL, UNLESS OTHERWISE APPROVED BY THE ENGINEER. ANY CABLES DAMAGED BY THE CONTRACTOR SHALL BE IMMEDIATELY REPAIRED AT HIS EXPENSE.
- 29. COORDINATION BY THE CONTRACTOR WITH THE EXISTING UTILITIES SHALL BE COMPLETED BEFORE CONSTRUCTION IS STARTED. CONTRACTOR IS REFERRED TO SECTION 50-17 OF THE SPECIAL PROVISIONS FOR SPECIFIC REQUIREMENTS. THE LOCATION OF UNDERGROUND UTILITIES AS INDICATED ON THE PLANS HAS BEEN OBTAINED FROM EXISTING RECORDS. NEITHER THE OWNER OR THE DESIGN ENGINEER ASSUME ANY RESPONSIBILITY WHATEVER IN RESPECT TO THE ACCURACY, COMPLETENESS OR SUFFICIENCY OF THE INFORMATION. THERE IS NO GUARANTEE, EITHER EXPRESSED OR IMPLIED THAT THE LOCATIONS, SIZE AND TYPE MATERIAL OF EXISTING UNDERGROUND UTILITIES AS INDICATED ARE REPRESENTATIVE OF THOSE TO BE ENCOUNTERED DURING CONSTRUCTION. IT SHALL BE THE ARE REPRESENTATIVE OF HOUSE TO BE ENCOUNTERED DURING CONSTRUCTION. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE ACTUAL LOCATION OF ALL SUCH FACILITIES, INCLUDING SERVICE CONNECTIONS TO UNDERGROUND UTILITIES. PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL NOTIFY THE UTILITY COMPANY OF HIS OPERATIONAL PLANS. THE CONTRACTOR SHALL MAKE ARRANGEMENTS FOR DETAILED INFORMATION AND ASSISTANCE IN LOCATING UTILITIES. IN THE EVENT AN UNEXPECTED UTILITY INTERFERENCE IS ENCOUNTERED DURING CONSTRUCTION, THE CONTRACTOR SHALL IMMEDIATELY NOTIFY THE UTILITY COMPANY, THE RESIDENT ENGINEER AND THE AIRPORT MANAGER. ANY SUCH MAINS AND/OR SERVICES DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED IMMEDIATELY AT HIS EXPENSE TO THE SATISFACTION OF THE
- 30. ALL AIRFIELD LIGHTING AND LIGHTING GUIDANCE SYSTEMS (NAVAIDS) LOCATED WITHIN AND IMMEDIATELY ADJACENT TO THE CONTRACTORS WORK ZONE SHALL BE CHECKED FOR OPERATIONAL CONDITION PRIOR TO THE DEPARTURE FROM THE AIRPORT WITH THE AIRPORT MANAGER. ANY DEFECIENCIES IN THESE SYSTEMS DUE TO THE ACTS OF CONTRACTOR OR HIS SUBCONTRACTORS, SUPPLIERS OR CONSULTANTS SHALL BE REPAIRED IMMEDIATELY.
- 31. ORANGE CONES SHALL BE PLACED AT 25' CENTERS ALONG THE PAVEMENT EDGE DURING CONCRETE POURING OPERATIONS OF THE CLOSURE LANES TO PREVENT VEHICLES FROM ENTERING PLASTIC CONCRETE. IN THE EVENT A VEHICLE ENTERS THE CONCRETE BEFORE A MINIMUM COMPRESSIVE STRENGTH OF 3,500 PSI HAS BEEN OBTAINED, SAID PAVEMENT SHALL BE REMOVED AND REPLACED AT THE CONTRACTOR'S EXPENSE.

### CONTRACTOR CROSSING RUNWAY AND TAXIWAY AIR OPERATIONS AREA (A.O.A.)

- 32. ANYTIME THE CONTRACTOR IS REQUIRED TO UTILIZE OR CROSS ACTIVE AIRFIELD PAVEMENTS FOR ACCESS TO AND FROM THE WORK ZONE, A FULL TIME CROSSING GUARD IN RADIO CONTACT WITH THE CONTROL TOWER SHALL BE FURNISHED BY THE CONTRACTOR FOR MOVEMENTS OF VEHICLES OR EQUIPMENT TO AND FROM THE WORK ZONE. THE RADIO OPERATOR SHALL BE FAMILIAR WITH AIRPORT GROUND CONTROL PROCEDURES AND DEMONSTRATE KNOWLEDGE OF SAME TO THE AIRPORT, THE AIRPORT RESERVES THE RIGHT TO APPROVE THE CROSSING GUARDS. THE CONTRACTOR SHALL PROVIDE THEIR OWN RADIOS. THIS COST SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PAYMENT OF MUNICIPAL FINES (\$500 PER OCCURRENCE)
  DUE TO AIRFIELD INCURSIONS BY HIS EMPLOYEES, SUBCONTRACTORS, SUPPLIERS, CONSULTANTS
- 33. ANY PAVEMENT DAMAGED BY CONTRACTOR'S OPERATIONS SHALL BE REPAIRED IMMEDIATELY BY HIM TO THE SATISFACTION OF THE RESIDENT ENGINEER AND AIRPORT MANAGER AT NO ADDITIONAL COST TO THE OWNER. PAVEMENT SHALL BE CONTINUALLY SWEPT TO PROVIDE DEBRIS FREE SURFACE DURING ALL HAUL ROAD OPERATIONS. THIS COST SHALL NOT BE PAID SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.
- 34. WORK WITHIN THE A.O.A. SHALL BE EXPEDITED. ANY DROP OFF SHALL BE ADEQUATELY LIGHTED, SIGNED AND BARRICADED. NO MATERIAL SHALL BE STOCKPILED WITHIN THE A.O.A. SHOULD IT BE NECESSARY FOR THE CONTRACTOR TO TEMPORARILY RELOCATE EQUIPMENT TO ALLOW AIRCRAFT TO PASS, THEY SHALL DO SO AT NO EXTRA COST TO THE PROJECT. THE CONTRACTOR SHALL NOTIFY THE RESIDENT ENCINEER AND AIRPORT MANAGER TEN (10) WORKING DAYS IN ADVANCE OF ANY PLANNED CONSTRUCTION WITHIN THESE LIMITS.


### MUNICIPALITIES GENERAL NOTES

- 1. ALL ELEVATIONS SHOWN ON PLANS ARE IN 1929 DATUM. SUBTRACT 0.24 FEET FROM
- 2. ALL CONTRACTORS AND SUBCONTRACTORS TO BE REGISTERED WITH BOTH THE VILLAGE OF WHEELING AND THE CITY OF PROSPECT HEIGHTS
- 3. ALL STORM SEWERS ON THE AIRPORT SITE ARE OWNED, OPERATED AND MAINTAINED BY THE CHICAGO EXECUTIVE AIRPORT.
- 4. THE CONTRACTOR SHALL SECURE A GRADING PERMIT FROM THE CITY OF PROSPECT HEIGHTS PRIOR TO ANY GRADING ACTIVITIES COMMENCING
- THE CONTRACTOR SHALL NOTIFY THE CITY OF PROSPECT HEIGHTS (847.398.6700) A MINIMUM OF 48 HOURS PRIOR TO ANY STORM SEWER INSTALLATION.
- 6. THE CONTRACTOR SHALL NOTIFY THE VILLAGE OF WHEELING (847.459.2600) TO WITNESS A PROOF ROLL OF BASE MATERIAL PRIOR TO PAVING OPERATIONS.
- 7. THE CONTRACTOR SHALL CONTACT STEVE SKIBER AT THE CITY OF PROSPECT HEIGHTS (847.398.6700) TO OBTAIN BUILDING DEMOLITION PERMITS. THE CITY SHALL BE NOTIFIED UPON COMPLETION OF DEMOLITION OPERATIONS FOR INSPECTION.

### DESIGN AIRCRAFT APPROACH CATEGORY: D DESIGN AIRPORT GROUP: III


CONTRACTOR SHALL PLAN AND PERFORM HIS WORK SO AS NOT TO INTERFERE OR HINDER THE PROGRESS, WORK OR HAUL ROAD ACCESS OF OTHER CONTRACTORS (SEE 

- CONSTRUCT PARTIAL PARALLEL TAXIWAY ECHO AND
- PARTIAL OVERLAY OF TAXIWAY ECHO
  CONSTRUCT SOUTHEAST QUADRANT APRON
- TAXIWAY LIMA EXTENSION, PHASE 1
- CONSTRUCT TAXIWAY CHARLIE APRON EXTENSION CONSTRUCT NORTHEAST QUAD T—HANGARS SOVEREIGN DEVELOPMENT IN SOUTHEAST QUAD
- BRIGADOON DEVELOPMENT IN EAST QUAD




### CONSTRUCTION EQUIPMENT AND TRUCK SIGNAL FLAG

NOT TO SCALE



### **CLOSED RUNWAY MARKER DETAIL**



OFF PAVEMENT CLOSED RUNWAY MARKER DETAIL

### **CLOSED RUNWAY MARKER DETAIL NOTES**

- 1. CLOSED RUNWAY MARKERS SHALL BE YELLOW
- 2. MARKERS SHALL BE MATERIAL APPROVED BY THE ENGINEER.
- 3. CONTRACTOR SHALL MAINTAIN AND RELOCATE MARKERS AS SHOWN ON THE PLANS OR AS NEEDED TO FACILITATE CONSTRUCTION
- 4. MARKERS ON PAVEMENT SHALL BE PLACED OVER EXISTING RUNWAY NUMERALS AS SHOWN
- 5. COST OF FURNISHING, INSTALLING, MAINTAINING AND REMOVING MARKERS SHALL BE CONSIDERED
- 6. DURING VARIOUS PHASES OF WORK, IT WILL BE NECESSARY TO CLOSE RUNWAYS TO AIR TRAFFIC ON A TEMPORARY BASIS AS COORDINATED WITH THE AIRPORT AND TOWER PERSONNEL. THE CONTRACTOR SHALL MARK THE RUNWAYS TO BE CLOSED BY PLACING A YELLOW CROSS AT THE LOCATION AND DIMENSIONS DETAILED ON THIS SHEET. THE CROSSES ARE SHOWN ON THE RESPECTIVE RUNWAYS ACCORDING TO THE VARIOUS PHASES OF WORK AS DELINEATED IN THE SUGGESTED SEQUENCE OF CONSTRUCTION.

### LIMITATIONS ON CONSTRUCTION WITHIN AIRPORT OPERATIONS AREA (A.O.A)

THE CONTRACTOR SHALL NOTIFY THE RESIDENT ENGINEER AND AIRPORT MANAGER TEN (10) WORKING DAYS IN ADVANCE OF ANY PLANNED CONSTRUCTION WITHIN 200' OF THE RUNWAY CENTERLINE. WORK SHALL BE EXPEDITED IN THESE AREAS AND AT THE END OF EACH WORKING DAY THESE AREAS SHALL BE SMOOTHLY GRADED TO ALLOW THE RUNWAY TO BE REOPENED UNLESS OTHERWISE STATED IN THE SEQUENCE OF CONSTRUCTION. AT LEAST ONE OF THE RUNWAYS SHALL REMAIN IN OPERATION AT ALL TIMES. IF NECESSARY STEEL PLATES SHALL BE FURNISHED AND INSTALLED BY THE CONTRACTOR TO COVER ANY OPEN TRENCHES OR EXCAVATION WITHIN THE A.O.A. IF DURING RUNWAY CLOSURE AN EMERGENCY IS DECLARED, THE CONTRACTOR SHALL IMMEDIATELY CLEAR THE RUNWAY OF ALL VEHICLES, MEN AND EQUIPMENT. THE CONTRACTOR WILL BE LIMITED TO 3 DAILY CLOSURES ON RUNWAY 16/34 NOT OTHERWISE NOTED IN THE SEQUENCE OF

### **TAXIWAYS**

ANY WORK WITHIN 72' OF THE TAXIWAY CENTERLINE WILL REQUIRE A TAXIWAY CLOSURE. CONSTRUCTION WILL BE ALLOWED UP TO THE EDGE OF THE TAXIWAY PAVEMENTS WITHOUT CLOSURE ON A LIMITED BASIS AS DETERMINED BY THE AIRPORT MANAGER. WORK WITHIN THE A.O.A. SHALL BE EXPEDITED. ANY DROP OFF SHALL BE ADEQUATELY LIGHTED, SIGNED AND BARRICADED. NO MATERIAL SHALL BE STOCKPILED WITHIN THE A.O.A. SHOULD IT BE NECESSARY FOR THE CONTRACTOR TO TEMPORARILY RELOCATE EQUIPMENT TO ALLOW AIRCRAFT TO PASS, THEY SHALL DO SO AT NO EXTRA COST TO THE PROJECT. THE CONTRACTOR SHALL NOTIFY THE RESIDENT ENGINEER AND AIRPORT CONSTRUCTION WITHIN THESE LIMITS. AIRPORT MANAGER FIVE (5) WORKING DAYS IN ADVANCE OF ANY PLANNED

### PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets

GROUND CONTROL FREQUENCY: 121.7 MHz

IN THE EVENT THE CONTRACTOR PROPOSES TO UTILIZE AN

POINT "A" CLOSEST CONSTRUCTION POINT TO RUNWAY 34

POINT "B" CLOSEST CONSTRUCTION POINT TO RUNWAY 6/24

POINT "C" CLOSEST CONSTRUCTION POINT TO RUNWAY 16 ELEVATION: 641.21

ON-SITE CONCRETE BATCH PLANT, LOCATION TO BE COORDINATED WITH RESIDENT ENGINEER AND ACTING AIRPORT

MANAGER TO ALLOW FOR APPROPRIATE AIRSPACE CLEARANCE. THE CONTRACTOR WILL BE RESPONSIBLE TO SUBMIT FAA FORM 7460 FOR AIRSPACE APPROVAL. THE RESIDENT ENGINEER WILL PROVIDE BASE AIRPORT INFORMATION FOR

AIR CONTROL FREQUENCY: 119.9 MHz

MAXIMUM ANTICIPATED HEIGHT OF

CONSTRUCTION EQUIPMENT: 25'

THE CONTRACTOR'S USE.

ELEVATION: 644.48 LATITUDE: 42° 06' 37.95" (NAD83)

LATITUDE: 42° 06' 42.78" (NAD83)

LATITUDE: 42° 07' 21.14" (NAD83)

LONGITUDE: 87° 54' 25.25" (NAD83)

LONGITUDE: 87° 54' 09.70" (NAD83)

LONGITUDE: 87° 54' 02.52" (NAD83)

FILE: phasing-notes.dwg LAYOUT: Layout1 JPDATE BÝ: johse SURVEY BOOK #

DATE: Thu 4/15/10 1:21pm XREF DWG: tbclnt-con2.dwg

### **REVISIONS** BY NUMBER DATE

THIS BAR IS EQUAL TO 2 AT FULL SCALE (34X22).


### AGO EXECUTIVE AIRPORT 3/PROSPECT HEIGHTS, ILLINOIS WAY 16/34 OFA/RSA IMPROVEME ) EXTEND TAXIWAY LIMA RUCTION DETAIL ONSTI Ο̈́Ω OF ( шŽ EQUENCI CHICAG WHEELING/F E 2 - RUNWA

### 9 CRAWFORD DESIGN BY SMS

111 PHAS

DRAWN BY СМТ CHECKED BY SMS APPROVED BY: MLK 04/16/10 JOB No: 09290-07 ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 7 OF 66 SHEETS



### STORM WATER POLLUTION PREVENTION PLAN

THE FOLLOWING PLAN IS ESTABLISHED AND INCORPORATED IN THE PROJECT TO DIRECT THE CONTRACTOR IN THE PLACEMENT OF TEMPORARY EROSION CONTROL SYSTEMS AND TO PROVIDE A STORM WATER POLLUTION PREVENTION PLAN FOR COMPLIANCE WITH NPDES.

THE PURPOSE OF THIS PLAN IS TO MINIMIZE EROSION WITHIN THE CONSTRUCTION SITE AND TO LIMIT SEDIMENTS FROM LEAVING THE SITE BY UTILIZING PROPER TEMPORARY EROSION CONTROL SYSTEMS AND PROVIDING GROUND COVER WITHIN A REASONABLE AMOUNT OF TIME.

CERTAIN EROSION CONTROL FACILITIES SHALL BE INSTALLED BY THE CONTRACTOR AT THE BEGINNING OF CONSTRUCTION. OTHER ITEMS SHALL BE INSTALLED BY THE CONTRACTOR AS DIRECTED BY THE ENGINEER ON A CASE BY CASE SITUATION DEPENDING ON THE CONTRACTOR'S SEQUENCE OF ACTIVITIES, TIME OF YEAR, AND EXPERIENCE CONDITIONS

THE CONTRACTOR SHALL INSTALL PERMANENT EROSION CONTROL SYSTEMS AND SEEDING WITHIN A TIMEFRAME SPECIFIED HEREIN AND AS DIRECTED BY THE ENGINEER, THEREFORE MINIMIZING THE AMOUNT OF AREA SUSCEPTIBLE TO EROSION AND REDUCING THE AMOUNT OF TEMPORARY SEEDING, WHICH WILL BE THE CONTRACTOR'S COST. THE ENGINEER WILL DETERMINE IF ANY TEMPORARY EROSION CONTROL SYSTEMS SHOWN IN THE PLAN CAN BE DELETED AND IF ANY ADDITIONAL TEMPORARY EROSION CONTROL SYSTEMS, WHICH ARE NOT INCLUDED IN THIS PLAN, SHALL BE ADDED. THE CONTRACTOR SHALL PERFORM ALL WORK AS DIRECTED BY THE ENGINEER AND AS SHOWN ON THE PLANS.

### SITE DESCRIPTION

THE FOLLOWING IS A DESCRIPTION OF THE CONSTRUCTION ACTIVITY WHICH IS THE SUBJECT OF THIS PLAN:

THIS PROJECT CONSISTS OF CONSTRUCTING TAXIWAY L AND NORTHEAST QUADRANT SITEWORK AT THE CHICAGO EXECUTIVE AIRPORT. THE PROJECT INCLUDES EARTH EXCAVATION, EMBANKMENT, STORM SEWERS, MANHOLES, INLETS VARIOUS PAVEMENT ITEMS, ELECTRICAL WORK AND OTHER MISCELLARGOUS CONSTRUCTION WORK.

THE FOLLOWING IS A DESCRIPTION OF THE INTENDED SEQUENCE OF MAJOR ACTIVITIES WHICH WILL DISTURB SOILS FOR MAJOR PORTIONS OF THE CONSTRUCTION SITE, SUCH AS GRUBBING, EXCAVATION AND GRADING:

- EXCAVATION AND EMBANKMENT WILL BE COMPLETED WITHIN THE PROJECT LIMITS TO GRADE OUT FOR THE PROPOSED DRAINAGE AND PAVEMENT IMPROVEMENTS.
- 2. STORM SEWERS, MANHOLES, INLETS AND CULVERT INSTALLATION.
- PLACEMENT, MAINTENANCE, REMOVAL AND PROPER CLEAN-UP OF TEMPORARY EROSION CONTROL. SUCH AS PERIMETER SILT FENCE, TEMPORARY DITCH CHECKS AND INLET PROTECTION.
- 4. PAVEMENT CONSTRUCTION.
- 5. FINAL GRADING, ELECTRICAL INSTALLATION AND OTHER MISCELLANEOUS ITEMS.
- PLACEMENT OF PERMANENT EROSION CONTROL, SUCH AS SEEDING, MULCHING AND EROSION CONTROL BLANKET.

### AREA OF CONSTRUCTION SITE

THE TOTAL AREA OF THE CONSTRUCTION SITE IS ESTIMATED TO BE 17 ACRES OF WHICH 13 ACRES WILL BE DISTURBED BY EXCAVATION, GRADING AND OTHER ACTIVITIES.

OTHER REPORTS, STUDIES AND PLANS WHICH AID IN THE DEVELOPMENT OF THE STORM WATER POLLUTION PREVENTION PLAN AS REFERENCED DOCUMENTS:

- INFORMATION OF THE SOILS AND TERRAIN WITHIN THE SITE WAS OBTAINED FROM TOPOGRAPHIC SURVEYS AND SOIL BORINGS THAT WERE UTILIZED FOR THE DEVELOPMENT OF THE PROPOSED TEMPORARY EROSION CONTROL SYSTEMS.
- PROJECT PLAN DOCUMENTS, SPECIFICATION AND SPECIAL PROVISIONS, AND PLAN DRAWINGS INDICATING DRAINAGE PATTERNS AND APPROXIMATE SLOPES ANTICIPATED AFTER GRADING ACTIVITIES WERE UTILIZED FOR THE PROPOSED PLACEMENT OF THE TEMPORARY EROSION CONTROL SYSTEMS.

### DRAINAGE TRIBUTARIES AND SENSITIVE AREAS RECEIVING RUNOFF FROM THIS CONSTRUCTION SITE:

THE CONSTRUCTION SITE DRAINS INTO THE WHEELING DRAINAGE DITCH AND DES PLAINES RIVER THROUGH A STORM SEWER SYSTEM.

### CONTROLS-EROSION CONTROLS AND SEDIMENT CONTROL

DESCRIPTION OF STABILIZATION PRACTICES AT THE BEGINNING OF CONSTRUCTION:

- 1. THE DRAWINGS SPECIFICATIONS AND SPECIAL PROVISIONS WILL ENSURE THAT EXISTING VEGETATION IS PRESERVED WHERE ATTAINABLE AND DISTURBED PORTIONS OF THE SITE WILL BE STABILIZED. STABILIZATION PRACTICES INCLUDE SEEDING AND MULCHING AS DIRECTED BY THE ENGINEER. STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED. BUT IN NO CASE MORE THAN 7 DAYS AFTER THE CONSTRUCTION ACTIVITY IN THAT PORTION OF THE SITE HAS TEMPORARILY OR PERMANENTLY CEASED.
- AS SOON AS REASONABLE ACCESS IS AVAILABLE TO ALL LOCATIONS WHERE WATER DRAINS AWAY FROM THE PROJECT, TEMPORARY DITCH CHECKS, INLET PROTECTION AND PERIMETER SILT FENCE SHALL BE INSTALLED AS CALLED OUT IN THE PLAN AND DIRECTED BY THE ENGINEER.
- THIS PLAN HAS BEEN PREPARED TO COMPLY WITH THE PROVISIONS OF THE NPDES PERMIT NUMBER ILR10, ISSUED BY THE ILLINOIS ENVIRONMENTAL PROTECTION AGENCY FOR STORM WATER DISCHARGES FROM CONSTRUCTION SITE ACTIVITIES.

### DESCRIPTION OF STABILIZATION PRACTICES DURING CONSTRUCTION:

DURING CONSTRUCTION, AREAS OUTSIDE THE CONSTRUCTION LIMITS AS OUTLINED PREVIOUSLY HEREIN SHALL BE PROTECTED. THE CONTRACTOR SHALL NOT USE THIS AREA FOR STAGING (EXCEPT AS DESCRIBED ON THE PLANS AND DIRECTED BY THE ENGINEER), PARKING OF VEHICLES OR CONSTRUCTION EQUIPMENT, STORAGE OF MATERIALS, OR OTHER CONSTRUCTION RELATED ACTIVITIES.

- WITHIN THE CONSTRUCTION LIMITS, AREAS WHICH MAY BE SUSCEPTIBLE TO EROSION AS DETERMINED BY
  THE ENGINEER SHALL REMAIN UNDISTURBED UNTIL FULL SCALE CONSTRUCTION IS UNDERWAY TO PREVENT
  LININGFCESSARY SOIL FROSION
- 2. EARTH STOCKPILES SHALL BE TEMPORARILY SEEDED, AT THE CONTRACTORS EXPENSE, IF THEY ARE TO REMAIN UNUSED FOR MORE THAN FOURTEEN DAYS.
- 3. AS CONSTRUCTION PROCEEDS, THE CONTRACTOR SHALL INSTITUTE THE FOLLOWING AS DIRECTED BY THE ENGINEER:

- A. PLACE TEMPORARY EROSION CONTROL FACILITIES AT LOCATIONS SHOWN ON THE PLANS.
- B. CONSTRUCT DITCHES AND PROVIDE TEMPORARY EROSION CONTROL SYSTEMS.
- C. BUILD NECESSARY EMBANKMENT AT CULVERT/STORM SEWER LOCATIONS AND THEN EXCAVATE AND PLACE PIPE.
- D. EXCAVATED AREAS AND EMBANKMENT AREAS SHALL BE PERMANENTLY SEEDED IMMEDIATELY AFTER FINAL GRADING. IF NOT, THEY SHALL BE TEMPORARILY SEEDED, AT THE CONTRACTOR'S COST, IF NO CONSTRUCTION ACTIVITY IN THE AREA IS PLANNED FOR SEVEN DAYS.
- 4. CONSTRUCTION EQUIPMENT SHALL BE STORED AND FUELED ONLY AT DESIGNATED LOCATIONS. ALL NECESSARY MEASURES SHALL BE TAKEN TO CONTAIN ANY FUEL OR POLLUTANT IN ACCORDANCE WITH EPA WATER QUALITY REGULATIONS. LEAKING EQUIPMENT OR SUPPLIES SHALL BE IMMEDIATELY REPAIRED OR REMOVED FROM THE SITE.
- 5. THE RESIDENT ENGINEER SHALL INSPECT THE PROJECT DAILY DURING CONSTRUCTION ACTIVITIES. INSPECTION SHALL ALSO BE DONE WEEKLY AND AFTER RAINS OF 1/2 OR GREATER OR EQUIVALENT SNOWFALL AND DURING WINTER SHUTDOWN PERIOD.
- 6. SEDIMENT COLLECTED DURING CONSTRUCTION OF THE VARIOUS TEMPORARY EROSION CONTROL SYSTEMS SHALL BE DISPOSED OF ON SITE ON A REGULAR BASIS AS DIRECTED BY THE ENGINEER. THE COST OF THIS MAINTENANCE SHALL BE INCLUDED IN THE UNIT BID PRICE FOR UNCLASSIFIED EXCAVATION AND FROSION CONTROL ITEMS
- 7. THE TEMPORARY EROSION CONTROL SYSTEMS SHALL BE REMOVED AS DIRECTED BY THE ENGINEER AFTER USE IS NO LONGER NEEDED OR NO LONGER FUNCTIONING. THE COST OF THIS REMOVAL SHALL BE INCLUDED IN THE UNIT BID PRICE FOR VARIOUS TEMPORARY EROSION CONTROL PAY ITEMS.

### DESCRIPTION OF STRUCTURAL PRACTICES AFTER FINAL GRADING:

- TEMPORARY EROSION CONTROL SYSTEMS SHALL BE LEFT IN PLACE WITH PROPER MAINTENANCE UNTIL PERMANENT EROSION CONTROL IS IN PLACE AND WORKING PROPERLY AND ALL PROPOSED TURF AREAS ARE SEEDED AND ESTABLISHED.
- 2. ONCE PERMANENT EROSION CONTROL SYSTEMS AS PROPOSED IN THE PLANS ARE FUNCTIONAL AND ESTABLISHED, TEMPORARY ITEMS SHALL BE REMOVED, CLEANED UP, AND DISTURBED TURF RESEEDED.


### MAINTENANCE AFTER CONSTRUCTION

CONSTRUCTION IS COMPLETE AFTER FINAL ACCEPTANCE BY THE ILLINOIS DIVISION OF AERONAUTICS. MAINTENANCE UP TO THIS DATE WILL BE REQUIRED BY THE CONTRACTOR.

NPDES PERMIT #	
DATE ISSUED:	
DATE EXPIRES:	

FILE: erosion cor LAYOUT: Layout1 UPDATE BY: joh:	ntrol.dwg	II 2 \DIOW\Sileets
SURVEY BOOK #	∤ /10 1:22	
taxiv	vav-base	-con2.dwg oavement.dwg drainage.dwg WG
topo	-txy-L.D	WG
REV NUMBER	/ISIONS	DATE
NUMBER	ы	DATE
O THIS BAR I	1	2
THIS BAR I AT FULL S	S EQUAL SCALE (3-	
		z
		PREVENTION PLAN
SLN		<u> </u>
S		0
IVE AIRPORT HEIGHTS, ILLINOIS DFA/RSA IMPROVEMENTS XIWAY LIMA		Ē
ORT ILL MPF		
	i   .	Ä
E A EIGH A/RS		
T HE		<b>8</b>
CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILL 2 - RUNWAY 16/34 OFA/RSA IMPE AND EXTEND TAXIWAY LIMA		POLLUTION
OSP 16,		Ξ
AGO /PR VAY	i	<b>P</b> 0
HIC NO AND		
		TER
		×
, IASE		Ž
풉		STORM
		ST
© Copyright CMT, Inc.  CANT MARPHY & TILY, NC. CONSULTAB ENGERS	+	lio.
© copyright CMT, Inc. PHY & TILLY, INC.		NTIN
© Cop.	19000	EXEC
Ö, MUF	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	20
AWFOF NSULTI	N esse	3
<b>8</b> 68		
		3
DESIGN BY:		SMS
DRAWN BY:		СМТ
		SMS
CHECKED BY:  APPROVED BY:		MLK
APPROVED BY: DATE:		MLK /16/10

SHEET 8 OF 66 SHEETS



- 1. 2-PLY REPLACEMENT SEDIMENT BAGS AND FILTER WRAP TO BE PLACED IN ALL INLETS, MANHOLES, TRENCH DRAINS AND CATCH BASINS LOCATED IN PAVED AREAS AND NONPAVED
- 2. FABRIC SHALL BE IN CONFORMANCE WITH VILLAGE OF WHEELING REQUIREMENTS.
- 3. FABRIC SHALL OVERLAY FRAME BY 2" (MIN.).
- 4. CONTRACTOR SHALL CLEAR DEBRIS AND SILT AS REQUIRED FROM FABRIC TO MAINTAIN DRAINAGE THROUGH THE STRUCTURE.
- 5. FABRIC SHALL REMAIN IN PLACE UNTIL TURFED AREAS HAVE DEVELOPED A MIN. OF 80% OF
- 6. COST OF FILTER WRAP SHALL BE CONSIDERED INCIDENTAL TO INLET PROTECTION.

### DRAINAGE STRUCTURE FILTER WRAP

N.T.S.



### NOTICE OF INTENT (NOI) GENERAL PERMIT TO DISCHARGE STORM SEWER

IMPORTANT: FORM MUST BE TYPED TO ENABLE AUTOMATED OPTICAL PROCESSING.

SUBMIT ORIGINAL - DO NOT SUBMIT PHOTOCOPY

OWN	OWNER INFORMATION  LIST FIRST MI. (SEE INSTRUCTIONS) OWNER TYPE:(SELECT ONE AND TYPE "X")										
	LAST FIRST		MI. (	SEE II	NSTRUCTIONS)	OWNER TY	PE:(SELECT ON	E AND TYPE "X")			
NAME: CHICAGO EXECUTIVE AIRPORT						PRIVAT	те П соц	JNTY STATE			
MAILING ADDRESS: 1020 SOUTH PLANT ROAD						X arv	SPE	CIAL DISTRICT			
CITY:	WHEELING ST. IL ZIP: 60090 FEDERAL										
CONTACT DENING DOLLIEN						TELEPHONE	AREA CODE	NUMBER			
PERSON						NUMBERS:	847	537-2580			

CONT	RACTOR INFO	ORMATION						
	LAST	LAST FIRST MI. (SEE INSTRUCTIONS)		RST MI. (SEE INSTRUCTIONS) TELEPHONE AREA CODE		NUMBER		
NAME:					NUMBERS:			
MAILING ADDRES			а	Υ		ST.	ZIP:	

### CONSTRUCTION SITE INFORMATION

SEL AND	TYPE :	EXISTING SITE		SITE			CHANGE OF INFORMATION							
FACILITY NAME	CHIC	AGO EXECUTIVE	Ξ Α	IRP	ORT			Other NPDE Permit Numb (if Applicabl	pers		N/A			
MAILING ADDRESS	10:	20 SOUTH PLAN	NT	RO	AD			TELEPHONE NUMBERS:		47	537	NUME 7-2		
CITY: \	WHEE	LING		ST.	IL	ZIP:	60090	LATITUDE: DE (NEAREST 15 SECONDS)	G. M	IN. SEC.	LATITUDE: (NEAREST 15 SECONDS)		MIN.	SEC.
COUNTY:	coo			CTION	13					NORTH	RANGE:	11	EAST	1
START	JCTION	,	END	STRU	CTION		MM/DD/YY	TOTAL SIZE C	ON I	17.0 A	CRES			


### TYPE OF CONSTRUCTION

RESIDENTIAL	COMMERCIAL	INDUSTRIAL	RECONSTRUCTION	X TRANSPORTATION	OTHER	
RECEIVING WATE						
DOES YOUR STORM W	TER DISCHARGE DIRE	CTLY TO: (SELECT ONE	AND TYPE "X")			
WATER OF THE	STATE OR	X STORM SEWER	OWNER OF STORM SEWER SYSTEM	WHEELING/PROSPI	ECT HTS.	
NAME OF CLOSEST RECEIVING WATER (IF KNOWN)	DES PLAIN	IES RIVER				
THE STORM WATER DISCHARGES? THE CONCENTRATION OF POLLUTANTS IN						

This Agency is authorized to require this information under Illinios Revised Statute, 1991, Chapter 111 1/2, section 1039. Information is required under that Section. Failure to do so may prevent this form from being processed and could respour application being denied. This form has been approved by the Forms Management Center.

FOR OFFICE USE ONLY

- SILT FENCE 5' MAX C. TO C. 48" MIN. FENCE POSTS, DRIVEN " MINIMUM INTO GROUND PERSPECTIVE VIEW



NOTES:

1. BALES SHALL BE PLACED AT THE TOE OF SLOPE OR ON A

THE ADJACENT BALES.

ARE HORIZONTAL.

2. EACH BALE SHALL BE EMBEDDED IN THE SOIL A MINIMUM OF 4 INCHES, AND PLACED SO THE BINDINGS

3. BALES SHALL BE SECURELY ANCHORED IN PLACE BY EITHER TWO STAKES OR REBARS DRIVEN THROUGH THE BALE. THE FIRST STAKE

4. INSPECTION SHALL E FREQUENT AND REPAIR REPLACEMENT SHALL E

MADE PROMPTLY AS NEEDED.

5. BALES SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFULNESS SO AS NOT TO BLOCK OR IMPEDE

COST OF REMOVAL
REPLACEMENT TO

6. AFTER FINAL APPROVAL OF THE ENGINEER, STRAW BALES

MAY BE REMOVED.
CONTRACTOR SHALL PLACE
SOD, EXCELSIOR BLANKET
WITH SEED OR KNITTED

STRAW MAT WITH SEED OVER THE DISTURBED AREAS. COST INCIDENTAL TO INLET

CHECK.

PROTECTION.

STORM FLOW OR DRAINAGE

REPLACEMENT TO BE INCLUDED IN UNIT PRICE FOR INLET PROTECTION/DITCH

IN EACH BALE SHALL BE
DRIVEN TOWARD THE
PREVIOUSLY LAID BALE AT AN
ANGLE TO FORCE THE BALES
TOGETHER. STAKES SHALL BE
DRIVEN FLUSH WITH THE

CONTOUR AND IN A ROW WITH ENDS TIGHTLY ABUTTING

### NOTES:

EROSION CONTROL FABRIC FENCE DETAIL

- 1. WHEN TWO SECTIONS OF FILTER CLOTH ADJOIN EACH OTHER THEY SHALL BE OVER-LAPPED BY 6" MIN. AND FOLDED.
- 2. MAINTENANCE SHALL BE PERFORMED AS NEEDED AND MATERIAL REMOVED WHEN "BULGES" DEVELOP IN THE SILT FENCE. MAINTENANCE, WHICH INCLUDES THE REPLACEMENT OF DAMAGED FENCE, SHALL BE CONSIDERED INCIDENTIAL TO THE COST OF THE FROSION CONTROL FENCE. OF THE EROSION CONTROL FENCE.
- 3. SILT FENCE SHALL BE INSTALLED PER LANDSCAPING/EROSION CONTROL PLAN OR AS DIRECTED BY THE ENGINEER.

FILTER FABRIC SHALL MEET THE REQUIREMENTS OF MATERIAL SPECIFIED FOR AR152540 IN THE ILLINOIS DEPARTMENT OF TRANSPORTATION DIVISION OF AERONAUTICS SUPPLEMENTAL SPECIFICATIONS AND RECURING SPECIAL PROVISIONS.

PLAN VIEW

SECTION A-A

SECTION B-B

-ROADSIDE DITCH IF NEEDED

10' MIN.

Α---

PAVEMENT

MOUNTABLE BERM

(OPTIONAL)

**EXISTING** 

PAVEMENT

FILTER FABRIC -

EXISTING GROUND

COARSE AGGREGATE

OPERATION.

\* MUST EXTEND FULL WIDTH OF INGRESS AND EGRESS


GROUND


∠FILTER FABRIC

- 2. ROCK OR RECLAIMED CONCRETE SHALL MEET ONE OF THE FOLLOWING IDOT COARSE AGGREGATE GRADATION, CA-1, CA-2, CA-3 OR CA-4.
- 3. ANY DRAINAGE FACILITIES REQUIRED BECAUSE OF WASHING SHALL BE CONSTRUCTED ACCORDING TO MANUFACTURERS SPECIFICATIONS AND SHALL BE INCIDENTAL TO THE CONTRACT.
- 4. MINIMUM WIDTH IS 14' FOR ONE-WAY TRAFFIC AND 20' FOR TWO WAY TRAFFIC. TWO-WAY TRAFFIC WIDTHS SHALL BE INCREASED A MINIMUM OF 4' FOR TRALER TRAFFIC. DEPENDING ON THE TYPE OF VEHICLE OR EQUIPMENT, SPEED, LOADS, CLIMATIC AND OTHER CONDITIONS UNDER WHICH VEHICLES AND EQUIPMENT OPERATE AN INCREASE IN THE MINIMUM WIDTHS MAY
- 5. ROADWAY SHALL FOLLOW THE CONTOUR OF THE NATURAL TERRAIN TO THE EXTENT POSSIBLE.
- 6. STABILIZED CONSTRUCTION ENTRANCE SHALL BE INCIDENTAL TO THE CONTRACT.

### STABILIZED CONSTRUCTION ENTRANCE

FROM NRCS STANDARD DRAWING NO. IL-630 - N.T.S.





**ELEVATION** 

HAY OR STRAW BALES AS A PERIMETER EROSION BARRIER N.T.S.

### PROPOSED BALES (COST INCIDENTAL TO INLET PROTECTION) - CATCH BASIN OR INLET EMBEDDED PROPOSED INLET - LIMITS OF LANDSCAPING (SEE NOTE 6) INLET PLACEMENT INLET PLACEMENT ISOMETRIC PROPOSED EROSION CONTROL FENCING -(COST INCIDENTAL TO INLET PROTECTION) — 4" VERTICAL FACE

### STORM INLET SEDIMENT TRAP DETAIL - TURF AREAS

N.T.S.

BEDDING DETAIL


PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets FILE: Details - Erosion Control.dwo LAYOUT: Layout1 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:49:45 AM XREF DWG: tbclnt-con2.dwg REVISIONS NUMBER BY DATE THIS BAR IS FOUAL TO 2 LINOIS UTIVE AIRPORT T HEIGHTS, ILLII OFA/RSA IMPRO FAXIWAY LIMA REVI LUTION PE AND DETA CHICAGO EXECUTIVE A HEELING/PROSPECT HEIGI ? - RUNWAY 16/34 OFA/R AND EXTEND TAXIWA ER POLI N ~ 0 S MURPHY ENGINEE!


# 

DESIGN BY SMS DRAWN BY CMT CHECKED BY: SMS APPROVED BY: MLK DATE: 04/16/10 JOB No: 09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 9 OF 66 SHEETS





PA052

K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: Bldg—photos Sht 1.dwg
LAYOUT: Layout1
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 11:00:31 AM
XREF DWG: tbcInt—con2.dwg

REVISIONS					
NUMBER	BY	DATE			
· · · · · · · · · · · · · · · · · · ·					

THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22).

CHICAGO EXECUTIVE AIRPORT
WHEELING/PROSPECT HEIGHTS, ILLINOIS
PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS
AND EXTEND TAXIWAY LIMA Ó

**PHOT** BUILDINGS SHEET 1 **EXISTING** 

MURPHY & 1 ENGINEERS 184-000613

CRAWFORD, N CONSULTING F

CHICA-O EXECUTIVE DESIGN BY: SMS DRAWN BY: CMT CHECKED BY: SMS

APPROVED BY: MLK DATE: 04/16/10 JOB No: 09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 12 OF 66 SHEETS















### NOTES:


1. THESE IMAGES REPRESENT EXISTING GENERAL CONDITIONS AT THE SITE AT THE TIME THE IMAGES WERE TAKEN. THE CONTRACTOR IS ENCOURAGED TO VISIT THE SITE AND INSPECT THE BUILDING STRUCTURES AND ANY OTHER FEATURE HE MAY DEEM NECESSARY IN ORDER TO SUBMIT A RESPONSIBLE BID FOR THEIR REMOVAL.

PA052

K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: Bldg—photos Sht 2.dwg
LAYOUT: Layout1
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:59:32 AM
XREF DWG: tbcInt—con2.dwg

REVISIONS					
NUMBER	BY	DATE			
0	1	2			

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).







DESIGN BY:	SMS
DRAWN BY:	CMT
CHECKED BY:	SMS
APPROVED BY:	MLK
DATE:	04/16/10
JOB No:	09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44 SHEET 13 OF 66 SHEETS
















### **NOTES:**

THESE IMAGES REPRESENT EXISTING GENERAL CONDITIONS AT THE SITE AT THE TIME THE IMAGES WERE TAKEN. THE CONTRACTOR IS ENCOURAGED TO VISIT THE SITE AND INSPECT THE BUILDING STRUCTURES AND ANY OTHER FEATURE HE MAY DEEM NECESSARY IN ORDER TO SUBMIT A RESPONSIBLE BID FOR THEIR REMOVAL.



PA052

K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: HAZ.dwg
LAYOUT: HAZ-1
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:09:45 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS					
NUMBER	BY	DATE			

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA HAZ-1 CAMT CRAWFORD, MURPHY & TILLY, N CONSULTING ENGINEERS License No. 184-000613 CHICA-30 EXECUTIVE

 DESIGN BY:
 SD

 DRAWN BY:
 SPB

 CHECKED BY:
 SD


 APPROVED BY:
 GF

 DATE:
 04/16/10

 JOB No:
 09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 14 OF 66 SHEETS



PA052

K:\ChicageExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: ACM.dwg
LAYOUT: ACM-1
UPDATE BY Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:02:11 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS					
NUMBER	BY	DATE			


THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA , MURPHY & TILLY, INC. 3 ENGNEERS 184-000613 CHICA-30 EXECUTIVE CRAWFORD, N CONSULTING E License No. 18

### DESIGN BY: SD DRAWN BY: SPB CHECKED BY: SD APPROVED BY: GF DATE: 04/16/10

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 15 OF 66 SHEETS




REVISIONS					
IUMBER	BY	DATE			

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

# ACM-2 CHICA-30 EXECUTIVE

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44





REVISIONS					
JMBER	BY	DATE			

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07
ILLINOIS PROJE	CT: PWK-3991




REVISIONS					
NUMBER	BY	DATE			
0	1	2			

ACM-5

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07
ILLINOIS PROJE	CT: PWK-3991

A.I.P. PROJECT: 3-17-0018-B44

SHEET 19 OF 66 SHEETS



PA052

K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: ACM.dwg
LAYOUT: ACM-6
UPDATE BP: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:05:53 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### ACM-6


CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA CAWFORD, MARPHY & TILLY, NC. CANSULTING PNGNEERS License No. 184-000613

CHICA-30 EXECUTIVE

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 20 OF 66 SHEETS



PA052

K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: ACM.dwg
LAYOUT: ACM-7
UPDATE BF: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:06:33 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).


### ACM-7


CHICA-30 EXECUTIVE

No.	
DESIGN BY:	SD
RAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
IOB No:	09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 21 OF 66 SHEETS





R:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: ACM.dwg
LAYOUT: ACM-9
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:07:53 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).


### 6-W)

CHICA-O EXECUTIVE CRAWFORD, N CONSULTING E License No. 18

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 23 OF 66 SHEETS



REVISIONS		
IUMBER	BY	DATE


THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA ACM-10 CRAWFORD MURPHY & TILY, NC. CONSULTING ENGINEERS LICENSE No. 184-000613 CHICASO EXECUTIVE

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 24 OF 66 SHEETS



PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets FILE: LEAD.dwg LAYOUT: LBP1 UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:10:47 AM
XREF DWG: tbcInt—con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

# CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA

- 1. CONTRACTOR MUST REMOVE LBP IN ACCORDANCE WITH ITEM 028300 LEAD ABATEMENT.
- LBP POSITIVE YELLOW PAINT WAS IDENTIFIED ON THE CROSS BAR HANGAR DOOR UNIT #34 AND THE TIRE RACK UNIT #2.
- 3. LBP TO REMAIN ON BUILDING COMPONENTS DURING BUILDING DEMOLITION AND BE DISPOSED OF AS GENERAL CONSTRUCTION DEBRIS IN ACCORDANCE WITH CURRENT FEDERAL, STATE AND LOCAL REGULATIONS.
- 4. IF SELECTIVE WORK WILL DISTURB LBP ON COMPONENT, CONTRACTOR MUST ABATE/REMOVE LBP NO LESS THAN ONE FOOT IN ALL DIRECTIONS FROM LOCATION OF PLANNED DISTURBANCE.

LEGEND



= T-HANGAR BUILDINGS TO BE DEMOLISHED



= LBP POSITIVE YELLOW PAINT TO BE REMOVED

ESIGN BY:	SD
RAWN BY:	SPB
CHECKED BY:	SD
PPROVED BY:	GF
ATE:	04/16/10
OB No:	09290-07
	•


CHICA-30 EXECUTIVE

, MURPHY & TILLY, INC. 3 ENGINEERS 184-000613

CRAWFORD, N CONSULTING E License No. 18

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 25 OF 66 SHEETS



PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: LEAD.dwg LAYOUT: LBP2 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:11:28 AM XREF DWG: tbclnt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA ņ BP

- 1. CONTRACTOR MUST REMOVE LBP IN ACCORDANCE WITH ITEM 028300 LEAD ABATEMENT.
- LBP POSITIVE BROWN PAINT WAS IDENTIFIED ON METAL FRAME SUPPORT CROSS BEAMS, METAL FRAME SUPPORT BEAMS, METAL CROSS BARS, I—BEAMS, AND EXTERIOR EAST OFFICE DOOR CASING OF HANGAR 2.
- 3. LBP TO REMAIN ON BUILDING COMPONENTS DURING BUILDING DEMOLITION AND BE DISPOSED OF AS GENERAL CONSTRUCTION DEBRIS IN ACCORDANCE WITH CURRENT FEDERAL, STATE AND LOCAL REGULATIONS.
- 4. IF SELECTIVE WORK WILL DISTURB LBP ON COMPONENT, CONTRACTOR MUST ABATE/REMOVE LBP NO LESS THAN ONE FOOT IN ALL DIRECTIONS FROM LOCATION OF PLANNED DISTURBANCE.

LEGEND
= T-HANGAR BUILDIN TO BE DEMOLISHED
= LBP POSITIVE BRO

	DRAWN BY:
INGS ED	CHECKED BY:
	APPROVED BY:
	DATE:
	JOB No:

DESIGN BY:


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

CRAWFORD, N CONSULTING E License No. 18

CHICAGO EXECUTIVE

SD SPB SD GF 04/16/10 09290-07

SHEET 26 OF 66 SHEETS



PA052

K:\ChicagoEvecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: LEAD.dwg
LAYOUT: LBP3
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:12:07 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

## CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA LBP-3

### NOTE:

- CONTRACTOR MUST REMOVE LBP IN
   ACCORDANCE WITH ITEM 028300 LEAD
   ABATEMENT.
- 2. LBP POSITIVE GREY PAINT WAS IDENTIFIED ON THE HANGAR DOOR CROSS BARS IN UNIT #9.
- 3. LBP TO REMAIN ON BUILDING COMPONENTS DURING BUILDING DEMOLITION AND BE DISPOSED OF AS GENERAL CONSTRUCTION DEBRIS IN ACCORDANCE WITH CURRENT FEDERAL, STATE AND LOCAL REGULATIONS.
- 4. IF SELECTIVE WORK WILL DISTURB LBP ON COMPONENT, CONTRACTOR MUST ABATE/REMOVE LBP NO LESS THAN ONE FOOT IN ALL DIRECTIONS FROM LOCATION OF PLANNED DISTURBANCE.

### LEGEND





= LBP POSITIVE GREY PAINT TO BE REMOVED

= T-HANGAR BUILDINGS TO BE DEMOLISHED


∠	
Τ,	
≓	
AURPHY & ENGINEERS 4-000613	
CMT SAWFORD, MARPHY & TILLY, IN CONSULTING ENGINEERS LICENSE No. 184-000613	

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
JOB No:	09290-07

CHICA-O EXECUTIVE

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 27 OF 66 SHEETS



PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: LEAD.dwg LAYOUT: LBP4
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:12:46 AM XREF DWG: tbclnt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### LBP

CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA

- LBP POSITIVE WHITE PAINT WAS IDENTIFIED ON METAL FRAME SUPPORT CROSS BEAM UNIT #33, HANGAR DOOR OF UNIT #16, AND CEILING IN UNIT #1.
- 3. LBP TO REMAIN ON BUILDING COMPONENTS DURING BUILDING DEMOLITION AND BE DISPOSED OF AS GENERAL CONSTRUCTION DEBRIS IN ACCORDANCE WITH CURRENT FEDERAL, STATE AND LOCAL REGULATIONS.
- 4. IF SELECTIVE WORK WILL DISTURB LBP ON COMPONENT, CONTRACTOR MUST ABATE/REMOVE LBP NO LESS THAN ONE FOOT IN ALL DIRECTIONS FROM LOCATION OF PLANNED DISTURBANCE.

= T-HANGAR BUILDINGS TO BE DEMOLISHED




= LBP POSITIVE WHITE PAINT TO BE REMOVED

CHAT CRAWFORD, MARPHY & TLLY, CONSULTING ENGINEERS LICENSE No. 184-000613	IN A CO EVERITURE

DESIGN BY:	SD
DRAWN BY:	SPB
CHECKED BY:	SD
APPROVED BY:	GF
DATE:	04/16/10
IOB No:	09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 28 OF 66 SHEETS



PA052 K:\ChicogoExecAp\0929007 Txy L Ph 2\Draw\Sheets FILE: LEAD.dwg LAYOUT: LBP5 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:13:25 AM XREF DWG: tbclnt-con2.dwg

REVISIONS		
NUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

### CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA LBP. CHICA-30 EXECUTIVE CRAWFORD, N CONSULTING I License No. 18

DESIGN BY:

DRAWN BY:

DATE:

JOB No:

CHECKED BY:

APPROVED BY:

SD

SPB

SD

GF

04/16/10


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44 SHEET 29 OF 66 SHEETS

### LEGEND

= T-HANGAR BUILDINGS TO BE DEMOLISHED



= LBP POSITIVE ORANGE PAINT TO BE REMOVED



PA052 K:\ChicogoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: LEAD.dwg
LAYOUT: LBP6 UPDATE BY: Jim Ohse SURVEY BOOK #
DATE: Friday, April 16, 2010 10:14:07 AM
XREF DWG: tbclnt-con2.dwg

REVISIONS		
IUMBER	BY	DATE

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA LBP-6

CRAWFORD, CONSULTING License No. 18



DESIGN BY: SD DRAWN BY: SPB CHECKED BY: SD APPROVED BY: GF 04/16/10 JOB No: 09290-07

CHICA-30 EXECUTIVE

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 30 OF 66 SHEETS


- CONTRACTOR MUST REMOVE LBP IN
   ACCORDANCE WITH ITEM 028300 LEAD
   ABATEMENT.
- 2. LBP POSITIVE BEIGE PAINT WAS IDENTIFIED ON ALL EXTERIOR HANGAR SURFACES.
- 3. LBP TO REMAIN ON BUILDING COMPONENTS DURING BUILDING DEMOLITION AND BE DISPOSED OF AS CENTRAL CONSTRUCTION DEBRIS IN ACCORDANCE WITH CURRENT FEDERAL, STATE AND LOCAL REGULATIONS.
- 4. IF SELECTIVE WORK WILL DISTURB LBP ON COMPONENT, CONTRACTOR MUST ABATE/REMOVE LBP NO LESS THAN ONE FOOT IN ALL DIRECTIONS FROM LOCATION OF PLANNED DISTURBANCE.

LEGEND

= LBP POSITIVE BEIGE PAINT TO BE REMOVED

### = T-HANGAR BUILDINGS TO BE DEMOLISHED





PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets FILE: LEAD.dwg LAYOUT: LBP7 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:14:47 AM XREF DWG: tbclnt-con2.dwg

REVISIONS		
BY	DATE	

THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22).

## CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA LBP-7

LEGEND

= T-HANGAR BUILDINGS TO BE DEMOLISHED

= LBP POSITIVE RED PAINT TO BE REMOVED

CRAWFORD, MURPHY & TI CONSULTING ENGINEERS License No. 184-000613




	49
I BY:	SD
BY:	SPB
ED BY:	SD
VED BY:	GF


IGA O EXECUTIVE

DRAWN CHECKE APPROV DATE: 04/16/10 JOB No: 09290-07

ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 31 OF 66 SHEETS





UNDERDRAIN DETAIL

EDGE OF P.C.C. PAVEMENT AREAS

NOT TO SCALE

### **LEGEND**

- (A) NEW 4" BITUMINOUS SURFACE COURSE (401) NEW 4" BITUMINOUS BASE COURSE (403) NEW 18" CRUSHED AGGREGATE BASE COURSE (209)
- B NEW TACK COAT (603)
- © NEW PRIME COAT (602)
- D NEW 6" (AVG.) TOPSOIL STRIPPING (152)
- E NEW EMBANKMENT FILL (152)
- F NEW SHOULDER FILL (152)
- © EXISTING GROUND LINE
- H NEW 10' WIDE SOIL GUARD
- NEW GROUND LINE
- J NEW TOPSOIL PLACEMENT (4" DEPTH) (905)
- (K) NEW SEEDING AND MULCHING (901 AND 908)
- L NEW POROUS BACKFILL (705)
- M NEW 6" CPPUP WITH SOCK (705)
- N NEW SOIL STABILIZATION FABRIC (156)
- O NEW 10" P.C.C. PAVEMENT (501)
- (P) NEW 6" CRUSHED AGGREGATE BASE COURSE (209)
- Q NEW 12" POROUS GRANULAR EMBANKMENT (208)
- R NEW UNCLASSIFIED EXCAVATION (152)
- (S) NEW 2" BITUMINOUS SURFACE COURSE (401) NEW 2" BITUMINOUS BASE COURSE (403) NEW 7" CRUSHED AGGREGATE BASE COURSE (209)

NEW BITUMINOUS ACCESS ROAD TYPICAL SECTION C-C

NOT TO SCALE

(J(K)

## © NEW ACCESS ROAD 1-1/2" (TYP) PROPOSED SHOULDER 12" MINIMUM & VARIES N B C D S E N





PAO52

K\\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: Typsec.dwg
LAYOUT: Layout1
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:25:11 AM
XREF DWG: tbclnt-con2.dwg

NUMBER

CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENT AND EXTEND TAXIWAY LIMA

PHASE

REVISIONS BY

THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).


DATE

NOIL

S


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44


SHEET 32 OF 66 SHEETS





NEW BITUMINOUS TAXIWAY TYPICAL SECTION B-B


NOT TO SCALE


















# FILLET DETAIL AND FILLET REINFORCING LAYOUT

DENOTES ODD SHAPED REINFORCED PANELS TO BE REINFORCED WITH DEFORMED WIRE FABRIC AS SHOWN ON THIS SHEET. ALL NON RECTANGULAR SHAPED PANELS SHALL BE REINFORCED. (REINFORCEMENT NOT SHOWN)




# TABLE 1 DEPTH OF CONTRACTION JOINT INITIAL SAW CUT T, INCHES T=(T/4) ±1/4"

			T	ABLE 2			
ĺ	PAVEMENT	DOV	DOWEL BAR DETAILS		TIE BAR DETAILS		
	THICKNESS T - INCHES	DIA. (d)	LENGTH	SPACING	BAR SIZE	LENGTH	SPACING
	10	1"	19"	12"	#5	30"	30"

I DIMENSION TABLES


PAVEMENT THICKNESS T - INCHES




**EXPANSION JOINTS** 

# JOINT NOTES

- ALL EDGES OF NEW SLABS, FREE STANDING OR CLOSURE, SHALL BE EDGED WITH AN APPROVED TOOL HAVING A RADIUS OF 1/8" TO 1/4" TO FACILITATE SAWING OF THE SEALANT RESERVOIR. A RADIUS > 1/4" WILL NOT BE ACCEPTABLE.
- 2. THE INITIAL SAWCUT FOR ALL LONGITUDINAL AND TRANSVERSE CONTRACTION JOINTS SHALL BE SAWED AS SOON AS POSSIBLE AFTER PLACEMENT OF THE PAYEMENT. SAWING OF LONGITUDINAL CONTRACTION JOINTS ADJACENT TO THE THICKENED EDGES SHALL BE GIVEN PRIORITY OVER OTHER LONGITUDINAL JOINT SAWING.
- 5. ALL DOWEL BARS SHALL BE SECURELY HELD IN PLACE BY MEANS OF A DOWEL BAR ASSEMBLY OR MECHANICALLY INSTALL PER ARTICLE 420,10 JOINTS OF THE ILLINOIS DEPARTMENT OF TRANSPORTATION "STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION", WHICH WILL INSURE THAT THEY WILL REMAIN PARALLEL TO THE PAVEMENT LANES. THE DOWEL BAR ASSEMBLIES OR MECHANICAL METHOD SHALL BE APPROVED BY THE ENGINEER PRIOR TO INSTALLATION.
- ALL TIE BARS AND MESH SHALL BE SECURELY HELD IN PLACE BY SUPPORT PINS OR PLACED BY OTHER APPROVED METHODS TO PREVENT SHIFTING DURING AND AFTER CONCRETE PLACEMENT.
- . WHEN TIE BARS ARE USED FOR SLIP-FORM LONGITUDINAL CONSTRUCTION JOINTS, ONE END OF THE TIE BAR SHALL BE BENT AND INSERTED INTO THE KEYWAY OF THE JOINT. THE BENT BARS SHALL BE STRAIGHTENED TO RIGHT ANGLES WITH LONGITUDINAL JOINT AND SHALL EXTEND INTO THE ADJACENT LANE PARALLET TO THE PAYEMENT SURFACE.
- 5. TIE BARS SHALL BE DEFORMED BARS IN CONFORMANCE WITH ASTM A615 OT ASTM A616, EXCEPT THAT RAIL STEEL BARS, GRADE 50 OR 60 SHALL NOT BE USED FOR THE BARS THAT ARE TO BE BENT OR RESTRAIGHTEND DURING CONSTRUCTION. TIE BARS DESIGNATED AS GRADE 40 IN ASTM A615 CAN BE USED FOR CONSTRUCTION REGARDING BENT BARS.
- THE INITIAL SAWCUT SHALL BE MADE TO THE 1/8" WIDTH INDICATED. INITIAL SAWING TO THE DIMENSION OF THE SECOND SAWCUT WILL NOT BE ALLOWED.
- 8. JOINTS SHALL BE DRY AND CLEAN BEFORE SEALING OPERATIONS BEGIN.
- 9. COST OF ALL JOINT SAWING, CLEANING AND SEALING OF NEW CONCRETE PAVEMENT SHALL BE CONSIDERED INCIDENTAL TO THE ASSOCIATED PAY ITEM AND NO SEPARATE PAYMENT SHALL BE MADE.
- 10. SHOULD THE POURING OPERATIONS REQUIRE THE INSERTION OF AN INTERMEDIATE HEADER, A DOWEL BASKET ASSEMBLY OR OTHER APPROVED METHOD OF DOWEL BAR PLACEMENT SHALL BE REQUIRED.
- 11. DOWEL BASKET ASSEMBLIES MEETING IDOT APPROVAL MAY BE PROPOSED BY THE CONTRACTOR TO BE APPROVED BY THE ENGINEER. DOWELS IN THE APPROVED BASKET ASSEMBLIES SHALL CONFORM TO TABLE 2.





# THICKENED EDGE

SYMBOL

PA052

K:\ChicogoExecAp\0929007 Txy L Ph 2\Draw\Shee
FILE: Details — Jointing.dwg
LAYOUT: Loyout1
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:48:06 AM
XREF DWG: tbcInt-con2.dwg

REVISIONS

NUMBER BY DATE

0 1 2


THIS BAR IS EQUAL TO 2"
AT FULL SCALE (34X22).


# CHICAGO EXECUTIVE AIRPORT IEELING/PROSPECT HEIGHTS, ILLINOIS - RUNWAY 16/34 OFA/RSA IMPROVEMEN' AND EXTEND TAXIWAY LIMA G Ň L N ENT Σ N PHASI CHICAGO DESIGN BY CMT DRAWN BY CMT CHECKED BY SMS APPROVED BY MLK DATE: 04/16/10 JOB No 09290-07


ILLINOIS PROJECT: PWK-3991

SHEET 38 OF 66 SHEETS

A.I.P. PROJECT: 3-17-0018-B44







NOTE : ADDITIONAL REQUIREMENTS FOR CONCRETE MANHOLE CASTINGS. AND RESILIENT SEAL AROUND PIPE ARE IN THE SPECIFICATIONS. FOR CONNECTING EXISTING SEWERS TO PROPOSED MANHOLES, SEE

# TYP. MANHOLE WALL JOINT

# NOTE:

NOTE:

CONC. SUPPORT FOR AN UNDERCUT

SEWER TO BE USED ONLY WHERE REQ'D.

BY THE ENG. AND SHALL BE PAID

FOR PER CU.YD. UNDER "CONC. CRADLE


OR ENCASEMENT" BID ITEM. IF CONC.


SUPPORT IS NOT REQ'D. SELECTED

GRANULAR BACKFILL SHALL EXTEND


TO TOP OF EXIST. SEWER.

MANHOLE TYPE	INSIDE DIA.	MIN. WALL THICKNESS
A-4	4'-0"	5"
A-5	5'-0"	6"
A-6	6'-0"	7"






-PROP. TEE 6" UD 6" UD CORE EXISTING STRUCTURE PROVIDE WATERTIGHT SEAL AT PIPE TO CONNECT PVC TO STORM SEWER CONNECTIONS USING WATER SEALING GROUT.



# **UNDERDRAIN CONNECTION DETAILS**

UNDERDRAIN CONNECTIONS AND FITTINGS, TEES AND ELBOWS USED FOR CONNECTIONS TO PROPOSED STRUCTURES AND STORM SEWERS / EXISTING STRUCTURES AND STORM SEWERS, SHALL BE CONSIDERED INCIDENTAL TO THE PROPOSED UNDERDRAIN.

INSIDE DIAMETER OF STORM SEWER (INCHES)	MAXIMUM TRENCH WIDTH	MAXIMUM PAVEMENT REMOVAL WIDTH
6	3'-7"	5'-7"
8	3'-9"	5'-9"
8 12	4'-2"	6'-2"
15	4'-6"	5'-9" 6'-2" 6'-6"
18	4'-2" 4'-6" 4'-9" 5'-0" 5'-4" 5'-7" 5'-11" 6'-6" 7'-1" 7'-8" 8'-3"	6'-9" 7'-0" 7'-4" 7'-7" 7'-11" 8'-6" 9'-1" 9'-8"
21	5'-0"	7'-0"
24	5'-4"	7'-4"
27	5'-7"	7'-7"
30 36	5'-11"	7'-11"
36	6'-6"	8'-6"
42	7'-1"	9'-1"
42 48	7'-8"	9'-8"
54	8'-3"	
60	8'-10"	10'-10" 11'-5" 12'-0" 12'-7" 13'-2" 13'-9" 14'-4" 14'-11"
66 72	9'-5"	11'-5"
72	I 10°-0°'	12'-0"
78	10'-7"	12'-7"
84	10'-7" 11'-2" 11'-9"	13'-2"
90	11'-9"	13'-9"
96	12'-4" 12'-11"	14'-4"
102	12'-11"	14'-11"
108	13'-6"	15'-6"



TRENCH DETAILS NOT TO SCALE

NON-PAVED AREAS

└ GRANULAR CRADLE (IDOT CA-6)

# STORM SEWER/UNDERDRAIN NOTES

- CONTRACTOR SHALL FIELD VERIFY EXISTING STORM SEWER/UNDERDRAIN INVERTS BEFORE INSTALLING PROPOSED
- ALL UNDERDRAIN CONNECTIONS, CORING INTO STRUCTURES, TEES, BENDS, STORM SEWER ETC. SHALL BE CONSIDERED INCIDENTAL TO THE COST OF THE UNDERDRAIN.
- 3. UNDERDRAIN SLOPES FOLLOW EDGE OF PAVEMENT SLOPE UNLESS OTHERWISE NOTED.
- 4. INSTALL PROPOSED ELECTRICAL DUCTS/CONDUITS TO BE CLEAR OF UNDERDRAIN, COST INCIDENTAL.
- 5. UNDERDRAIN CONFLICTS WITH EXISTING CONDITIONS SHALL BE RESOLVED AND COST SHALL BE INCIDENTAL TO
- PRIOR TO ORDERING AND INSTALLING ALL FIELD TILE REPLACEMENT PIPE, THE CONTRACTOR SHALL FIELD VERIFY THE LOCATION AND INVERTS OF EXISTING FIELD TILE CONNECTIONS. ADJUSTMENTS SHALL BE MADE AS NECESSARY AT NO ADDITIONAL COST TO THE CONTRACT.
- 7. CORING OF DRAINAGE STRUCTURE AND REMOVAL OF EXISTING STORM SEWER MANHOLE/INLET CONCRETE BENCHES TO FACILITATE CONNECTIONS OF PROPOSED STORM SEWER PIPE SHALL BE CONSIDERED INCIDENTAL TO THE COST OF THE PIPE.

PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Shee FILE: Details - Drainage.dwg LAYOUT: Layout1 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:54:33 AM XREF DWG: tbclnt-con2.dwg


	REVISIONS			
NUMBER	BY	DATE		
0	1	2		
Tillo D	10.10.50111	TO 0"		


THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).

# CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA <u>ত</u> œ SE MURPHY & ENGINEERS 90 CRAWFORD, N DESIGN BY: MLK DRAWN BY JRO CHECKED BY: SMS APPROVED BY: MLK DATE: 04/16/10

JOB No:


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44 SHEET 41 OF 66 SHEETS





SECTION-B


NO SCALE



PROVIDE BENT-CLIP TYPE FASTENER FOR REMOVING PANELS (STAINLESS STEEL)

SADDLE CLIP


NO SCALE



# GRATING DETAILS - PLAN VIEW

NO SCALE

ONE SECTION OF GRATING DETAILED.
TOTAL OF 3 SECTIONS REQUIRED FOR 12" & 15". TOTAL OF 4 SECTIONS REQUIRED FOR 18"
TOTAL OF 5 SECTIONS REQUIRED FOR 24".
SEE SPECIAL PROVISIONS FOR FURTHER DETAILS.




BAR L NO SCALE BAR U, U1 AND U2 NO SCALE

# BILL OF MATERIALS INLET BOX


TYPE	BAR	QUANTITY	SIZE	LENGTH
12"	h	4	#4	9'-11"
15"	h	4	#4	11'-7"
18"	h	6	#4	13'-8"
24"	h	6	#4	17'-6"
12"	h1	2	#4	8'-0"
15"	h1	2	#4	10'-0"
18"	h1	2	#4	12'-0"
24"	h1	2	#4	15'-0"
12"	L	4	#4	2'-0"
15"	ī	4	#4	2'-0"
18"	Ē	4	#4	2'-0"
24"	L	4	#4	2'-0"
12"	U	4	#4	5'-2"
15"	Ü	6	#4	5'-6"
18"	Ü	8	#4	5'-9"
24"	Ü	12	#4	6'-4"
12"	U1	4	#4	4'-8"
15"	U1	3	#4	5'-0"
18"	U1	4	#4	5'-3"
24"	U1	4	#4	5'-10"
12"	U2	2	#4	4'-8"
15"	U2	2	#4	5'-0"
18"	U2	2	#4	5'-3"
24"	U2	2	#4	5'-10"
12"	V	4	#4	1'-4"
15"	V	4	#4	1'-8"
18"	V	6	#4	1'-10"
24"	V	6	#4	2'-5"
12"	V1	_	#4	_
15"	V1	4	#4	1'-4"
18"	V1	6	#4	1'-5"
24"	V1	6	#4	2'-0"
12"	V2	_	#4	
15"	V2 V2	_	#4	_
18"	V2 V2	_	#4	_
24"	V2	8	#4	1'-6"
CONC	DETE CI	RUCTURES		
12"ø	NEIE 31	ROCTORES	CU.YD.	2
15"ø			CU.YD.	2
18"ø			CU.YD.	3
24"ø			CU.YD.	3
	OPCELLE	NT BARS		
	ORCEME	CAND IN	POUND	85
12"0			POUND	100
12"ø 15"ø				
15"ø			POUND	145
12"ø 15"ø 18"ø 24"ø			POUND POUND	145 200
15"ø 18"ø 24"ø	NC.		POUND	
15"ø 18"ø 24"ø GRATII	NG		POUND	200
15"ø 18"ø 24"ø GRATII 12"ø	NG		POUND SQ.FT.	200
15"ø 18"ø 24"ø GRATII	NG		POUND	200

# TABLE OF DIMENSIONS

DIMENSION	12 <b>"</b> ø	15 <b>"</b> ø⁄	18"ø	24"ø
Α	10'-3"	12\ <del>/</del> 1"	14'-0"	17 ×10"
В	2'-6"	2'-1Q"	3'-1"	3/-8"
С	9'-5"	11'-4'	13'-3"	17'-1"\



# SECTION A-A NO SCALE



PA052 k:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets
FILE: Details — Slopebox.dwg \_AYOUT: Layout1 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:45:36 AM XREF DWG: tbclnt-con2.dwg


	REVISIONS	i
NUMBER	BY	DATE
,		


THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22).


CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS PHASE 2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS AND EXTEND TAXIWAY LIMA	SLOPE BOX INLET DETAILS
CMT CRAWFORD, MARPHY & TILY, INC. CONDUITED ENDINGS	CHICAGO EXECUTIVE
DESIGN BY:	MLK
DRAWN BY:	JRO
CHECKED BY:	SMS
APPROVED BY:	MLK
DATE: JOB No:	04/16/10
JOB No:	09290-07


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 42 OF 66 SHEETS










	AIRFIELD SIGNAGE SCHEDULE				
NEW	NEW	NEW	NEW	NEW	
SIGN	SIGN	SIGN	SIGN	SIGN	
NUMBER	FACE	LEGEND	TYPE	LOCATION	
S1	N	BΓVNK	0	STA. 638+34, 100' LT.	
	S	11 ♣	3	Ç RUNWAY 16/34	
S2	N	BFVNK	0	STA. 438+84, 50' LT.	
	S	◆1.1 1	2,3	© TAXIWAY L	
S3	W E	BFVNK	0 2,3	STA. 7+25, 50' RT. Ç TAXIWAY L1	
S4	W	†Σ-91 [1]	2,1	STA. 7+43, 50'LT.	
	E	BLANK	0	© TAXIWAY L1	
S5	z o	BFVNK	0	STA. 441+37, 50'LT.	
RELOCATED SIGN		BDAZZBM	3	© TAXIWAY L	
S6	z s	רן ורש BLANK	3,2 0	STA. 441+34, 50'RT. Ç TAXIWAY L	
S7	W E	BFVNK	0 3,2	STA. 7+25, 50' RT. © TAXIWAY L	

# PAVEMENT MARKING NOTES

- 1. ALL TAXIWAY MARKINGS ARE YELLOW WITH A 6" BLACK BORDER.
- 2. THE PAVEMENT SURFACE SHALL BE CLEAN AND DRY PRIOR TO MARKING.

# NEW SIGN TYPE LEGEND

- 0 BLANK PANEL BLACK
- 1 RUNWAY/TAXIWAY HOLDLINE WHITE LEGEND ON RED BACKGROUND
  2 LOCATION SIGN YELLOW LEGEND ON BLACK BACKGROUND
  3 DIRECTION/INFORMATION SIGN BLACK LEGEND ON YELLOW BACKGROUND



## LEGEND

	<u>LEGEND</u>
0 0	EXISTING BASE/STAKE MOUNTED MEDIUM INTENSITY TAXIWAY LIGHT
	EXISTING BASE/STAKE MOUNTED/IN-PAVEMENT HIGH INTENSITY RUNWAY LIGHT
	EXISTING AIRFIELD GUIDANCE SIGN
	EXISTING CONDUIT/DUCT BANK
0	EXISTING ELECTRIC/STORM/SANITARY MANHOLE/WATER VALVE VAULT
	EXISTING ELECTRIC HANDHOLE
16/34	EXISTING RUNWAY 16/34 CIRCUIT
6/24	EXISTING RUNWAY 6/24 CIRCUIT
G/D	EXISTING TAXIWAY G AND D CIRCUIT
DLY	EXISTING TAXIWAY D,L,M,N,Y AND 2 CIRCUIT
ABEF	EXISTING TAXIWAY A,B,E AND F CIRCUIT
REIL	EXISTING REIL CABLES
——— FAA-E ———	EXISTING FAA CABLES
RGL	EXISTING RUNWAY GUARD LIGHT CIRCUIT
RDR	EXISTING RUNWAY DISTANCE REMAINING CIRCUIT
	EXISTING RUNWAY 6 PAPI CIRCUIT (3 $\#4$ XLP-USE, 1 $\#8$ GND. IN 2" PVC CONDUIT 1-6 PAIR $\#18$ SHIELDED IN 2" PVC W/ BARE COUNTERPOISE)
REIL 12	EXISTING RUNWAY 12 REIL CIRCUIT (2 #4 XLP-USE, 1 #8 GND. IN 2" PVC CONDUIT)
PAPI 12	EXISTING RUNWAY 12 PAPI CIRCUIT (3 $\#4$ XLP-USE, 1 $\#8$ GND. IN 2" PVC CONDUIT 1-6 PAIR $\#18$ SHIELDED IN 2" PVC W/ BARE COUNTERPOISE)
•	NEW BASE MOUNTED MEDIUM INTENSITY QUARTZ TAXIWAY LIGHT
$A^{\blacksquare}_{W}_{W}^{\bullet}_{W}$	NEW BASE/IN-PAVEMENT QUARTZ RUNWAY LIGHT — A — AMBER LENSE W — WHITE LENSE
	NEW AIRFIELD GUIDANCE SIGN
● <sub>S</sub>	NEW SPLICE CAN
	NEW ELECTRIC HANDHOLE
	NEW MULTI-WAY PCC ENCASED DUCT BANK
	NEW 2" GRS CONDUIT
	NEW 2" PCC ENCASED SPLIT DUCT
	NEW RUNWAY GUARD LIGHT CIRCUIT
_ · _ · _	NEW TAXIWAY LIMA CIRCUIT
	NEW TAXIWAY A, B, D, E, F AND Y (ABDEFY) CIRCUIT
—— 16/34 ——	NEW RUNWAY 16/34 CIRCUIT
	NEW RUNWAY 6/24 CIRCUIT
<del></del>	NEW $1/C$ #8, 5KV, L-824, TYPE C CABLE IN 2" PVC CONDUIT, DIRECT BURIED NUMBER OF TICK MARKS INDICATE NUMBER OF CABLES (TYPICAL FOR ALL AIRFIELD LIGHTING CIRCUITS)

# ELECTRICAL / LIGHTING NOTES

- 1. SEE EXISTING CONDITIONS FOR LIGHTING REMOVALS.
- 2. ALL EXISTING TAXIWAY AND RUNWAY AIRFIELD LIGHTING CIRCUITS, FAA CABLES AND OTHER AIRPORT ELECTRICAL CABLES SHALL REMAIN IN SERVICE UNTIL REPLACED AS DIRECTED BY THE RESIDENT ENGINEER. ALL TEMPORARY CABLING AND SPLICING SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.
- 3. AT ANY LOCATION WHERE THE NEW DUCT OR CABLE ROUTE CROSSES AN EXISTING UTILITY, THE CONTRACTOR SHALL HAND EXCAVATE AND LOCATE THE EXISTING UTILITY PRIOR TO TRENCHING. COST OF LOCATING ALL EXISTING UTILITIES SHALL BE INCIDENTAL TO THE CONTRACT.
- 4. THE LOCATION OF EXISTING UTILITIES ARE APPROXIMATE. THE CONTRACTOR SHALL OPEN THE ENTIRE TRENCH BETWEEN MANHOLES BEFORE ANY CONDUIT IS LAID TO ASCERTAIN THE EXISTENCE AND POSITION OF ANY
- 5. CONTRACTOR SHALL COORDINATE THE LOCATION OF THE EXISTING AND PROPOSED UTILITIES PRIOR TO INSTALLATION OF THE PROPOSED UNIT DUCTS, CONDUITS AND DUCT BANKS. ANY DAMAGES TO EXISTING UTILITIES SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR'S EXPENSE.
- 6. CONTRACTOR SHALL PROVIDE PULL WIRE FOR ALL DUCT BANKS AND CAP THE UNUSED DUCT BANKS FOR FUTURE USE.
- 7. CONTRACTOR SHALL CONNECT EXISTING CABLE TO NEW CABLE IN SIGN/LIGHT/MANHOLE/HANDHOLE/SPICE CAN. COST OF CONNECTION SHALL BE INCIDENTAL TO THE CABLE.
- 8. NO 90 DEGREE BENDS WILL BE ALLOWED IN CONDUIT.
- 9. CONTRACTOR SHALL CORE HOLES INTO EXISTING MANHOLES/HANDHOLES AS REQUIRED. THE COST OF CORING AND GROUTING SHALL BE INCIDENTAL TO THE INSTALLATION OF THE PROPOSED CABLE OR DUCT.
- 10. ALL LIGHTS SHALL HAVE QUARTZ BULBS. ALL SIGNS SHALL BE LED.
- 11. AT EXISTING DUCT BANKS THAT FALL WITHIN THE NEW PAVEMENT, THE CONTRACTOR SHALL STAMP OR OTHERWISE MARK THE DUCT LOCATION WITHIN THE PAVEMENT, AS DIRECTED BY THE RESIDENT ENGINEER,
- 12. ALL SPLICES SHALL BE WATERPROOF. COST OF SPLICES SHALL BE INCIDENTAL TO THE COST OF THE CABLE.
- 13. RELOCATED SIGN SHALL BE INSTALLED ON A NEW BASE WITH NEW BASE CAN, NEW MOUNTING HARDWARE AND NEW TRANSFORMER. THE EXISTING SIGN IS FOUR MODULES.
- 14. SEE NEW CABLE LAYOUT SHEETS 1 THROUGH 4 FOR ELECTRICAL CIRCUIT INSTALLATION INFORMATION.
- 15. REMOVAL OF AIRFIELD LIGHTING CIRCUIT CABLE WHERE CALLED OUT IN PLANS SHALL BE CONSIDERED INCIDENTAL TO INSTALLATION OF NEW CABLE.

PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheet FILE: lighting—bypass.dwg LAYOUT: Lavout1 UPDATE BY: johse SURVEY BOOK # DATE: Fri 4/16/10 8:46am XREF DWG: light-mark—Txy L.dwg
KEYMAP.dwg
tbclnt-con2.dwg
base-con2-pavement.dw
base-con2-airfield.dwg

REVISIONS					
NUMBER	BY	DATE			
0	1	2			
THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).					

# CHICAGO EXECUTIVE AIRPORT WHEELING/PROSPECT HEIGHTS, ILLINOIS : 2 - RUNWAY 16/34 OFA/RSA IMPROVEMI AND EXTEND TAXIWAY LIMA 귑 OUT Y L1 > < IG LA

LIGHTING T#

CMT CRAWFORD, MURPHY & TILY, INC. CONSULTING ENGINEERS LICENSE No. 184-000613	


PHASE


CHICAGO EXECUTIVE DESIGN BY CMT CHECKED BY SMS


APPROVED BY: DATE: 04/16/10 JOB No: 09290-07


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44


SHEET 46 OF 66 SHEETS














# 200' FROM POINT OF TANGENCY PROPOSED 12" WIDE YELLOW TAXIWAY & W/ 6" BLACK BORDER (TYP.) FO.5' & EXISTING 3' WIDE WHITE RUNWAY & STRIPE

# TAXIWAY LEAD-IN TANGENT DETAIL

NOT TO SCALE








# 2' TO HOLDING POSITION MARKER 15" VARIES PER 15" 15" VARIES PER LEGEND 15" VARIES PER LEG

# SURFACE PAINTED HOLDING POSITION SIGN

NOT TO SCALE

- 1. ALL SURFACE PAINTED HOLDING POSITION SIGNS SHALL HAVE A RED BACKGROUND WITH A WHITE INSCRIPTION.
- 2. ALL SURFACE PAINTED LOCATION SIGNS SHALL HAVE A BLACK BACKGROUND WITH A YELLOW INSCRIPTION.
- 3. ALL SURFACE PAINTED SIGNS SHALL BE OUTLINED WITH A 6" BLACK BORDER.
- 4. LEGENDS SHALL BE AS SHOWN ON THE LIGHTING AND PAVEMENT MARKING PLAN SHEETS 1
- 5. ALL LETTERS, NUMBERS AND SYMBOLS SHALL CONFORM TO FIGURES A-1 THROUGH A-5 IN FAA ADVISORY CIRCULAR 150/5340-1J (LATEST EDITION), APPENDIX 1.



### RUNWAY HOLDING POSITION MARKING

NOT TO SCALE

PA052

K:\ChicogoExecAp\0929007 Txy L Ph 2\Draw\Sheet:
FILE: Details — Marking.dwg
LAYOUT: Layout1

UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:47:15 AM
XREF DWG: tbcInt—con2.dwg

REVISIONS			
NUMBER	BY	DATE	
0	1	2	

THIS BAR IS EQUAL TO 2 AT FULL SCALE (34X22).

CHICAGO EXECUTIVE AIRPORT
WHEELING/PROSPECT HEIGHTS, ILLINOIS
2 - RUNWAY 16/34 OFA/RSA IMPROVEMENTS
AND EXTEND TAXIWAY LIMA
PAVEMENT MARKING DETAILS

CRAWFORD, MJRPHY & TILLY, NC. CONSULTNG ENGNEERS License No. 184-000613

PHASE

CRAWFORD, MJRPH CONSULTING ENGIN

 DESIGN BY:
 CMT

 DRAWN BY:
 CMT

 CHECKED BY:
 SMS


 APPROVED BY:
 MLK

 DATE:
 04/16/10

 JOB No:
 09290-07


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 52 OF 66 SHEETS




# TYPE A - CABLE SPLICE

FOR SPLICES IN HOMERUNS AND FOR EXTENSIONS
TO EXISTING CABLES ONLY



# TYPE B - CABLE SPLICE

FOR SPLICES FOR USE AT JUNCTION OF HOMERUN WITH LOOP CIRCUIT N.T.S.




# TYPE C AND D - CABLE SPLICE

FOR SPLICES AT
RUNWAY/TAXIWAM.T.BOHTS AND SIGNS


# **NOTES**

- INSIDE DIAMETER OF CONNECTOR SHALL PROPERLY MATCH THE OUTSIDE DIAMETER OF CABLE.
- 2. WRAP WITH AT LEAST ONE LAYER OF RUBBER OR SYNTHETIC RUBBER TAPE AND ONE LAYER OF PLASTIC TAPE, ONE—HALF LAPPED, EXTENDING AT LEAST 1—1/2 INCHES ON EACH SIDE OF JOINT.
- 3. THE COST OF FURNISHING AND INSTALLING ALL SPLICE MATERIALS SHALL BE INCIDENTAL TO THE ASSOCIATED CABLE ITEMS.
- 4. THE CONTRACTOR SHALL HAVE A MINIMUM OF TWO (2) TYPE A SPLICE KITS ON THE JOB SITE AT ALL TIMES FOR EMERGENCY REPAIRS.



# NOTES

- INSTALL A NON-CORROSIVE DISC OF 2"
   MINIMUM DIAMETER WITH THE NUMBER
   PERMANENTLY STAMPED, CUT OUT, OR
   ENGRAVED UNDER THE HEAD OF THE BASE
   PLATE BOLT OR ATTACHED TO LIGHT FLANGE
   WITH A SET SCREW.
- 2. NUMERALS SHOWN ARE FOR ILLUSTRATIVE PURPOSES ONLY. ALL EXISTING AND PROPOSED TAXIWAY AND RUNWAY LIGHTS AND SIGNS SHALL BE TAGGED AS DIRECTED BY THE RESIDENT ENGINEER. ALL LIGHTS ON EXISTING CIRCUITS THAT HAVE LIGHTING IMPROVEMENTS (PROPOSED OR RELOCATED LIGHTS) SHALL BE RETAGGED.
- 3. COST OF TAGGING LIGHTS SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT.




# TURF AREA CABLE TRENCH DETAIL

OT TO SCALE


# **NOTES**

- TRENCHES WITH MORE THAN 2 CABLES SHALL BE INCREASED 3" IN WIDTH FOR EACH ADDITIONAL CABLE. IF SPECIFIED ON PLANS, TWO PARALLEL TRENCHES MAY BE CONSTRUCTED.
- 2. DEPTH OF TRENCHES SHALL BE AS SHOWN UNLESS OTHERWISE SPECIFIED ON THE PLANS.
- 3. SAND BACKFILL SHALL BE USED IF THE EXISTING SOIL DOES NOT MEET THE BACKFILL REQUIREMENTS.
- 4. ALL DISTURBED SURFACES SHALL BE RESTORED TO THEIR ORIGINAL CONDITION. COST IS INCIDENTAL.
- 5. FAA RTR CABLES SHALL BE INSTALLED IN 4" PVC AS SHOWN ON PLAN. BOTH CABLES SHALL BE INSTALLED IN THE SAME DUCT.
- 6. THE COST OF COUNTERPOISE CABLE AND GROUND RODS SHALL BE INCIDENTAL TO PAY ITEMS FOR PAPI AND FAA RTR CABLES.




# RUNWAY/TAXIWAY LIGHTING CIRCUIT CONNECTION DETAIL

NOT TO SCALE




# CONCRETE ENCASED DUCT END DETAIL NO SCALE




# EXTENSION OF EXISTING DUCT

NOTE: COST OF CONNECTION SHALL BE CONSIDERED INCIDENTAL TO PROPOSED DUCT.



# DUCT MARKER DETAIL

PROPOSED PAVEMENT



4-WAY

ELECTRICAL DUCT


TURF

2-WAY


# CONCRETE ENCASED DUCT BANKS NOT TO SCALE

# **NOTES**

- 1. DIMENSIONS ARE MINIMUM.
- 2. CONCRETE SHALL CONFORM TO ITEM 610.
- 3. ALL CONDUIT SHALL BE SCHEDULE 40 PVC.
- 4. TOP OF CONCRETE ENCASEMENT IN TURF AREAS SHALL NOT BE LESS THAN 24" BELOW FINISHED GRADE.
- 5. 4" SPLIT DUCT SHALL BE CONCRETE ENCASED WITH 3" MINIMUM CONCRETE SURROUNDING 4" CONDUIT. COST INCIDENTAL TO SPLIT DUCT.



# LIGHT IDENTIFICATION DETAIL NOT TO SCALE




# INSTALLATION OF ELEVATED RGL (TYPICAL)


NOT TO SCALE

# **GENERAL NOTES**

- 1. TRANSFORMER HOLDER MAY BE ANY COMMERCIALLY AVAILABLE BRICK.
- 2. BREAKING GROOVE COUPLINGS SHALL NOT BE OVER 1" ABOVE GROUND LINE.
- 3. ISOLATION TRANSFORMERS COME WITH A FACTORY INSTALLED PLUG (TYPE 1, CLASS A, STYLE 2) AND RECEPTACLE (TYPE 1, CLASS A, STYLE 9). A TYPE 1, CLASS B, STYLE 3 PLUG AND TYPE 1, CLASS B, STYLE 10 RECEPTACLE SHALL BE INSTALLED ON THE 1/C, No. 8, 5000 V., L-824 TYPE C CABLES FOR CONNECTION TO EACH TRANSFORMER.
- 4. TO FURTHER REDUCE THE POSSIBILITY OF WATER/MOISTURE ENTRANCE INTO THE CONNECTOR BETWEEN THE CABLE AND THE FIELD ATTACHED CONNECTOR, IT IS REQUIRED THAT A HEAT SHRINKABLE TUBING WITH INTERNAL ADHESIVE BE APPLIED OVER THE ENTIRE CABLE CONNECTOR.
- 5. ALL LIGHTS, CABLES AND TRANSFORMERS TO BE REMOVED SHALL REMAIN THE THE PROPERTY OF THE AIRPORT. AT THE DISCRETION OF THE AIRPORT MANAGER THE CONTRACTOR MAY BE REQUIRED TO DISPOSE OF THESE MATERIALS OFFSITE.
- DUCT MARKERS SHALL BE INSTALLED AT EVERY NEW DUCT AND AT EVERY EXISTING DUCT USED FOR THIS PROJECT.



# CONC ENCASED (4-WAY) ELECTRICAL DUCT BACKFILL NOT TO SCALE




# ELEVATED RGL LAYOUT DETAIL (TYPICAL)

NOT TO SCALE

# NOTES

 DISTANCE FROM TXY. EDGE MAY BE INCREASED UP TO A MAXIMUM OF 17' AND A MINIMUM OF 12'. KEEP BOTH BOXES AT SAME DISTANCE FROM TAXIWAY PAVEMENT.




14"

# ADJUST REIL DETAIL

NOT TO SCALE

# **NOTES**

 CONTRACTOR TO DISCONNECT EXISTING POWER AND CONTROL WIRES, ADJUST REIL VERTICALLY AND RE—CONNECT POWER AND CONTROL WIRES.



### SIGNAGE NOTES

- 1. ALL SIGNS ARE 2—SIDED LED SIGNS. STYLE 2 AND CLASS 2 AS MANUFACTURED BY ADB OR APPROVED EQUAL.
- 2. TRANSFORMER WATTAGE AS RECOMMENDED BY MANUFACTURER FOR LED SIGNS.
- 3. LIGHTED SIGNS SHALL BE BASE MOUNTED ONLY.
- 4. THE NUMBER OF MODULES PER SIGN SHALL BE AS RECOMMENDED BY THE MANUFACTURER.
- 5. CONTRACTOR SHALL SUBMIT DETAILED SHOP DRAWING INCLUDING SIGN, COLOR, SIZE AND PROPOSED LEGEND, IN ENOUGH DETAIL AND DETERMINE PROPOSED SPACING AND OTHER INFORMATION REQUIRED BY SPECIAL PROVISIONS. CONTRACTOR TO VERIFY PROPOSED SIGN LOCATIONS AND ORIENTATIONS WITH RESIDENT ENGINEER PRIOR TO INSTALLATION.

PA052

K:\ChicagoExeckp\0929007 Txy L Ph 2\Draw\Sheet
FILE: Details — Electrical — 2.dwg
LAYOUT: Layout1
UPDATE BY: Jim Ohse
SURVEY BOOK #
DATE: Friday, April 16, 2010 10:52:13 AM
XREF DWG: tbcInt—con2.dwg

REVISIONS		
NUMBER	BY	DATE
0	1	2
THIS BAR IS EQUAL TO 2" AT FULL SCALE (34X22).		


# CHICAGO EXECUTIVE AIRPORT ELING/PROSPECT HEIGHTS, ILLINOIS RUNWAY 16/34 OFA/RSA IMPROVEMENT AND EXTEND TAXIWAY LIMA S S S ~ N SE CRAWFORD DESIGN BY CMT DRAWN BY CMT CHECKED BY SMS APPROVED BY MLK DATE 04/16/10

JOB No:

ILLINOIS PROJECT: PWK-3991

A.I.P. PROJECT: 3-17-0018-B44

SHEET 54 OF 66 SHEETS



# 5. AFTER CONCRETE HAS SET, REMOVE HOOP TOOL AND MUD PLATE. INSTALL FLANGE AND SPACER RINGS AS REQUIRED AND LIGHT ASSEMBLY. A TEMPORARY STEEL COVER MAY BE INSTALLED IF LIGHT FIXTURE IS TO BE

6. AFTER FIXTURE INSTALLATION, FILL THE ANNULAR SPACE BETWEEN THE FIXTURE BASE AND SURROUNDING PAVEMENT WITH P-606 SEALANT. ANNULAR SPACE SHALL BE NO MORE THAN 3/4" WIDE.

CAUTION TO AVOID AGGREGATE SEGREGATION DURING THIS PROCEDURE.

7. INSTALL BASE AND RINGS SO THAT OUTER EDGE OF LIGHT FIXTURE WILL BE AT SAME ELEVATION AS THE FINISHED PAVEMENT SURFACE TO (+) 0" (-) 1/16" TOLERANCE. THE TOTAL THICKNESS OF THE SPACER/FLANGE RINGS SHALL BE NO LARGER THAN 3/4" MAX. NO MORE THAN 3 RINGS SHALL BE USED.

# EXISTING ELEVATED TAXIWAY/RUNWAY LIGHT TO BE ADJUSTED

EXISTING

CAN

EXISTING CONCRETE

6" (TYP.) -

PROPOSED P.C.

CONCRETE (610) SLOPE TO DRAIN (TYP)

PLAN VIEW

- EXISTING CONCRETE TO BE

REMOVED (TYP)

NOT TO SCALE

SURVEY BOOK # DATE: Friday, April 16, 2010 10:51:24 AM XREF DWG: tbcInt-con2.dwg **REVISIONS** RY DATE NUMBER THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22). CHICAGO EXECUTIVE AIRPORT IEELING/PROSPECT HEIGHTS, ILLINOIS - RUNWAY 16/34 OFA/RSA IMPROVEM AND EXTEND TAXIWAY LIMA N 90 DESIGN BY CMT CMT CHECKED BY SMS APPROVED BY JOB No 09290-07 ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44


SHEET 55 OF 66 SHEETS

FILE: Details - Electrical - 3.dwg

LAYOUT: Lavout1

UPDATE BY: Jim Ohse





# PROP. AIRFIELD ELECT. VAULT PLAN VIEW

1/4" = 1'-0'


### NOTES:

- 1. ALL PROPOSED WORK OR ITEMS BEING MODIFIED ARE SHOWN IN BOLD. ALL OTHER ITEMS SHOWN ARE
- 2. CONTRACTOR SHALL REMOVE EXISTING 10KW REGULATOR AND INSTALL NEW 30KW REGULATOR. INSTALL NEW 100A, 2-POLE DISCONNECT AND POWER FEED AND RE-INSTALL EXISTING CONTROLS AND TAXIWAY CIRCUIT.
- 3. REMOVE EXISTING 30A CIRCUIT BREAKER IN HV DISTRIBUTION PANEL AND REPLACE WITH NEW 100A, 2-POLE CIRCUIT BREAKER. MATCH EXISTING CIRCUIT BREAKER AND UPDATE CIRCUIT DIRECTORY

# PROPOSED VAULT NOMENCLATURE

- 1) EXISTING 30KW (5-STEP) REGULATOR FOR RUNWAY 16/34.
- 2 EXISTING 20KW (5-STEP) REGULATOR FOR RUNWAY 6/24.
- 3 EXISTING 20KW (5-STEP) REGULATOR FOR RUNWAY 12/30.
- 4 EXISTING 10KW (3-STEP) REGULATOR FOR TAXIWAY G,D AND 34 HOLD APRON.
- (5) EXISTING 10KW (3-STEP) REGULATOR FOR RUNWAY 16/34 RDR.
- 6 EXITSTING 15KW (3-STEP) REGULATOR FOR RUNWAY 16/34 RGL.
- 7 EXISTING 10 KW (3-STEP) REGULATOR FOR RUNWAY 16 APPROACH LIGHTING.
- (8) EXISTING 10 KW (3-STEP) REGULATOR FOR HFC APRON LIGHTING.
- 9 EXISTING 10KW (3-STEP) REGULATOR FOR TAXIWAY A,B,E AND F.
- 10 EXISTING 20KW (3-STEP) REGULATOR FOR TAXIWAY K.
- (11) EXISTING 30 KW (5-STEP) REGULATOR FOR SPARE (STAND-BY) USE.
- 12 EXISTING 30KW (3-STEP) REGULATOR FOR TAXIWAY D,L,M,N AND Y.
- (13) EXISTING 10KW (3-STEP) REGULATOR FOR TAXIWAY C.
- (14) FUTURE AIRFIELD LIGHTING REGULATOR.
- (15) EXISTING MAIN UTILITY SERVICE CIRCUIT BREAKER DISCONNECT. 800A, 480V, 3-POLE.
- (16) EXISTING AUTOMATIC TRANSFER SWITCH. 800A, 480V, 3-POLE.

- (7) EXISTING HIGH VOLTAGE POWER DISTRIBUTION PANEL. 480V, 3-PHASE WITH 800AMP MAIN CIRCUIT BREAKER. INSTALL 1-100A, 2-POLE CIRCUIT BREAKER IN EXISTING PANELBOARD (SEE NOTE 3).
- (18) EXISTING 150KVA, 480V-280Y/120V, 3Ø, 4-WIRE TRANSFORMER.
- $\ensuremath{\textcircled{19}}$  EXISTING LOW VOLTAGE LIGHTING PANEL. 208Y/120V, 3-PHASE WITH 400AMP MAIN CIRCUIT BREAKER.
- $\ensuremath{\textcircled{20}}$  existing PLC control cabinet to be modified. See vault control details sheet.
- (21) EXISTING 800AMP CT CABINET.
- (22) EXISTING 12"x12"x12' LONG HIGH VOLTAGE WIREWAY.
- (23) EXISTING 12"X12"x12' LONG LOW VOLTAGE WIREWAY.
- (24) EXISTING 12"x12"x9' LONG HIGH VOLTAGE WIREWAY. HOMERUN CABLES FOR PROPOSED TAXIWAY C CIRCUIT SHALL BE TIED INTO SECONDARY CABLES FROM REGULATOR IN WIREWAY USING L-823 CONNECTORS. CONNECTORS SHALL BE TARDED AND LABELED. TAPED AND LABELED.
- (25) EXISTING 12"x12"x9' LONG LOW VOLTAGE WIREWAY.
- 26 NEW 30KW (3-STEP) REGULATOR FOR TAXIWAY A,B,D,E,F AND Y (SEE NOTE 2).
- 27 NEW 2 #2 THWN, 1 #4 GND. IN EXISTING 4" GRS CONDUIT FOR TAXIWAY A,B,D,E,F AND Y REGULATOR.
- (28) NEW 2 #2 THWN, 1 #4 GND. (POWER) AND EXISTING 4 #12 THWN (CONTROLS) IN NEW 2" FLEX CONDUIT (PROVIDE 3'MIN. SLACK).



# PROPOSED L-821 CONTROL PANEL MODIFICATIONS

# NOTES:

- 1. CONTRACTOR SHALL COORDINATE ALL WORK IN THE EXISTING CONTROL TOWER WITH THE AIRWAYS FACILITIES AND THE RESIDENT ENGINEER. CONTRACTOR SHALL GIVE A MINIMUM OF 2 DAYS NOTICE PRIOR TO BEGINNING WORK IN THE TOWER.
- 2. PROPOSED WORK OF ITEMS BEING MODIFIED ARE SHOWN IN BOLD. ALL OTHER ITEMS SHOWN ARE FOR INFORMATIONAL PURPOSES ONLY.
- 3. NEW LABELS SHALL MATCH THE EXISTING LABELS.

PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets FILE: Details - Electrical - 4.dwg LAYOUT: Layout1 UPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:50:37 AM XREF DWG: tbcInt-con2.dwg

> REVISIONS NUMBER BY DATE


> > THIS BAR IS EQUAL TO 2' AT FULL SCALE (34X22)

# CHICAGO EXECUTIVE AIRPORT HEELING/PROSPECT HEIGHTS, ILLINOIS P - RUNWAY 16/34 OFA/RSA IMPROVEMENT AND EXTEND TAXIWAY LIMA Σ ~ Ш Ш S **O** CRAWFORD, CONSULTING

DRAWN BY JRO CHECKED BY SMS APPROVED BY DATE: 04/16/10 JOB No:


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44

SHEET 56 OF 66 SHEETS




## NOTES:

- THE LOCATION OF THE NEW KEY PAD, OPERATED GATE DRIVER, DISCONNECT, KEY PAD, AND DETECTOR LOOPS ARE FOR INFORMATION ONLY AND SHALL BE FIELD ADJUSTED PER THE MANUFACTURER RECOMMENDATION.
- 2. THE MINIMUM BURIAL DEPTH FOR GRS CONDUIT IS 24" BELOW FINISHED GRADE.
- 3. NO DIRECT BURIED CABLE WILL BE ALLOWED IN THE INSTALLATION OF THE NEW KEY PAD OPERATED GATE DRIVER.
- NEW KEY PAD SHALL BE MODEL # 55-LCK1000 BY LINK CONTROLS OR EQUAL.
- 5. INSTALL ADDITIONAL KEYPAD AT THE GATE OPERATOR FOR PEDESTRIAN EXIT.




flaor OR AS RECOMMENDED BY MFG.



# NEW KEY PAD OPERATED GATE AND DETECTOR LOOP LAYOUT

NOT TO SCALE

PER MANUFACTURERS RECOMENDATION CONTRACTOR SHALL COORDINATE THIS WORK WITH ENGINEEER.



# DIGITAL KEY PAD MOUNTING DETAIL


OCATIONS, DETAILS AND CHARACTER OF EQUIPMENT SHOWN ON THIS SHEET ARE GENERIC. EQUIPMENT LOCATIONS SHALL BE AS RECOMMENDED BY THE EQUIPMENT MANUFACTURER.

# VEHICULAR BARRIER DETAIL

- THE VEHICULAR BARRIERS WILL NOT BE MEASURED SEPARATELY FOR PAYMENT BUT SHALL BE CONSIDERED INCIDENTAL TO ELECTRIC GATE.
- LOCATION OF UNDERGROUND ELECTRICAL ITEMS SHALL BE COORDINATED WITH VEHICULAR BARRIERS TO AVOID ANY CONFLICTS.


## NOTES:

- CANTILEVERED GATE SHALL BE SUFFICIENTLY RIGID TO WITHSTAND FLEXING OR BENDING DURING WINDY CONDITIONS. CONTRACTOR SHALL PROVIDE STIFFENERS, STRUCTURAL SHAPES IN EXCESS OF THE MINIMUM SPECIFIED DIMENSIONS OR ADDITIONAL ROLLERS AND POSTS SUFFICIENT TO PREVENT DISPLACEMENT OF THE GATE BY WIND OR BY UNAUTHORIZED PERSONNEL.
- CONTRACTOR SHALL PROVIDE AND INSTALL GATE AS A COMPLETE WORKING UNIT. THE GATE WORK SHALL INCLUDE, BUT NOT BE LIMITED TO THE GATE, GATE OPERATOR AND FOUNDATION, AND POWER CABLES CONDUIT, CARD, READER, TRENCHING, CIRCUIT BREAKERS, VEHICULAR BARRIERS AND ALL CONNECTIONS, LABOR AND MATERIALS NECESSARY TO COMPLETE OPERATION.
- LOCATION OF THE GATE OPERATOR SHALL BE AS RECOMMENDED BY THE MANUFACTURER.
- THE FABRIC TYPE AND FINISH OF THE GATE SHALL MATCH WITH THE PROPOSED FENCE OR AS DIRECTED BY THE ENGINEER.
- ALL PROPOSED SLIDING VEHICULAR GATES SHALL HAVE ENCLOSED TRUCK ASSEMBLIES, PAGE FORTRESS OR EQUAL.



# SERVICE ENTRANCE AND PANELBOARD

NOT TO SCALE



NOT TO SCALE

PA052 K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheets FILE: Details — Electric Gate.dwg LAYOUT: Layout1 JPDATE BY: Jim Ohse SURVEY BOOK # DATE: Friday, April 16, 2010 10:53:46 AM XREF DWG: tbcInt-con2.dwg

(BACKFRAME)

**SECTION** 

C OF ROLLER

ITEM 610 CONCRETE

GATE OPENING

FROST LEG (TYP.) -

GATE POST (TYP.)

BY DATE

REVISIONS

WIRE AS DETAILED PER PLAN VIEWS

INSULATED BUSHING 1/2"x 12" THREADED "J" ANCHOR BOLTS (4 REQD.)

└ 2" MIN.

FENCE @

OPERATOR 🛼

#4 REBAR (TYP.)

3/4" R.S. CONDUIT STUB UP 2" (TYP. OF 2)

BACK FRAME EXTENSION

6" Ø FROST LEG (TYP. OF 4)

THIS BAR IS FOUAL TO 2 AT FULL SCALE (34X22).

CHICAGO EXECUTIVE AIRPORT IEELING/PROSPECT HEIGHTS, ILLINOIS - RUNWAY 16/34 OFA/RSA IMPROVEM AND EXTEND TAXIWAY LIMA

ш

G

9

N


PHASE


3 DESIGN BY: MLK DRAWN BY JRO


CHECKED BY SMS APPROVED BY: MLK DATE 04/16/10 JOB No: 09290-07


ILLINOIS PROJECT: PWK-3991 A.I.P. PROJECT: 3-17-0018-B44


SHEET 58 OF 66 SHEETS











































SHEET 66 OF 66 SHEETS

PA052

K:\ChicagoExecAp\0929007 Txy L Ph 2\Draw\Sheet
FILE: Eng Info.dwg
LAYOUT: Layout1

UPDATE BY: Jim Ohse
SURVEY BOOK #

NUMBER

DATE: Friday, April 16, 2010 10:43:06 AM
XREF DWG: tbcInt-con2.dwg
taxiway-base-con2.dwg
base-con2-pavement.dwg
topo-txy-L.DWG

**REVISIONS** 

BY

DATE