

1. COVER SHEET
2. GENERAL NOTES & STATUS OF UTILITIES
- 3-6. SUMMARY OF QUANTITIES
7. SCHEDULE OF QUANTITIES
8. LINE DIAGRAM
9. TYPICALS
- 10-11. DETOUR PLAN
12. DRAINAGE DETAILS
- 13-61. STRUCTURE DETAILS
- 62-63. CADD STANDARDS

HIGHWAY STANDARDS

701400-10	701428-01
701401-12	701451-05
701402-12	701901-08
701406-12	704001-08
701411-09	780001-05
701426-09	782006-01

DESIGN DESIGNATION

INTERSTATE


<u>I-74</u>	<u>I-474 EB</u>
ADT: 38800 (2017)	ADT: 13800 (2017)
MU: 1850	MU: 400
SU: 700	SU: 350

FREEWAY

<u>IL 6 EB</u>	<u>IL 6 WB</u>
ADT: 35000 (2019)	ADT: 9500 (2017)
MU: 1050	MU: 300
SU: 1250	SU: 500

RAMPS (2017)

<u>RAMP D</u>	<u>RAMP C</u>	<u>RAMP E</u>
ADT: 4150	ADT: 6900	ADT: 1100
MU: 50	MU: 175	MU: 60
SU: 100	SU: 200	SU: 90



FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.


J.U.L.I.E.
JOINT UTILITY LOCATION INFORMATION FOR EXCAVATORS
1-800-892-0123
OR 811

PROJECT ENGINEER: RICH DOTSON (309)671-3455
PROJECT MANAGER: ANNA DEVINE (309)671-3475
CONTALOG NO. 035641-00D
CONTRACT NO. 68E52

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

**PROPOSED
HIGHWAY PLANS**

FAI ROUTE 474 & 74
FAP ROUTE 318 (I-474, I-74, IL 6)
SECTION 72(1HB,HB-1,2,3)BR
PROJECT NHPP-R034(528)
BRIDGE REHABILITATION
PEORIA COUNTY
C-94-087-18




PROJECT LOCATION
SN 072-0106,-0107,
-0108,-0109,-0110,
-0111

GROSS LENGTH = 2,700 FT. = 0.51 MILE
NET LENGTH = 2,700 FT. = 0.51 MILE

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORA	63*	1
		ILLINOIS	CONTRACT NO. 68E52	

* 63 + 12 = 75 TOTAL SHEETS
63 + 16 = 79 TOTAL SHEETS
D-94-065-18



PROJECT DESCRIPTION:
BRIDGE REHABILITATION TO 6 STRUCTURES, SN 072-0106, -0107, -0108, -0109, -0110, & -0111. REHABILITATION INCLUDES, BUT NOT LIMITED TO: HYDROSCARIFY AND MICROSILICA OVERLAY, JOINT REPLACEMENTS, DECK PATCHING, PARAPET WALL EXTENSIONS, SUBSTRUCTURE REPAIRS, AND ANY OTHER RELATED COLLATERAL WORK NECESSARY TO COMPLETE THIS PROJECT AS SHOWN IN THE PLANS AND AS DESCRIBED HEREIN.

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBMITTED March 19, 2021
Paul A. Jones
REGION THREE ENGINEER

May 7, 2021
Scott A. Elk
ENGINEER OF DESIGN AND ENVIRONMENT

May 7, 2021
James M. Jones
DIRECTOR OF HIGHWAYS PROJECT IMPLEMENTATION 13

**PRINTED BY THE AUTHORITY
OF THE STATE OF ILLINOIS**

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION	
				0006	CODE 0013
				ROADWAY	BRIDGE
				90% FED	90% FED
				10% STATE URBAN	10% STATE URBAN
20700220	POROUS GRANULAR EMBANKMENT	CU YD	3	3	
28100225	STONE RIPRAP, CLASS B3	TON	6	6	
28100825	STONE DUMPED RIPRAP, CLASS B3	TON	59	59	
42001300	PROTECTIVE COAT	SQ YD	5893		5893
Z0004556	HOT - MIX ASPHALT SURFACE REMOVAL, (DECK)	SQ YD	5580		5580
44201785	CLASS D PATCHES, TYPE 1, 12 INCH	SQ YD	4	4	
50102400	CONCRETE REMOVAL	CU YD	125.1		125.1
50300100	FLOOR DRAINS	EACH	19		19
50300225	CONCRETE STRUCTURES	CU YD	3.7		3.7
50300255	CONCRETE SUPERSTRUCTURE	CU YD	130		130
50300260	BRIDGE DECK GROOVING	SQ YD	5453		5453
50500405	FURNISHING AND ERECTING STRUCTURAL STEEL	POUND	26,150		26,150
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	11,310		11,310
50800515	BAR SPLICERS	EACH	156		156
50800530	MECHANICAL SPLICERS	EACH	144		144

MODEL: D:\default\...
 FILE: 68E52...
 PROJECT: 04_68E52...
 DISTRICT: 4...
 SHEETS: 0468E52...

USER NAME = *USER*	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 1:1000	CHECKED -	REVISED -
PLOT DATE = 3/19/2021	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	3
ILLINOIS FED. AID PROJECT			CONTRACT NO. 68E52	

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION		
				0006	CODE 0013	
				ROADWAY	BRIDGE	
				90% FED	90% FED	
				10% STATE URBAN	10% STATE URBAN	
52000110	PREFORMED JOINT STRIP SEAL	FOOT	878		878	
52100010	ELASTOMERIC BEARING ASSEMBLY, TYPE 1	EACH	46		46	
52100520	ANCHOR BOLTS, 1"	EACH	80		80	
52100530	ANCHOR BOLTS, 1 1/4"	EACH	68		68	
63301210	REMOVE AND RE-ERECT STEEL PLATE BEAM GUARD RAIL, TYPE A	FOOT	12.5	12.5		
67000400	ENGINEER'S FIELD OFFICE, TYPE A	CAL MO	11	11		
67100100	MOBILIZATION	L SUM	1	1		
70100207	TRAFFIC CONTROL AND PROTECTION, STANDARD 701402	EACH	4	4		
70100420	TRAFFIC CONTROL AND PROTECTION, STANDARD 701411	EACH	2	2		
70100700	TRAFFIC CONTROL AND PROTECTION, STANDARD 701406	L SUM	1	1		
70100800	TRAFFIC CONTROL AND PROTECTION, STANDARD 701401	L SUM	1	1		
70100820	TRAFFIC CONTROL AND PROTECTION, STANDARD 701451	L SUM	1	1		
70107005	PAVEMENT MARKING BLACKOUT TAPE, 5"	FOOT	2351	2351		
70107007	PAVEMENT MARKING BLACKOUT TAPE, 7"	FOOT	20	20		
70107009	PAVEMENT MARKING BLACKOUT TAPE, 9"	FOOT	700	700		

MODEL: Defaul...
 FILE: \\server\com\des\illinois\p\DOT Documents\DOT District 4\Projects\04_68E52\CAD\as\CD\sheet\0468E52-ant-500.dgn

USER NAME = #USER*	DESIGNED -	REVISED -
	DRAWN -	REVISED -
PLOT SCALE = 1/100	CHECKED -	REVISED -
PLOT DATE = 3/19/2021	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	4
ILLINOIS FED. AID PROJECT			CONTRACT NO. 68E52	

MODEL: D:\default\...
 FILE: 68E52.dwg
 PROJECT: DISTRICT 4
 CONTRACT: 68E52
 SHEETS: 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100

CODE NO.	ITEM	UNIT	TOTAL QUANTITY	CONSTRUCTION CODE	
				0006 ROADWAY 90% FED 10% STATE URBAN	0013 BRIDGE 90% FED 10% STATE URBAN
70107025	CHANGEABLE MESSAGE SIGN	CAL DA	370	370	
70300150	SHORT TERM PAVEMENT MARKING REMOVAL	SQ FT	7634	7634	
70300904	PAVEMENT MARKING TAPE, TYPE IV 4"	FOOT	18354.5	18354.5	
70400100	TEMPORARY CONCRETE BARRIER	FOOT	2975	2975	
70400200	RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	2450	2450	
70600250	IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3	EACH	4	4	
70600350	IMPACT ATTENUATORS, RELOCATE (NON- REDIRECTIVE), TEST LEVEL 3	EACH	4	4	
* 78009004	MODIFIED URETHANE PAVEMENT MARKING - LINE 4"	FOOT	5649	5649	
* 78009006	MODIFIED URETHANE PAVEMENT MARKING - LINE 6"	FOOT	568	568	
* 78009008	MODIFIED URETHANE PAVEMENT MARKING - LINE 8"	FOOT	1310	1310	
X5017305	PROTECTIVE SHIELD (PERMANENT)	SQ YD	1804		1804
X6025602	MANHOLES TO BE ADJUSTED WITH FRAME AND GRATE (SPECIAL)	EACH	1	1	
Z0001899	JACK AND REMOVE EXISTING BEARINGS	EACH	80		80
Z0003600	BEAM STRAIGHTENING	L SUM	1		1
Z0012130	BRIDGE DECK SCARIFICATION 3/4"	SQ YD	5580		5580



*= SPECIALTY ITEM

USER NAME = #USER*	DESIGNED -	REVISED -
PLOT SCALE = 1/100	DRAWN -	REVISED -
PLOT DATE = 3/19/2021	CHECKED -	REVISED -
	DATE -	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SUMMARY OF QUANTITIES

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	5
ILLINOIS FED. AID PROJECT			CONTRACT NO. 68E52	



GENERAL NOTES

All structural steel shall conform to AASHTO Classification M-270 Gr. 36, unless otherwise noted.
 Reinforcement bars designated (E) shall be epoxy coated.
 Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.
 Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
 Joint openings shall be adjusted according to Article 520.04 of the Std. Specs. when the deck is poured at an ambient temperature other than 50° F.

TOTAL BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Concrete Removal	Cu. Yd.	18.4
Concrete Superstructure	Cu. Yd.	20.0
Preformed Joint Strip Seal	Foot	181
Reinforcement Bars, Epoxy Coated	Pound	3360
Bar Splicers	Each	40
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	3.7
* Protective Coat	Sq. Yd.	1835
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	538
Hot-Mix Asphalt Surface Removal Deck	Sq. Yd.	1746
Furnishing & Erecting Structural Steel	Pound	8570
Elastomeric Bearing Assembly, Type I	Each	14
Jack & Remove Existing Bearings	Each	28
Anchor Bolts, 1 1/4"Ø	Each	56
Protective Shield (Permanent)	Sq. Yd.	494
Floor Drains	Each	7
Bridge Deck Grooving	Sq. Yd.	1721
Bridge Deck Microsilica Concrete Overlay, 2 1/4"	Sq. Yd.	1746
Bridge Deck Scarification, 3/4"	Sq. Yd.	1746
Polymer Concrete	Cu. Ft.	8.1

* On new concrete and overlay areas



Expires 11/30/2022

- (A) - Remove and replace expansion joint with Preformed Joint Strip Seal.
- (B) - Bearing removal and replacement at Abutments.
- (C) - HMA Surface Removal, Bridge deck scarification with new Microsilica Concrete Overlay and Bridge Deck Grooving.
- (D) - Wingwall and Railing Modifications. See sheet 12 of 14 for details.
- (E) - Polymer Concrete Nosing. See sheet 8 of 14 for details.
- (F) - Substructure Repairs


DESIGNED - Jeffrey S. Burke	EXAMINED - <i>Ting A. Deck</i>	DATE - MAY 07, 2021
CHECKED - Chi-Cheung Chau	ENGINEER OF STRUCTURAL SERVICES	
DRAWN - <i>jostermann</i> Venkat Ramana	PASSED - <i>Chi Carl Puzey</i>	REVISED - 05/28/2021 JSB
CHECKED - JSB CCC	ENGINEER OF BRIDGES AND STRUCTURES	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**GENERAL PLAN AND ELEVATION
F.A.I. 474 OVER F.A.I. 74
SN 072-0106 (SB) & 072-0107 (NB)**

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	13
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				


SHEET NO. 1 OF 14 SHEETS



CROSS SECTION THRU SPANS 1 & 3 AT ABUTMENT
(Looking South)



CROSS SECTION THRU SPAN 2 AT ABUTMENT
(Looking South)



TYPICAL CROSS SECTION THRU MID-SPAN
(Looking South)

* Radial to CL of FAI 474

Entire Sheet
1

DESIGNED - JSB
CHECKED - CCC
DRAWN - Jim Ostermann VVR
CHECKED - JSB CCC

EXAMINED
PASSED
Timothy A. [Signature]
ENGINEER OF STRUCTURAL SERVICES
[Signature]
ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 07, 2021
REVISED 05/28/2021 JSB
REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

STAGING CROSS SECTIONS
SN 072-0106 (SB)


SHEET NO. 2 OF 14 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	14
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				


REVIS 6/1/21



CROSS SECTION THRU SPANS 1 & 3 AT ABUTMENT
(Looking South)



CROSS SECTION THRU SPAN 2 AT ABUTMENT
(Looking South)




TYPICAL CROSS SECTION THRU MID-SPAN
(Looking South)

* Radial to CL of FAI 474

Sheet Added
1

DESIGNED - JSB	EXAMINED - <i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 07, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	STAGING CROSS SECTIONS SN 072-0107 (NB)	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CHECKED - CCC	PASSED - <i>Carl Rieger</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED - 05/28/2021 JSB			474	72(1HB,HB-1,2,3)BR	PEORIA	63	14A
DRAWN - Jim Ostermann VVR			SHEET NO. 2A OF 14 SHEETS		CONTRACT NO. 68E52				
CHECKED - JSB CCC					ILLINOIS FED. AID PROJECT				




PLAN

Notes:
 Areas of deck repairs shown are estimated. The Engineer shall show actual locations of deck repairs on As-built Plans.
 An estimated amount of 70 S.F of Structural Repair of Concrete (depth less than or equal to 5") was added to each structure for repairs to the underside of the overhang soffit.

N.B. Traffic
 S.N. 072-0107


S.B. Traffic
 S.N. 072-0106




FLOOR DRAIN DETAILS
 (7-Locations)

DRAIN REPAIR LEGEND

- - Previously plugged drains to be removed by full depth deck patch.
- - Floor Drain to be removed with full depth deck patch and replaced with new floor drains.




CONCRETE REMOVAL & REPLACEMENT
 PLAN AT FLOOR DRAINS
 Existing reinf. to remain.




TOP PLAN
 (Showing Aluminum Tube)

SECTION A-A


* Dimension as req'd by Pipe Clamp.



OVERLAY TREATMENT
 AT FLOOR DRAINS



SECTION THRU CONCRETE REMOVAL &
 REPLACEMENT AT FLOOR DRAINS



BILL OF MATERIAL

Item	Unit	Total
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	3.7
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	140
Floor Drains	Each	7

DESIGNED - JSB
 CHECKED - CCC
 DRAWN - Jim Ostermann VVR
 CHECKED - JSB CCC

EXAMINED
 PASSED
 ENGINEER OF STRUCTURAL SERVICES
 ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 07, 2021
 REVISED 05/28/2021 JSB
 REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

DECK SLAB REPAIR
 SN 072-0106 (SB) & 072-0107 (NB)


SHEET NO. 3 OF 14 SHEETS

F.A.I. RTE. 474 SECTION 72(1HB,HB-1,2,3)BR COUNTY PEORIA TOTAL SHEETS 63 SHEET NO. 15 CONTRACT NO. 68E52 ILLINOIS FED. AID PROJECT


REVISED 6/1/21




CONCRETE REMOVAL DETAILS
N. ABUT., 072-0106 (S.B.)



CONCRETE REPLACEMENT DETAILS
N. ABUT., 072-0106 (S.B.)



SECTION A-A
(Near Center Roadway)
(Dims at RT Ls to end of deck)



SECTION B-B
(Near Center Roadway)
(Dims at RT Ls to end of deck)

Notes:
Hatched areas indicate removal.
Bend a(E) bars in field as necessary.
For bar details and Bill of Material, see sheet 8 of 14.

* Measured radially to centerline F.A.I. 474.

DESIGNED - JSB
CHECKED - CCC
DRAWN - Jim Ostermann VVR
CHECKED - JSB CCC

EXAMINED
PASSED
ENGINEER OF STRUCTURAL SERVICES
ENGINEER OF BRIDGES AND STRUCTURES


DATE - MAY 07, 2021
REVISED 05/28/2021 JSB
REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


JOINT REMOVAL AND REPLACEMENT DETAILS - N. ABUT.
SN 072-0106 (SB)

SHEET NO. 4 OF 14 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	16
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				




CONCRETE REMOVAL DETAILS
S. ABUT., 072-0106 (S.B.)



CONCRETE REPLACEMENT DETAILS
S. ABUT., 072-0106 (S.B.)



SECTION A-A
(Near C Roadway)
(Dims at RT L's to end of deck)



SECTION B-B
(Near C Roadway)
(Dims at RT L's to end of deck)

Notes:
Hatched areas indicate removal.
Bend a(E) bars in field as necessary.
For bar details and Bill of Material, see sheet 8 of 14.

* Measured radially to C F.A.I. 474.

DESIGNED - JSB
CHECKED - CCC
DRAWN - Jim Ostermann VVR
CHECKED - JSB CCC

EXAMINED
PASSED
ENGINEER OF STRUCTURAL SERVICES
ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 07, 2021
REVISED 05/28/2021 JSB
REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

JOINT REMOVAL AND REPLACEMENT DETAILS - S. ABUT.
SN 072-0106 (SB)


SHEET NO. 5 OF 14 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	17
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				


REVISED 6/1/21




CONCRETE REMOVAL DETAILS
N. ABUT., 072-0107 (N.B.)



CONCRETE REPLACEMENT DETAILS
N. ABUT., 072-0107 (N.B.)



SECTION A-A
(Near C Roadway)
(Dims at RT L's to end of deck)




SECTION B-B
(Near C Roadway)
(Dims at RT L's to end of deck)


Notes:
Hatched areas indicate removal.
Bend a(E) bars in field as necessary.
For bar details and Bill of Material, see sheet 8 of 14.

* Measured radially to C F.A.I. 474.


DESIGNED - JSB	EXAMINED - <i>Timothy A. Daulton</i>	DATE - MAY 07, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION		JOINT REMOVAL AND REPLACEMENT DETAILS - N. ABUT. SN 072-0107 (NB)		F.A.I. RTE. 474	SECTION 72(1HB,HB-1,2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 18
CHECKED - CCC	PASSED - <i>Carl R. Roper</i>	REVISOR 05/28/2021 JSB					ILLINOIS	FED. AID PROJECT			
DRAWN - Jim Ostermann VVR	ENGINEER OF BRIDGES AND STRUCTURES	REVISOR -	SHEET NO. 6 OF 14 SHEETS		CONTRACT NO. 68E52						
CHECKED - JSB CCC							REVISED 6/1/21				




CONCRETE REMOVAL DETAILS
S. ABUT., 072-0107 (N.B.)



CONCRETE REPLACEMENT DETAILS
S. ABUT., 072-0107 (N.B.)



SECTION A-A
(Near Centerline Roadway)
(Dims at RT Ls to end of deck)



SECTION B-B
(Near Centerline Roadway)
(Dims at RT Ls to end of deck)

Notes:
Hatched areas indicate removal.
Bend a(E) bars in field as necessary.
For bar details and Bill of Material, see sheet 8 of 14.

* Measured radially to Centerline F.A.I. 474.

DESIGNED - JSB
CHECKED - CCC
DRAWN - Jim Ostermann VVR
CHECKED - JSB CCC

EXAMINED
PASSED
ENGINEER OF STRUCTURAL SERVICES
ENGINEER OF BRIDGES AND STRUCTURES


DATE - MAY 07, 2021
REVISED 05/28/2021 JSB
REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


JOINT REMOVAL AND REPLACEMENT DETAILS - S. ABUT.
SN 072-0107 (NB)

SHEET NO. 7 OF 14 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	19
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				




SECTION THRU BRIDGE PARAPET




SECTION THRU SPAN 1 & 3 PARAPET


See Sheets 2 & 2A of 14 for dimensions



POLYMER CONCRETE NOSING DETAIL




VIEW C-C




RAIL POST ANCHORAGE DEVICE DETAILS

New Rail Post Anchorage Devices will be required at locations where posts are connected to new concrete. Cost to be included with Concrete Removal (8-Required)




BAR d2(E)

Min. Bar Laps
#5 = 3'-6"
#6 = 4'-10"



BARS d(E)



BAR d1(E)

BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a(E)	32	#6	6'-0"	—
a1(E)	8	#5	25'-6"	—
a2(E)	8	#5	27'-10"	—
a3(E)	8	#5	25'-3"	—
a4(E)	8	#5	26'-10"	—
a5(E)	8	#5	22'-1"	—
a6(E)	8	#5	22'-4"	—
a7(E)	8	#5	24'-2"	—
a8(E)	8	#5	22'-2"	—
d(E)	32	#5	4'-10"	—
d1(E)	32	#5	3'-8"	—
d2(E)	24	#4	2'-3"	—
h(E)	16	#6	6'-0"	—
h1(E)	2	#6	25'-6"	—
h2(E)	2	#6	27'-10"	—
h3(E)	2	#6	25'-3"	—
h4(E)	2	#6	26'-10"	—
h5(E)	2	#6	22'-1"	—
h6(E)	2	#6	22'-4"	—
h7(E)	2	#6	24'-2"	—
h8(E)	2	#6	22'-2"	—
Concrete Removal		Cu. Yd.	18.4	
Concrete Superstructure		Cu. Yd.	20.0	
Reinforcement Bars, Epoxy Coated		Pound	2910	

DESIGNED - JSB
CHECKED - CCC
DRAWN - Jim Ostermann VVR
CHECKED - JSB CCC

EXAMINED
PASSED
ENGINEER OF STRUCTURAL SERVICES
ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 07, 2021
REVISED 05/28/2021 JSB
REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

JOINT REPLACEMENT DETAILS
SN 072-0106 (SB) & 072-0107 (NB)


SHEET NO. 8 OF 14 SHEETS

F.A.I. RTE. 474
SECTION 72(1HB,HB-1,2,3)BR
COUNTY PEORIA
TOTAL SHEETS 63
SHEET NO. 20
CONTRACT NO. 68E52
ILLINOIS FED. AID PROJECT

REVISION 6/1/21



FOR SKEWS $\leq 30^\circ$
PLAN AT PARAPET




SECTION C-C

Notes:
The strip seal shall be made continuous and shall have a minimum thickness of $\frac{1}{4}$ ". The configuration of the strip seal shall match the configuration of the locking edge rails. Open or "webbed" strip seal gland configurations are not permitted. The gland shall be sized for a maximum rated movement of 4 inches.
The locking edge rails depicted are configured for typical applications and are conceptual only. The actual configuration of the locking edge rails and matching strip seal may vary from manufacturer to manufacturer provided they fit the application and meet the minimum anchorage shown. Flanged edge rails, however, will not be allowed. Locking edge rails may exceed the $4\frac{1}{2}$ " maximum depth provided the anchorage system is revised according to the manufacturer's recommendation.
The manufacturer's recommended installation methods shall be followed.


All steel components shall be galvanized after fabrication according to Article 520.03 of the Standard Specifications.
The Maximum space between locking edge rail segments shall be $\frac{3}{16}$ " and sealed with a suitable sealant; however, any rail joint within 10' measured perpendicular to the face of the curb or parapet shall be welded as shown in the locking edge rail splice detail.

Cost of parapet sliding plates, embedded plates, and anchorage studs included with Preformed Joint Strip Seal.
39" constant slope barrier shown, 44" constant slope barrier similar as noted.


The concrete opening below the strip seal will vary based on the locking edge rail chosen by the Contractor. Deck and parapet lengths shown elsewhere in the plans are dimensioned to the concrete opening, not the joint opening, and are based on the rolled locking edge rail. If the Contractor elects to use a different locking edge rail, dimensional adjustments may be required. One exception to this would be the strip seal joint at the end of the precast bridge approach slab. For these cases the pavement connector length shall be adjusted, not the length of the bridge approach slab.




SECTION A-A



SECTION B-B




TRIMETRIC VIEW
(Showing back plates only)




SECTION THRU ROLLED RAIL JOINT

* $\frac{3}{8}$ " \varnothing x 6" studs at 6" cts. (alternate angled/bent studs with horizontal studs)
 $\frac{3}{8}$ " \varnothing threaded rods in $\frac{7}{16}$ " \varnothing holes at ± 4 "-0" cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned, or sawed off flush with the plates after concrete is set.

* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.




SECTION THRU WELDED RAIL JOINT



LOCKING EDGE RAILS

** Back gouge not required if complete joint penetration is verified by mock-up.



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue.
Rolled rail shown, welded rail similar.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	181

DESIGNED - JSB
CHECKED - CCC
DRAWN - Jim Ostermann VVR
CHECKED - JSB CCC

EXAMINED
PASSED
ENGINEER OF STRUCTURAL SERVICES
ENGINEER OF BRIDGES AND STRUCTURES


DATE - MAY 07, 2021
REVISED 05/28/2021 JSB
REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL
SN 072-0106 (SB) & 072-0107 (NB)


SHEET NO. 9 OF 14 SHEETS

F.A.I. RTE. 474
SECTION 72(1HB,HB-1,2,3)BR
COUNTY PEORIA
TOTAL SHEETS 63
SHEET NO. 21
CONTRACT NO. 68E52
ILLINOIS FED. AID PROJECT



ELEVATION AT ABUTMENT

TYPE I ELASTOMERIC EXP. BRG.



SECTION A-A

BEAM REACTIONS

		072-0106(SB)	072-0107(NB)
R _p	(K)	86.2	76.7
R _t	(K)	49.3	43.3
Imp.	(K)	10.6	9.3
R (Total)	(K)	146.1	129.3

Notes:

Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.

New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel.


Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).

Min. jack capacity = 83 Tons.


Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (F_y=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.


Cost of Side retainers and Stainless Steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.




PLAN TOP AND BOTTOM PLATE



SECTION B-B




STEEL EXTENSION DETAIL



BEARING ASSEMBLY


Note:

Shim plates shall not be placed under Bearing Assembly.





EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.



TOP BEARING PLATE TO GIRDER CONNECTION DETAIL

Str. No.	Angle "A"
0106 (SB)	10°28'58"
0107 (NB)	10°28'24"



SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.

1/4" Stainless steel plate, A240, Type 304, No. 1 finish

TYI/REPS 5-17-2018

DESIGNED - JSB	EXAMINED - Timothy A. [Signature]	DATE - MAY 07, 2021
CHECKED - CCC	ENGINEER OF STRUCTURAL SERVICES	
DRAWN - Jim Ostermann	VVR	REVISOR - 05/28/2021 JSB
CHECKED - JSB	CCC	ENGINEER OF BRIDGES AND STRUCTURES



STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

BEARING REPLACEMENT - NORTH ABUTMENTS SN 072-0106 (SB) & 072-0107 (NB)

SHEET NO. 10 OF 14 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	22
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				




REVISED 6/1/21







BEAM REACTIONS

	072-0106(SB)	072-0107(NB)
R _U (K)	86.2	76.7
R _L (K)	49.3	43.3
Imp. (K)	10.6	9.3
R (Total) (K)	146.1	129.3


Notes:
 Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.
 New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel.
 Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).
 Min. jack capacity = 83 Tons.
 Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (F_y=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.
 Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.
 Cost of Side retainers and Stainless Steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.



FIXED BEARINGS



Str. No.	Angle "A"
0106 (SB)	10°28'58"
0107 (NB)	10°28'24"



EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.

BILL OF MATERIAL

Item	Unit	Total
Jack and Remove Existing Bearings	Each	14
Furnishing and Erecting Structural Steel	Pound	5140
Anchor Bolts, 1 1/4 inch	Each	28

DESIGNED - JSB
 CHECKED - CCC
 DRAWN - Jim Ostermann VVR
 CHECKED - JSB CCC

EXAMINED
 PASSED
 ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 07, 2021
 REVISED 05/28/2021 JSB
 REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BEARING REPLACEMENT - SOUTH ABUTMENTS
 SN 072-0106 (SB) & 072-0107 (NB)


SHEET NO. 11 OF 14 SHEETS

F.A.I. RTE. 474
 SECTION 72(1HB,HB-1,2,3)BR
 COUNTY PEORIA
 TOTAL SHEETS 63
 SHEET NO. 23
 CONTRACT NO. 68E52
 ILLINOIS FED. AID PROJECT


REVISED 6/1/21




PROPOSED ELEVATION



INSIDE VIEW AT APPROACH BENT




SECTION A-A




PLAN


* Epoxy v(E) bars in 9" min. holes according to Article 584 of the Standard Specs.



CAST END CAP



BAR u(E)



BAR v(E)

NOTES

Reinforcement bars designated (E) shall be epoxy coated.
 Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

**TOTAL BILL OF MATERIAL
8 LOCATIONS**

Bar	No.	Size	Length	Shape
h9(E)	48	#5	5'-2"	—
u(E)	32	#4	3'-5"	□
v(E)	48	#5	2'-4"	U
Concrete Superstructure			Cu. Yd.	1.6
Reinforcement Bars, Epoxy Coated			Pound	450

DESIGNED - JSB
 CHECKED - CCC
 DRAWN - Jim Ostermann VVR
 CHECKED - JSB CCC

EXAMINED
 PASSED
 ENGINEER OF STRUCTURAL SERVICES
 ENGINEER OF BRIDGES AND STRUCTURES


DATE - MAY 07, 2021
 REVISED 05/28/2021 JSB
 REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**WINGWALL AND RAILING MODIFICATIONS
SN 072-0106 (SB) & 072-0107 (NB)**

SHEET NO. 12 OF 14 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	24
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				




SOUTH ABUTMENT FACE
(SN 072-0106)



SOUTH ABUTMENT FACE
(SN 072-0107)



NORTH ABUTMENT FACE
(SN 072-0106)



NORTH ABUTMENT FACE
(SN 072-0107)

Note:
An additional 50% has been included
with the estimated quantity.

BILL OF MATERIAL

Item	Unit	Total
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	398

DESIGNED - JSB	EXAMINED	DATE - MAY 07, 2021
CHECKED - CCC	<i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	
DRAWN - Jim Ostermann VVR	PASSED	REVISED Δ 05/28/2021 JSB
CHECKED - JSB CCC	<i>Carl Ruyter</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SUBSTRUCTURE CONCRETE REPAIRS
SN 072-0106 (SB) & 072-0107 (NB)

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	25
CONTRACT NO. 68E52			ILLINOIS FED. AID PROJECT	

SHEET NO. 13 OF 14 SHEETS

Δ REVISED 6/1/21



STANDARD BAR SPLICER ASSEMBLY PLAN
 (All components shall be provided from one supplier)

Threaded splicer bar length = min. lap length + 1 1/2" + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.


SN 072-0106

Location	Bar size	No. assemblies required	Minimum lap length
N. Abut - deck	#5	8	3'-6"
S. Abut - deck	#5	8	3'-6"
N. Abut - appr.	#6	2	4'-0"
S. Abut - appr.	#6	2	4'-0"



SN 072-0107

Location	Bar size	No. assemblies required	Minimum lap length
N. Abut - deck	#5	8	3'-6"
S. Abut - deck	#5	8	3'-6"
N. Abut - appr.	#6	2	4'-0"
S. Abut - appr.	#6	2	4'-0"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.

"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

Notes:

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars.

Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.

See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

1-1-2020

DESIGNED - JSB	EXAMINED
CHECKED - CCC	PASSED
DRAWN - Jim Ostermann VVR	
CHECKED - JSB CCC	

 ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 07, 2021
 ENGINEER OF BRIDGES AND STRUCTURES	REVISED 05/28/2021 JSB REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION


BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS
 SN 072-0106 (SB) & 072-0107 (NB)

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	26
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				


SHEET NO. 14 OF 14 SHEETS

REVISED 6/1/21


Notes:
 See special provision for Permanent Protective Shield System.
 Timber sizes shown are nominal sizes. Rough sawn timber of the dimensions shown will also be considered acceptable.
 The minimum Fb and Fv values shown are the tabulated design values given in the National Design Specification for Wood Construction for No. 2 Spruce-Pine-Fir without adjustment factors applied. Better grades or other species with equal or higher allowable stresses will also be considered acceptable.
 The timber spacings shown have been determined using allowable stresses with all adjustment factors necessary for the anticipated service conditions. All timber shall be treated.
 Plywood shall be 5/8" rated Exterior type plywood by APA.
 Plywood shall be placed such that the face grain is perpendicular to the timber supports. When less than a full sheet (4' width) of plywood is used, the width of the strip used shall not be less than 2'.
 Transverse plywood joints shall be supported by timbers.
 When 4" x 6" timbers are used, they shall be placed such that the wide face is horizontal and the narrow face is vertical.
 Design load = 200 psf.



PPC I-BEAMS AND BULB-T's



STEEL BEAMS



SECTION A-A

TIMBER SPACING

Beam Spacing (ft.)	Timber Sizes (in.)		
	4" x 4" with min. Fb=775 psi Fv=135 psi	4" x 6" with min. Fb=775 psi Fv=135 psi	6" x 6" with min. Fb=575 psi Fv=125 psi
	Maximum Timber Spacing (in.)		
4.5	16	16	16
4.75	16	16	16
5.0	16	16	16
5.25	16	16	16
5.5	16	16	16
5.75	16	16	16
6.0	16	16	16
6.25	12	16	16
6.5	12	16	16
6.75	12	16	16
7.0	8	16	16
7.25	8	16	16
7.5	8	16	16
7.75	8	16	16
8.0	8	12	16
8.25	8	12	16
8.5	6	12	12
8.75	6	12	12
9.0	6	8	12

PPC I-BEAMS AND BULB-T's

BEAM	"A"
36" I-Beam	1 1/2"
42" I-Beam	1 1/2"
48" I-Beam	1 1/2"
54" I-Beam	1 3/8"
63" Bulb-T	3 3/8"
72" Bulb-T	3 3/8"

Sheet Added

BILL OF MATERIAL

Item	Unit	Total
Protective Shield (Permanent)	Sq. Yd.	494

PPS-1/REP 10-27-2020

DESIGNED - JSB
 CHECKED - CCC
 DRAWN - Jim Ostermann VVR
 CHECKED - JSB CCC

EXAMINED
 PASSED
 ENGINEER OF STRUCTURAL SERVICES
 ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 07, 2021
 REVISED 05/28/2021 JSB


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

PERMANENT PROTECTIVE SHIELD
 SN 072-0106 (SB) & 072-0107 (NB)


SHEET NO. 14A OF 14 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	26A
CONTRACT NO. 68E52				

ILLINOIS FED. AID PROJECT
 ADDED SHEET 6/1/21



ELEVATION



PLAN

GENERAL NOTES

All structural steel shall conform to AASHTO Classification M-270 Gr. 36, unless otherwise noted.
 Reinforcement bars designated (E) shall be epoxy coated.
 Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.
 Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
 Joint openings shall be adjusted according to Article 520.04 of the Std. Specs. when the deck is poured at an ambient temperature other than 50° F.
 All new structural steel and bearing assemblies shall be hot-dip galvanized. See Special Provisions for "Hot Dip Galvanizing for Structural Steel."

TOTAL BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Concrete Removal	Cu. Yd.	21.1
Concrete Superstructure	Cu. Yd.	24.3
Bridge Deck Microsilica Concrete Overlay, 2 1/4"	Sq. Yd.	1825
Bridge Deck Grooving	Sq. Yd.	1677
Floor Drains	Each	4
Preformed Joint Strip Seal	Foot	211
Reinforcement Bars, Epoxy Coated	Pound	2710
Bar Splicers	Each	40
Protective Coat	Sq. Yd.	1825
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	441
Furnishing & Erecting Structural Steel	Pound	11810
Elastomeric Bearing Assembly, Type I	Each	14
Jack & Remove Existing Bearings	Each	28
Anchor Bolts, 1"Ø	Each	56
Protective Shield (Permanent)	Sq. Yd.	511
Hot-Mix Asphalt Surface Removal Deck	Sq. Yd.	1825
Polymer Concrete	Cu. Ft.	6.5
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	1.8
Bridge Deck Scarification, 3/4"	Sq. Yd.	1825
Floor Drain	Each	4

* On new concrete and microsilica concrete overlay only.






- (A) - Remove and replace expansion joint with Preformed Joint Strip Seal.
- (B) - Bearing removal and replacement at Abutments.
- (C) - Bridge deck scarification with new Microsilica Concrete Overlay
- (D) - Wingwall and Railing Modifications. See sheet 15 of 17 for details.
- (E) - Polymer Concrete Nosing. See sheet 9 of 17 for details.
- (F) - Substructure Repairs

DESIGNED - CHI-CHEUNG CHAU	EXAMINED - <i>Twig A. Beck</i>	DATE - MAY 7, 2021
CHECKED - JEFFREY S. BURKE	ENGINEER OF STRUCTURAL SERVICES	
DRAWN <i>jostermann</i>	PASSED - <i>Dr. Carl Puzy</i>	REVISOR - 05/21/2021 CCC
CHECKED - CCC JSB	ENGINEER OF BRIDGES AND STRUCTURES	REVISOR -




STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

GENERAL PLAN AND ELEVATION
 F.A.I. 474 OVER F.A.I. 74
 SN 072-0108 (SB) & 072-0109 (NB)

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1.2,3)BR	PEORIA	63	27
			CONTRACT NO. 68E52	
		ILLINOIS	FED. AID PROJECT	



DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	STAGING CROSS SECTIONS SN 072-0108 (SB)	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
CHECKED - JSB	PASSED - <i>Carl R. Meyer</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED - 05/21/2021 CCC			474	72(1HB,HB-1,2,3)BR	PEORIA	63	28	
DRAWN - Jim Ostermann steffen		REVISED -			CONTRACT NO. 68E52					
CHECKED - CCC JSB					SHEET NO. 2 OF 17 SHEETS					



DESIGNED - CCC
 CHECKED - JSB
 DRAWN - Jim Ostermann steffen
 CHECKED - CCC JSB


EXAMINED
 PASSED
 ENGINEER OF STRUCTURAL SERVICES
 ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 7, 2021
 REVISED - 05/21/2021 CCC
 REVISED -

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

**STAGING CROSS SECTIONS
 SN 072-0109 (NB)**
 SHEET NO. 3 OF 17 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	29
CONTRACT NO. 68E52				



Note:
 The exterior surfaces of the floor drains shall be painted with the finish coat as specified in the special provisions for Cleaning and Painting New Metal Structures. The exterior surfaces of the drains shall be cleaned according to Society of Protective Coatings' Spec. SSPC-SP1 prior to painting. Fiberglass pipe shall conform to ASTM D 2996, with short-time rupture strength hoop tensile stress of 30,000 p.s.i. minimum. Galvanize clamping device according to AASHTO M232. Cost of clamping device and galvanizing included with Floor Drains.

DRAIN REPAIR LEGEND

- - Previously plugged drains to be removed by full depth deck patch.
- - Floor Drain to be removed with full depth deck patch and replaced with new floor drains.


Perform Structural Repair of Concrete ≤ 5" at bottom of overhangs where necessary.

Note:
 Areas of deck repairs shown are estimated. The Engineer shall show actual locations of deck repairs on As-built Plans.


Item	Unit	Total
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	1.8
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	70
Floor Drain	Each	4

* Estimated



CONCRETE REMOVAL & REPLACEMENT PLAN AT FLOOR DRAINS
 Existing reinf. to remain.




SECTION THRU CONCRETE REMOVAL & REPLACEMENT AT FLOOR DRAINS



OVERLAY TREATMENT AT FLOOR DRAINS




TOP PLAN (Showing Aluminum Tube)



SECTION A-A

* Dimension as req'd by Pipe Clamp.



FLOOR DRAIN DETAILS (4-Locations)

DESIGNED -	EXAMINED -	DATE - MAY 7, 2021
CHECKED -	ENGINEER OF STRUCTURAL SERVICES	
DRAWN <i>jostermann</i>	PASSED -	REVISOR <i>CCC</i> - 05/21/2021
CHECKED -	ENGINEER OF BRIDGES AND STRUCTURES	REVISOR -

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



DECK SLAB REPAIRS SN 072-0108 (SB) & 072-0109 (NB)

SHEET NO. 4 OF 17 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	30
CONTRACT NO. 68E52				

ILLINOIS FED. AID PROJECT


REVISED 6/1/21




Notes:
 Hatched areas indicate removal.
 Bend a(E) bars in field as necessary.
 For bar details and Bill of Material,
 see sheet 9 of 17.
 * Measured radially to \bar{C} F.A.I. 474.

CONCRETE REMOVAL DETAILS
 N. ABUT., 072-0108 (S.B.)

CONCRETE REPLACEMENT DETAILS
 N. ABUT., 072-0108 (S.B.)




SECTION A-A
 (Near \bar{C} Roadway)
 (Dims at RT Ls to end of deck)




SECTION B-B
 (Near \bar{C} Roadway)
 (Dims at RT Ls to end of deck)

DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	JOINT REMOVAL AND REPLACEMENT DETAILS - N. ABUT. SN 072-0108 (SB)	F.A.I. RTE. 474	SECTION 72(1HB,HB-1.2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 31	
CHECKED - JSB	PASSED - <i>Carl Rieger</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED - 05/21/2021 CCC			CONTRACT NO. 68E52					
DRAWN - Jim Ostermann steffen		REVISED -			SHEET NO. 5 OF 17 SHEETS					
CHECKED - CCC JSB					ILLINOIS FED. AID PROJECT					




Notes:
 Hatched areas indicate removal.
 Bend a(E) bars in field as necessary.
 For bar details and Bill of Material,
 see sheet 9 of 17.
 * Measured radially to \bar{C} F.A.I. 474.


CONCRETE REMOVAL DETAILS
 S. ABUT., 072-0108 (S.B.)



CONCRETE REPLACEMENT DETAILS
 S. ABUT., 072-0108 (S.B.)




SECTION A-A
 (Near \bar{C} Roadway)
 (Dims at RT L's to end of deck)




SECTION B-B
 (Near \bar{C} Roadway)
 (Dims at RT L's to end of deck)


DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i>	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION		JOINT REMOVAL AND REPLACEMENT DETAILS - S. ABUT. SN 072-0108 (SB)		F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
CHECKED - JSB	ENGINEER OF STRUCTURAL SERVICES	REVISOR - 05/21/2021 CCC					474	72(1HB,HB-1.2,3)BR	PEORIA	63	32
DRAWN - Jim Ostermann steffen	PASSED - <i>Carl R. Roper</i>	REVISOR -	SHEET NO. 6 OF 17 SHEETS		ILLINOIS FED. AID PROJECT		CONTRACT NO. 68E52				
CHECKED - CCC JSB	ENGINEER OF BRIDGES AND STRUCTURES						REVISED 6/1/21				




CONCRETE REMOVAL DETAILS
N. ABUT., 072-0109 (N.B.)



CONCRETE REPLACEMENT DETAILS
N. ABUT., 072-0109 (N.B.)



SECTION A-A
(Near \bar{C} Roadway)
(Dims at RT Ls to end of deck)




SECTION B-B
(Near \bar{C} Roadway)
(Dims at RT Ls to end of deck)


Notes:
Hatched areas indicate removal.
Bend a(E) bars in field as necessary.
For bar details and Bill of Material,
see sheet 9 of 17.

* Measured radially to \bar{C} F.A.I. 474.


DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i>	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	JOINT REMOVAL AND REPLACEMENT DETAILS - N. ABUT. SN 072-0109 (NB)	F.A.I. RTE. 474	SECTION 72(1HB,HB-1.2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 33	
CHECKED - JSB	PASSED - <i>Carl Rieger</i>	REVISED Δ - 05/21/2021 CCC			CONTRACT NO. 68E52					
DRAWN - Jim Ostermann steffen	ENGINEER OF BRIDGES AND STRUCTURES	REVISED -			SHEET NO. 7 OF 17 SHEETS					
CHECKED - CCC JSB	ENGINEER OF STRUCTURAL SERVICES				ILLINOIS FED. AID PROJECT					




CONCRETE REMOVAL DETAILS
S. ABUT., 072-0109 (N.B.)



CONCRETE REPLACEMENT DETAILS
S. ABUT., 072-0109 (N.B.)



SECTION A-A
(Near \bar{C} Roadway)
(Dims at RT Ls to end of deck)




SECTION B-B
(Near \bar{C} Roadway)
(Dims at RT Ls to end of deck)


Notes:
Hatched areas indicate removal.
Bend a(E) bars in field as necessary.
For bar details and Bill of Material,
see sheet 9 of 17.

* Measured radially to \bar{C} F.A.I. 474.



DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	JOINT REMOVAL AND REPLACEMENT DETAILS - S. ABUT. SN 072-0109 (NB)		F.A.I. RTE. 474	SECTION 72(1HB,HB-1,2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 34
CHECKED - JSB	PASSED - <i>Carl R. Steffen</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED Δ - 05/21/2021 CCC		SHEET NO. 8 OF 17 SHEETS		CONTRACT NO. 68E52		ILLINOIS FED. AID PROJECT		
DRAWN - Jim Ostermann steffen		REVISED -								
CHECKED - CCC JSB										




SECTION THRU SPAN 1 & 3 PARAPET



SECTION THRU SPAN 2 PARAPET




VIEW C-C



RAIL POST ANCHORAGE DEVICE DETAILS

New Rail Post Anchorage Devices will be required at locations where posts are connected to new concrete. Cost to be included with Concrete Removal (-Required)



POLYMER CONCRETE NOSING DETAIL

BILL OF MATERIAL				
Bar	No.	Size	Length	Shape
a(E)	32	#6	6'-0"	—
a1(E)	16	#5	27'-2"	—
a2(E)	8	#5	26'-1"	—
a3(E)	8	#5	25'-3"	—
a4(E)	16	#5	25'-5"	—
a5(E)	8	#5	27'-6"	—
a6(E)	8	#5	27'-8"	—
d(E)	40	#5	4'-10"	┌
d1(E)	40	#5	3'-8"	┌
d2(E)	16	#4	2'-3"	┌
h(E)	16	#6	6'-0"	—
h1(E)	4	#6	27'-2"	—
h2(E)	2	#6	26'-1"	—
h3(E)	2	#6	25'-3"	—
h4(E)	4	#6	25'-5"	—
h5(E)	2	#6	27'-6"	—
h6(E)	2	#6	29'-8"	—
Concrete Removal			Cu. Yd.	21.1
Concrete Superstructure			Cu. Yd.	21.1
Reinforcement Bars, Epoxy Coated			Pound	3240

DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i>	DATE - MAY 7, 2021
CHECKED - JSB	ENGINEER OF STRUCTURAL SERVICES	
DRAWN - Jim Ostermann steffen	PASSED - <i>Carl Ringer</i>	REVISOR - 05/21/2021 CCC
CHECKED - CCC JSB	ENGINEER OF BRIDGES AND STRUCTURES	REVISOR -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

JOINT REPLACEMENT DETAILS
SN 072-0108 (SB) & 072-0109 (NB)

SHEET NO. 9 OF 17 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1.2,3)BR	PEORIA	63	35
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				

REVISOR 6/1/21



ELEVATION AT ABUTMENT

TYPE I ELASTOMERIC EXP. BRG.



SECTION A-A

BEAM REACTIONS

R ρ	(K)	79.4
R $\frac{1}{4}$	(K)	46.7
Imp.	(K)	10.1
R (Total)	(K)	136.2

Notes:

Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.


New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel. Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).

Min. jack capacity = 85 Tons.


Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.


Cost of Side retainers and Stainless Steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.




PLAN TOP AND BOTTOM PLATE



SECTION B-B




STEEL EXTENSION DETAIL



BEARING ASSEMBLY


Note:

Shim plates shall not be placed under Bearing Assembly.




SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.



ANCHOR BOLT LOCATION PLAN



EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.

BILL OF MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly, Type I	Each	7
Jack and Remove Existing Bearings	Each	7
Furnishing and Erecting Structural Steel	Pound	3330
Anchor Bolts, 1"Ø	Each	14

TYI/REPS 5-17-2018

DESIGNED - CCC	EXAMINED	DATE - MAY 7, 2021
CHECKED - JSB	<i>Timothy A. Daburdell</i>	
DRAWN - daburdell nn steffen	ENGINEER OF STRUCTURAL SERVICES	
CHECKED - CCC JSB	<i>Carl R. Steffen</i>	
	ENGINEER OF BRIDGES AND STRUCTURES	

REVISOR	REVISION
▲	05/21/2021 CCC


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BEARING REPLACEMENT - NORTH ABUTMENT
SN 072-0108 (SB)

SHEET NO. 11 OF 17 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	37
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				

REVISED 6/1/21



ELEVATION AT ABUTMENT

TYPE I ELASTOMERIC EXP. BRG.



SECTION A-A

BEAM REACTIONS

R \bar{D}	(K)	84.3
R \bar{L}	(K)	49.1
Imp.	(K)	10.7
R (Total)	(K)	144.1

Notes:

Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.

New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel.


Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).

Min. jack capacity = 90 Tons.


Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.


Cost of Side retainers and Stainless Steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.




PLAN TOP AND BOTTOM PLATE



SECTION B-B




STEEL EXTENSION DETAIL



BEARING ASSEMBLY


Note:

Shim plates shall not be placed under Bearing Assembly.




EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.



SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.



ANCHOR BOLT LOCATION PLAN

BILL OF MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly, Type I	Each	7
Jack and Remove Existing Bearings	Each	7
Furnishing and Erecting Structural Steel	Pound	3470
Anchor Bolts, 1"Ø	Each	14

DESIGNED - CCC
 CHECKED - JSB
 DRAWN - daburdell in steffen
 CHECKED - CCC JSB

EXAMINED - *Timothy A. Dand...*
 ENGINEER OF STRUCTURAL SERVICES
 PASSED - *Carl...*
 ENGINEER OF BRIDGES AND STRUCTURES


DATE - MAY 7, 2021
 REVISED - 05/21/2021 CCC
 REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION


BEARING REPLACEMENT - NORTH ABUTMENT
 SN 072-0109 (NB)

SHEET NO. 13 OF 17 SHEETS


F.A.I. RTE. 474 SECTION 72(1HB,HB-1.2,3)BR COUNTY PEORIA TOTAL SHEETS 63 SHEET NO. 39
 CONTRACT NO. 68E52
 ILLINOIS FED. AID PROJECT




PROPOSED ELEVATION



INSIDE VIEW AT APPROACH BENT




SECTION A-A



PLAN

* Epoxy grout v(E) bars in 9" min. holes according to Article 584 of the Standard Specifications.



CAST END CAP


NOTES

Reinforcement bars designated (E) shall be epoxy coated.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h7(E)	48	#5	5'-1"	—
u(E)	32	#4	3'-5"	□
v(E)	48	#5	2'-4"	⌋
				△
Concrete Superstructure			Cu. Yd.	1.6
Reinforcement Bars, Epoxy Coated			Pound	440



BAR u(E)

BAR v(E)


DESIGNED - CCC	EXAMINED - <i>Timothy A. Daulton</i>	DATE - MAY 7, 2021
CHECKED - JSB	ENGINEER OF STRUCTURAL SERVICES	
DRAWN - Jim Ostermann steffen	PASSED - <i>Carl Rieger</i>	REVISED - 05/21/2021 CCC
CHECKED - CCC JSB	ENGINEER OF BRIDGES AND STRUCTURES	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**WINGWALL AND RAILING MODIFICATIONS
SN 072-0108 (SB) & 072-0109 (NB)**

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	41
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				


SHEET NO. 15 OF 17 SHEETS




SOUTH ABUTMENT FACE
(SN 072-0108)



SOUTH ABUTMENT FACE
(SN 072-0109)



NORTH ABUTMENT FACE
(SN 072-0108)



NORTH ABUTMENT FACE
(SN 072-0109)

①

* An additional 50% is included in the Structural Repair of Concrete. Final areas shall be marked in the field by the Engineer and marked on the As-Built plans.

BILL OF MATERIAL

Item	Unit	Total
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	371

①

DESIGNED - CCC	EXAMINED	DATE - MAY 7, 2021
CHECKED - JSB	<i>Timothy A. Daburdell</i> ENGINEER OF STRUCTURAL SERVICES	
DRAWN <i>daburdell</i> tk steffen	PASSED	REVISED ① - 05/21/2021 CCC
CHECKED - CCC JSB	<i>Carl Ruyter</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**SUBSTRUCTURE CONCRETE REPAIRS
SN 072-0108 (SB) & 072-0109 (NB)**


SHEET NO. 16 OF 17 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	42
CONTRACT NO. 68E52				
ILLINOIS		FED. AID PROJECT		

Notes:
 See special provision for Permanent Protective Shield System.
 Timber sizes shown are nominal sizes. Rough sawn timber of the dimensions shown will also be considered acceptable.
 The minimum Fb and Fv values shown are the tabulated design values given in the National Design Specification for Wood Construction for No. 2 Spruce-Pine-Fir without adjustment factors applied. Better grades or other species with equal or higher allowable stresses will also be considered acceptable.
 The timber spacings shown have been determined using allowable stresses with all adjustment factors necessary for the anticipated service conditions.
 All timber shall be treated.
 Plywood shall be 5/8" rated Exterior type plywood by APA.
 Plywood shall be placed such that the face grain is perpendicular to the timber supports. When less than a full sheet (4' width) of plywood is used, the width of the strip used shall not be less than 2'.
 Transverse plywood joints shall be supported by timbers.
 When 4" x 6" timbers are used, they shall be placed such that the wide face is horizontal and the narrow face is vertical.
 Design load = 200 psf.



PPC I-BEAMS AND BULB-T'S




STEEL BEAMS

TIMBER SPACING

Beam Spacing (ft.)	Timber Sizes (in.)		
	4" x 4" with min. Fb=775 psi Fv=135 psi	4" x 6" with min. Fb=775 psi Fv=135 psi	6" x 6" with min. Fb=575 psi Fv=125 psi
	Maximum Timber Spacing (in.)		
4.5	16	16	16
4.75	16	16	16
5.0	16	16	16
5.25	16	16	16
5.5	16	16	16
5.75	16	16	16
6.0	16	16	16
6.25	12	16	16
6.5	12	16	16
6.75	12	16	16
7.0	8	16	16
7.25	8	16	16
7.5	8	16	16
7.75	8	16	16
8.0	8	12	16
8.25	8	12	16
8.5	6	12	12
8.75	6	12	12
9.0	6	8	12

PPC I-BEAMS AND BULB-T'S

BEAM	"A"
36" I-Beam	1 1/2"
42" I-Beam	1 1/2"
48" I-Beam	1 1/2"
54" I-Beam	1 5/8"
63" Bulb-T	3 3/8"
72" Bulb-T	3 3/8"



SECTION A-A

BILL OF MATERIAL


Item	Unit	Total
Protective Shield (Permanent)	Sq. Yd.	511

PPS-1/REP 10-27-2020


DESIGNED - CCC CHECKED - JSB DRAWN - Jim Ostermann steffen CHECKED - CCC JSB	EXAMINED PASSED  ENGINEER OF STRUCTURAL SERVICES  ENGINEER OF BRIDGES AND STRUCTURES	DATE - MAY 7, 2021 SHEET ADDED 05/21/2021 CCC REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PERMANENT PROTECTIVE SHIELD SN 072-0108 (SB) & 072-0109 (NB)	F.A.I. RTE. 474 SECTION 72(1HB,HB-1,2,3)BR COUNTY PEORIA TOTAL SHEETS 63 SHEET NO. 43A CONTRACT NO. 68E52 ILLINOIS FED. AID PROJECT
---	---	---	---	---	---

GENERAL NOTES

All structural steel shall conform to AASHTO Classification M-270 Gr. 36, unless otherwise noted.
 Reinforcement bars designated (E) shall be epoxy coated.
 Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.
 Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
 Joint openings shall be adjusted according to Article 520.04 of the Std. Specs. when the deck is poured at an ambient temperature other than 50° F.
 All new structural steel and bearing assembly shall be hot-dip galvanized. See Special Provisions for "Hot Dip Galvanizing for Structural Steel."



ELEVATION



PLAN

- (A) - Remove and replace expansion joint with Preformed Joint Strip Seal.
- (B) - Bearing removal and replacement at Abutments.
- (C) - Bridge deck scarification with new Microsilica Concrete Overlay on Spans 1 thru 3.
- (D) - Polymer Concrete Nosing. See sheet 6 of 11 for details.
- (E) - Substructure Repairs

TOTAL BILL OF MATERIAL



ITEM	UNIT	QUANTITY
Concrete Removal	Cu. Yd.	14
Concrete Superstructure	Cu. Yd.	14
Bridge Deck Microsilica Concrete Overlay, 2 1/4"	Sq. Yd.	928.4
Bridge Deck Grooving	Sq. Yd.	916.2
Floor Drains	Each	8
Preformed Joint Strip Seal	Foot	118
Reinforcement Bars, Epoxy Coated	Pound	1640
Bar Splicers	Each	20
* Protective Coat	Sq. Yd.	975.1
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	253
Furnishing & Erecting Structural Steel	Pound	3570
Elastomeric Bearing Assembly, Type I	Each	6
Jack & Remove Existing Bearings	Each	12
Anchor Bolts, 1 1/4" Ø	Each	24
Protective Shield (Permanent)	Sq. Yd.	288
Hot-Mix Asphalt Surface Removal Deck	Sq. Yd.	928.4
Bridge Deck Scarification, 3/4"	Sq. Yd.	928.4
Mechanical Splicers	Each	48
Polymer Concrete	Cu. Ft.	4.2
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	3.3

* On new concrete & microsilica concrete overlay only.




EXPIRES 11-30-2022


DESIGNED - ADRIAN T. HALLOWAY	EXAMINED - <i>Tracy A. Beck</i>	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	GENERAL PLAN AND ELEVATION F.A.I. 474 OVER F.A.I. 74 SN 072-0110	F.A.I. RTE. 474	SECTION 72(1HB,HB-1,2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 44	
CHECKED - VICTOR H. VELIZ	PASSED - <i>Dr. Carl Puzey</i>	REVISOR - 05/25/2021 ATH		SHEET NO. 1 OF 11 SHEETS	CONTRACT NO. 68E52					
DRAWN - <i>jostermamm</i> Steffen	ENGINEER OF BRIDGES AND STRUCTURES	REVISOR -		ILLINOIS FED. AID PROJECT						
CHECKED - ATH VHV				REVISED 6/1/21						




**CONCRETE REMOVAL & REPLACEMENT
PLAN AT FLOOR DRAINS**
Existing reinf. to remain.




**SECTION THRU CONCRETE REMOVAL &
REPLACEMENT AT FLOOR DRAINS**




FLOOR DRAIN DETAILS
(8-Locations)



**ALUMINUM
TUBE**




**FIBERGLASS
PIPE**




SECTION A-A

** Dimension as req'd by Pipe Clamp.




TOP PLAN
(Showing Aluminum Tube)



**OVERLAY TREATMENT
AT FLOOR DRAINS**

Note:
Areas of deck repairs shown are estimated. The Engineer shall show actual locations of deck repairs on As-built Plans.



1

Note:
The exterior surfaces of the floor drains shall be painted with the finish coat as specified in the special provisions for Cleaning and Painting New Metal Structures. The exterior surfaces of the drains shall be cleaned according to Society of Protective Coating's Spec. SSPC-SP1 prior to painting. Fiberglass pipe shall conform to ASTM D 2996, with short-time rupture strength hoop tensile stress of 30,000 p.s.i. minimum. Galvanize clamping device according to AASHTO M232. Cost of clamping device and galvanizing included with Floor Drains.

BILL OF MATERIAL

Item	Unit	Total
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	3.3
Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	70
Floor Drain	Each	8

1

DESIGNED - ATH
CHECKED - VHV
DRAWN - Jim Ostermann Steffen
CHECKED - ATH VHV

EXAMINED
PASSED
Timothy A. Daulton
ENGINEER OF STRUCTURAL SERVICES
Carl R. Rieger
ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 7, 2021
REVISED - 05/25/2021 ATH
REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**DECK SLAB REPAIR
SN 072-0110**

SHEET NO. 3 OF 11 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	46

CONTRACT NO. 68E52
ILLINOIS FED. AID PROJECT



FIXED BEARINGS

BEAM REACTIONS

R _⊥	(K)	111.8
R _∥	(K)	47.0
Imp.	(K)	8.7
R (Total)	(K)	167.5

Notes:

Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.



New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel.

Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).





Min. jack capacity = **105 Tons**

Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (F_y=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.



STEEL EXTENSION DETAIL



EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.

BILL OF MATERIAL

Item	Unit	Total
Jack and Remove Existing Bearings	Each	6
Furnishing and Erecting Structural Steel	Pound	2040
Anchor Bolts, 1 1/2" Ø	Each	12

DESIGNED - ATH	EXAMINED - <i>Timothy A. Daulton</i>	DATE - MAY 7, 2021
CHECKED - VHV	ENGINEER OF STRUCTURAL SERVICES	
DRAWN - Jim Ostermann	PASSED - <i>Carl R. Steffen</i>	REVISED - 05/25/2021 ATH
CHECKED - ATH VHV	ENGINEER OF BRIDGES AND STRUCTURES	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

**BEARING REPLACEMENT - SOUTH ABUTMENT
SN 072-0110**


SHEET NO. 9 OF 11 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	52
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				

REVISED 6/1/21



SOUTH ABUTMENT FACE
(SN 072-0110)



NORTH ABUTMENT FACE
(SN 072-0110)

BILL OF MATERIAL		
Item	Unit	Total
* Structural Repair of Concrete (Depth ≤ 5")	Sq. Ft.	183

* Includes a 50% contingency.


DESIGNED - ATH	EXAMINED	DATE - MAY 7, 2021
CHECKED - VHV	<i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	
DRAWN - Jim Ostermann Steffen	PASSED	REVISED Δ - 05/25/2021 ATH
CHECKED - ATH VHV	<i>Carl Ruyter</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED -

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**


**SUBSTRUCTURE CONCRETE REPAIRS
SN 072-0110**

SHEET NO. 10 OF 11 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	53
ILLINOIS FED. AID PROJECT			CONTRACT NO. 68E52	



PPC I-BEAMS AND BULB-T'S



STEEL BEAMS



SECTION A-A

TIMBER SPACING

Beam Spacing (ft.)	Timber Sizes (in.)		
	4" x 4" with min. Fb=775 psi Fv=135 psi	4" x 6" with min. Fb=775 psi Fv=135 psi	6" x 6" with min. Fb=575 psi Fv=125 psi
	Maximum Timber Spacing (in.)		
4.5	16	16	16
4.75	16	16	16
5.0	16	16	16
5.25	16	16	16
5.5	16	16	16
5.75	16	16	16
6.0	16	16	16
6.25	12	16	16
6.5	12	16	16
6.75	12	16	16
7.0	8	16	16
7.25	8	16	16
7.5	8	16	16
7.75	8	16	16
8.0	8	12	16
8.25	8	12	16
8.5	6	12	12
8.75	6	12	12
9.0	6	8	12

PPC I-BEAMS AND BULB-T'S

BEAM	"A"
36" I-Beam	1 1/2"
42" I-Beam	1 1/2"
48" I-Beam	1 1/2"
54" I-Beam	1 5/8"
63" Bulb-T	3 3/8"
72" Bulb-T	3 3/8"

Notes:
 See special provision for Permanent Protective Shield System.
 Timber sizes shown are nominal sizes. Rough sawn timber of the dimensions shown will also be considered acceptable.
 The minimum Fb and Fv values shown are the tabulated design values given in the National Design Specification for Wood Construction for No. 2 Spruce-Pine-Fir without adjustment factors applied. Better grades or other species with equal or higher allowable stresses will also be considered acceptable.
 The timber spacings shown have been determined using allowable stresses with all adjustment factors necessary for the anticipated service conditions.
 All timber shall be treated.
 Plywood shall be 5/8" rated Exterior type plywood by APA.
 Plywood shall be placed such that the face grain is perpendicular to the timber supports. When less than a full sheet (4' width) of plywood is used, the width of the strip used shall not be less than 2'.
 Transverse plywood joints shall be supported by timbers.
 When 4" x 6" timbers are used, they shall be placed such that the wide face is horizontal and the narrow face is vertical.
 Design load = 200 psf.

BILL OF MATERIAL


Item	Unit	Total
Protective Shield (Permanent)	Sq. Yd.	288

PPS-1/REP 10-27-2020


DESIGNED - ATH	EXAMINED - <i>Timothy A. Daulton</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	PERMANENT PROTECTIVE SHIELD SN 072-0110	F.A.I. RTE. 474	SECTION 72(1HB,HB-1,2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 54A
CHECKED - VHV	PASSED - <i>Carl R. Meyer</i> ENGINEER OF BRIDGES AND STRUCTURES	SHEET ADDED 05/25/2021 ATH			CONTRACT NO. 68E52				
DRAWN - Jim Ostermann Steffen	REVISOR -				SHEET NO. 11A OF 11 SHEETS				
CHECKED - ATH VHV					ILLINOIS FED. AID PROJECT				

GENERAL NOTES

All structural steel shall conform to AASHTO Classification M-270 Gr. 36, unless otherwise noted.
 Reinforcement bars designated (E) shall be epoxy coated.
 Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose or potentially detrimental foreign material shall be removed from the surfaces in contact with concrete. Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be included in the pay item covering removal of the existing concrete.
 Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
 Existing reinforcement bars extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost included with Concrete Removal.
 Joint openings shall be adjusted according to Article 520.04 of the Std. Specs. when the deck is poured at an ambient temperature other than 50° F.
 All new structural steel and bearing assembly shall be hot-dip galvanized. See Special Provisions for "Hot Dip Galvanizing for Structural Steel."



ELEVATION



PLAN

- (A) - Remove and replace joint with Preformed Joint Strip Seal.
- (B) - Bearing removal and replacement at Abutments.
- (C) - Bridge deck scarification with new Microsilica Overlay and diamond grinding. (All Spans)
- (D) - Wingwall and Railing Modifications. See sheet 17 of 19 for details.
- (E) - Substructure Repairs
- (F) - Straighten Fascia Girder and replace missing anchor bolt at Hinge.
- (G) - Perform Structural Repair of Concrete \leq 5" at Overhang where necessary. (70 Sq. Ft. Estimated)



EXPIRES 11-30-2022


TOTAL BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Concrete Removal	Cu. Yd.	71.6
Concrete Superstructure	Cu. Yd.	71.6
Bridge Deck Microsilica Concrete Overlay, 2 1/4"	Sq. Yd.	1080.5
Bridge Deck Grooving	Sq. Yd.	1138.7
Preformed Joint Strip Seal	Foot	368
Reinforcement Bars, Epoxy Coated	Pound	3600
Bar Splicers	Each	56
Protective Coat	Sq. Yd.	1257.5
Structural Repair of Concrete (Depth \leq 5")	Sq. Ft.	230
Furnishing & Erecting Structural Steel	Pound	2200
Elastomeric Bearing Assembly, Type I	Each	12
Jack & Remove Existing Bearings	Each	12
Anchor Bolts, 1"Ø	Each	24
Protective Shield (Permanent)	Sq. Yd.	511
Hot-Mix Asphalt Surface Removal Deck	Sq. Yd.	1080.5
Bridge Deck Scarification, 3/4"	Sq. Yd.	1080.5
Mechanical Splicers	Each	96
Concrete Structures	Cu. Yd.	2.1
Temporary Shoring and Cribbing	Each	1
Beam Straightening	L. Sum	1


* On new concrete and overlay only.

DESIGNED - Adrian T. Halloway	EXAMINED - <i>Tracy A. Beck</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	GENERAL PLAN AND ELEVATION F.A.I. 474 RAMP OVER F.A.I. 474 SN 072-0111 (SB)	F.A.I. RTE. 474	SECTION 72(1HB,HB-1,2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 55	
CHECKED - Victor H. Veliz	PASSED - <i>David Carl Puzey</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED Δ 05/28/2021 ATH			CONTRACT NO. 68E52					
DRAWN - Jim Ostermann <i>daburdell</i>	REVISOR -				SHEET NO. 1 OF 19 SHEETS					
CHECKED - ATH VHV					ILLINOIS FED. AID PROJECT					


Notes:
 See special provision for Permanent Protective Shield System.
 Timber sizes shown are nominal sizes. Rough sawn timber of the dimensions shown will also be considered acceptable.
 The minimum Fb and Fv values shown are the tabulated design values given in the National Design Specification for Wood Construction for No. 2 Spruce-Pine-Fir without adjustment factors applied. Better grades or other species with equal or higher allowable stresses will also be considered acceptable.
 The timber spacings shown have been determined using allowable stresses with all adjustment factors necessary for the anticipated service conditions. All timber shall be treated.
 Plywood shall be 5/8" rated Exterior type plywood by APA.
 Plywood shall be placed such that the face grain is perpendicular to the timber supports. When less than a full sheet (4' width) of plywood is used, the width of the strip used shall not be less than 2'.
 Transverse plywood joints shall be supported by timbers.
 When 4" x 6" timbers are used, they shall be placed such that the wide face is horizontal and the narrow face is vertical.
 Design load = 200 psf.



PPC I-BEAMS AND BULB-T's



STEEL BEAMS



SECTION A-A

TIMBER SPACING

Beam Spacing (ft.)	Timber Sizes (in.)		
	4" x 4" with min. Fb=775 psi Fv=135 psi	4" x 6" with min. Fb=775 psi Fv=135 psi	6" x 6" with min. Fb=575 psi Fv=125 psi
	Maximum Timber Spacing (in.)		
4.5	16	16	16
4.75	16	16	16
5.0	16	16	16
5.25	16	16	16
5.5	16	16	16
5.75	16	16	16
6.0	16	16	16
6.25	12	16	16
6.5	12	16	16
6.75	12	16	16
7.0	8	16	16
7.25	8	16	16
7.5	8	16	16
7.75	8	16	16
8.0	8	12	16
8.25	8	12	16
8.5	6	12	12
8.75	6	12	12
9.0	6	8	12

PPC I-BEAMS AND BULB-T's

BEAM	"A"
36" I-Beam	1 1/2"
42" I-Beam	1 1/2"
48" I-Beam	1 1/2"
54" I-Beam	1 3/8"
63" Bulb-T	3 3/8"
72" Bulb-T	3 3/8"

Removed Deck Slab Repair sheet and replaced it with Permanent Protective Shield sheet.

BILL OF MATERIAL

Item	Unit	Total
Protective Shield (Permanent)	Sq. Yd.	511

PPS-1/REP 10-27-2020

DESIGNED - ATH
 CHECKED - VHV
 DRAWN - Jim Ostermann daburdell
 CHECKED - ATH VHV

EXAMINED
 PASSED
 ENGINEER OF STRUCTURAL SERVICES
 ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 7, 2021
 REVISED 05/28/2021 ATH
 REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

PERMANENT PROTECTIVE SHIELD
 SN 072-0111

SHEET NO. 3 OF 19 SHEETS


F.A.I. SECTION COUNTY TOTAL SHEETS SHEET NO.
 474 72(1HB,HB-1,2,3)BR PEORIA 63 57
 CONTRACT NO. 68E52
 ILLINOIS FED. AID PROJECT

REVISED 6/1/21




PULLING DEVICE **PARTIAL PLANS** **PUSHING DEVICE**
SUGGESTED BEAM STRAIGHTENING METHODS


Straightening force shall be maintained on all load transfer blocking during beam straightening.




ELEVATION AT HINGE #1



ELEVATION AT HINGE #2



SECTION A-A



SECTION B-B




PHOTO 1
(Showing beam shift)



PHOTO 2
(Showing missing bolt)

Notes:
 Contractor shall contact the Bridge Office Repairs Unit for further guidance if there is any difficulty in straightening or achieving the required 1 3/4" movement to restore the beam to its original location.
 Cost of anchor bolts, nuts and washers included with Furnishing & Erecting Structural Steel.



EXISTING DEFORMATION TO BE STRAIGHTENED
(Looking South)

REP-1 8-16-2018

DESIGNED - ATH	EXAMINED
CHECKED - VHV	PASSED
DRAWN - Jim Ostermann daburdell	
CHECKED - ATH VHV	

Timothy A. Daburdell
 ENGINEER OF STRUCTURAL SERVICES
 Carl R. Poyner
 ENGINEER OF BRIDGES AND STRUCTURES


DATE - MAY 7, 2021
REVISED 05/28/2021 ATH
REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BEAM STRAIGHTENING DETAILS
SN 072-0111


SHEET NO. 4 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	58
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				




CONCRETE REPLACEMENT DETAILS - N. ABUT.
 * Measured radially to F.A.I. 474 .


Notes:
 Bend transverse bars in field as necessary.
 For bending bar diagrams, Section Thru Parapets and Bill of Material, see sheet 13 of 19.
 Bars indicated thus 4x2-#5 etc. indicates 4 lines of bars with 2 lengths per line.




DESIGNED - ATH	EXAMINED - <i>Timothy A. Daburdell</i> ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	JOINT REPLACEMENT DETAILS - S. ABUT. SN 072-0111	F.A.I. RTE. 474	SECTION 72(1HB,HB-1,2,3)BR	COUNTY PEORIA	TOTAL SHEETS 63	SHEET NO. 61E	
CHECKED - VHV	PASSED - <i>Carl R. Meyer</i> ENGINEER OF BRIDGES AND STRUCTURES	REVISED Δ 05/28/2021 ATH			CONTRACT NO. 68E52					
DRAWN - Jim Ostermann <i>daburdell</i>		REVISED -			SHEET NO. 12 OF 19 SHEETS					
CHECKED - ATH VHV					ILLINOIS FED. AID PROJECT					



SECTION THRU BRIDGE PARAPET




SECTION THRU ABUTMENT AT APPROACH




RAIL POST ANCHORAGE DEVICE DETAILS


New Rail Post Anchorage Devices will be required at locations where posts are connected to new concrete. Relocate post as necessary to miss joint openings. Cost to be included with Concrete Removal. (8-Required)




BARS d(E)



BAR d1(E)



BARS d2(E) & u(E)



BAR d3(E)

BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a(E)	24	#6	6'-0"	—
a1(E)	8	#5	22'-11"	—
a2(E)	8	#5	22'-6"	—
a3(E)	8	#5	28'-6"	—
a4(E)	8	#5	23'-3"	—
a5(E)	8	#5	26'-1"	—
a6(E)	8	#5	25'-3"	—
a7(E)	8	#5	27'-9"	—
a8(E)	8	#5	26'-9"	—
d(E)	59	#4	4'-10"	—
d1(E)	23	#5	3'-8"	—
d2(E)	16	#4	2'-3"	—
d3(E)	18	#5	4'-5"	—
h1(E)	4	#6	24'-0"	—
h2(E)	4	#6	23'-4"	—
h3(E)	4	#6	29'-0"	—
h4(E)	4	#6	27'-11"	—
u(E)	176	#4	1'-11"	—
Concrete Removal			Cu. Yd.	71.6
Concrete Superstructure			Cu. Yd.	71.6
Reinforcement Bars, Epoxy Coated			Pound	3130

DESIGNED - ATH
 CHECKED - VHV
 DRAWN - Jim Ostermann daburdell
 CHECKED - ATH VHV

EXAMINED
 PASSED
 ENGINEER OF STRUCTURAL SERVICES
 ENGINEER OF BRIDGES AND STRUCTURES

DATE - MAY 7, 2021
 REVISED 05/28/2021 ATH
 REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

JOINT REPLACEMENT DETAILS
 SN 072-0111

SHEET NO. 13 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	61F
CONTRACT NO. 68E52				
ILLINOIS		FED. AID PROJECT		

REVISED 6/1/21



ELEVATION AT ABUTMENT

TYPE I ELASTOMERIC EXP. BRG.




SECTION A-A


BEAM REACTIONS

R _l	(K)	33.2
R _t	(K)	42.0
Imp.	(K)	11.0
R (Total)	(K)	86.2


Notes:
 Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.
 New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel.
 Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).
 Min. jack capacity = 45 Tons.
 Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.
 Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.
 Cost of Side retainers and Stainless Steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.




PLAN TOP AND BOTTOM PLATE



SECTION B-B




STEEL EXTENSION DETAIL



BEARING ASSEMBLY


Note:
 Shim plates shall not be placed under Bearing Assembly.




SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.

* 3 3/4" or 2" See Anchor Bolt Location Plan for clip details.



ANCHOR BOLT LOCATION PLAN



EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.

BILL OF MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly, Type I	Each	6
Jack and Remove Existing Bearings	Each	6
Furnishing and Erecting Structural Steel	Pound	1030
Anchor Bolts, 1"Ø	Each	12

TYI/REPS 5-17-2018

DESIGNED - ATH	CHECKED - VHV	DRAWN - Jim Ostermann daburdell	CHECKED - ATH VHV
----------------	---------------	---------------------------------	-------------------

EXAMINED	 ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021
PASSED	 ENGINEER OF BRIDGES AND STRUCTURES	REVISED 05/28/2021 ATH REVISED -


STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

BEARING REPLACEMENT - N. ABUT.
 SN 072-0111

SHEET NO. 15 OF 19 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	61H
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				

REVISION 6/1/21



ELEVATION AT ABUTMENT

TYPE I ELASTOMERIC EXP. BRG.




SECTION A-A


BEAM REACTIONS

R _φ	(K)	44.2
R _L	(K)	42.8
Imp.	(K)	11.1
R (Total)	(K)	98.1


Notes:
 Diaphragm removal and reinstallation may be required to facilitate drilling holes. Cost included with Furnishing and Erecting Structural Steel.
 New steel extensions, shim plates and connection bolts are included with Furnishing and Erecting Structural Steel.
 Prior to ordering any material, the Contractor shall verify in the field all bearing height and shim thickness dimensions. Adjustment must account for deck heave due to pack rust (if present).
 Min. jack capacity = 35 Tons.
 Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. ASTM A307 Grade C anchor bolts may be used in lieu of ASTM F1554 Grade 36 (Fy=36ksi). The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.
 Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.
 Cost of Side retainers and Stainless Steel plates shall be included in the cost of Elastomeric Bearing Assembly, Type I.




PLAN TOP AND BOTTOM PLATE



SECTION B-B




STEEL EXTENSION DETAIL



BEARING ASSEMBLY


Note:
 Shim plates shall not be placed under Bearing Assembly.




SIDE RETAINER

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates.

* 4 1/2" or 5 1/2"
 See Anchor Bolt Location Plan for clip details.



ANCHOR BOLT LOCATION PLAN



EXISTING BEARING REMOVAL DETAIL

Cost included with Jack and Remove Existing Bearings.

BILL OF MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly, Type I	Each	6
Jack and Remove Existing Bearings	Each	6
Furnishing and Erecting Structural Steel	Pound	1190
Anchor Bolts, 1"Ø	Each	12

TYI/REPS 5-17-2018

DESIGNED - ATH	EXAMINED
CHECKED - VHV	PASSED
DRAWN - Jim Ostermann daburdell	
CHECKED - ATH VHV	


 ENGINEER OF STRUCTURAL SERVICES	DATE - MAY 7, 2021
 ENGINEER OF BRIDGES AND STRUCTURES	REVISED 05/28/2021 ATH REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION


BEARING REPLACEMENT - S. ABUT.
 SN 072-0111

SHEET NO. 16 OF 19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
474	72(1HB,HB-1,2,3)BR	PEORIA	63	611
CONTRACT NO. 68E52				
ILLINOIS FED. AID PROJECT				




PIER 1
(Looking West)




PIER 2
(Looking West)

Entire sheet revised.




ELEVATION




PLAN

* Epoxy grout n(E) bars in 9" min. holes according to Article 584 of the Standard Specifications.




REPAIR DETAIL


- Concrete in this area to be paid as Concrete Structures.
- Concrete in this area is included with Structural Repair of Concrete (Depth ≤ 5").




SEC B-B



SEC A-A



BAR u(E)



BAR x(E)

BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	4	#5	9'-5"	
h1(E)	7	#5	4'-11"	
u(E)	6	#5	10'-0"	
v(E)	5	#5	3'-4"	
x(E)	30	#5	1'-6"	
Concrete Structures			Cu. Yd.	1.4
Reinforcement Bars, Epoxy Coated			Pound	200
** Structural Repair of Concrete (Depth ≤ 5")			Sq. Ft.	160
Temporary Shoring and Cribbing			Each	1

** Includes a 50% contingency.