


PLAN



Reflector Placement

- Median areas for Removal and Replacement. Cost included with Concrete Removal and Concrete Superstructure.
- Approach shoulder areas for Removal and Replacement. Cost included with Bridge Approach Shoulder Removal and Concrete Superstructure.

NOTES
 Prismatic curb reflectors shall be placed on median curb top surfaces for the length of the deck at 15' intervals and 2' from median centerline. They shall be installed according to Article 782 of the Standard Specifications prior to sealer application. Adhesive cost shall be incidental to reflector installation. Existing inlet, frame, and grate are to remain in place. (see Bridge Approach Shoulder Pavement and Drain Std. 609001)

SN.062-0050
 IL.17 over I-39

| | | | |
|--------------------------------------|----------------------|----------------|---------------|
| FILE NAME = | USER NAME = #USER# | DESIGNED - CEJ | REVISED - --- |
| #FILE#68729 SN062-0050 IL.17ovr I-39 | | DRAWN - CEJ | REVISED - --- |
| | PLOT SCALE = #SCALE# | CHECKED - --- | REVISED - --- |
| | PLOT DATE = #DATE# | DATE - --- | REVISED - --- |

**STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION**

REMOVAL & REPLACEMENT
 NOT TO SCALE SHEET NO. ___ OF ___ SHEETS STA. _____ TO STA. _____

| | | | | |
|---|------------|----------|--------------------|-----------|
| F.A.P. RTE. | SECTION | COUNTY | TOTAL SHEETS | SHEET NO. |
| 412 | 62-2HB-2II | MARSHALL | 9 | 9 |
| FED. ROAD DIST. NO. 4 ILLINOIS FED. AID PROJECT | | | CONTRACT NO. 68729 | |