



PILE SPECIFICATIONS

ASTM Standards
A 252 Grade 2

Mild Carbon Steel
Pipe or equivalent

3/8" wall thickness

12" I.D., 12 3/4" O.D.

Accommodates a 14" I.D.
MOAB Internal Bushing

NOTE
STEEL PILING TO BE DRIVEN IN ACCORDANCE WITH
ARTICLE 512 OF THE STANDARD SPECIFICATIONS.

STREAM BED ELEVATION IS APPROXIMATELY ELEV 599.
PILE TIP ELEVATION ESTIMATED AT ELEV 575.
PILE SHALL EXTEND ABOVE THE STREAM BED TO ELEV 634
AND SHALL BE ANCHORED INTO THE DECK WITH STABILIZER
BRACKETS AS SHOWN ABOVE.

MOABS, STABILIZER BRACKET ASSEMBLY AND CONSULTATION ON PILE
INSTALLATION PROVIDED BY DEBRIS FREE, INC. OJAI, CA.

FILE NAME =	USER NAME = #USER#	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	MOAB	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
#FILE#		DRAWN -	REVISED -			88	(195-3B-3)M-1	WHITESIDE	8	5	
PLOT SCALE = #SCALE#		CHECKED -	REVISED -			SCALE: _____ SHEET NO. OF _____ SHEETS STA. _____ TO STA. _____		CONTRACT NO. 64D97			
PLOT DATE = #DATE#		DATE -	REVISED -			FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT					