


**NOTES:**

- ① WHITE BAR PAVEMENT MARKING LINE - 24" SOLID
- ② WHITE PAVEMENT MARKING LINE - 8" SOLID
- ③ WHITE PAVEMENT MARKING LINE - 8" SOLID, 2' LONG, 6' GAP
- ④ YELLOW PAVEMENT MARKING LINE - 6" SOLID, 10' LONG, 30' GAP
- ⑤ EXISTING DOUBLE YELLOW PAVEMENT MARKING LINE - 4" SOLID EACH
- ⑥ DOUBLE YELLOW PAVEMENT MARKING LINE - 4" SOLID EACH
- ⑦ YELLOW PAVEMENT MARKING LINE - 12" SOLID @ 20' CTS.
- ⑧ PAVEMENT MARKING SYMBOL, SEE STANDARD NO. 780001-01
- ⑨ WHITE PAVEMENT MARKING LINE - 4" SOLID

- 1) STOP LINES ARE SOLID WHITE 24" WIDE EXTENDING ACROSS ALL APPROACH LANES.
- 2) LINES SHALL NOT BE LAID DIRECTLY OVER A LONGITUDINAL CRACK OR JOINT NOR OVER A TAR OR ASPHALT PAINTED LINE THE EDGE OF CENTER LINE OR LANE LINE SHALL BE OFFSET A MINIMUM OF 2 INCHES FROM A LONGITUDINAL CRACK OR JOINT.
- 3) SEE DETAILS FOR PLACEMENT OF TURN LANE MARKINGS.
- 4) EXISTING CURB AND GUTTER NOT SHOWN FOR PURPOSES OF CLARITY.
- 5) PERMANENT PAVEMENT MARKING SHALL BE THERMOPLASTIC FROM STA. 566+59 TO STA. 577+39.

- ◆ RAISED REFLECTIVE PAVEMENT MARKER, TWO WAY AMBER
- ◆ RAISED REFLECTIVE PAVEMENT MARKER, ONE WAY AMBER
- ◆ RAISED REFLECTIVE PAVEMENT MARKER, ONE WAY CLEAR



FILE NAME =	USER NAME = duncanbd	DESIGNED -	REVISED - DIST 3 COMMENT	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>IL 47 &amp; IL 165 PAVEMENT MARKING PLAN</b>	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
ci:\projects\ed02404\consult\cadd\drawings\shpmp02.dgn		DRAWN - MAP	REVISED - 5/27/04			326		FORD	22	19	
		CHECKED - RRM	REVISED - BDD 01/28/08			CONTRACT NO. 66423					
		DATE - 02/26/04	REVISED -			FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT					
				SCALE: 1" = 50'		SHEET NO. OF SHEETS STA. TO STA.					