

LANDSCAPING TABLE						
LOCATION	TOPSOIL FURNISH & PLACE 4"	SEEDING CLASS 2A	MULCH METHOD 2	NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT
	SQ YD	ACRE	ACRE	POUND	POUND	POUND
IL 98	1519	0.31	0.31	27.9	27.9	27.9
TOTAL	1519	0.31	0.31	27.9	27.9	27.9

TEMPORARY EROSION CONTROL SEEDING		
LOCATION	AREA ACRE	TOTAL POUND
JOBSITE	0.31	31
X 2 APPLICATIONS		62
TOTAL		62

EARTHWORK TABLE				
LOCATION	CHANNEL EXCAVATION	EARTH EXCAVATION	FOR INFORMATION ONLY	
			EARTH EXCAVATION (W/SHRINKAGE)	EMBANKMENT
			CU YD	CU YD
IL 98	52	452	339	327
TOTAL	52	452	339	327

SHRINKAGE FACTOR 25%

GUARDRAIL REMOVAL	
LOCATION	FOOT
LT 144+77 TO 145+77	100
RT 144+77 TO 145+77	100
TOTAL	200

CLASS D PATCHES, TYPE IV, 13 INCH	
LOCATION	SQ YD
144+88 TO 145+52	256
TOTAL	256

GUARDRAIL MARKERS TYPE A	
LOCATION	EACH
LT 143+55.5 TO 146+43	4
RT 142+45 TO 146+45	4
TOTAL	8

GUARDRAIL AGGREGATE EROSION CONTROL	
LOCATION	TON
LT 143+55.5 TO 146+43	56.8
RT 142+45 TO 146+45	79
TOTAL	135.8

PERIMETER EROSION BARRIER	
LOCATION	FOOT
LT 143+15 TO 144+65	153
LT 146+50 TO 146+83	43
SUBTOTAL	196
X 2 APPLICATIONS	
TOTAL	392

GUARDRAIL TABLE				
LOCATION	STEEL PLATE BEAM GUARDRAIL TYPE A	STEEL PLATE BEAM GUARDRAIL ATTACHED TO STRUCTURES	TRAFFIC BARRIER TERMINAL TYPE 1 TANGENT SPECIAL	TERMINAL MARKER DIRECT APPLIED
	FOOT	FOOT	EACH	EACH
LT 143+55.5 TO 143+93			1	1
LT 143+93 TO 146+05.5	175	37.5		
LT 146+05.5 TO 146+43			1	1
RT 142+45 TO 142+82.5			1	1
RT 142+82.5 TO 146+07.5	287.5	37.5		
RT 146+07.5 TO 146+45			1	1
TOTALS	462.5	75	4	4

BOX CULVERT BACKFILL TABLE					
LOCATION	REMOVAL & DISPOSAL OF UNSUITABLE MATERIAL	TRENCH BACKFILL	GEOTECHNICAL FABRIC FOR GROUND STABILIZATION	ROCKFILL	POROUS GRANULAR EMBANKMENT SPECIAL
	CU YD	CU YD	SQ YD	CU YD	CU YD
145+20	95.2	35.6	126.9	74	46.6
TOTAL	95.2	35.6	126.9	74	46.6

TEMPORARY DITCH CHECKS	
LOCATION	EACH
LT 145+75	1
LT 146+25	1
RT 143+00	1
RT 143+55	1
RT 144+10	1
RT 144+66	1
RT 145+57	1
RT 146+00	1
RT 146+40	1
SUBTOTAL	9
X 2 APPLICATIONS	
TOTAL	18

LOCATION	DEPTH	STONE DUMPED RIP RAP CLASS B3	FILTER FABRIC
	IN	SQ YD	SQ YD
RT 144+65 TO 144+93	8	28.9	28.9
LT 144+68 TO 145+08	8	42.4	42.4
RT 145+30 TO 145+56	8	26.8	26.8
LT 145+47 TO 145+75	8	29.5	29.5
TOTAL		127.6	127.6

CHANGEABLE MESSAGE SIGN	
NUM. OF SIGNS	CAL MO
2 SIGNS - 2 WEEKS EACH	1
TOTAL	1

AGGREGATE DITCH CHECKS	
LOCATION	EACH
D. S. END OF CULVERT	1
TOTAL	1

HOT-MIX ASPHALT SHOULDERS 8"	
LOCATION	SQ YD
LT 143+45.5 TO 144+88	79.2
LT 145+52 TO 146+53	56.1
RT 142+35 TO 144+88	140.6
RT 145+52 TO 146+55	57.2
TOTAL	333.1