

INDEX OF SHEETS

SHEET NO.	TITLE
1	COVER SHEET
2	INDEX OF SHEETS, HIGHWAY STANDARDS AND GENERAL NOTES
3	SUMMARY OF QUANTITIES
4-5	EXISTING AND PROPOSED TYPICAL SECTIONS
6	SCHEDULE OF QUANTITIES
7	CONTROL POINT TIE-OFFS
8-9	PLAN AND PROFILE SHEETS
10	GUARDRAIL AND SHOULDER DETAILS
11-18	BRIDGE SHEETS
19-20	DETOUR SIGNING DETAILS
21	TRAFFIC CONTROL AND PROTECTION DEVICES (ROAD AND SIDEROAD/STREET CLOSURES)
22-25	PAVEMENT MARKING AND MARKERS (RURAL AND URBAN APPLICATIONS)
26-30	CROSS SECTIONS

HIGHWAY STANDARDS

STANDARD NO.	DESCRIPTION
000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-01	AREA OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
280001-04	TEMPORARY EROSION CONTROL SYSTEMS
515001-02	NAME PLATE FOR BRIDGES
630001-07	STEEL PLATE BEAM GUARDRAIL
630301-04	SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
631032-03	TRAFFIC BARRIER TERMINAL, TYPE 6A
635006-02	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-01	REFLECTOR MARKER AND MOUNTING DETAILS
701006-02	OFF-RD OPERATIONS, 2L, 2W, 4.5m (15') TO 600 mm (24") FROM PAVEMENT EDGE
701311-02	LANE CLOSURE 2L, 2W MOVING OPERATIONS - DAY ONLY
701901	TRAFFIC CONTROL DEVICES
720001	SIGN PANEL MOUNTING DETAILS
780001-01	TYPICAL PAVEMENT MARKINGS

GENERAL NOTES:

G.N.-100  
ENGLISH UNITS OF MEASUREMENT SHALL GOVERN OVER AND SUPERSEDE ANY METRIC UNITS SHOWN IN THIS CONTRACT. WHERE INCLUDED, METRIC UNITS ARE FOR INFORMATION ONLY.

G.N.-105.09A  
ALL ELEVATIONS SHOWN IN THE PLANS ARE BASED ON NORTH AMERICAN VERTICAL DATUM OF 1988. (NAVD 88)

G.N.-107.31  
UTILITY LINES WERE PLOTTED FROM INFORMATION FURNISHED BY THE VARIOUS UTILITY COMPANIES INVOLVED (QUALITY LEVEL C &/OR QUALITY LEVEL D) AND THE ACCURACY SHOULD BE CONSIDERED APPROXIMATE ONLY.

UTILITY COMPANIES MAY BE ADJUSTING THEIR FACILITIES DURING CONSTRUCTION. THE CONTRACTOR SHALL COOPERATE WITH THESE ORGANIZATIONS WHILE THESE ADJUSTMENTS ARE BEING PERFORMED. J.U.L.I.E. - JOINT UTILITY LOCATION INFORMATION FOR EXCAVATORS SYSTEM (800)892-0123 OR 811.

G.N.-406  
THE QUANTITIES INCLUDED IN THE PLANS FOR HOT-MIX ASPHALT RESURFACING ARE INTENDED TO GIVE THE COVERAGE SHOWN ON THE TYPICAL CROSS SECTIONS. IT IS NOT INTENDED TO INCREASE THE THICKNESS OF THE HOT-MIX ASPHALT MIXTURE IN ORDER TO USE ALL OF THE QUANTITIES INCLUDED IN THE CONTRACT.

G.N.-406H

MIXTURE REQUIREMENTS

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS


PROJECT:

LOCATION(S):	FAS 520 STA. 70+62.50 TO STA. 72+14.50
MIXTURE USE(S):	SURFACE COURSE AND LEVEL BINDER
AC/PG:	PG 64-22
RAP %: (MAX)**	15%
DESIGN AIR VOIDS:	4.0% @ NDESIGN=50
MIXTURE COMPOSITION: (GRADATION MIXTURE)	IL 9.5
FRICTION AGGREGATE:	MIXTURE C

COMMITMENTS

THERE ARE NO COMMITMENTS ON THIS PROJECT.

FILE NAME = c:\p\projects\6506794 (68)\2008\_03\_21 Final submittal\microstation files\index.dgn



USER NAME = collierbw	DESIGNED - RRD	REVISED -
	DRAWN - KAS	REVISED -
PLOT SCALE =	CHECKED - JAR	REVISED -
PLOT DATE = 3/24/2008	DATE - 3/14/08	REVISED -

STATE OF ILLINOIS  
DEPARTMENT OF TRANSPORTATION

INDEX OF SHEETS, HIGHWAY STANDARDS AND GENERAL NOTES

SCALE: AS SHOWN SHEET NO. OF SHEETS STA. TO STA.

F.A.S. RTE. 502	SECTION 186BR1BR	COUNTY CHAMPAIGN	TOTAL SHEETS 30	SHEET NO. 2
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			CONTRACT NO. 70426	