

HOT MIX ASPHALT SHOULDERS, 11 1/2"

LOCATION				LENGTH	WIDTH	AREA
				(FEET)	(FEET)	(SQ YD)
717+39.77	TO	718+66.42	LT. MED	126.6	6.0	84.4
717+59.86	TO	719+07.89	RT. MED	148.0	6.0	98.7
722+97.00	TO	724+68.56	LT. O/S	171.6	10.0	190.6
723+15.65	TO	724+68.56	LT. MED	152.9	6.0	101.9
723+49.84	TO	724+75.48	RT. MED	125.6	6.0	83.8
723+67.68	TO	724+75.48	RT. O/S	107.8	10.0	119.8
795+21.50	TO	796+24.27	LT. O/S	102.8	6.0	68.5
795+21.50	TO	796+70.63	LT. MED	149.1	10.0	165.7
796+16.15	TO	797+57.59	RT. MED	141.4	6.0	94.3
796+16.15	TO	798+03.94	RT. O/S	187.8	10.0	208.7
800+31.71	TO	802+19.45	LT. O/S	187.7	10.0	208.6
800+78.07	TO	802+19.45	LT. MED	141.4	6.0	94.3
801+65.02	TO	803+70.85	RT. MED	205.8	6.0	137.2
802+11.38	TO	803+70.85	RT. O/S	159.5	10.0	177.2
852+31.40	TO	853+52.40	LT. O/S	121.0	10.0	134.4
853+52.40	TO	853+99.50	LT. O/S	47.1	12.0	62.8
853+99.50	TO	854+38.50	LT. O/S	39.0	14.0	60.7
854+38.50	TO	854+85.50	LT. O/S	47.0	12.0	62.7
854+85.50	TO	856+51.40	LT. O/S	165.9	10.0	184.3
852+31.40	TO	856+51.40	LT. MED.	420.0	6.0	280.0
853+31.30	TO	854+97.90	RT. O/S	166.6	10.0	185.1
854+97.90	TO	855+46.90	RT. O/S	49.0	12.0	65.3
855+46.90	TO	855+89.10	RT. O/S	42.2	14.0	65.6
855+89.10	TO	856+38.10	RT. O/S	49.0	12.0	65.3
856+38.10	TO	857+51.30	RT. O/S	113.2	10.0	125.8
853+31.30	TO	857+51.30	RT. MED.	420.0	6.0	280.0
TOTAL =						3405.8

TRAFFIC BARRIER TERMINAL, TYPE 6

LOCATION				NO.
				(EACH)
RT. MEDIAN	718+70.98	TO	719+37.86	1.0
LT. MEDIAN	723+09.61	TO	723+53.04	1.0
RT. MEDIAN	797+20.45	TO	797+66.09	1.0
RT.	797+66.80	TO	798+12.45	1.0
LT.	800+23.21	TO	800+68.86	1.0
LT. MEDIAN	800+69.57	TO	801+15.21	1.0
TOTAL =				6.0

FILLING INLETS, (SPECIAL)

LOCATION	STATION	EACH
LT. SHLDR	722+93.96	1.0
RT. MED.	723+46.86	1.0
LT. SHLDR	796+27.27	1.0
LT. MED	796+73.63	1.0
RT. MED.	797+60.59	1.0
RT. SHLDR	798+06.95	1.0
RT. MED.	801+62.02	1.0
RT. SHLDR	802+08.36	1.0
TOTAL		8.0

STEEL PLATE BEAM GUARD RAIL, REMOVAL

LOCATION				LENGTH
				(FEET)
LT.	718+06.15	TO	718+55.92	49.8
MEDIAN	717+46.03	TO	719+13.85	167.8
RT.	718+92.83	TO	719+45.78	52.9
LT.	722+82.74	TO	724+41.00	158.3
MEDIAN	723+09.61	TO	724+96.57	187.0
MEDIAN	795+72.00	TO	797+63.59	191.6
RT.	796+25.00	TO	798+09.94	184.9
LT.	800+25.71	TO	802+14.00	188.3
MEDIAN	800+72.07	TO	802+60.00	187.9
TOTAL =				1368.5

TERMINAL MARKER-DIRECT APPLIED

LOCATION	STATION	EACH
RT. MEDIAN	716+35.52	1.0
LT. SHLD	723+85.38	1.0
LT. MEDIAN	725+91.00	1.0
RT. MEDIAN	794+83.87	1.0
RT. SHLD	797+16.98	1.0
LT. SHLD	801+18.69	1.0
LT. MEDIAN	803+51.74	1.0
TOTAL =		7.0