



SCHEDULE OF QUANTITIES

TREE REMOVAL, 6-15" DIA. (UNIT)	
Harrison	
291+69, 58.5' RT	10.00
292+14, 58.6' RT	10.00
292+30, 60.4' RT	10.00
292+45, 62.5' RT	10.00
293+11, 60.5' RT	10.00
TOTAL	50.00

EARTH EXCAVATION (CU. YD.)	
Harrison Avenue	5,296.00
Perryville Road	1,628.00
TOTAL	6,924.00

REMOVE & DISPOSE UNS MATL (CU. YD.)	
Harrison Avenue	1,424.00
Perryville Road	711.00
TOTAL	2,135.00

TRENCH BACKFILL (CU. YD.)	
HARRISON	
292+79, 55.0' RT	10.00
314+00, 0' RT	2.00
330+40, RT & LT	8.00
332+45, RT & LT	10.00
PERRYVILLE	
20+56, 55' LT	7.00
22+06, 47.5' LT	6.00
TOTAL	43.00

GEOTECH FAB FIGR STAB (SQ. YD.)	
Harrison Avenue	4,239.00
Perryville Road	2,167.00
TOTAL	6,406.00

TOPSOIL FURNISH AND PLACE 4" (SQ. YD.)	
Harrison Avenue	8,058.00
Perryville Road	4,028.00
TOTAL	12,086.00

SEEDING CLASS 1A (Acre)	
Harrison Avenue	2.00
Perryville Road	1.00
TOTAL	3.00

FERTILIZER NUTRIENTS (LBS)	
Harrison Avenue	
Nitrogen	74.00
Phosphorus	74.00
Potassium	74.00
Perryville Road	
Nitrogen	150.00
Phosphorus	150.00
Potassium	150.00
TOTAL EACH	224.00

MULCH METHOD 3 (Acre)	
Harrison Avenue	2.00
Perryville Road	1.00
TOTAL	3.00

EROSION CONTROL BLANKET (SQ. YD.)	
320+00-323+90, RT	1,185.00
320+50-321+60, LT	100.00
321+75-322+30, LT	50.00
322+80-328+25, LT	2,505.00
324+10-330+00, RT	1,840.00
328+75-330+00, LT	390.00
330+00-331+30, LT	510.00
330+00, RT-16+50, L	1,550.00
331+45-333+50, LT	705.00
337+00, LT-24+00, F	1,475.00
TOTAL	10,310.00

TEMP DITCH CHECKS (EA.)	
325+00-328+00, RT	4.00
328+25, LT	1.00
328+75, LT	1.00
330+00, RT	1.00
330+40, LT	1.00
331+00, RT-16+50, L	5.00
332+50-333+00, LT	2.00
TOTAL	15.00

PERIMETER EROSION BARRIER (FT)	
287+75-292+50, RT	500.00
320+00-323+90, RT	390.00
320+50-321+60, LT	110.00
321+75-322+30, LT	55.00
322+80-328+25, LT	580.00
324+10-330+00, RT	590.00
328+75-330+00, LT	130.00
330+00-331+30, LT	130.00
330+00-16+50, LT	420.00
331+45-333+50, LT	205.00
337+00-24+00, RT	370.00
TOTAL	3,480.00

INLET AND PIPE PROTECTION (EACH)	
289+00, RT Harrison	1.00
292+38, RT Harrison	1.00
314+00, MED Harrison	1.00
323+00, MED Harrison	1.00
326+00, MED Harrison	1.00
334+00, ISLN Harrison	1.00
20+60, MED Perryville	1.00
22+00, MED Perryville	1.00
24+00, MED Perryville	1.00
TOTAL	9.00

SUB-BASE GRANULAR MATERIAL, T-B, 4" (SQ. YD.)	
287+68 TO 292+67, RT	209
313+13 TO 318+31	709
320+52 TO 334+16, RT & LT	14082
TOTAL	15,000.00

AGGREGATE BASE COURSE, TYPE B, 4" (SQ. YD.)	
Driveways, 320+52-333+00, RT & Shoulders, 320+52-333+00, RT &	276.00
	3,239.00
TOTAL	3,515.00

AGGREGATE BASE COURSE, TYPE B, 8" (SQ. YD.)	
287+91 TO 292+64, RT	581.00
TOTAL	581.00

BIT MATERIALS (PRIME COAT) (GAL)	
287+91 TO 320+52, RT & LT	2,008.00
TOTAL	2,008.00

AGGREGATE (PRIME COAT) (TON)	
320+52 TO 334+16, RT & LT	9.00
TOTAL	9.00

HMA SURFACE COURSE, MIX "C", N30 (TON)	
287+91 TO 292+64, RT	60.00
TOTAL	60.00

HMA SURFACE COURSE, MIX "D", N70 (TON)	
287+91 TO 320+52, RT & LT	3,335.00
TOTAL	3,335.00

INCIDENTAL HOT-MIX ASPHALT SURFACING, 3" (TON)	
288+27, RT	8.10
288+48, RT	8.20
289+69, RT	8.20
290+80, RT	8.30
317+75, LT	22.80
320+45, LT	6.00
321+68, LT	6.00
322+45, LT	18.70
323+93, RT	9.30
331+42, LT	6.40
TOTAL	102.00

PCC PAVEMENT, JOINTED 10" (SQ. YD.)	
Harrison Avenue	12,067.00
Perryville Road	1,678.00
TOTAL	13,745.00

HMA SURFACE REMOVAL- COLD MILLING (SQ. YD.)	
287+91 TO 320+52, RT & LT	27,098.00
TOTAL	27,098.00

PAVEMENT REMOVAL (SQ. YD.)	
287+68 TO 292+67, RT	579.00
320+52 TO 334+16, RT & LT	11,940.00
335+07 TO 336+42, RT & LT	452.00
TOTAL	12,971.00

DRIVEWAY PAVEMENT REMOVAL (SQ. YD.)	
288+27, RT	47.70
288+48, RT	48.70
289+69, RT	48.20
290+80, RT	48.40
317+75, LT	134.80
320+45, LT	35.70
321+68, LT	35.60
322+45, LT	111.20
323+93, RT	55.30
331+42, LT	38.40
TOTAL	604.00

COMBINATION CURB & GUTTER REMOVAL (FT)	
20+25 TO 24+41, RT & LT	1,169.00
TOTAL	1,169.00

COMB C&G REMOVE & REPLACEMENT (FT)	
287+91 TO 320+52, RT & LT	3,000.00
TOTAL	3,000.00

GUTTER OUTLET REMOVAL (EACH)	
287+67, RT	1.00
TOTAL	1.00

ISLAND REMOVAL (SQ FT)	
333+71, RT	261.00
334+38, LT	224.00
334+71, RT	504.00
335+33, LT	267.00
TOTAL	1,256.00

MEDIAN REMOVAL SPECIAL (SQ FT)	
313+13 TO 318+31, RT & I	7,817.00
320+52 TO 328+79, RT & I	11,037.00
329+37 TO 333+83, RT & I	4,282.00
334+89, LT	167.00
TOTAL	23,303.00

MEDIAN SURFACE REM & REP (SQ FT)	
287+91 TO 320+52, RT & I	4,000.00
TOTAL	4,000.00

AGGREGATE SHOULDERS, 6" TYPE B (SQ. YD.)	
328+68, LT	44.00
328+91, LT	44.00
TOTAL	88.00

AGG SHOULDERS, (SPECIAL) 6" TYPE B (SQ. YD.)	
287+91 TO 292+64, RT	105.00
TOTAL	105.00

HMA SHOULDERS, 3" (SQ. YD.)	
287+91 TO 320+52, RT & I	1,075.00
TOTAL	1,075.00

HMA SHOULDERS, 8" (SQ. YD.)	
320+52 TO 334+16, RT & I	2,932.00
TOTAL	2,932.00

PIPE CULVERT REMOVAL (FEET)	
288+27, RT	22.00
288+48, RT	23.00
289+69, RT	20.00
290+80, RT	20.00
317+75, LT	35.00
320+45, LT	20.00
321+68, LT	20.00
322+45, LT	35.00
323+93, RT	20.00
331+42, LT	20.00
TOTAL	235.00

PRC FLARED END SECTION 12" (EACH)	
330+40.9, 67' RT	1.00
TOTAL	1.00

PRC FLARED END SECTION 18" (EACH)	
293+04, 55' RT	1.00
TOTAL	1.00

PRC FLARED END SECTION 24" (EACH)	
328+61, 65' LT	1.00
TOTAL	1.00

PRC FLARED END SECTION 36" (EACH)	
328+57, 58' LT	1.00
TOTAL	1.00

STORM SEWER CL A, TY 1, 12" (FOOT)	
289+00, 50' RT	8.00
292+38, 50' RT	8.00
330+40, RT & LT	32.00
TOTAL	48.00

STORM SEWER CL A, TY 1, 18" (FOOT)	
288+08 TO 293+04, 55' RT	487.00
TOTAL	487.00

STORM SEWER CL A, TY 1, 24" (EACH)	
328+61, 65' LT	6.00
TOTAL	6.00

STORM SEWER CL A, TY 1, 36" (EACH)	
328+57, 58' LT	6.00
TOTAL	6.00

INLETS TYPE A, T-3, FRAME & GRATE (EACH)	
328+57, 9.5' LT	1.00
330+40, 9.5' LT	1.00
332+45, 9.5' LT	1.00
TOTAL	3.00

INLETS TYPE A, T-4, FRAME & GRATE (EACH)	
20+56, 55' LT	1.00
22+06, 47.5' LT	1.00
TOTAL	2.00

MANHOLES TO BE ADJUSTED (EACH)	
288+09, 50' RT	1.00
20+86, 96' LT	1.00
22+05, 44' LT	1.00
TOTAL	3.00

MANHOLES TO BE RECONSTRUCTED (EACH)	
288+09, 56' RT	1.00
332+45, 51' LT	1.00
TOTAL	2.00

INLETS TO BE ADJUSTED WITH NEW T-4 F&G (EACH)	
19+06, 33' LT	1.00
20+56, 48' LT	1.00
22+06, 33' LT	1.00
24+06, 33' LT	1.00
TOTAL	4.00

INLETS TO BE RECON W \ SALVAGED F&G (EACH)	
325+85, 6' LT	1.00
TOTAL	1.00

REMOVING INLETS (EACH)	
328+55, 4' LT	1.00
330+40, 5.3' LT	1.00
20+56, 48' LT	1.00
22+06, 33' LT	1.00
TOTAL	4.00

REMOVING MANHOLES TO MAINTAIN FLOW (EACH)	
20+56, 48' LT	1.00
TOTAL	1.00

COMB CC & G, TYPE B-6.06 (FEET)	
325+90 TO 326+40, LT	298.00
333+58, RT	32.00
334+30, LT	23.00
334+65, RT	33.00
335+51, LT	28