

PAVEMENT SCHEDULE										
LOCATION STATION TO STATION	LENGTH	WIDTH	HMA SURF. REM. BUTT-JOINT (SQ YD)	HMA SURF. REM. (2 1/4") (SQ YD)	LEVELING BINDER (MM) N50 (3/4") (TON)	HMA SURF. COURSE MIX "C" N50 (1 1/2") (TON)	BIT. MAT. PRIME CT. (TON)	AGG. PRIME CT. (TON)	STRIP REFLECTIVE CRACK CONTROL (FOOT)	
FAP 745 (IL 104)										
STA. 1253+70.00 TO STA. 1253+77.50	7.50	24	20.00	-	0.84	1.68	0.01	0.04	7.5	
STA. 1253+77.50 TO STA. 1276+22.50	2245.00	24	-	5986.67	251.44	502.88	2.27	11.97	2245.0	
STA. 1276+22.50 TO STA. 1276+30.00	7.50	24	20.00	-	0.84	1.68	0.01	0.04	7.5	
TOTAL			40.0	5986.7	253.1	506.2	2.3	12.1	2260.0	

GUTTER SCHEDULE							
LOCATION STATION TO STATION	GUTTER REMOVAL (FOOT)	EXCAVATING AND GRADING EXISTING SHOULDER (UNIT)	CONCRETE GUTTER TYPE A (FOOT)	CLASS SI CONCRETE (OUTLET) (CU YD)	PIPE UNDERDRAINS 4" (FOOT)	CONCRETE HEADWALLS FOR PIPE DRAINS (EACH)	PIPE UNDERDRAIN 4" (SPECIAL) (FOOT)
FAP 745 (IL 104)							
LEFT							
STA. 1253+70.00 TO STA. 1256+60.00	290.0	2.9	290.0	4	290	1	20.0
STA. 1262+70.00 TO STA. 1265+60.00	290.0	2.9	290.0	8.5	290	1	20.0
STA. 1267+81.00 TO STA. 1269+74.00	193.0	1.93	193.0	7.5	193	1	20.0
STA. 1271+77.00 TO STA. 1276+30.00	453.0	4.53	453.0	3	453	1	20.0
RIGHT							
STA. 1253+70.00 TO STA. 1257+90.00	420.0	4.2	420.0	4	420	1	20.0
STA. 1262+29.00 TO STA. 1265+60.00	331.0	3.31	331.0	8.5	331	1	20.0
STA. 1267+61.00 TO STA. 1269+10.00	149.0	1.49	149.0	7.5	149	1	20.0
STA. 1271+35.00 TO STA. 1276+30.00	495.0	4.95	495.0	3	495	1	20.0
TOTAL		2621.0	26.2	2621.0	46.0	2621.0	160.0

PAVEMENT PATCHING			
LOCATION	PATCHING TYPE II 15 INCH (SQ YD)	PATCHING TYPE III 15 INCH (SQ YD)	PATCHING TYPE IV 15 INCH (SQ YD)
FAP 745 (IL 104)	20.0	22.0	30.0
TOTAL		20.0	30.0

TEMPORARY RAMPS			
LOCATION STATION	LENGTH (FT)	WIDTH (FT)	AREA (SQ YD)
FAP 745 (IL-100)			
MAINLINE			
1253+70.00	7.5	24	20
1276+30.00	7.5	24	20
TOTAL			40

SIDEROAD AND ENTRANCE SCHEDULE										
LOCATION FAP 745 (IL 104)	WIDTH ACROSS FRONT (FT)	WIDTH ACROSS BACK (FT)	LENGTH OF IMPROVEMENT FROM EOP (FT)	EXIST. SURF. TYPE	PREPARATION OF BASE (SQ YD)	INCIDENTAL HOT-MIX ASPH. SURF. (TON)	BIT. MAT. PRIME COAT (TON)	AGGREGATE PRIME COAT (TON)	AGGREGATE SURF. CSE. TYPE B (TON)	AGGREGATE FOR TEMP. ACCESS (TON)
P.E. LT. STA. 1256+08	42	12	8	AGG	24.00	2.69	0.01	0.05	1.00	2.00
P.E. RT. STA. 1257+32	42	12	8	AGG	24.00	2.69	0.01	0.05	1.00	2.00
P.E. LT. STA. 1262+37	42	12	8	AGG	24.00	2.69	0.01	0.05	1.00	2.00
M.B.T. RT. STA. 1262+70	64	20	8	AGG	37.33	4.18	0.01	0.07	-	-
M.B.T. RT. STA. 1269+26	64	20	8	AGG	37.33	4.18	0.01	0.07	-	-
P.E. LT. STA. 1270+08	42	12	8	AGG	24.00	2.69	0.01	0.05	1.00	2.00
TOTAL					170.66	19.12	0.06	0.34	4.00	8.00

PERMANENT SURVEY MARKER			
LOCATION STATION	LOCATION	EXISTING MONUMENT DESCRIPTION	PERMANENT SURVEY MARKERS, TYPE I (EACH)
FAP 745 (IL 104)			
STA. 1259+48.99	CENTER, SECTION 8	RAILROAD SPIKE	1
TOTAL			1