

SIGNAL HEAD, 1-FACE, 1-SECTION
 THE BOTTOM OF THE HOUSING SHALL
 BE NOT LESS THAN 12" (305mm) NOR
 MORE THAN 24" (610mm) ABOVE THE
 TOP OF THE SIGN.

4" (102 mm) X 6" (152 mm)
 WOOD POST AND SIGN

FLASHER
 CONTROLLER
 AND CABINET

FLASHER
 CONTROLLER
 AND CABINET

CONDUIT CLAMP

7' (2,134m) MIN. URBAN
 5' (1,524m) MIN. RURAL

1/2" (38mm) G.S. CONDUIT. FIVE
 EVENLY SPACED CONDUIT
 CLAMPS SHALL BE USED TO
 ATTACH CONDUIT TO POST

1/2" (38mm) DRILLED HOLE CENTERED
 AT 18" (457mm) FROM GROUND LEVEL

1/2" (38mm) DRILLED HOLE CENTERED
 AT 4" (102mm) FROM GROUND LEVEL

EDGE OF PAVEMENT

30" (76mm) MIN.

POST MOUNTED FLASHING BEACON
 WITH CONTROLLER AND CABINET

FILE NAME = W:\diststd\22x34\ts04.dgn	USER NAME = gaglionobt	DESIGNED -	REVISED - 01-01-07
		DRAWN -	REVISED -
	PLOT SCALE = 50.0000' / IN.	CHECKED -	REVISED -
	PLOT DATE = 1/4/2008	DATE -	REVISED -

STATE OF ILLINOIS
 DEPARTMENT OF TRANSPORTATION

POST MOUNTED FLASHING BEACON
 WITH CONTROLLER AND CABINET

SCALE: NONE SHEET NO. 2 OF 3 SHEETS STA. TO STA.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
303	134-N-1	LAKE	62	53
TS-04		CONTRACT NO. 60L28		
FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT				