



HMA MIXTURE REQUIREMENTS	
MIXTURE TYPE	AIR VOIDS & Ndes
APPROACH SLAB	
HOT-MIX ASPHLT SURFACE COURSE, MIX D, N70. (IL 9.5mm)	4% @ 70 GYR
HOT-MIX ASPHALT SHOULDERS	
HOT-MIX ASPHLT SURFACE COURSE, MIX D, N70. (IL 9.5mm)	4% @ 70 GYR
LEVELING BINDER (M M), N70 (IL 9.5 mm)	4% @ 70 GYR
TEMPORARY PAVEMENT	
HOT-MIX ASPHLT BINDER COURSE; IL 19.0, N50; 8"	4% @ 50 GYR

- NOTES:**
- EXISTING CONFLICTING PAVEMENT MARKINGS SHALL BE REMOVED.
 - ALL SIGNS SHALL BE POST LANE MOUNTED IF THE CLOSURE TIME EXCEEDS FOUR HOURS.
 - CONTINUOUS REFLECTIVE TEMPORARY PAVEMENT MARKING TAPE SHALL BE PLACED THROUGHOUT THE TAPER AND FOR 250' ALONG SIDE THE WORK AREA WHERE THE CLOSURE TIME IS GREATER THAN FOURTEEN DAYS.
THE LEFT EDGE LINE SHALL BE YELLOW AND THE RIGHT EDGE LINE SHALL BE WHITE.

THE UNIT WEIGHT USED TO CALCULATE ALL HMA SURFACE MIXTURE QUANTITIES IS 112 LBS/SQ. YD./IN.

THE "AC" TYPE FOR POLYMERIZED HMA MIXES SHALL BE "SBS / SBR PG 76-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64 -22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

FOR USE OF RECYCLED MATERIALS SEE SPECIAL PROVISIONS.