

# HOT-MIX ASPHALT SCHEDULE

•40600200•    ••40600300••    •••40600625•••    •••40600635•••    •••40600837•••    •••40603085•••    •••40603310•••    ••••40603590••••    48203019

Location	Remarks	Length	Proposed Surface		Bit Materials	Agg	Leveling Binder	Leveling Binder	Polymerized	Hot-Mix Asphalt	Hot-Mix Asphalt	Polymerized	Hot-Mix Asphalt
			Width	Sq Yd	Prime Coat (2 Applications)	Prime Coat	(Machine Method), N50	(Machine Method), N70	Leveling Binder (Machine Method), N70	Binder Course, IL-19.0, N70	Surface Course, Mix "C", N50	Surface Course, Mix "F", N70	Shoulders, 5 1/2"
					Ton	Ton	Ton	Ton	Ton	Ton	Ton	Ton	Sq Yd
US Bus 20 - Mainline Resurfacing													
Sta 300 + 97 - 301 + 72	Start / Butt Joint	75	42'	351.9	0.20	0.53			19.7				32.5
Sta 301 + 72 - 306 + 14		442	42' - 52'	2,388.9	1.37	3.58			133.8				220.4
Sta 306 + 14 - 310 + 00	Milled Section	386	52' & Var	2,428.9	1.39	3.64			136.0				224.1
Sta 310 + 00 - 313 + 96		396	40' - 33'	1,665.3	0.95	2.50			93.3				153.6
Sta 313 + 96 - 317 + 24		328	33' - 25'	1,035.8	0.59	1.55			58.0				95.6
Sta 317 + 24 - 324 + 63		739	25' - 24'	1,989.7	1.14	2.98			111.4				183.5
Sta 324 + 63 - 335 + 82		1119	24'	3,027.3	1.73	4.54			169.5				279.3
Sta 335 + 82 - 360 + 49		2467	24'	6,633.2	3.79	9.95			371.5				611.9
Sta 360 + 49 - 366 + 00		551	24'	1,480.5	0.85	2.22			82.9				136.6
Sta 366 + 00 - 366 + 75	End / Butt Joint	75	24'	205.0	0.12	0.31			11.5				18.9
US Bus 20 - Mainline Widening													
Sta 308 + 84 - 310 + 00	Start Full-Depth Shoulder	116	5' - 12'	144.9	0.08				8.1	60.9			13.4
Sta 310 + 00 - 313 + 96	Start of Widening	396	13' - 37'	1,043.7	0.60				58.4	438.4			96.3
Sta 313 + 96 - 318 + 63		467	24'	1,244.2	0.71				69.7	522.6			114.8
Sta 318 + 63 - 335 + 82		1719	24'	4,536.4	2.59				254.0	1905.3			418.5
Sta 335 + 82 - 345 + 09		927	24'	2,445.8	1.40				137.0	1027.2			225.6
Sta 345 + 09 - 360 + 49		1540	24'	4,107.3	2.35				230.0	1725.1			378.9
Sta 360 + 49 - 366 + 00	End of Widening	551	46' - 10'	1,794.3	1.03				100.5	753.6			165.5
Sta 366 + 00 - 366 + 75	End Full-Depth Shoulder	75	10' - 4'	50.2	0.03				2.8	21.1			4.6
Mainline (LT) - Variable Depth													
Sta 310 + 00 - 313 + 96	Start Profile Change	396	40' - 33'	1,665.3	0.95	2.50		92.6					
Sta 313 + 96 - 316 + 74		278	33' - 25'	895.8	0.51	1.34		162.1					
Sta 316 + 74 - 317 + 09	Start Correction	35	25' - 24'	95.3	0.05	0.14		22.9					
Sta 317 + 09 - 318 + 63		154	24'	410.7	0.23	0.62		24.4					
Sta 318 + 63 - 319 + 40		77	24'	205.3	0.12	0.31		28.4					
Sta 319 + 40 - 324 + 63		523	24'	1,394.7	0.80	2.09		307.9					
Sta 324 + 63 - 335 + 82	Full Super	1119	24'	2,984.0	1.71	4.48		389.2					
Sta 335 + 82 - 344 + 32		850	24'	2,266.7	1.30	3.40		234.0					
Sta 344 + 32 - 345 + 09		77	24'	205.3	0.12	0.31		19.3					
Sta 345 + 09 - 346 + 63	End Correction	154	24'	410.7	0.23	0.62		21.7					
Sta 346 + 63 - 346 + 98		35	24'	93.3	0.05	0.14		14.5					
Sta 346 + 98 - 360 + 49		1351	24'	3,602.7	2.06	5.40		358.3					
Sta 360 + 49 - 366 + 00	End Profile Change	551	24'	1,469.3	0.84	2.20		162.1					