

| | | | | |
|-----------------------|----------|---------------------------|--------------|-----------|
| F.A.S. RTE. | SECTION | COUNTY | TOTAL SHEETS | SHEET NO. |
| 2466 | (11)RS-3 | WOODFORD | 23 | 13 |
| FED. ROAD DIST. NO. . | | ILLINOIS FED. AID PROJECT | | |

Sideroads, Entrances, and Mailbox Turnouts

| LOCATION | TYPE | Material | LENGTH | AREA | HMA SURF. REMOVAL (BUTT JT.) | TEMP. RAMP | POLY. BIT. MATRLS. PRIME COAT | AGG. PRIME COAT | INCID. HMA 2" SURFACE |
|-------------|-------------|-----------|--------|---------|------------------------------|------------|-------------------------------|-----------------|-----------------------|
| STATION | | | FOOT | SQ. YD. | SQ. YD. | SQ. YD. | TON | TON | TON |
| 199+02 RT | PE | Bit | 12 | 32 | 32 | | 0.01 | 0.1 | 3.58 |
| 200+07.6 RT | PE w/MB | Bit | 10 | 45 | 45 | | 0.02 | 0.1 | 5.04 |
| 200+07.6 LT | PE | Gravel | 12 | 45.3 | 45.3 | | 0.02 | 0.1 | 5.07 |
| 206+94 LT | PE | Gravel | 11 | 38.5 | 38.5 | | 0.02 | 0.1 | 4.31 |
| 206+94 RT | MB | Gravel | 49 | 34.4 | 34.4 | | 0.01 | 0.1 | 3.85 |
| 212+27 LT | CE | PCC/w Bit | 10 | 73.9 | 73.9 | | 0.03 | 0.1 | 8.28 |
| 213+85.4 RT | CR 1425E | Bit | 15 | 40 | 40 | 7.22 | 0.02 | 0.1 | 4.48 |
| 213+85.4 LT | PE | Bit | 10 | 28.9 | 28.9 | | 0.01 | 0.1 | 3.24 |
| 214+38.2 RT | CE | Bit | 17 | 91.6 | 91.6 | | 0.04 | 0.2 | 10.26 |
| 214+91 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 215+50 RT | CE | Bit | 9 | 24 | 24 | | 0.01 | 0.0 | 2.69 |
| 218+60.6 LT | PE | Bit | 11 | 31.8 | 31.8 | | 0.01 | 0.1 | 3.56 |
| 219+66.2 RT | CE/MB | Bit | 10 | 59.5 | 59.5 | | 0.02 | 0.1 | 6.66 |
| 220+19 LT | PE | Bit | 10 | 23.9 | 23.9 | | 0.01 | 0.0 | 2.68 |
| 221+77.4 RT | CE | Bit | 11 | 85.6 | 85.6 | | 0.03 | 0.2 | 9.59 |
| 223+35.8 LT | MABLE DR. | Bit | 22 | 114.9 | 114.9 | 15 | 0.05 | 0.2 | 12.87 |
| 225+99.8 LT | CE | PCC | 8 | 26.2 | 26.2 | | 0.01 | 0.1 | 2.93 |
| 227+58.2 RT | CE | PCC | 15 | 101.7 | 101.7 | | 0.04 | 0.2 | 11.39 |
| 229+69.4 RT | PE w/MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 229+69.4 LT | PE w/MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 231+70 RT | PE | Gravel | 33 | 28.9 | 28.9 | | 0.01 | 0.1 | 3.24 |
| 232+80 LT | PE | Bit | 37 | 30.56 | 30.56 | | 0.01 | 0.1 | 3.42 |
| 233+00 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 236+03 RT | PE w/MB | Bit | 10 | 28.9 | 28.9 | | 0.01 | 0.1 | 3.24 |
| 237+08.6 LT | PE | Bit | 10 | 30.6 | 30.6 | | 0.01 | 0.1 | 3.43 |
| 239+19.8 LT | PE | Bit | 10 | 30.6 | 30.6 | | 0.01 | 0.1 | 3.43 |
| 239+72.6 RT | PE w/MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 239+72.6 LT | PE | Bit | 10 | 31.7 | 31.7 | | 0.01 | 0.1 | 3.55 |
| 241+03 LT | PE | Bit | 10 | 26.7 | 26.7 | | 0.01 | 0.1 | 2.99 |
| 242+89.4 RT | PE | Bit | 10 | 28.9 | 28.9 | | 0.01 | 0.1 | 3.24 |
| 242+89.4 LT | PE | Bit | 6 | 17 | 17 | | 0.01 | 0.0 | 1.9 |
| 245+00.6 RT | PE | Bit | 10 | 31.7 | 31.7 | | 0.01 | 0.1 | 3.55 |
| 248+70.2 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 249+75.8 RT | TR w/MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 249+75.8 LT | PE | Bit | 10 | 32.22 | 32.22 | | 0.01 | 0.1 | 3.61 |
| 255+56.6 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 256+62.2 LT | PE | Bit | 20 | 91.11 | 91.11 | | 0.04 | 0.2 | 10.20 |
| 257+15 LT | PE | Bit | 12 | 106 | 106 | | 0.04 | 0.2 | 11.87 |
| 271+40.2 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 271+40.2 LT | PE | Bit | 20 | 84.4 | 84.4 | | 0.03 | 0.2 | 9.45 |
| 274+57 LT | FE | Bit | 12 | 32 | 32 | | 0.01 | 0.1 | 3.58 |
| 279+32.2 LT | GRIMM RD. | Bit | 25 | 164.61 | 164.61 | 21.11 | 0.07 | 0.3 | 18.44 |
| 281+96.6 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 291+13.2 LT | PE | Bit | 24 | 103 | 103 | | 0.04 | 0.2 | 11.54 |
| 291+13.2 RT | PE w/MB | Bit | 24 | 98 | 98 | | 0.04 | 0.2 | 10.98 |
| 292+71.6 LT | CE | Bit | 25 | 113.89 | 113.89 | | 0.05 | 0.2 | 12.76 |
| 294+82.8 LT | CE | Bit | 23 | 111.56 | 111.56 | | 0.04 | 0.2 | 12.49 |
| 297+46.8 LT | FARNEYVILLE | Bit | 24 | 102.67 | 102.67 | 10.56 | 0.04 | 0.2 | 11.50 |
| 311+19.6 RT | MB | Bit | 72 | 52 | 52 | | 0.02 | 0.1 | 5.82 |
| 311+19.6 LT | PE | Bit | 10 | 26.67 | 26.67 | | 0.01 | 0.1 | 2.99 |
| 325+98 RT | PE | Bit | 10 | 25 | 25 | | 0.01 | 0.1 | 2.80 |

SCHEDULE OF QUANTITIES