

F.A. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
332	(F-1,1)RS-4	CLARK	46	5
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

### GENERAL NOTES (cont'd)

G.N.-406H

MIXTURE REQUIREMENTS

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

LOCATION	IL 1 37+30.00 TO 141+85.00	IL 1 MAINLINE 63+76.26 TO 141+85.00	IL 1 SOUTHBOUND THROUGH LANE 101+18.40 TO 102+65.00	IL 1 MAINLINE 37+30.00 TO 141+85.00	IL 1 BITUMINOUS SHOULDERS 37+30.00 TO 63+76.26
MIXTURE USE	PARTIAL DEPTH PATCH/PAVEMENT CLEANING/INCIDENT.	POLYMER LEVEL BINDER	POLYMER BINDER	POLYMER SURFACE	LOW ESAL SURFACE
AC/PG	PG 64-22	SBS PG 70-22	SBS PG 70-22	SBS PG 70-22	PG 58-22*
RAP % (MAX)	10	0	0	0	30
DESIGN AIR VOIDS	4.0% @ Ndes=70	4.0% @ Ndes=70	4.0% @ Ndes=70	4.0% @ Ndes=70	3.0% @ Ndes=30
MIX COMP (GRADATION)	IL 9.5	IL 9.5	IL 19.0	IL 9.5	IL 9.5L
FRICTION AGGREGATE	MIX C	MIX C	N.A.	MIX D	MIX C

\* PG 64-22 MAY BE USED IF THE MAXIMUM % OF RAP USED IN THE MIX IS 20% OR LESS.