

SCHEDULE OF QUANTITIES (cont'd)

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
332	(F-1,DRS-4	CLARK	46	9
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

THERMOPLASTIC PAVEMENT MARKINGS, LETTERS AND SYMBOLS

STATION		SQ FT
66+38.26	(LEFT TURN, URBAN, SMALL)	8.8
67+11.50	(LEFT TURN, URBAN, SMALL)	8.8
67+76.75	(LEFT TURN, URBAN, SMALL)	8.8
68+42.00	(LEFT TURN, URBAN, SMALL)	8.8
70+65.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
73+97.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
77+25.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
80+55.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
83+80.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
87+43.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
91+25.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
94+88.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
97+53.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
99+04.00	(LEFT TURN, URBAN, SMALL)	8.8
99+80.50	(LEFT TURN, URBAN, SMALL)	8.8
2800+94.00	(LEFT TURN, URBAN, SMALL - E. ARCHER AVE.)	8.8
2801+70.00	(LEFT TURN, URBAN, SMALL - E. ARCHER AVE.)	8.8
101+39.50	(RIGHT TURN, URBAN, SMALL)	8.8
101+39.50	(LEFT TURN, URBAN, SMALL)	8.8
101+98.70	(RIGHT TURN, URBAN, SMALL)	8.8
102+20.40	(LEFT TURN, URBAN, SMALL)	8.8
103+25.00	(LEFT TURN, URBAN, SMALL)	8.8
103+92.00	(LEFT TURN, URBAN, SMALL)	8.8
105+72.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
106+98.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
109+42.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
110+73.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
112+97.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
114+68.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
116+62.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
118+38.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
120+57.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
122+97.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
124+48.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
126+62.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
127+68.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
129+77.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
132+15.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
134+53.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
136+96.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
139+46.00	(LEFT TURN, BI-DIRECTIONAL)	17.6
TOTAL =		599.0

THERMOPLASTIC PAVEMENT MARKINGS, LINE 4"

STATION	TO	STATION	OFFSET	COLOR	TYPE	FEET
37+30.00		53+59.31	11.0' LT.	WHITE	SOLID	1,629.3
37+30.00		63+76.26	CENTERLINE	YELLOW	DASH	661.6
37+30.00		42+58.96	11.0' RT.	WHITE	SOLID	529.0
44+17.68		47+82.86	11.0' RT.	WHITE	SOLID	365.2
48+64.86		63+76.26	11.0' RT.	WHITE	SOLID	1,511.4
54+41.31		56+56.92	11.0' LT.	WHITE	SOLID	215.6
57+38.92		59+63.82	11.0' LT.	WHITE	SOLID	224.9
60+45.82		62+57.69	11.0' LT.	WHITE	SOLID	211.9
63+39.69		63+76.26	11.0' LT.	WHITE	SOLID	36.6
63+39.69		63+76.26	0.3' RT.	YELLOW	SOLID	36.6
63+76.26		65+62.26	0' - 6' LT.	YELLOW	SOLID	379.9
63+76.26		65+62.26	0' - 6' RT.	YELLOW	SOLID	379.9
63+76.26		65+56.26	11' - 18' LT.	WHITE	SOLID	180.0
63+76.26		65+56.26	11' - 18' RT.	WHITE	SOLID	180.0
66+38.26		68+60.00	6.0' LT.	YELLOW	SOLID	443.5
66+38.26		68+60.00	6.0' RT.	WHITE	SOLID	221.7
1798+60.33		1799+82.00	CENTERLINE	YELLOW	DASH	30.4 (VINE)
69+40.00		71+90.00	6.0' LT.	YELLOW	SOLID	250.0
69+40.00		71+90.00	6.0' LT.	YELLOW	DASH	62.5
69+40.00		71+90.00	6.0' RT.	YELLOW	SOLID	250.0
69+40.00		71+90.00	6.0' RT.	YELLOW	DASH	62.5
72+70.00		75+25.00	6.0' LT.	YELLOW	SOLID	245.0
72+70.00		75+25.00	6.0' LT.	YELLOW	DASH	63.8
72+70.00		75+25.00	6.0' RT.	YELLOW	SOLID	245.0
72+70.00		75+25.00	6.0' RT.	YELLOW	DASH	63.8
76+00.00		78+50.00	6.0' LT.	YELLOW	SOLID	250.0
76+00.00		78+50.00	6.0' LT.	YELLOW	DASH	62.5
76+00.00		78+50.00	6.0' RT.	YELLOW	SOLID	250.0
76+00.00		78+50.00	6.0' RT.	YELLOW	DASH	62.5
79+30.00		81+80.00	6.0' LT.	YELLOW	SOLID	250.0
79+30.00		81+80.00	6.0' LT.	YELLOW	DASH	62.5
79+30.00		81+80.00	6.0' RT.	YELLOW	SOLID	250.0
79+30.00		81+80.00	6.0' RT.	YELLOW	DASH	62.5
82+60.00		85+00.00	6.0' LT.	YELLOW	SOLID	240.0
82+60.00		85+00.00	6.0' LT.	YELLOW	DASH	60.0
82+60.00		85+00.00	6.0' RT.	YELLOW	SOLID	240.0
82+60.00		85+00.00	6.0' RT.	YELLOW	DASH	60.0
86+00.00		88+85.00	6.0' LT.	YELLOW	SOLID	285.0
86+00.00		88+85.00	6.0' LT.	YELLOW	DASH	71.3
86+00.00		88+85.00	6.0' RT.	YELLOW	SOLID	285.0
86+00.00		88+85.00	6.0' RT.	YELLOW	DASH	71.3
89+65.00		92+60.00	6.0' LT.	YELLOW	SOLID	295.0
89+65.00		92+60.00	6.0' LT.	YELLOW	DASH	73.8
89+65.00		92+60.00	6.0' RT.	YELLOW	SOLID	295.0
89+65.00		92+60.00	6.0' RT.	YELLOW	DASH	73.8
93+40.00		96+35.00	6.0' LT.	YELLOW	SOLID	295.0
93+40.00		96+35.00	6.0' LT.	YELLOW	DASH	73.8
93+40.00		96+35.00	6.0' RT.	YELLOW	SOLID	295.0
93+40.00		96+35.00	6.0' RT.	YELLOW	DASH	73.8
97+10.00		98+15.00	6.0' LT.	YELLOW	SOLID	105.0
97+10.00		98+15.00	6.0' LT.	YELLOW	DASH	26.3
97+10.00		98+15.00	6.0' RT.	YELLOW	SOLID	105.0
97+10.00		98+15.00	6.0' RT.	YELLOW	DASH	26.3
98+15.00		100+00.00	6.0' LT.	YELLOW	SOLID	370.0
99+04.00		100+00.00	6.0' RT.	WHITE	SOLID	96.0
2800+75.50		2801+70.00	CENTERLINE	YELLOW	SOLID	189.0 (ARCHER)
2800+75.50		2801+70.00	11.0' LT.	WHITE	SOLID	94.5
101+21.50		101+98.70	18.0' LT.	WHITE	SOLID	77.2

THERMOPLASTIC PAVEMENT MARKINGS, LINE 4"

STATION	TO	STATION	OFFSET	COLOR	TYPE	FEET
101+21.50		101+98.70	18.0' LT.	WHITE	SOLID	77.2
101+21.50		102+20.40	6.0' LT.	WHITE	SOLID	98.9
101+21.50		102+20.40	6.0' RT.	YELLOW	SOLID	197.8
102+20.40		103+25.00	6' RT. - 6' LT.	YELLOW	SOLID	209.2
103+25.00		104+10.00	6.0' LT.	YELLOW	SOLID	170.0
103+25.00		104+10.00	6.0' RT.	WHITE	SOLID	85.0
104+90.00		107+80.00	6.0' LT.	YELLOW	SOLID	290.0
104+90.00		107+80.00	6.0' LT.	YELLOW	DASH	72.5
104+90.00		107+80.00	6.0' RT.	YELLOW	SOLID	290.0
104+90.00		107+80.00	6.0' RT.	YELLOW	DASH	72.5
108+60.00		111+55.00	6.0' LT.	YELLOW	SOLID	295.0
108+60.00		111+55.00	6.0' RT.	YELLOW	DASH	73.8
108+60.00		111+55.00	6.0' RT.	YELLOW	SOLID	295.0
108+60.00		111+55.00	6.0' RT.	YELLOW	DASH	73.8
112+35.00		115+30.00	6.0' LT.	YELLOW	SOLID	295.0
112+35.00		115+30.00	6.0' RT.	YELLOW	SOLID	295.0
112+35.00		115+30.00	6.0' RT.	YELLOW	DASH	73.8
116+00.00		119+00.00	6.0' LT.	YELLOW	SOLID	300.0
116+00.00		119+00.00	6.0' LT.	YELLOW	DASH	75.0
116+00.00		119+00.00	6.0' RT.	YELLOW	SOLID	300.0
116+00.00		119+00.00	6.0' RT.	YELLOW	DASH	75.0
116+00.00		119+00.00	6.0' RT.	YELLOW	SOLID	300.0
116+00.00		119+00.00	6.0' RT.	YELLOW	DASH	75.0
119+60.00		121+55.00	6.0' LT.	YELLOW	SOLID	195.0
119+60.00		121+55.00	6.0' LT.	YELLOW	DASH	48.8
119+60.00		121+55.00	6.0' RT.	YELLOW	SOLID	195.0
119+60.00		121+55.00	6.0' RT.	YELLOW	DASH	48.8
122+35.00		125+10.00	6.0' LT.	YELLOW	SOLID	275.0
122+35.00		125+10.00	6.0' LT.	YELLOW	DASH	68.8
122+35.00		125+10.00	6.0' RT.	YELLOW	SOLID	275.0
122+35.00		125+10.00	6.0' RT.	YELLOW	DASH	68.8
126+00.00		128+30.00	6.0' LT.	YELLOW	SOLID	230.0
126+00.00		128+30.00	6.0' LT.	YELLOW	DASH	57.5
126+00.00		128+30.00	6.0' RT.	YELLOW	SOLID	230.0
126+00.00		128+30.00	6.0' RT.	YELLOW	DASH	57.5
129+15.00		135+15.00	6.0' LT.	YELLOW	SOLID	600.0
129+15.00		135+15.00	6.0' LT.	YELLOW	DASH	150.0
129+15.00		135+15.00	6.0' RT.	YELLOW	SOLID	600.0
129+15.00		135+15.00	6.0' RT.	YELLOW	DASH	150.0
135+85.00		138+00.00	6.0' LT.	YELLOW	SOLID	215.0
135+85.00		138+00.00	6.0' LT.	YELLOW	DASH	53.8
135+85.00		138+00.00	6.0' RT.	YELLOW	SOLID	215.0
135+85.00		138+00.00	6.0' RT.	YELLOW	DASH	53.8
138+00.00		141+00.00	6' LT. - 1' RT.	YELLOW	SOLID	300.0
138+00.00		141+00.00	6' LT. - 1' RT.	YELLOW	DASH	75.0
138+00.00		141+00.00	6' RT. - 13' RT.	YELLOW	SOLID	300.0
138+00.00		141+00.00	6' RT. - 13' RT.	YELLOW	DASH	75.0
141+00.00		141+85.00	1.0' RT.	YELLOW	SOLID	85.0
141+00.00		141+85.00	1.0' RT.	YELLOW	DASH	21.3
141+00.00		141+85.00	13.0' RT.	YELLOW	SOLID	85.0
141+00.00		141+85.00	13.0' RT.	YELLOW	DASH	21.3
TOTAL =						22,068.0