| LETTING DATE June 15, 2007 ITEM NUMBER 14A | Proposal Submitted By Name Address City/State Zip Code Telephone Number FEIN Number FAX Number |
|---|---|
| This proposal car by only those con AUTHORIZATION Construction. (SEE INSTRUCT) PROPOS Illinois Departm | PROSPECTIVE BIDDERS To be used for bidding purposes Inpanies that request and receive written IN TO BID from IDOT's Central Bureau of IONS ON THE INSIDE OF COVER) AL COVER SHEET Thent of Transportation AERONAUTICS Municipal |
| Δ ψ MINICIPAL DESIG | · . |
| Z COUNTY DESIGN | ATION White |
| ILLINOIS PROJECT | T NO. CUL-3683 |
| FEDERAL PROJEC | CT NO. 3-17-0109-B7 |
| Is the Option for Bituminous Materials Cost Adjustments Selected? Please See Pages 69 and 70 and Mark the Appropriate Box Below: | PLEASE MARK THE APPROPRIATE BOX BELOW: A Bid Bond is included. |

☐ Yes

] No

A Cashier's Check or a Certified Check is included.

INSTRUCTIONS

ABOUT IDOT PROPOSALS: All proposals issued by IDOT are potential bidding proposals. Each proposal contains all Certifications and Affidavits, a Proposal Signature Sheet and a Proposal Bid Bond required for Prime Contractors to submit a bid after written **Authorization to Bid** has been issued by IDOT's Central Bureau of Construction.

HOW MANY PROPOSALS SHOULD PROSPECTIVE BIDDERS REQUEST?: Prospective bidders should, prior to submitting their initial request for plans and proposals, determine their needs and request the total number of plans and proposals needed for each item requested. There will be a nonrefundable charge of \$15 for each set of plans and specifications issued.

WHO CAN BID?: Bids will be accepted from only those companies that request and receive written Authorization to Bid from IDOT's Central Bureau of Construction.

WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?: When a prospective prime bidder submits a "Request for Proposal Forms and Plans" he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued a **Proposal Denial and/or Authorization Form**, approved by the Central Bureau of Construction, that indicates which items have been approved For Bidding. If **Authorization to Bid** cannot be approved, the **Proposal Denial and/or Authorization Form** will indicate the reason for denial. If a contractor has requested to bid but has not received a **Proposal Denial and/or Authorization Form**, they should contact the Central Bureau of Construction in advance of the letting date.

WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?: Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

- 1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
- 2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

ABOUT SUBMITTING BIDS: It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?

| Questions Regarding | Call |
|---|--|
| Prequalification and/or Authorization to Bid Preparation and submittal of bids Mailing of plans and proposals | 217/782-3413 217/782-7806 217/782-7806 |
| | |



| DE | റ | PO | S. | ١T |
|----|---|----|------|----|
| 11 | w | LV | ונטי | 3L |

| 1. | Proposal of | - |
|----|--|---|
| | | |
| | for the improvement officially known as: | _ |

- (a) Carmi Municipal Airport
- (b) The proposed improvement shown in detail on the plans issued by the Department schedule and detail sheets included herein, includes, in general, the following described work:

Extend Partial Parallel Taxiway

TO THE DEPARTMENT OF TRANSPORTATION

The plans for the proposed work are those issued by the Department of Transportation to cover the work described above.

The specifications are those prepared by the Department of Transportation, Division of Aeronautics and designated as "Standard Specifications for Construction of Airports," adopted January, 1985, the "Supplemental Specifications and Recurring Special Provisions," adopted July 1, 2004 and the "Special Provisions" thereto, adopted and in effect on the date of invitation for bids.

3. **COMPLETION TIME/LIQUIDATED DAMAGES**. It being understood and agreed that the completion within the time limit is an essential part of the contract, the bidder agrees to complete the work within 35 calendar days, unless additional time is granted by the Engineer in accordance with the provisions of the specifications. In case of failure to complete the work on or before the time named herein, or within such extra time as may have been allowed by extensions, the bidder agrees that the Department of Transportation shall withhold from such sum as may be due him/her under the terms of this contract, the costs, as set forth below, which costs shall be considered and treated not as a penalty but as damages due to the State from the bidder by reason of the failure of the bidder to complete the work within the time specified in the contract. The following Schedule of Deductions supersedes the table given in Section 60-09 of the Division's Standard Specifications for Construction of Airports.

Schedule of Deductions for Each Day of Overrun in Contract Time

| tract Amount | Daily Charge |
|-------------------------|---|
| To and <u>Including</u> | Calendar <u>Day</u> |
| \$ 25,000 | \$ 300 |
| 100,000 | 375 |
| 500,000 | 550 |
| 1,000,000 | 725 |
| 2,000,000 | 900 |
| 3,000,000 | 1,100 |
| 5,000,000 | 1,300 |
| 7,500,000 | 1,450 |
| 10,000,000 | 1,650 |
| | To and Including \$ 25,000 100,000 500,000 1,000,000 2,000,000 3,000,000 5,000,000 7,500,000 |

A daily charge shall be made for every day shown on the calendar beyond the specified contract time in calendar days.

- 4. ASSURANCE OF EXAMINATION AND INSPECTION/WAIVER. The undersigned further declares that he/she has carefully examined the proposal, plans, specifications, supplemental and applicable recurring special provisions, form of contract and contract bonds, and special provisions, and that he/she has inspected in detail the site of the proposed work, and that he/she has familiarized themselves with all of the local conditions affecting the contract and the detailed requirements of construction, and understands that in making this proposal he/she waives all right to plead any misunderstanding regarding the same.
- 5. **EXECUTION OF CONTRACT AND CONTRACT BONDS.** The undersigned further agrees to execute a contract for this work and present the same to the department within fifteen (15) days after the contract has been mailed to him/her. The undersigned further agrees that he/she and his/her surety will execute and present within fifteen (15) days after the contract has been mailed to him/her contract bonds satisfactory to and in the form prescribed by the Department of Transportation, in the penal sum of the full amount of the contract, guaranteeing the faithful performance of the work in accordance with the terms of the contract and guaranteeing payment in full all bills and accounts for materials and labor used in the construction of the work.
- **6. PROPOSAL GUARANTY.** Accompanying this proposal is either a bid bond on the department form, executed by a corporate surety company satisfactory to the department, or a proposal guaranty check consisting of a bank cashier's check or a properly certified check for not less than 5 per cent of the amount bid or for the amount specified in the following schedule:

| | Amount | Prop of Bid Guar | osal <u>ranty</u> | : | Amount o | f Bid | Proposal <u>Guaranty</u> |
|-------------|--------|---------------------|----------------------|--------------|----------|--------------|-----------------------------|
| Up to | | \$5,000\$1 | 50 | \$2,000,000 | to | \$3,000,000 | \$100,000 |
| \$5,000 | to | \$10,000\$3 | 00 | \$3,000,000 | to | \$5,000,000 | \$150,000 |
| \$10,000 | to | \$50,000\$1,0 | 00 | \$5,000,000 | to | \$7,500,000 | \$250,000 |
| \$50,000 | to | \$100,000\$3,0 | 00 | \$7,500,000 | to | \$10,000,000 | \$400,000 |
| \$100,000 | to | \$150,000\$5,0 | 00 | \$10,000,000 | to | \$15,000,000 | \$500,000 |
| \$150,000 | to | \$250,000\$7,5 | 00 | \$15,000,000 | to | \$20,000,000 | \$600,000 |
| \$250,000 | to | \$500,000\$12,5 | 00 | \$20,000,000 | to | \$25,000,000 | \$700,000 |
| \$500,000 | to | \$1,000,000\$25,0 | 00 | \$25,000,000 | to | \$30,000,000 | \$800,000 |
| \$1,000,000 | to | \$1,500,000\$50,0 | 00 | \$30,000,000 | to | \$35,000,000 | \$900,000 |
| \$1,500,000 | to | \$2,000,000\$75,0 | 00 | over | | \$35,000,000 | \$1,000,000 |

Bank cashier's checks or properly certified checks accompanying proposals shall be made payable to the Treasurer, State of Illinois, when the state is awarding authority; the county treasurer, when a county is the awarding authority; or the city, village, or town treasurer, when a city, village, or town is the awarding authority.

\$ \$

If a combination bid is submitted, the proposal guaranties which accompany the individual proposals making up the combination will be considered as also covering the combination bid.

| Attach Cashier's Check or Certified Check Here |
|--|
| In the event that one proposal guaranty check is intended to cover two or more proposals, the amount must be equal to the sum of the proposal guaranties which would be required for each individual proposal. If the guaranty check is placed in another proposal, state below where it may be found. |
| The proposal guaranty check will be found in the proposal for: Item |
| Airport |

Mark the proposal cover sheet as to the type of proposal guaranty submitted.

7. COMBINATION BIDS. The undersigned further agrees that if awarded the contract for the sections contained in the following combination, he/she will perform the work in accordance with the requirements of each individual proposal comprising the combination bid specified in the schedule below, and that the combination bid shall be prorated against each section in proportion to the bid submitted for the same. If an error is found to exist in the gross sum bid for one or more of the individual sections included in a combination, the combination bid shall be corrected as provided below.

A combination bid is a total bid received on 2 or more proposals. No combination bids other than those specifically set up by the Department will be considered. Separate proposal forms will be issued for each project in the combination so bids may be submitted on the combination as well as on separate units of the combination. The Department reserves the right to make awards on combination bids or separate bids to the best advantage of the Department.

If a combination bid is submitted on 2 or more proposals, separate proposals on each individual contract shall also be submitted, and unless separate proposals are so submitted, the combination bid will not be considered. If the bidder desires to submit a combination bid, the bidder shall state, in the place provided in the proposal form, the amount of the combination bid for the entire combination.

If a combination bid is submitted on any stipulated combination, and errors are found to exist in computing the gross sum bid on any one or more of the individual proposals, corrections shall be made, by the Department and the amount of the combination bid shall be corrected so that it will be in the same proportion to the sum of the corrected gross sum bid as the combination bid submitted was to the sum of the gross sum bid submitted.

The following provisions shall govern combination bidding:

- (a) A combination bid which is submitted for 2 or more proposals and awarded on that basis shall have the bid prorated against each proposal in proportion to the bid submitted for each proposal.
- (b) Separate contracts shall be executed for each individual proposal included in the combination.
- (c) The contract time for all contracts awarded on a combination bid shall be the sum of all calendar days contained within each contract included in the combination, unless otherwise provided in the contracts.
- (d) In the event the Contractor fails to complete any or all of the contracts on the combination bid within the contract time, including any authorized extension, the liquidated damages shall be determined from the schedule of deductions shown above in paragraph 3 for each day of overrun in contract time, based on the combination bid total, and shall be computed on the combination and prorated against the 2 or more individual contracts based on the dollar value of each contract.

(e) The plans and Special Provisions for each separate contract shall be construed separately for all requirements, except as described in paragraphs (a) through (d) listed above.

When a combination bid is submitted, the schedule below must be completed in each proposal comprising the combination.

If alternate bids are submitted for one or more of the sections comprising the combination, a combination bid must be submitted for each alternate.

Schedule of Combination Bids

| Combination | | Combination B | id |
|-------------|----------------------------------|---------------|-------|
| No. | Sections Included in Combination | Dollars | Cents |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

8. **SCHEDULE OF PRICES.** The undersigned submits herewith his/her schedule of prices covering the work to be performed under this contract; he/she understands that he/she must show in the schedule the unit prices (with no more than two decimal places, i.e. \$25.35, not \$25.348) for which he/she proposes to perform each item of work, that the extensions must be made by him/her, and that if not so done his/her proposal may be rejected as irregular.

The undersigned further agrees that the unit prices submitted herewith are for the purpose of obtaining a gross sum, and for use in computing the value of additions and deductions; that if there is a discrepancy between the gross sum bid and that resulting from the summation of the quantities multiplied by their respective unit prices, the latter shall govern.

ECMS002 DTGECM03 ECMR003 PAGE RUN DATE - 05/01/07 RUN TIME - 231507 ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - CR003

| FED PROJECT ILL PROJECT 7-0109-BXX CU-L -3683 | P. C. | | | | | | | | | | | | | ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; | | |
|---|----------------------|---------------------|-----------------------------|-----------------------------|--------------------|-------------------|---------------------------------|--------------------------------|----------------------------|---------------------------|-----------------------------|----------------|-------------------------|---------------------------------------|-------------------------|-------------|
| 3-1 | OUANTITY | 5,226.000 X | | | 25.000 X | - | 4.000 X | 1.000 X | 7.000 X | 2.000 X | 2.000 X | - | 1.000 X | 1.000 X | 6,624.000 X | 1,507.000 X |
| r NAME | UNIT OF MEASURE | L.F. | L.S. | L. F. | EACH | EACH | _ | EACH | EACH | EACH | EACH | PAIR | L.S. | L.S. | C. Y. | L.F. |
| NAME CODE DIST AIRPOR 193 09 CARMI MUNICIPAL | PAY ITEM DESCRIPTION | 1/C #8 5 KV UG CABI | INSTALL ELECTRICAL EQUIPMEN | 2-WAY CONCRETE ENCASED DUCT | MITL-STAKE MOUNTED | MITL-BASE MOUNTED | TAXI GUIDANCE SIGN, 3 CHARACTER | TAXI GUIDANCE SIGN, 4 CHARACTE | REMOVE STAKE MOUNTED LIGHT | REMOVE TAXI GUIDANCE SIGN | RELOCATE TAXI GUIDANCE SIGN | RELOCATE REILS | ENGINEER'S FIELD OFFICE | HAUL ROUTE | UNCLASSIFIED EXCAVATION | SILT FENCE |
| COUNTY N WHITE | I T E M NUMBER | 10815 | 109200 | 10502 | 125410 | 125415 | 125443 | 125444 | 125901 | 125904 | 125964 | 125967 | 150510 | 150540 | R152410 | 6510 |

STATE JOB #-

| ON ECMSOOD DIGECMOS ECMBOOS BAGE | RIN DATE - 05/01/07 | RUN TIME - 231507 |
|----------------------------------|---------------------|-------------------------|
| RIATI | | CONTRACT NUMBER - CR003 |

| CE | 2 | 1 | | ! ! ! | i I | 1 1 | 1 | 1 1 | 1 | 1 1 | 1 1 | 1 | | | |
|----------------------|-------------|-------------------|---|-------------|------------------------|--------------------|---------------------------------|---------------------------|-------------------------|----------------------------|------------------------------------|----------------------------|---|----------------------|---|
| TOTAL PRIC | SOLLAND | | 1 | | | | ;] ; ! ! ! ! | | ; | | | | 1 | | |
| T PRICE ARS CENTS | | | | | | - II | | | - II | | - II | - II | | H | 1 |
| IND | × | | | | -×- | | - - - - - - | | | ; ; ; —×: | ; ; ; - × | ; ; - - - - | ; ; ; —×: | · | ; ; ; ; |
| QUANTITY | 5.000 | 9,268.000 | 2.000 | 23.000 | 1,478.000 | 4,217.000 | 3,065.000 | 977.000 | 175.000 | 604.000 | 2,996.000 | 856.000 | 19,920.000 | 1.000 | 80.000 |
| UNIT OF MEASURE | EACH | S.Y. | EACH | S.Y. | NOL | NOL | NOT | NOL | S.Y. | S.Y. | GAL. | GAL. | S.F. | L.S. | L.F. |
| PAY ITEM DESCRIPTION | DITCH CHECK | SEPARATION FABRIC | HEADWALL PROTECTION | RIPRAP | BITUMINGUS BASE COURSE | OVERSIZE AGGREGATE | CRUSHED AGGREGATE BASE COURSE | BITUMINOUS SURFACE COURSE | BUTT JOINT CONSTRUCTION | REMOVE BITUMINOUS PAVEMENT | BITUMINOUS PRIME COAT | BITUMINOUS TACK COAT | PAVEMENT MARKING-WATERBORNE | TEMPORARY MARK & LIG | 18" RCP, C |
| ITEM | AR156511 | R156513 | R15652 | R156540 | AR201610 | R2085 | R209510 | | | R401900 | 602510 | R603510 | R620520 | R620912 | R701518 |

က

ILLINOIS DEPARTMENT OF TRANSPORTATION SCHEDULE OF PRICES CONTRACT NUMBER - CROO3

ECMS002 DTGECM03 ECMR003 PAGE RUN DATE - 05/01/07 RUN TIME - 231507

| : L H + | | | | | ·) | |
|------------------|---|---------------------------------------|-------------|---|---|----------|
| NUMBER | PAY ITEM DESCRIPTION | UNIT OF | QUANTITY | DOLLARS CENTS DOLLARS | S DOLLARS LOTS | V |
| AR705410 | AR705410 POROUS BACKFILL | c. Y. | 311.000 X | | | 2 |
| AR705524 | 4" PERFORATED UND | · · · · · · · · · · · · · · · · · · · | 4,090.000 X | | | <u>'</u> |
| AR705630 | 1 | EACH | | | | 1 |
| AR752418 | AR752418 PRECAST REINFORCED CONC. FES 18" | EACH | 2.000 X | | 1 | 1 |
| AR901510 SEEDING | SEEDING | ACRE | 11.000 X | 1 | | <u> </u> |
| AR908510 | AR908510 MULCHING | ACRE | 11,000 X | | | I f |
| | | | | | | |

DTF

1. EACH PAY ITEM SHOULD HAVE A UNIT PRICE AND A TOTAL PRICE.

TOTAL

- THE UNIT PRICE SHALL GOVERN IF NO TOTAL PRICE IS SHOWN OR IF THERE IS A DISCREPANCY BETWEEN THE PRODUCT OF THE UNIT PRICE MULTIPLIED BY THE QUANTITY. 2
 - 3. IF A UNIT PRICE IS OMITTED, THE TOTAL PRICE WILL BE DIVIDED BY THE QUANTITY IN ORDER TO ESTABLISH A UNIT PRICE.
 - A BID MAY BE DECLARED UNACCEPTABLE IF NEITHER A UNIT PRICE NOR A TOTAL PRICE IS SHOWN. 4.

THE PRECEDING SCHEDULE OF PRICES MUST BE

COMPLETED AND RETURNED.

STATE REQUIRED ETHICAL STANDARDS GOVERNING CONTRACT PROCUREMENT: ASSURANCES, CERTIFICATIONS AND DISCLOSURES

I. GENERAL

- **A.** Article 50 of the Illinois Procurement Code establishes the duty of all State chief procurement officers, State purchasing officers, and their designees to maximize the value of the expenditure of public moneys in procuring goods, services, and contracts for the State of Illinois and to act in a manner that maintains the integrity and public trust of State government. In discharging this duty, they are charged by law to use all available information, reasonable efforts, and reasonable actions to protect, safeguard, and maintain the procurement process of the State of Illinois.
- **B.** In order to comply with the provisions of Article 50 and to carry out the duty established therein, all bidders are to adhere to ethical standards established for the procurement process, and to make such assurances, disclosures and certifications required by law. By execution of the Proposal Signature Sheet, the bidder indicates that each of the mandated assurances has been read and understood, that each certification is made and understood, and that each disclosure requirement has been understood and completed.
- **C.** In addition to all other remedies provided by law, failure to comply with any assurance, failure to make any disclosure or the making of a false certification shall be grounds for termination of the contract and the suspension or debarment of the bidder.

II. ASSURANCES

A. The assurances hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous assurance, and the surety providing the performance bond shall be responsible for the completion of the contract.

B. Felons

1. The Illinois Procurement Code provides:

Section 50-10. Felons. Unless otherwise provided, no person or business convicted of a felony shall do business with the State of Illinois or any state agency from the date of conviction until 5 years after the date of completion of the sentence for that felony, unless no person held responsible by a prosecutorial office for the facts upon which the conviction was based continues to have any involvement with the business.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-10.

C. Conflicts of Interest

1. The Illinois Procurement Code provides in pertinent part:

Section 50-13. Conflicts of Interest.

- (a) Prohibition. It is unlawful for any person holding an elective office in this State, holding a seat in the General Assembly, or appointed to or employed in any of the offices or agencies of state government and who receives compensation for such employment in excess of 60% of the salary of the Governor of the State of Illinois, or who is an officer or employee of the Capital Development Board or the Illinois Toll Highway Authority, or who is the spouse or minor child of any such person to have or acquire any contract, or any direct pecuniary interest in any contract therein, whether for stationery, printing, paper, or any services, materials, or supplies, that will be wholly or partially satisfied by the payment of funds appropriated by the General Assembly of the State of Illinois or in any contract of the Capital Development Board or the Illinois Toll Highway authority.
- (b) Interests. It is unlawful for any firm, partnership, association or corporation, in which any person listed in subsection (a) is entitled to receive (i) more than 7 1/2% of the total distributable income or (ii) an amount in excess of the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.
- (c) Combined interests. It is unlawful for any firm, partnership, association, or corporation, in which any person listed in subsection (a) together with his or her spouse or minor children is entitled to receive (i) more than 15%, in the aggregate, of the total distributable income or (ii) an amount in excess of 2 times the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.
- (d) Securities. Nothing in this Section invalidates the provisions of any bond or other security previously offered or to be offered for sale or sold by or for the State of Illinois.
- (e) Prior interests. This Section does not affect the validity of any contract made between the State and an officer or employee of the State or member of the General Assembly, his or her spouse, minor child or any combination of those persons if that contract was in existence before his or her election or employment as an officer, member, or employee. The contract is voidable, however, if it cannot be completed within 365 days after the officer, member, or employee takes office or is employed.

The current salary of the Governor is \$145,877.00. Sixty percent of the salary is \$87,526.20.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-13, or that an effective exemption has been issued by the Board of Ethics to any individual subject to the Section 50-13 prohibitions pursuant to the provisions of Section 50-20 of the Code and Executive Order Number 3 (1998). Information concerning the exemption process is available from the Department upon request.

D. Negotiations

1. The Illinois Procurement Code provides in pertinent part:

Section 50-15. Negotiations.

- (a) It is unlawful for any person employed in or on a continual contractual relationship with any of the offices or agencies of State government to participate in contract negotiations on behalf of that office or agency with any firm, partnership, association, or corporation with whom that person has a contract for future employment or is negotiating concerning possible future employment.
- 2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-15, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

E. Inducements

1. The Illinois Procurement Code provides:

Section 50-25. Inducement. Any person who offers or pays any money or other valuable thing to any person to induce him or her not to bid for a State contract or as recompense for not having bid on a State contract is guilty of a Class 4 felony. Any person who accepts any money or other valuable thing for not bidding for a State contract or who withholds a bid in consideration of the promise for the payment of money or other valuable thing is guilty of a Class 4 felony.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-25, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

F. Revolving Door Prohibition

1. The Illinois Procurement Code provides:

Section 50-30. Revolving door prohibition. Chief procurement officers, associate procurement officers, State purchasing officers, their designees whose principal duties are directly related to State procurement, and executive officers confirmed by the Senate are expressly prohibited for a period of 2 years after terminating an affected position from engaging in any procurement activity relating to the State agency most recently employing them in an affected position for a period of at least 6 months. The prohibition includes, but is not limited to: lobbying the procurement process; specifying; bidding; proposing bid, proposal, or contract documents; on their own behalf or on behalf of any firm, partnership, association, or corporation. This Section applies only to persons who terminate an affected position on or after January 15, 1999.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-30, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

G. Reporting Anticompetitive Practices

1. The Illinois Procurement Code provides:

Section 50-40. Reporting anticompetitive practices. When, for any reason, any vendor, bidder, contractor, chief procurement officer, State purchasing officer, designee, elected official, or State employee suspects collusion or other anticompetitive practice among any bidders, offers, contractors, proposers, or employees of the State, a notice of the relevant facts shall be transmitted to the Attorney General and the chief procurement officer.

2. The bidder assures the Department that it has not failed to report any relevant facts concerning the practices addressed in Section 50-40 which may involve the contract for which the bid is submitted.

H. Confidentiality

1. The Illinois Procurement Code provides:

Section 50-45. Confidentiality. Any chief procurement officer, State purchasing officer, designee, or executive officer who willfully uses or allows the use of specifications, competitive bid documents, proprietary competitive information, proposals, contracts, or selection information to compromise the fairness or integrity of the procurement, bidding, or contract process shall be subject to immediate dismissal, regardless of the Personnel code, any contract, or any collective bargaining agreement, and may in addition be subject to criminal prosecution.

2. The bidder assures the Department that it has no knowledge of any fact relevant to the practices addressed in Section 50-45 which may involve the contract for which the bid is submitted.

I. Insider Information

1. The Illinois Procurement Act provides:

Section 50-50. Insider information. It is unlawful for any current or former elected or appointed State official or State employee to knowingly use confidential information available only by virtue of that office or employment for actual or anticipated gain for themselves or another person.

2. The bidder assures the Department that it has no knowledge of any facts relevant to the practices addressed in Section 50-50 which may involve the contract for which the bid is submitted.

III. CERTIFICATIONS

A. The certifications hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous certification, and the surety providing the performance bond shall be responsible for completion of the contract.

B. Bribery

1. The Illinois Procurement Code provides:

Section 50-5. Bribery.

- (a) Prohibition. No person or business shall be awarded a contract or subcontract under this Code who:
 - (1) has been convicted under the laws of Illinois or any other state of bribery or attempting to bribe an officer or employee of the State of Illinois or any other state in that officer's or employee's official capacity; or
 - (2) has made an admission of guilt of that conduct that is a matter of record but has not been prosecuted for that conduct.
- (b) Businesses. No business shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of the business if the employee or agent is no longer employed by the business and:
 - (1) the business has been finally adjudicated not guilty; or
 - (2) the business demonstrates to the governmental entity with which it seeks to contract, and that entity finds that the commission of the offense was not authorized, requested, commanded, or performed by a director, officer, or high managerial agent on behalf of the business as provided in paragraph (2) of subsection (a) of Section 5-4 of the Criminal Code of 1961.
- (c) Conduct on behalf of business. For purposes of this Section, when an official, agent, or employee of a business committed the bribery or attempted bribery on behalf of the business and in accordance with the direction or authorization of a responsible official of the business, the business shall be chargeable with the conduct.
- (d) Certification. Every bid submitted to and contract executed by the State shall contain a certification by the contractor that the contractor is not barred from being awarded a contract or subcontract under this Section. A contractor who makes a false statement, material to the certification, commits a Class 3 felony.
- 2. The bidder certifies that it is not barred from being awarded a contract under Section 50.5.

C. Educational Loan

- 1. Section 3 of the Educational Loan Default Act provides:
- § 3. No State agency shall contract with an individual for goods or services if that individual is in default, as defined in Section 2 of this Act, on an educational loan. Any contract used by any State agency shall include a statement certifying that the individual is not in default on an educational loan as provided in this Section.
- 2. The bidder, if an individual as opposed to a corporation, partnership or other form of business organization, certifies that the bidder is not in default on an educational loan as provided in Section 3 of the Act.

D. Bid-Rigging/Bid Rotating

- 1. Section 33E-11 of the Criminal Code of 1961 provides:
- § 33E-11. (a) Every bid submitted to and public contract executed pursuant to such bid by the State or a unit of local government shall contain a certification by the prime contractor that the prime contractor is not barred from contracting with any unit of State or local government as a result of a violation of either Section 33E-3 or 33E-4 of this Article. The State and units of local government shall provide the appropriate forms for such certification.
- (b) A contractor who makes a false statement, material to the certification, commits a Class 3 felony.

A violation of Section 33E-3 would be represented by a conviction of the crime of bid-rigging which, in addition to Class 3 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be barred for 5 years from the date of conviction from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

A violation of Section 33E-4 would be represented by a conviction of the crime of bid-rotating which, in addition to Class 2 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be permanently barred from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

2. The bidder certifies that it is not barred from contracting with the Department by reason of a violation of either Section 33E-3 or Section 33E-4.

E. International Anti-Boycott

- 1. Section 5 of the International Anti-Boycott Certification Act provides:
- § 5. State contracts. Every contract entered into by the State of Illinois for the manufacture, furnishing, or purchasing of supplies, material, or equipment or for the furnishing of work, labor, or services, in an amount exceeding the threshold for small purchases according to the purchasing laws of this State or \$10,000.00, whichever is less, shall contain certification, as a material condition of the contract, by which the contractor agrees that neither the contractor nor any substantially-owned affiliated company is participating or shall participate in an international boycott in violation of the provisions of the U.S. Export Administration Act of 1979 or the regulations of the U.S. Department of Commerce promulgated under that Act.
- 2. The bidder makes the certification set forth in Section 5 of the Act.

F. Drug Free Workplace

- 1. The Illinois "Drug Free Workplace Act" applies to this contract and it is necessary to comply with the provisions of the "Act" if the contractor is a corporation, partnership, or other entity (including a sole proprietorship) which has 25 or more employees.
- 2. The bidder certifies that if awarded a contract in excess of \$5,000 it will provide a drug free workplace by:
- (a) Publishing a statement notifying employees that the unlawful manufacture, distribution, dispensation, possession or use of a controlled substance, including cannabis, is prohibited in the contractor's workplace; specifying the actions that will be taken against employees for violations of such prohibition; and notifying the employee that, as a condition of employment on such contract, the employee shall abide by the terms of the statement, and notify the employer of any criminal drug statute conviction for a violation occurring in the workplace no later than five (5) days after such conviction.
- (b) Establishing a drug free awareness program to inform employees about the dangers of drug abuse in the workplace; the contractor's policy of maintaining a drug free workplace; any available drug counseling, rehabilitation, and employee assistance programs; and the penalties that may be imposed upon employees for drug violations.
- (c) Providing a copy of the statement required by subparagraph (1) to each employee engaged in the performance of the contract and to post the statement in a prominent place in the workplace.
- (d) Notifying the Department within ten (10) days after receiving notice from an employee or otherwise receiving actual notice of the conviction of an employee for a violation of any criminal drug statute occurring in the workplace.
- (e) Imposing or requiring, within 30 days after receiving notice from an employee of a conviction or actual notice of such a conviction, an appropriate personnel action, up to and including termination, or the satisfactory participation in a drug abuse assistance or rehabilitation program approved by a federal, state or local health, law enforcement or other appropriate agency.
- (f) Assisting employees in selecting a course of action in the event drug counseling, treatment, and rehabilitation is required and indicating that a trained referral team is in place.
- (g) Making a good faith effort to continue to maintain a drug free workplace through implementation of the actions and efforts stated in this certification.

G. Debt Delinquency

1. The Illinois Procurement Code provides:

Section 50-11 and 50-12. Debt Delinquency.

The contractor or bidder certifies that it, or any affiliate, is not barred from being awarded a contract under 30 ILCS 500. Section 50-11 prohibits a person from entering into a contract with a State agency if it knows or should know that it, or any affiliate, is delinquent in the payment of any debt to the State as defined by the Debt Collection Board. Section 50-12 prohibits a person from entering into a contract with a State agency if it, or any affiliate, has failed to collect and remit Illinois Use Tax on all sales of tangible personal property into the State of Illinois in accordance with the provisions of the Illinois Use Tax Act. The contractor further acknowledges that the contracting State agency may declare the contract void if this certification is false or if the contractor, or any affiliate, is determined to be delinquent in the payment of any debt to the State during the term of the contract.

H. Sarbanes-Oxley Act of 2002

1. The Illinois Procurement Code provides:

Section 50-60(c).

The contractor certifies in accordance with 30 ILCS 500/50-10.5 that no officer, director, partner or other managerial agent of the contracting business has been convicted of a felony under the Sarbanes-Oxley Act of 2002 or a Class 3 or Class 2 felony under the Illinois Securities Law of 1953 for a period of five years prior to the date of the bid or contract. The contractor acknowledges that the contracting agency shall declare the contract void if this certification is false.

I. Section 42 of the Environmental Protection Act

The contractor certifies in accordance with 30 ILCS 500/50-12 that the bidder or contractor is not barred from being awarded a contract under this Section which prohibits the bidding on or entering into contracts with the State of Illinois or a State agency by a person or business found by a court or the Pollution Control Board to have committed a willful or knowing violation of Section 42 of the Environmental Protection Act for a period of five years from the date of the order. The contractor acknowledges that the contracting agency may declare the contract void if this certification is false.

J. Executive Order Number 1 (2007) Regarding Lobbying on Government Procurements

The bidder hereby warrants and certifies that they have complied and will comply with the requirements set forth in this Order. The requirements of this warrant and certification are a material part of the contract, and the contractor shall require this warrant and certification provision to be included in all approved subcontracts.

IV. DISCLOSURES

A. The disclosures hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous disclosure, and the surety providing the performance bond shall be responsible for completion of the contract.

B. Financial Interests and Conflicts of Interest

1. Section 50-35 of the Illinois Procurement Code provides that all bids of more than \$10,000 shall be accompanied by disclosure of the financial interests of the bidder. This disclosed information for the successful bidder, will be maintained as public information subject to release by request pursuant to the Freedom of Information Act.

The financial interests to be disclosed shall include ownership or distributive income share that is in excess of 5%, or an amount greater than 60% of the annual salary of the Governor, of the bidding entity or its parent entity, whichever is less, unless the contractor or bidder is a publicly traded entity subject to Federal 10K reporting, in which case it may submit its 10K disclosure in place of the prescribed disclosure. The disclosure shall include the names, addresses, and dollar or proportionate share of ownership of each person making the disclosure, their instrument of ownership or beneficial relationship, and notice of any potential conflict of interest resulting from the current ownership or beneficial interest of each person making the disclosure having any of the relationships identified in Section 50-35 and on the disclosure form.

In addition, all disclosures shall indicate any other current or pending contracts, proposals, leases, or other ongoing procurement relationships the bidding entity has with any other unit of state government and shall clearly identify the unit and the contract, proposal, lease, or other relationship.

2. <u>Disclosure Forms</u>. Disclosure Form A is attached for use concerning the individuals meeting the above ownership or distributive share requirements. Subject individuals should be covered each by one form. In addition, a second form (Disclosure Form B) provides for the disclosure of current or pending procurement relationships with other (non-IDOT) state agencies. **The forms must be included with each bid or incorporated by reference.**

C. <u>Disclosure Form Instructions</u>

Form A: For bidders that have previously submitted the information requested in Form A

The Department has retained the Form A disclosures submitted by all bidders responding to these requirements for the April 24, 1998 or any subsequent letting conducted by the Department. The bidder has the option of submitting the information again or the bidder may sign the following certification statement indicating that the information previously submitted by the bidder is, as of the date of signature, current and accurate. The Certification must be signed and dated by a person who is authorized to execute contracts for the bidding company. Before signing this certification, the bidder should carefully review its prior submissions to ensure the Certification is correct. If the Bidder signs the Certification, the Bidder should proceed to Form B instructions.

CERTIFICATION STATEMENT

| I have determined that the Form A disclosure information previously submitted is current an incorporated by reference in this bid. Any necessary additional forms or amendments to previously. | |
|--|---------------------------------------|
| (Bidding Company) | |
| Name of Authorized Representative (type or print) Title of Authorized Representative (type or print) | prized Representative (type or print) |
| Signature of Authorized Representative | Date |

Form A: For bidders who have NOT previously submitted the information requested in Form A

D.

If the bidder is a publicly traded entity subject to Federal 10K reporting, the 10K Report may be submitted to meet the requirements of Form A. If a bidder is not subject to Federal 10K reporting, the bidder must determine if any individuals are required by law to complete a financial disclosure form. To do this, the bidder should answer each of the following questions. A "YES" answer indicates Form A must be completed. If the answer to each of the following questions is "NO", then the NOT APPLICABLE STATEMENT on the second page of Form A must be signed and dated by a person that is authorized to execute contracts for the bidding company. Note These questions are for assistance only and are not required to be completed.

| 1. | Does anyone in your organization have a direct or beneficial ownership share of greater than 5% of the bidding entity or parent entity? YES NO |
|-----------------------------------|--|
| 2. | Does anyone in your organization have a direct or beneficial ownership share of less than 5%, but which has a value greater than \$87,526.20? YES NO |
| 3. | Does anyone in your organization receive more than \$87,526.20 of the bidding entity's or parent entity's distributive income? (Note: Distributive income is, for these purposes, any type of distribution of profits. An annual salary is not distributive income.) YES NO |
| 4. | Does anyone in your organization receive greater than 5% of the bidding entity's or parent entity's total distributive income, but which is less than \$87,526.20? YES NO |
| | (Note: Only one set of forms needs to be completed <u>per person per bid</u> even if a specific individual would require a yes answer to more than one question.) |
| bidding e authorize | answer to any of these questions requires the completion of Form A. The bidder must determine each individual in the bidding entity or the entity's parent company that would cause the questions to be answered "Yes". Each form must be signed and dated by a person that is do to execute contracts for your organization. Photocopied or stamped signatures are not acceptable . The person signing can be, but does to be, the person for which the form is being completed. The bidder is responsible for the accuracy of any information provided. |
| | wer to each of the above questions is "NO", then the <u>NOT APPLICABLE STATEMENT</u> on page 2 of Form A must be signed and dated by a at is authorized to execute contracts for your company. |
| bidding e | Identifying Other Contracts & Procurement Related Information Disclosure Form B must be completed for each bid submitted by the mitty. It must be signed by an individual who is authorized to execute contracts for the bidding entity. Note: Signing the NOT APPLICABLE ENT on Form A does not allow the bidder to ignore Form B. Form B must be completed, signed and dated or the bidder may be considered insive and the bid will not be accepted. |
| procuren | ler shall identify, by checking Yes or No on Form B, whether it has any pending contracts (including leases), bids, proposals, or other ongoing nent relationship with any other (non-IDOT) State of Illinois agency. If "No" is checked, the bidder only needs to complete the signature box attom of Form B. If "Yes" is checked, the bidder must do one of the following: |
| agency p attached and are n | If the bidder did not submit an Affidavit of Availability to obtain authorization to bid, the bidder must list all non-IDOT State of Illinois ending contracts, leases, bids, proposals, and other ongoing procurement relationships. These items may be listed on Form B or on an sheet(s). Do not include IDOT contracts. Contracts with cities, counties, villages, etc. are not considered State of Illinois agency contracts of to be included. Contracts with other State of Illinois agencies such as the Department of Natural Resources or the Capital Development ast be included. Bidders who submit Affidavits of Availability are suggested to use Option II. |
| "See Aff Illinois a | If the bidder is required and has submitted an Affidavit of Availability in order to obtain authorization to bid, the bidder may write or type idavit of Availability" which indicates that the Affidavit of Availability is incorporated by reference and includes all non-IDOT State of gency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. For any contracts that are not covered by the of Availability, the bidder must identify them on Form B or on an attached sheet(s). These might be such things as leases. |
| Bidders | Submitting More Than One Bid |
| | submitting multiple bids may submit one set of forms consisting of all required Form A disclosures and one Form B for use with all bids. dicate in the space provided below the bid item that contains the original disclosure forms and the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms and the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains the original disclosure forms are the bid items which incorporate the forms by the contains th |
| | he bid submitted for letting item contains the Form A disclosures or Certification Statement and the Form B sclosures. The following letting items incorporate the said forms by reference: |
| | |

RETURN WITH BID/OFFER

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form A Financial Information & Potential Conflicts of Interest Disclosure

| Contractor Name | | | | | | | |
|---|---|---|--|---|--|---|---------------------------|
| Legal Address | | | | | | | |
| City, State, Zip | | | | | | | |
| Telephone Number | | | | | Fax Number (if avai | ilable) | |
| enter into a contract with Disclosure Form. This in | <u></u> | lose the financia he publicly avail | al information a able contract file nit a 10K disclo | nd potential e. This Forn osure in sati | conflict of interest interest into A must be completed isfaction of the requir | formation as specif for bids in excess o | ied in thi of \$10,000 |
| of ownership or distr the Governor's salar for each individual | nancial Information. The ributive income share in exy as of 10/1/2000). (Make meeting these requiremental (type or print information) | e individual nacess of 5%, or copies of the ents) | amed below lor an interest | has an inte which has | erest in the BIDDER s a value of more the | han \$87,526.20 | (60% o |
| NAME: | | | | | | | |
| ADDRESS | | | | | | | |
| Type of own | nership/distributable inco | ome share: | | | | | |
| stock | sole proprietorship |) | partnershi | р | other: (expla | in on separate s | heet): |
| % or \$ value | of ownership/distributable | e income shar | re: | | | | |
| conflict of interest re | tential Conflicts of Intercelationships apply. If the a | nswer to any | question is " | Yes", plea | ase attach addition | al pages and des | scribe. |
| (b) State en | nployment of spouse, fathers 2 years. | er, mother, so | n, or daughte | r, includir | | | |
| | | | | | Yes | No | _ |
| any unit of | e status; the holding of elect local government authorize currently or in the previous | ed by the Cor | | | | | |
| | 1 | ž | | | Yes | No | _ |
| (d) Relation son, or days | nship to anyone holding eloghter | ective office | currently or in | n the prev | ious 2 years; spous | se, father, mothe | er, |
| 2011, 01 3444 | 5 . | | | | Yes | No | _ |

RETURN WITH BID/OFFER

| States of Amer statutes of the S | office; the holding of any appointive government office ica, or any unit of local government authorized by the C State of Illinois, which office entitles the holder to comp | Constitution of the State | of Illinois or the |
|---|--|---|---|
| the discharge o | f that office currently or in the previous 3 years. | Yes | No |
| (f) Relationship mother, son, or | o to anyone holding appointive office currently or in the daughter. | previous 2 years; spous | se, father, |
| , , | | Yes | No |
| (g) Employmen | nt, currently or in the previous 3 years, as or by any regin | | ate government. No |
| (h) Relationshi son, or daughte | p to anyone who is or was a registered lobbyist in the prer. | • • | |
| | | Yes | · |
| committee regi | ed employment, currently or in the previous 3 years, by a stered with the Secretary of State or any county clerk of stered with either the Secretary of State or the Federal E | the State of Illinois, or Board of Elections. | any political action |
| | | Yes | No |
| 2 years by any | to anyone; spouse, father, mother, son, or daughter; where registered election or re-election committee registered values of Elections. | with the Secretary of Sta h either the Secretary | mployee in the last the or any county clerk of State or the |
| | APPLICABLE STATEM | | |
| This Disclosure Form | A is submitted on behalf of the INDIVIDUAL name | ed on previous page. | |
| Completed by: | | | |
| Completed by: | Name of Authorized Representative (type of | or print) | |
| - | Title of Authorized Representative (type o | r print) | |
| Completed by: | C'and an Challish along the ind Dance | | - Data |
| | Signature of Individual or Authorized Repre | sentative | Date |
| | NOT APPLICABLE STATE | | |
| I have determined the completion of this Fo | at no individuals associated with this organization means ${f A}$. | eet the criteria that wo | ould require the |
| This Disclosure Form | A is submitted on behalf of the CONTRACTOR list | ted on the previous pa | ge. |
| - | Name of Authorized Representative (type of | or print) | |
| <u>-</u> | Title of Authorized Representative (type o | r print) | |
| <u>-</u> | Signature of Authorized Representative | ve | Date |

17

RETURN WITH BID/OFFER

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form B Other Contracts & Procurement Related Information Disclosure

| Contractor Name | | |
|--|--|--|
| Legal Address | | |
| City, State, Zip | | |
| Telephone Number | | Fax Number (if available) |
| Disclosure of the information contained in the ILCS 500). This information shall become p bids in excess of \$10,000, and for all open-end | art of the publicly available contract | |
| DISCLOSURE OF OTHER COM | NTRACTS AND PROCUREMENT | RELATED INFORMATION |
| 1. Identifying Other Contracts & Procurer pending contracts (including leases), bids, pro Illinois agency: Yes No If "No" is checked, the bidder only needs to contract the pending contracts of the pending contracts agency in the pending leases. | posals, or other ongoing procurement | t relationship with any other State of |
| 2. If "Yes" is checked. Identify each such relinformation such as bid or project number (att INSTRUCTIONS: | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| THE FOLL | OWING STATEMENT MUST BE | SIGNED |
| | | |
| Name of A | Authorized Representative (type or pr | rint) |
| Title of A | authorized Representative (type or pri | int) |
| Sign | ature of Authorized Representative | Date |

SPECIAL NOTICE TO CONTRACTORS

The following requirements of the Illinois Department of Human Rights' Rules and Regulations are applicable to bidders on all construction contracts advertised by the Illinois Department of Transportation:

CONSTRUCTION EMPLOYEE UTILIZATION PROJECTION

- (a) All bidders on construction contracts shall complete and submit, along with and as part of their bids, a Bidder's Employee Utilization Form (Form BC-1256) setting forth a projection and breakdown of the total workforce intended to be hired and/or allocated to such contract work by the bidder including a projection of minority and female employee utilization in all job classifications on the contract project.
- (b) The Department of Transportation shall review the Employee Utilization Form, and workforce projections contained therein, of the contract awardee to determine if such projections reflect an underutilization of minority persons and/or women in any job classification in accordance with the Equal Employment Opportunity Clause and Section 7.2 of the Illinois Department of Human Rights' Rules and Regulations for Public Contracts adopted as amended on September 17, 1980. If it is determined that the contract awardee's projections reflect an underutilization of minority persons and/or women in any job classification, it shall be advised in writing of the manner in which it is underutilizing and such awardee shall be considered to be in breach of the contract unless, prior to commencement of work on the contract project, it submits revised satisfactory projections or an acceptable written affirmative action plan to correct such underutilization including a specific timetable geared to the completion stages of the contract.
- (c) The Department of Transportation shall provide to the Department of Human Rights a copy of the contract awardee's Employee Utilization Form, a copy of any required written affirmative action plan, and any written correspondence related thereto. The Department of Human Rights may review and revise any action taken by the Department of Transportation with respect to these requirements.



PART I. IDENTIFICATION

| Human Rights | |
|-----------------|----------------------|
| Bid Number: | Duration of Project: |
| Name of Bidder: | |

PART II. WORKFORCE PROJECTION

A. The undersigned bidder has analyzed minority group and female populations, unemployment rates and availability of workers for the location in which this contract work is to be performed, and for the locations from which the bidder recruits employees, and hereby submits the following workforce projection including a projection for minority and female employee utilization in all job categories in the workforce to be allocated to this contract:

| the workforce to be a | mocated | to this | Comir | ici. | TABL | ΕA | | | | | | | | TABLE | ЕВ | | |
|---------------------------|---|---------|----------|------|------------|-------|-----|------|-------------|---------|--------|------------|---------------------------|-------|-----|------|------------|
| | TOTAL Workforce Projection for Contract CURRENT EMPLOYEES | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | SIGNED | ļ | | | |
| 100 | | | | MIN | ORITY | EMPLO | | | | | AINEES | TE TOD | mon | | CNC | RACT | |
| JOB CATEGORIES | TO: | | DI / | CV | HICD | MIC | _ | THER | APPF TIC | | | HE JOB | TOTAL MINO EMPLOYEES EMPL | | | | |
| CATEGORIES | M | F | BLA M | F | HISPA M | F | M | NOR. | M | ES F | M | INEES F | M | F | | M | OYEES F |
| OFFICIALS | IVI | Г | IVI | Г | IVI | Г | IVI | Г | IVI | Г | IVI | Г | IVI | Г | | IVI | Г |
| (MANAGERS) | | | | | | | | | | | | | | | | | |
| SUPERVISORS | | | | | | | | | | | | | | | | | |
| FOREMEN | | | | | | | | | | | | | | | | | |
| CLERICAL | | | | | | | | | | | | | | | | | |
| EQUIPMENT OPERATORS | | | | | | | | | | | | | | | | | |
| MECHANICS | | | | | | | | | | | | | | | | | |
| TRUCK DRIVERS | | | | | | | | | | | | | | | | | |
| IRONWORKERS | | | | | | | | | | | | | | | | | |
| CARPENTERS | | | | | | | | | | | | | | | | | |
| CEMENT MASONS | | | | | | | | | | | | | | | | | |
| ELECTRICIANS | | | | | | | | | | | | | | | | | |
| PIPEFITTERS, PLUMBERS | | | | | | | | | | | | | | | | | |
| PAINTERS | | | | | | | | | | | | | | | | | |
| LABORERS, SEMI-SKILLED | | | | | | | | | | | | | | | | | |
| LABORERS, UNSKILLED | | | | | | | | | | | | | | | | | |
| TOTAL | | | | | | | | | | | | | | | | | |

| TABLE C | | | | | | | | |
|-------------|---------|------------|---------|----------|---------|--------|----|------|
| 7 | TOTAL T | raining Pr | ojectio | n for Co | ontract | | | |
| EMPLOYEES | TOT | TOTAL | | | | *OTHER | | |
| IN | EMPLO | OYEES | BLA | ACK | HISP. | ANIC | MI | NOR. |
| TRAINING | M | F | M | F | M | F | M | F |
| APPRENTICES | | | | | | | | |
| | | | | | | | | |
| ON THE JOB | | | | | | | | |
| TRAINEES | | | | | | | | |

^{*}Other minorities are defined as Asians (A) or Native Americans (N).

Please specify race of each employee shown in Other Minorities column.

Note: See instructions on page 2

| FOR DEPARTMENT USE ONLY | |
|-------------------------|--|
| | |
| | |
| | |
| | |
| | |

BC 1256 - Pg 1 (Rev. 3/98) IL 494-0454

PART II. WORKFORCE PROJECTION - continued

| | included in "Total Employees" under Table A is the total number of new hires that would be employed in the event ne undersigned bidder is awarded this contract. |
|--------------------------|--|
| T | the undersigned bidder projects that: (number) new hires would be recruited from the area in which the contract project is located; and/or (number) new hires would be recruited from the area in which the bidder's principal |
| 0 | ffice or base of operation is located. |
| | included in "Total Employees" under Table A is a projection of numbers of persons to be employed directly by the indersigned bidder as well as a projection of numbers of persons to be employed by subcontractors. |
| | he undersigned bidder estimates that (number) persons will be irectly employed by the prime contractor and that (number) persons will be mployed by subcontractors. |
| PART III | . AFFIRMATIVE ACTION PLAN |
| u ir co (g u | the undersigned bidder understands and agrees that in the event the foregoing minority and female employee tilization projection included under PART II is determined to be an underutilization of minority persons or women any job category, and in the event that the undersigned bidder is awarded this contract, he/she will, prior to commencement of work, develop and submit a written Affirmative Action Plan including a specific timetable geared to the completion stages of the contract) whereby deficiencies in minority and/or female employee tilization are corrected. Such Affirmative Action Plan will be subject to approval by the contracting agency and the Department of Human Rights . |
| SI | the undersigned bidder understands and agrees that the minority and female employee utilization projection abmitted herein, and the goals and timetable included under an Affirmative Action Plan if required, are deemed to e part of the contract specifications. |
| Company | Telephone Number |
| Address | |
| | NOTICE REGARDING SIGNATURE |
| | dder's signature on the Proposal Signature Sheet will constitute the signing of this form. The following signature needs to be completed only if revisions are required. |
| Signatu | re: Title: Date: |
| Instruction | ons: All tables must include subcontractor personnel in addition to prime contractor personnel. |
| Table A - | Include both the number of employees that would be hired to perform the contract work and the total number currently employed (Table B) that will be allocated to contract work, and include all apprentices and on-the-job trainees. The "Total Employees" column should include all employees including all minorities, apprentices and on-the-job trainees to be employed on the contract work. |
| Table B - | Include all employees currently employed that will be allocated to the contract work including any apprentices and on-the-job trainees currently employed. |
| Table C - | Indicate the racial breakdown of the total apprentices and on-the-job trainees shown in Table A. BC-1256-Pg. 2 (Rev. 3/98) |

<u>CERTIFICATIONS REQUIRED BY STATE AND/OR FEDERAL LAW</u>. The bidder is required by State and/or Federal law to make the below certifications and assurances as a part of the proposal and contract upon award. It is understood by the bidder that the certifications and assurances made herein are a part of the contract.

By signing the Proposal Signature Sheet, the bidder certifies that he/she has read and completed each of the following certifications and assurances, that required responses are true and correct and that the certified signature of the Proposal Signature Sheet constitutes an endorsement and execution of each certification and assurance as though each was individually signed:

A. By the execution of this proposal, the signing bidder certifies that the bidding entity has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action, in restraint of free competitive bidding in connection with the submitted bid. This statement made by the undersigned bidder is true and correct under penalty of perjury under the laws of the United States.

B. CERTIFICATION, EQUAL EMPLOYMENT OPPORTUNITY:

| 1. | Have you participated in any previous contracts or subcontracts subject to the equal opportunity clause. YES NO |
|----|---|
| 2. | If answer to #1 is yes, have you filed with the Joint Reporting Committee, the Director of OFCC, any Federal agency, or the former President's Committee on Equal Employment Opportunity, all reports due under the applicable filing requirements of those organizations? YES NO |

- C. BUY AMERICAN STEEL AND MANUFACTURED PRODUCTS FOR CONSTRUCTION CONTRACTS (JAN 1991)
 - (a) The Aviation Safety and Capacity Expansion Act of 1990 provides that preference be given to steel and manufactured products produced in the United States when funds are expended pursuant to a grant issued under the Airport Improvement Program. The following terms apply:
 - 1. <u>Steel and manufactured products</u>. As used in this clause, steel and manufactured products include (1) steel produced in the United States or (2) a manufactured product produced in the United States, if the cost of its components mined, produced or manufactured in the United States exceeds 60 percent of the cost of all its components and final assembly has taken place in the United States. Components of foreign origin of the same class or kind as the products referred to in subparagraphs (b)(1) or (2) shall be treated as domestic.
 - 2. <u>Components</u>. As used in this clause, components means those articles, materials, and supplies incorporated directly into steel and manufactured products.
 - 3. <u>Cost of Components</u>. This means the costs for production of the components, exclusive of final assembly labor costs.
 - (b) The successful bidder will be required to assure that only domestic steel and manufactured products will be used by the Contractor, subcontractors, materialmen, and suppliers in the performance of this contract, except those-
 - (1) that the U.S. Department of Transportation has determined, under the Aviation Safety and Capacity Expansion Act of 1990, are not produced in the United States in sufficient and reasonably available quantities of a satisfactory quality;
 - (2) that the U.S. Department of Transportation has determined, under the Aviation Safety and Capacity Expansion Act of 1990, that domestic preference would be inconsistent with the public interest; or
 - (3) that inclusion of domestic material will increase the cost of the overall project contract by more than 25 percent.

(End of Clause)

D. BUY AMERICAN CERTIFICATE (JAN 1991)

By submitting a bid/proposal under this solicitation, except for those items listed by the offeror below or on a separate and clearly identified attachment to this bid/proposal, the offeror certifies that steel and each manufactured product, is produced in the United States (as defined in the clause Buy American - Steel and Manufactured Products or Buy American - Steel and Manufactured Products For Construction Contracts) and that components of unknown origin are considered to have been produced or manufactured outside the United States.

Offerors may obtain from (IDOT, Division of Aeronautics) lists of articles, materials, and supplies excepted from this provision.

| PRODUCT | COUNTRY OF ORIGIN |
|---------|-------------------|
| | |
| | |
| | |

E. NPDES CERTIFICATION

In accordance with the provisions of the Illinois Environmental Protection Act, the Illinois Pollution Control Board Rules and Regulations (35 Ill. Adm. Code, Subtitle C, Chapter I), and the Clean Water Act, and the regulations thereunder, this certification is required for all construction contracts that will result in the disturbance of five or more acres total land area.

The undersigned bidder certifies under penalty of law that he/she understands the terms and conditions of the general National Pollutant Discharge Elimination System (NPDES) permit (ILR100000) that authorizes the storm water discharges associated with industrial activity from the construction site identified as part of this certification.

The Airport Owner or its Agent will:

- 1) prepare, sign and submit the Notice of Intent (NOI)
- 2) conduct site inspections and complete and file the inspection reports
- 3) submit Incidence of Non-Compliance (ION) forms
- 4) submit Notice of Termination (NOT) form

Prior to the issuance of the Notice-to-Proceed, for <u>each</u> erosion control measure identified in the Storm Water Pollution Prevention Plan, the contractor or subcontractor responsible for the control measure(s) must sign the above certification (forms to be provided by the Department).

F. NON-APPROPRIATION CLAUSE

By submitting a bid/proposal under this solicitation the offeror certifies that he/she understands that obligations of the State will cease immediately without penalty or further payment being required in any fiscal year the Illinois General Assembly fails to appropriate or otherwise make available sufficient funds for this contract.

G. Contractor is not delinquent in the payment of any debt to the State (or if delinquent has entered into a deferred payment plan to pay the debt), and Contractor acknowledges the contracting state agency may declare the contract void if this certification is false (30 ILCS 500/50-11, effective July 1, 2002).

NOTICE TO BIDDERS

- 1. TIME AND PLACE OF OPENING BIDS. Sealed proposals for the improvement described herein will be received by the Department of Transportation at the Harry R. Hanley Building, 2300 South Dirksen Parkway in Springfield, Illinois until 10:00 o'clock a.m., June 15, 2007. All bids will be gathered, sorted, publicly opened and read in the auditorium at the Department of Transportation's Harry R. Hanley Building shortly after the 10:00 a.m. cut off time.
- 2. **DESCRIPTION OF WORK**. The proposed improvement, shown in detail on the plans issued by the Department includes, in general, the following described work:

Extend Partial Parallel Taxiway

- **3. INSTRUCTIONS TO BIDDERS**. (a) This Notice, the invitation for bids, proposal and award shall, together with all other documents in accordance with Article 10-15 of the Illinois Standard Specifications for Construction of Airports, become part of the contract. Bidders are cautioned to read and examine carefully all documents, to make all required inspections, and to inquire or seek explanation of the same prior to submission of a bid.
 - (b) State law, and, if the work is to be paid wholly or in part with Federal-aid funds, Federal law requires the bidder to make various certifications as a part of the proposal and contract. By execution and submission of the proposal, the bidder makes the certification contained therein. A false or fraudulent certification shall, in addition to all other remedies provided by law, be a breach of contract and may result in termination of the contract.
- 4. AWARD CRITERIA AND REJECTION OF BIDS. This contract will be awarded to the lowest responsive and responsible bidder considering conformity with the terms and conditions established by the Department in the proposal and contract documents. The issuance of plans and proposal forms for bidding based upon a prequalification rating shall not be the sole determinant of responsibility. The Department reserves the right to determine responsibility at the time of award, to reject any or all proposals, to readvertise the proposed improvement, and to waive technicalities.
- **5. PRE-BID CONFERENCE.** There will be a pre-bid conference held at N/A at the Carmi Municipal Airport administration building. For engineering information, contact Chuck Hagloch of Hanson Professional Services, Inc. at (217) 747-9376.
- **6. DISADVANTAGED BUSINESS POLICY.** The DBE goal for this contract is <u>6.0</u>%.
- 7. SPECIFICATIONS AND DRAWINGS. The work shall be done in accordance with the Illinois Standard Specifications for Construction of Airports, the Illinois Division of Aeronautics Supplemental Specifications and Recurring Special Provisions, the Special Provisions dated <u>March 23, 2007, Revised May 8, 2007</u> and the Construction Plans dated <u>Maech 23, 2007, Revised May 8, 2007</u> as approved by the Department of Transportation, Division of Aeronautics.

- **8. INSPECTION OF RECORDS.** The Contractor shall maintain an acceptable cost accounting system. The Sponsor, the FAA, and the Comptroller General of the United States shall have access to any books, documents, paper, and records of the Contractor which are directly pertinent to the specific contract for the purposes of making an audit, examination, excerpts, and transcriptions. The Contractor shall maintain all required records for <u>three years</u> after the Sponsor makes final payment and all other pending matters are closed.
- **9. RIGHTS TO INVENTIONS.** All rights to inventions and materials generated under this contract are subject to Illinois law and to regulations issued by the FAA and the Sponsor of the Federal grant under which this contract is executed. Information regarding these rights is available from the FAA and the Sponsor.

10. TERMINATION OF CONTRACT.

- 1. The Sponsor may, be written notice, terminate this contract in whole or in part at any time, either for the Sponsor's convenience or because of failure to fulfill the contract obligations. Upon receipt of such notice services shall be immediately discontinued (unless the notice directs otherwise) and all materials as may have been accumulated in performing this contract, whether completed or in progress, delivered to the Sponsor.
- If the termination is for the convenience of the Sponsor, an equitable adjustment in the contract price shall be made, but no amount shall be allowed for anticipated profit on unperformed services.
- 3. If the termination is due to failure to fulfill the Contractor's obligations, the Sponsor may take over the work and prosecute the same to completion by contract or otherwise. In such case, the Contractor shall be liable to the Sponsor for any additional cost occasioned to the Sponsor thereby.
- 4. If, after notice of termination for failure to fulfill contract obligations, it is determined that the Contractor had not so failed, the termination shall be deemed to have been effected for the convenience of the Sponsor. In such event, adjustment in the contract price shall be made as provided in paragraph 2 of this clause.
- 5. The rights and remedies of the sponsor provided in this clause are in addition to any other rights and remedies provided by law or under this contract.

- 11. BIDDING REQUIREMENTS AND BASIS OF AWARD. When alternates are included in the proposal, the following shall apply:
 - a. Additive Alternates
 - (1) Bidders must submit a bid for the Base Bid and for all Additive Alternates.
 - (2) Award of this contract will be made to the lowest responsible qualified bidder computed as follows:

The lowest aggregate amount of (i) the Base Bid plus (ii) any Additive Alternate(s) which the Department elects to award.

The Department may elect not to award any Additive Alternates. In that case, award will be to the lowest responsible qualified bidder of the Base Bid.

- b. Optional Alternates
 - (1) Bidders must submit a bid for the Base Bid and for either Alternate A or Alternate B or for both Alternate A and Alternate B.
 - (2) Award of this contract will be made to the lowest responsible qualified bidder computed as follows:

The lower of the aggregate of either (i) the Base Bid plus Alternate A or (ii) the Base Bid plus Alternate B.

12. CONTRACT TIME. The Contractor shall complete all work within the specified contract time. Any calendar day extension beyond the specified contract time must be fully justified, requested by the Contractor in writing, and approved by the Engineer, or be subject to liquidated damages.

The contract time for this contract is $\underline{35}$ calendar days and is based on anticipated notice-to-proceed date of $\underline{\text{July } 30}$, 2007.

- 13. INDEPENDENT WEIGHT CHECKS. The Department reserves the right to conduct random unannounced independent weight checks on any delivery for bituminous, aggregate or other pay item for which the method of measurement for payment is based on weight. The weight checks will be accomplished by selecting, at random, a loaded truck and obtaining a loaded and empty weight on an independent scale. In addition, the department may perform random weight checks by obtaining loaded and empty truck weights on portable scales operated by department personnel.
- 14. GOOD FAITH COMPLIANCE. The Illinois Department of Transportation has made a good faith effort to include all statements, requirements, and other language required by federal and state law and by various offices within federal and state governments whether that language is required by law or not. If anything of this nature has been left out or if additional language etc. is later required, the bidder/contractor shall cooperate fully with the Department to modify the contract or bid documents to correct the deficiency. If the change results in increased operational costs, the Department shall reimburse the contractor for such costs as it may find to be reasonable.

PROPOSAL SIGNATURE SHEET

The undersigned bidder hereby makes and submits this bid on the subject Proposal, thereby assuring the Department that all requirements of the Invitation for Bids and rules of the Department have been met, that there is no misunderstanding of the requirements of paragraph 4 of this Proposal, and that the contract will be executed in accordance with the rules of the Department if an award is made on this bid.

| | Firm Name | | |
|---|--|------------------------------|---------------------|
| (IF AN INDIVIDUAL) | Signature of Owner | | |
| | Business Address | | |
| | | | |
| | Firm Name | | |
| (IF A CO-PARTNERSHIP) | Ву | | |
| | Business Address | | |
| | Name and Address of All | Members of the Firm: | |
| | | | |
| | Corporate Name | | |
| (IF A CORPORATION) | D ₁₁ | | Corporate Seal |
| | Attest | | President |
| | Business Address | | Corporate Secretary |
| | Name of Corporate Office | | |
| | | | |
| | President | Corporate Secretary | Treasurer |
| | NOTARY CERTIFIC | ATION | |
| STATE OF ILLINOIS, | ALL SIGNATURES MUST BI | | |
| COUNTY OF | | | |
| I, | , a Notary Public in and for said cou | inty, do hereby certify that | |
| | | h-1-1f -fh:JJ) | |
| | (Insert names of individual(s) signing | | |
| bidder, appeared before me this day voluntary | me to be the same persons whose names are in person and acknowledged that they sig | | |
| act for the uses and purposes therein | | | |
| | seal this day | | |
| My commission expires | | Notary I | (Seal) |
| | | 1 total y 1 | |

Return with Bid



Division of Aeronautics Proposal Bid Bond

(Effective January 1, 2002)

| | | | Item No. 14A |
|---|---|--|--|
| | III. Proj. | _Carmi Municipal Airport NoCUL-3683 pj. No. 3-17-0109-B7 | Letting Date: <u>June 15, 2007</u> |
| KNOW ALL MEN BY THES | SE PRESENTS. that we, $_$ | | , as |
| firmly bound unto the, herei specified in Section 6, PRO | POSAL GUARANTEE of the | he Proposal Document, which | , as SURETY are held and sent of the total bid price or of the amount hever is the lesser sum, well and truly to be paid executors, administrators, successors, and |
| | te of Illinois, Department of | f Transportation, Division of A | has submitted a Bid Proposal to the SPONSOR Aeronautics, for the improvement designated by |
| within the time and as spec approved by the AGENT, a Bidding and Contract Docus sufficient surety for the faith prosecution thereof; or if, in contract and to give the spe between the amount in the perform the work covered be | ified in the Bidding and Coind if after the award, the Pments including evidence of full performance of such cothe event of the failure of the cified bond, the PRINCIPA Bid Proposal and such largy said Proposal Document | ntract Documents, submit the RINCIPAL shall enter into a coff insurance coverage's and portract and for prompt payme the PRINCIPAL to make the IAL pays to the SPONSOR the ger amount for which the SPOR, then, this obligation to be vo | sposal of the PRINCIPAL; and if PRINCIPAL shall a DBE Utilization Plan that is acceptable and contract in accordance with the terms of the providing such bond as specified with good and ant of labor and material furnished in the required DBE submission or to enter into such a difference not to exceed the penalty hereof DNSOR may contract with another party to bid; otherwise to remain in full force and effect. |
| set forth in the preceding pa demand therefor. If the SUF | aragraph, then the SURET RETY does not make full pa RETY is liable to the SPON | Y shall pay the penal sum to a ayment within such period of SOR and to the AGENT for a | PAL has failed to comply with any requirement as the SPONSOR within fifteen (15) days of written time, the AGENT may bring an action to collect all its expenses, including attorney's fees, incurred |
| IN WITNESS WHEREOF, t | ne said PRINCIPAL and th | ie said SURETY have caused | d this instrument to be signed by |
| their respective officers this | day of | | A.D., 20 |
| PRINCIPAL | | SURETY | |
| (Company Name) | | (Company I | Name) |
| By: | e) | By: | (Signature of Attorney-in-Fact) |
| (Signature & Title | | | |
| | Notary Cer | rtification for Principal and | Surety |
| State of Illinois |)) ss: | | |
| County of |) | | |
| l, | | , a Notary Pu | ublic in and for said County, do hereby certify that |
| | | and | |
| (Insert names of i | ndividuals signing on beha | alf of PRINCIPAL & SURETY) |) |
| PRINCIPAL and SURETY, | appeared before me this d | | ubscribed to the foregoing instrument on behalf of ged respectively, that they signed and delivered rth. |
| Given under my hand an | d notary seal this | day of | A.D., 20 |
| My commission expires _ | | | (Alstream D. H.C.) |
| the PRINCIPAL is ensuring | the identified electronic bid | | (Notary Public) may file an Electronic Bid Bond. By signing below, and the PRINCIPAL and SURETY are firmly bound on above. |
| Electronic Bid Bond ID# | Comp | pany/Bidder Name | Signature and Title Form D.E. (Rev. 12-2001) |



PROPOSALS

for construction work advertised for bids by the Illinois Department of Transportation

| Item No. | Item No. | Item No. |
|----------|----------|----------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

Submitted By:

| Name: |
|------------|
| Name. |
| |
| |
| Address: |
| Address. |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| Phone No. |
| r none no. |
| |
| |

Bidders should affix this form to the front of a 10" x 13" envelope and use that envelope for the submittal of bids. If proposals are mailed, they should be enclosed in a second or outer envelope addressed to:

Engineer of Design and Environment - Room 323 Illinois Department of Transportation 2300 South Dirksen Parkway Springfield, Illinois 62764

CONTRACTOR OFFICE COPY OF CONTRACT SPECIFICATIONS

NOTICE

None of the following material needs to be returned with the bid package unless the special provisions require documentation and/or other information to be submitted.



CONTRACT REQUIREMENTS

- (1) <u>Airport Improvement Program projects</u>. The work in this contract is included in the federal Airport Improvement Program and is being undertaken and accomplished by the Illinois Department of Transportation, Division of Aeronautics and the Municipality, hereinafter called the Co-Sponsors, in accordance with the terms and conditions of a Grant Agreement between the Co-Sponsors and the United States, under the Airport and Airway Improvement Act of 1982 (Public Law 97-248; Title V, Section 501 et seq., September 3, 1982; 96 Stat. 671; codified at 49 U.S.C Section 2201 et seq.) and Part 152 of the Federal Aviation Regulations (14 CFR Part 152), pursuant to which the United States has agreed to pay a certain percentage of the costs of the Project that are determined to be allowable Project costs under the Act. The United States is not a party to this contract and no reference in this contract to FAA or representative thereof, or to any rights granted to the FAA or any representative thereof, or the United States, by the contract, makes the United States a party to this contract.
- (2) <u>Consent of Assignment</u>. The Contractor shall obtain the prior written consent of the Co-Sponsors to any proposed assignment of any interest in or part of this contract.
 - (3) Convict Labor. No convict labor may be employed under this contract.
- (4) <u>Veterans Preference</u>. In the employment of labor, except in executive, administrative, and supervisory positions, preference shall be given to veterans of the Vietnam era and disabled veterans as defined in Section 515(c) of the Airport and Airway Improvement Act of 1982. However, this preference shall apply only where the individuals are available and qualified to perform the work to which the employment relates.
- (5) <u>Withholding: Sponsor from Contractor</u>. Whether or not payments or advances to the Co-Sponsors are withheld or suspended by the FAA, the Co-Sponsors may withhold or cause to be withheld from the Contractor so much of the accrued payments or advances as may be considered necessary to pay laborers and mechanics employed by the Contractor or any subcontractor on the work the full amount of wages required by this contract.
- (6) Nonpayment of Wages. If the Contractor or subcontractor fails to pay any laborer or mechanic employed or working on the site of the work any of the wages required by this contract the Co-Sponsors may, after written notice to the Contractor, take such action as may be necessary to cause the suspension of any further payment or advance of funds until the violations cease.
- (7) <u>FAA Inspection and Review</u>. The Contractor shall allow any authorized representative of the FAA to inspect and review any work or materials used in the performance of this contract.
- (8) <u>Subcontracts</u>. The Contractor shall insert in each of his subcontracts the provisions contained in Paragraphs (1), (3), (6), and (7) above and also a clause requiring the subcontractors to include these provisions in any lower tier subcontracts which they may enter into, together with a clause requiring this insertion in any further subcontracts that may in turn be made.
- (9) Contract Termination. A breach of Paragraph (6), (7), and (8) above may be grounds for termination of the contract.

PROVISIONS REQUIRED BY THE REGULATIONS OF THE SECRETARY OF LABOR 29 CFR 5.5

- (a) Contract Provisions and Related Matters.
 - (1) Minimum Wages.

Revised 1/92

- (i) All laborers and mechanics employed or working upon the site of the work will be paid unconditionally and not less often than once a week, and without subsequent deduction or rebate on any account (except such payroll deductions as are permitted by regulations issued by the Secretary of Labor under the Copeland Act (29 CFR Part 3)), the full amount of wages and bona fide fringe benefits (or cash equivalents thereof) due at time of payment computed at rates not less than those contained in the wage determination of the Secretary of Labor which is attached hereto and made a part hereof, regardless of any contractual relationship which may be alleged to exist between the Contractor and such laborers and mechanics. Contributions made or costs reasonably anticipated for bona fide fringe benefits under section 1(b)(2) of the Davis-Bacon Act on behalf of laborers or mechanics are considered wages paid to such laborers or mechanics, subject to the provision of paragraph (a)(1)(iv) of this section; also, regular contributions made or costs incurred for more than a weekly period (but not less often than quarterly) under plans, funds, or programs which cover the particular weekly period, are deemed to be constructively made or incurred during such weekly period. Such laborers and mechanics shall be paid the appropriate wage rate and fringe benefits on the wage determination for the classification of work actually performed, without regard to skill, except as provided in paragraph 5.5(a)(4). Laborers or mechanics performing work in more than one classification may be compensated at the rate specified for each classification for the time actually worked therein; provided, that the employer's payroll records accurately set forth the time spent in each classification in which work is performed. The wage determination (including any additional classification and wage rates conformed under paragraph (a)(1)(ii) of this section) and the Davis-Bacon poster (WH-1321) shall be posted at all times by the Contractor and its subcontractors at the site of the work in a prominent and accessible place where it can be easily seen by the workers.
- (ii)(A) The contracting officer shall require that any class of laborers or mechanics which is not listed in the wage determination and which is to be employed under the contract shall be classified in conformance with the wage determination. The contracting officer shall approve an additional classification and wage rate and fringe benefits therefor only when the following criteria have been met:
 - (1) The work to be performed by the classification requested is not performed by a classification in the wage determination; and
 - (2) The classification is utilized in the area by the construction industry; and
 - (3) The proposed wage rate, including any bona fide fringe benefits, bears a reasonable relationship to the wage rates contained in the wage determination.
- (ii)(B) If the Contractor and the laborers and mechanics to be employed in the classification (if known), or their representatives, and the contracting officer agree on the classification and wage rate (including the amount designated for fringe benefits where appropriate), a report of the action taken shall be sent by the contracting officer to the Administrator of the Wage and Hour Division, Employment Standards Administration, U.S. Department of Labor, Washington, D.C. 20210. The Administrator, or an authorized representative, will approve, modify, or disapprove every additional classification action within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary. (Approved by the Office of Management and Budget under OMB control number 1215-0140).
- (ii)(C) In the event the Contractor, the laborers or mechanics to be employed in the classification or their representatives, and the contracting officer do not agree on the proposed classification and wage rate (including the amount designated for fringe benefits, where appropriate), the contracting officer shall refer the questions, including the views of all interested parties and the recommendation of the contracting officer, to the Administrator for determination. The Administrator, or an authorized representative, will issue a determination within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary. (Approved by the Office of Management and Budget under OMB control number 1215-0140).

- (ii)(D) The wage rate (including fringe benefits where appropriate) determined pursuant to subparagraphs (1)(B) or (C) of this paragraph, shall be paid to all workers performing work in the classification under this contract from the first day on which work is performed in the classification.
- (iii) Whenever the minimum wage rate prescribed in the contract for a class of laborers or mechanics includes a fringe benefit which is not expressed as an hourly rate, the Contractor shall either pay the benefit as stated in the wage determination or shall pay another bona fide fringe benefit or an hourly cash equivalent thereof.
- (iv) If the Contractor does not make payments to a trustee or other third person, the Contractor may consider as part of the wages of any laborer or mechanic the amount of any costs reasonably anticipated in providing bona fide fringe benefits under a plan or program, provided, that the Secretary of Labor has found, upon the written request of the Contractor, that the applicable standards of the Davis-Bacon Act have been met. The Secretary of Labor may require the Contractor to set aside in a separate account assets for the meeting of obligations under the plan or program. (Approved by the Office of Management and Budget under OMB control number 1215-0140).
- (2) Withholding. The Federal Aviation Administration shall upon its own action or written request of an authorized representative of the Department of Labor withhold or cause to be withheld from the Contractor under this contract or any other Federal contract with the same prime Contractor, or any other Federally-assisted contract subject to Davis-Bacon prevailing wage requirements, which is held by the same prime Contractor, so much of the accrued payments or advances as may be considered necessary to pay laborers and mechanics, including apprentices, trainees, and helpers, employed by the Contractor or any subcontractor the full amount of wages required by the contract. In the event of failure to pay any laborer or mechanic, including any apprentice, trainee, or helper, employed or working on the site of the work, all or part of the wages required by the contract, the (Agency) may, after written notice to the Contractor, sponsor, applicant, or owner, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds until such violations have ceased.

(3) Payrolls and basic records.

- (i) Payrolls and basic records relating thereto shall be maintained by the Contractor during the course of the work and preserved for a period of three years thereafter for all laborers and mechanics working at the site of the work. Such records shall contain the name, address, and social security number of each such work, his or her correct classification, hourly rates of wages paid (including rates of contributions or costs anticipated for bona fide fringe benefits or cash equivalents thereof of the types described in section 1(b)(2)(B) of the Davis-Bacon Act), daily and weekly number of hours worked, deductions made and actual wages paid. Whenever the Secretary of Labor has found under 29 CFR 5.5(a)(1)(iv) that the wages of any laborer or mechanic include the amount of any costs reasonably anticipated in providing benefits under a plan or program described in section 1(b)(2)(B) of the Davis-Bacon Act, the Contractor shall maintain records which show that the commitment to provide such benefits is enforceable, that the plan or program is financially responsible, and that the plan or program has been communicated in writing to the laborers or mechanics affected, and records which show the costs anticipated or the actual cost incurred in providing such benefits. Contractors employing apprentices or trainees under approved programs shall maintain written evidence of the registration of apprenticeship programs and certification of trainee programs, the registration of the apprentices and trainees, and the ratios and wage rates prescribed in the applicable programs. (Approved by the Office Management and Budget under OMB control numbers 1215-0140 and 1215-0017).
- (ii)(A) The Contractor shall submit weekly for each week in which any contract work is performed a copy of all payrolls to the Federal Aviation Administration if the agency is a party to the contract, but if the agency is not such a party, the Contractor will submit the payrolls to the applicant, sponsor, or owner, as the case may be, for transmission to the Federal Aviation Administration. The payrolls submitted shall set out accurately and completely all of the information required to be maintained under paragraph 5.5(a)(3)(i) of Regulations, 29 CFR Part 5. This information may be submitted in any form desired.

Optional Form WH-347 is available for this purpose and may be purchased from the Superintendent of Documents (Federal Stock Number 029-005-00014-1), U.S. Government Printing Office, Washington, D.C. 20402. The prime Contractor is responsible for the submission of copies of payrolls by all subcontractors. (Approved by the Office of Management and Budget under OMB control number 1215-0149).

- (ii)(B) Each payroll submitted shall be accompanied by a "Statement of Compliance," signed by the Contractor, or subcontractor or his or her agent who pays or supervises the payment of the persons employed under the contract and shall certify the following:
 - (1) That the payroll for the payroll period contains the information required to be maintained under paragraph 5.5(a)(3)(i) of Regulations, 29 CFR Part 5 and that such information is correct and complete;
 - (2) That each laborer or mechanic (including each helper, apprentice, and trainee) employed on the contract during the payroll period has been paid the full weekly wages earned, without rebate, either directly or indirectly, and that no deductions have been made either directly or indirectly from the full wages earned, other than permissible deductions as set forth in Regulations, 29 CFR Part 3;
 - (3) That each laborer or mechanic has been paid not less than the applicable wage rates and fringe benefits or cash equivalents for the classification of work performed as specified in the applicable wage determination incorporated into the contract.
- (ii)(C) The weekly submission of a properly executed certification set forth on the reverse side of Optional Form WH-347 shall satisfy the requirement for submission of the "Statement of Compliance" required by paragraph (a)(3)(ii)(B) of this section.
- (ii)(D) The falsification of any of the above certifications may subject the Contractor or subcontractor to civil or criminal prosecution under Section 1001 of Title 18 and Section 231 of Title 31 of the United States Code.
- (iii) The Contractor or subcontractor shall make the records required under paragraph (a)(3)(i) of this section available for inspection, copying, or transcription by authorized representatives of the (write the name of the agency) or the Department of Labor, and shall permit such representatives to interview employees during working hours on the job. If the Contractor or subcontractor fails to submit the required records or to make them available, the Federal agency may, after written notice to the Contractor, sponsor, applicant, or owner, take such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds. Furthermore, failure to submit the required records upon request or to make such records available may be grounds for debarment action pursuant to 29 CFR 5.12.

(4) Apprentices and Trainees

(i) Apprentices. Apprentices will be permitted to work at less than the predetermined rate for the work they performed when they are employed pursuant to and individually registered in a bona fide apprenticeship program registered with the U.S. Department of Labor, Employment and Training Administration, Bureau of Apprenticeship and Training, or with a State Apprenticeship Agency recognized by the Bureau, or if a person is employed in his or her first 90 days of probationary employment as a apprentice in such an apprenticeship program, who is not individually registered in the program, but who has been certified by the Bureau of Apprenticeship and Training or a State Apprenticeship Agency (where appropriate) to be eligible for probationary employment as an apprentice. The allowable ratio of apprentices to journeymen on the job site in any craft classification shall not be greater than the ratio permitted to the Contractor as to the entire work force under the registered program. Any worker listed on a payroll at an apprentice wage rate, who is not registered or otherwise employed as stated above, shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any apprentice performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed. Where a Contractor is performing construction on a project in a locality other than that in which its program is registered, the ratios and wage rates (expressed in percentages of the journeyman's hourly rate) specified in the Contractor's or subcontractor's registered program shall be observed. Every apprentice must be paid at not less than the rate specified in the registered program for the apprentice's level of progress, expressed as a percentage of the journeymen hourly rate specified in the applicable wage determination. Apprentices shall be paid fringe benefits in accordance with the provisions of the apprenticeship program. If the apprenticeship program does not specify fringe benefits, apprentices must be paid the full amount of fringe benefits listed on the wage determination for the applicable classification. If the Administrator determines that a different practice prevails for the applicable apprentice classification, fringes shall be paid in accordance with that determination. In the event the Bureau of Apprenticeship and Training, or a State Apprenticeship Agency recognized by the Bureau, withdraws approval of an apprenticeship program, the Contractor will no longer be permitted to utilize apprentices at less than the applicable predetermined rate for the work performed until an acceptable program is approved.

- (ii) Trainees. Except as provided in 29 CFR 5.16, trainees will not be permitted to work at less than the predetermined rate for the work performed unless they are employed pursuant to and individually registered in a program which has received prior approval, evidenced by formal certification by the U.S. Department of Labor, Employment and Training Administration. The ratio of trainees to journeymen on the job site shall not be greater than permitted under the plan approved by the Employment and Training Administration. Every trainee must be paid at not less than the rate specified in the approved program for the trainee's level of progress, expressed as a percentage of the journeyman hourly rate specified in the applicable wage determination. Trainees shall be paid fringe benefits in accordance with the provisions of the trainee program. If the trainee program does not mention fringe benefits, trainees shall be paid the full amount of fringe benefits listed on the wage determination unless the Administrator of the Wage and Hour Division determines that there is an apprenticeship program associated with the corresponding journeyman wage rate on the wage determination which provides for less than full fringe benefits for apprentices. Any employee listed on the payroll at a trainee rate who is not registered and participating in a training plan approved by the Employment and Training Administration shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any trainee performing work on the job site in excess of the ration permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed. In the event the Employment and Training Administration withdraws approval of a training program, the contract will no longer be permitted to utilize trainees at less than the applicable predetermined rate for the work performed until an acceptable program is approved.
- (iii) Equal employment opportunity. The utilization of apprentices, trainees and journeymen under this part shall be in conformity with the equal employment opportunity requirements of Executive Order 11246, as amended, and 29 CFR Part 30.
- (5) Compliance with Copeland Act requirements. The Contractor shall comply with the requirements of 29 CFR Part 3, which are incorporated by reference in this contract.
- (6) Subcontracts. The Contractor or subcontractor shall insert in any subcontracts the clauses contained in paragraph (a)(1) through (10) of this contract and such other clauses as the Federal Aviation Administration may by appropriate instructions require, and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime Contractor shall be responsible for the compliance by an subcontractor or lower tier subcontractor with all the contract clauses in 29 CFR 5.5.
- (7) Contract determination: debarment. A breach of these contract clauses paragraphs (a)(1) through (10) and the 2nd clause (b)(1) through (5) below may be grounds for termination of the contract and for debarment as a Contractor and a subcontractor as provided in 29 CFR 5.12.
- (8) Compliance with Davis-Bacon and Related Act requirements. All rulings and interpretations of the Davis-Bacon and Related Acts contained in 29 CFR Parts 1, 3, and 5 are herein incorporated by referenced in this contract.
- (9) Disputes concerning labor standards. Disputes arising out of the labor standards provisions of this contract shall not be subject to the general disputes clause of this contract. Such disputes shall be resolved in accordance with the procedures of the Department of Labor set forth in 29 CFR Parts 5, 6, and 7. Disputes within the meaning of this clause include disputes between the Contractor (or any of its subcontractors) and the contracting agency, the U.S. Department of Labor, or the employees or their representatives.

- (i) By entering into this contract, the Contractor certifies that neither it (nor he or she) nor any person or firm who has an interest in the Contractor's firm is a person or firm ineligible to be awarded Government contracts by virtue of section 3(a) of the Davis-Bacon Act or 29 CFR 5.12(a)(1).
- (ii) No part of this contract shall be subcontracted to any person or firm ineligible for award of a Government contract by virtue of section 3(a) of the Davis-Bacon Act or 29 CFR 5.12(a)(1).
 - (iii) The penalty for making false statements is prescribed in the U.S. Criminal Code, 18 U.S.C. 1001.
- (b) Contract Work Hours and Safety Standards Act. The Agency Head shall cause or require the contracting officer to insert the following clauses set forth in paragraphs (b)(1), (2), (3), (4) and (5) of this section in full in AIP construction contracts in excess of \$2,000. These clauses shall be inserted in addition to the clauses required by paragraph 5.5(a) or paragraph 4.6 of Part 4 of this title. As used in this paragraph, the terms "laborers" and "mechanics" include watchmen and guards.
 - (1) Overtime requirements: No Contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers, mechanics, watchmen or guards (including apprentices and trainees described in paragraphs 5 and 6 above) shall require or permit any laborer, mechanic, watchman or guard in any workweek in which he/she is employed on such work, to work in excess of 40 hours in such workweek unless such laborer, mechanic, watchman or guard receives compensation at a rate not less than one and one-half times his/her basic rate of pay for all hours worked in excess of 40 hours in such workweek.
 - (2) Violations: Liability for Unpaid Wages; Liquidated Damages: In the event of any violation of the clause set forth in subparagraph (1) of this paragraph, the Contractor and any subcontractor responsible therefore shall be liable to any affected employee for his/her unpaid wages. In addition, such Contractor and subcontractor shall be liable to the United States (in case of work done under contract for the District of Columbia or a territory, to such District or to such territory), for liquidated damages. Such liquidated damages shall be computed with respect to each individual laborer, mechanic, watchman or guard employed in violation of the clause set forth in subparagraph (1) of this paragraph, in the sum of \$10.00 for each calendar day on which such employee was required or permitted to work in excess of the standard workweek of 40 hours without payment of the overtime wages required by the clause set forth in subparagraph (1) of this paragraph.
 - (3) Withholding for unpaid wages and liquidated damages. The (write in the name of the Federal agency or the loan or grant recipient) shall upon its own action or upon written request of an authorized representative of the Department of Labor withhold or cause to be withheld, from any moneys payable on account of work performed by the Contractor or subcontractor under any such contract or any other Federal contract with the same prime Contractor, or any other Federally-assisted contract subject to the Contract Work Hours and Safety Standards Act, which is held by the same prime Contractor, such sums as may be determined to be necessary to satisfy any liabilities of such Contractor or subcontractor for unpaid wages and liquidated damages as provided in the clause set forth in subparagraph (2) of this paragraph.
 - (4) Subcontracts. The Contractor or subcontractor shall insert in any subcontracts the clauses set forth in subparagraph (1) through (4) of this paragraph and also a clause requiring the subcontractors to include these clauses in any lower tier subcontracts. The prime Contractor shall be responsible for compliance by any subcontractor or lower tier subcontractor with the clauses set forth in subparagraphs (1) through (4) of this paragraph.
 - (5) Working Conditions. No Contractor or subcontractor may require any laborer or mechanic employed in the performance of any contract to work in surroundings or under working conditions that are unsanitary, hazardous, or dangerous to his health or safety as determined under construction safety and health standards (29 CFR 1926) issued by Department of Labor.

(c) In addition to the clauses contained in paragraph (b), in any contract subject only to the Contract Work Hours and Safety Standards Act and not to any of the other statutes cited in paragraph 5.1, the Agency Head shall cause or require the contracting officer to insert a clause requiring that the Contractor or subcontractor shall maintain payrolls and basic payroll records during the course of the work and shall preserve them for a period of three years from the completion of the contract for all laborers and mechanics, including guards and watchmen, working on the contract. Such records shall contain the name and address of each such employee, social security number, correct classifications, hourly rates of wages paid, daily and weekly number of hours worked, deductions made, and actual wages paid. Further, the Agency Head shall cause or require the contracting officer to insert in any such contract a clause providing that the records to be maintained under this paragraph shall be made available by the Contractor or subcontractor for inspection, copying, or transcription by authorized representatives of the (write the name of agency) and the Department of Labor, and the Contractor or subcontractor will permit such representatives to interview employees during working hours on the job. (Approved by the Office of Management and Budget under OMB control numbers 1215-0140 and 1215-0017).

FEDERAL REGULATIONS VOL. 40, #74, WEDNESDAY, APRIL 16, 1975, PAGE 17124, ADMINISTRATION OF THE CLEAR AIR ACT & WATER POLLUTION CONTROL ACT (with respect to Federal Grants)

In connection with the administration of the Clean Air Act and the Water Pollution Control Act with respect to Federal Grants, specific requirements have been imposed of any contract which is not exempt under the provisions of 40 CFR 15.5.

- (1) Any facility listed on the EPA List of Violating Facilities pursuant to Paragraph 15.20 of 40 CFR as of the date of the contract award will not be utilized in the performance of any non-exempt contract or subcontract.
- (2) The Contractor shall comply with all the requirements of Section 114 of the Clean Air Act, as amended, 42 USC 1857 et seq. and Section 308 of the Federal Water Pollution Control Act, as amended, 33 USC 1251 et seq. relating to inspection, monitoring, entry, reports and information, as well as all other requirements specified in Section 114 and Section 308 of the Air Act and Water Act, respectively, and all regulations and guidelines issued thereunder after the award of the contract.
- (3) Prompt notification shall be required prior to contract award to the awarding official by the Contractor who will receive the award of the receipt of any communication from the Director, Office of Federal Activities, U.S. Environmental Protection Agency, indicating that a facility to be utilized for the contract is under consideration to be listed on the EPA List of Violating Facilities.
- (4) The Contractor shall include or cause to be included the criteria and requirements in paragraphs 1 through 4 in any non-exempt subcontract and will take such action as the Government may direct as a means of enforcing such provisions.

Attachment No. 1

During the performance of the contract, the Contractor agrees as follows:

- (1) The Contractor will not discriminate against any employee or applicant for employment because of race, color, religion, sex or national origin. The Contractor will take affirmative action to ensure that applicants are employed, and that employees are treated during employment without regard to their race, color, religion, sex or national origin. Such action shall include, but not be limited to the following: Employment, upgrading, demotion or transfer, recruitment or recruitment advertising, layoff or termination, rates of pay or other forms of compensation, and selection for training including apprenticeship. The Contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.
- (2) The Contractor will, in all solicitations or advertisements for employees placed by or on the behalf of the Contractor, state that all qualified applicants will receive consideration for employment without regard to race, color, religion, sex or national origin.
- (3) The Contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or worker's representatives of the Contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment.
- (4) The Contractor will comply with all provisions of Executive Order 11246 of September 24, 1965, and of the rules, regulations, and relevant orders of the Secretary of Labor.
- (5) The Contractor will furnish all information and reports required by Executive Order 11246 of September 24, 1965, and by rules, regulations and orders of the Secretary of Labor, or pursuant thereto, and will permit access to his books, records, and accounts by the administering agency and the Secretary of Labor for purposes of investigation to ascertain compliance with such rules, regulations, and orders.
- (6) In the event of the Contractor's noncompliance with the nondiscrimination clauses of this contract or with any of the said rules, regulations, or orders, this contract may be canceled, terminated, or suspended in whole or in part and the Contractor may be declared ineligible for further government contracts or federally assisted construction contracts in accordance with procedures authorized in Executive Order 11246 of 24 September 1965, and such other sanctions may be imposed and remedies invoked as provided in Executive Order 11246 of 24 September 1965, or by rule, regulation or order of the Secretary of Labor, or as otherwise provided by law.
- (7) The Contractor will include the portion of the sentence immediately preceding paragraph (1) and the provisions of paragraphs (1) through (7) in every subcontract or purchase order unless exempted by rules, regulations, or orders of the Secretary of Labor issued pursuant to Section 204 of Executive Order 11246 of 24 September 1965, so that such provisions will be binding upon each subcontractor or vendor. The Contractor will take such action with respect to any subcontract or purchase order as the administering agency may direct as means of enforcing such provisions, including sanctions for noncompliance; provided, however, that in the event a Contractor becomes involved in, or is threatened with, litigation with a subcontractor or vendor as a result of such direction by the administering agency, the Contractor may request the United States to enter into such litigation to protect the interests of the United States.

ATTACHMENT NO. 2

EACH PRIME CONTRACTOR SHALL INSERT IN EACH SUBCONTRACT THE CERTIFICATION IN APPENDIX B, AND FURTHER, SHALL REQUIRE ITS INCLUSION IN ANY LOWER TIER SUBCONTRACT, PURCHASE ORDER, OR TRANSACTION THAT MAY IN TURN BE MADE.

- Appendix B of 49 CFR Part 29 -

This certification applies to subcontractors, material suppliers, vendors and other lower tier participants.

Appendix B--Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion--Lower Tier Covered Transactions

Instructions for Certification

- 1. By signing and submitting this proposal, the prospective lower tier participant is providing the certification set out below.
- 2. The certification in this clause is a material representation of fact upon which reliance was placed when this transaction was entered into. If it is later determined that the prospective lower tier participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment.
- 3. The prospective lower tier participant shall provide immediate written notice to the person to which this proposal is submitted if at any time the prospective lower tier participant learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.
- 4. The terms "covered transaction," "debarred," "suspended," "ineligible," "lower tier covered transaction, "participant," "person," "primary covered transaction," "principal," "proposal," and "voluntarily excluded," as used in this clause sections of rules implementing Executive Order 12549. You may contact the person to which this proposal is submitted for assistance in obtaining a copy of those regulations.
- 5. The prospective lower tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency with which this transaction originated.
- 6. The prospective lower tier participant further agrees by submitting this proposal that it will include this clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion--Lower Tier Covered Transaction," without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions.
- 7. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that it is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not required to, check the Nonprocurement List.
- 8. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of a participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- 9. Except for transactions authorized under paragraph 5 of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment.

Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion--Lower Tier Covered Transactions

- (1) The prospective lower tier participant certifies, by submission of this proposal, that neither it nor its principals is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any Federal department or agency.
- (2) Where the prospective lower tier participant is unable to certify to any of the statements in this certification, such prospective participant shall attach an explanation to this proposal.

STATE REQUIRED CONTRACT PROVISIONS

ALL FEDERAL-AID CONSTRUCTION CONTRACTS

Effective February 1, 1969 Revised January 2, 1973

The following provisions are State of Illinois requirements and are in addition to the Federal requirements.

"EQUAL EMPLOYMENT OPPORTUNITY"

In the event of the Contractor's noncompliance with any provisions of this Equal Employment Opportunity Clause, the Illinois Fair Employment Practices Act or the Fair Employment Practices Commission's Rules and Regulations for Public Contracts, the Contractor may be declared nonresponsible and therefore ineligible for future contracts or subcontracts with the State of Illinois or any of its political subdivisions or municipal corporations, and the contract may be canceled or avoided in whole or in part, and such other sanctions or penalties may be imposed or remedies invoked as provided by statute or regulation.

During the performance of this contract, the Contractor agrees as follows:

- (1) That it will not discriminate against any employee or applicant for employment because of race, color, religion, sex, national origin or ancestry; and further that it will examine all job classifications to determine if minority persons or women are underutilized and will take appropriate affirmative action to rectify any such underutilization.
- (2) That, if it hires additional employees in order to perform this contract or any portion hereof, it will determine the availability (in accordance with the Commission's Rules and Regulations for Public Contracts) of minorities and women in the area(s) from which it may reasonably recruit and it will hire for each job classification for which employees are hired in such a way that minorities and women are not underutilized.
- (3) That, in all solicitations or advertisements for employees placed by it or on its behalf, it will state that all applicants will be afforded equal opportunity without discrimination because of race, color, religion, sex, national origin or ancestry.
- (4) That it will send to each labor organization or representative of workers with which it has or is bound by a collective bargaining or other agreement or understanding, a notice advising such labor organization or representative of the Contractors obligations under the Illinois Fair Employment Practices Act and the Commission's Rules and Regulations for Public Contracts. If any such labor organization or representative fails or refuses to cooperate with the Contractor in its efforts to comply with such Act and Rules and Regulations, the Contractor will promptly so notify the Illinois Fair Employment Practices Commission and the contracting agency and will recruit employees from other sources when necessary to fulfill its obligations thereunder.
- (5) That it will submit reports as required by the Illinois Fair Employment Practices Commission's Rules and Regulations for Public Contracts, furnish all relevant information as may from time to time be requested by the Commission or the contracting agency, and in all respects comply with the Illinois Fair Employment Practices Act and the Commission's Rules and Regulations for Public Contracts.
- (6) That it will permit access to all relevant books, records, accounts and work sites by personnel of the contracting agency and the Illinois Fair Employment Practices Commission for purposes of investigation to ascertain compliance with the Illinois Fair Employment Practices Act and the Commission's Rules and Regulations for Public Contracts.
- (7) That it will include verbatim or by reference the provisions of paragraphs 1 through 7 of this clause in every performance subcontract as defined in Section 2.10(b) of the Commission's Rules and Regulations for Public Contracts so that such provisions will be binding upon every subcontractor; and that it will also so include the provisions or paragraphs 1, 5, 6 and 7 in every supply subcontract as defined in Section 2.10(a) of the Commission's Rules and Regulations for Public Contracts so that such provisions will be binding upon every such subcontractor. In the same manner as with other provisions of this contract, the Contractor will be liable for compliance with applicable provisions of this clause by all its subcontractors; and further it will promptly notify the contracting agency and the Illinois Fair Employment Practices Commission in the event any subcontractor fails or refuses to comply therewith. In addition, no Contractor will utilize any subcontractor declared by the Commission to be nonresponsible and therefore ineligible for contracts or subcontracts with the State of Illinois or any of its political subdivisions or municipal corporations.

CONSTRUCTION CONTRACT PROCUREMENT POLICIES

TABLE OF CONTENTS

| SECTIO | V | 1 |
|---------------|----|---|
| SECTION | ٠, | 1 |

Proposal Requirements and Conditions

SUB-SECTION

| | ADVERTISEMENT (Notice to Bidders) | |
|------|--|----|
| 1-02 | PREQUALIFICATION OF BIDDERS | 42 |
| 1-03 | CONTENTS OF PROPOSAL FORMS | 43 |
| 1-04 | ISSUANCE OF PROPOSAL FORMS | 43 |
| 1-05 | INTERPRETATION OF QUANTITIES IN BID SCHEDULE | 43 |
| | EXAMINATION OF PLANS, SPECIFICATIONS, AND SITE | |
| | PREPARATION OF THE PROPOSAL | |
| 1-08 | REJECTION OF PROPOSALS | 44 |
| 1-09 | PROPOSAL GUARANTY | 44 |
| | DELIVERY OF PROPOSALS | |
| 1-11 | WITHDRAWAL OF PROPOSALS | 45 |
| | PUBLIC OPENING OF PROPOSALS | |
| | DISQUALIFICATION OF BIDDERS | |
| | WORKER'S COMPENSATION INSURANCE | |
| | | |

SECTION 2

Award and Execution of Contract

SUB-SECTION

| 2-01 | CONSIDERATION OF PROPOSALS | . 45 |
|------|--|------|
| 2-02 | AWARD OF CONTRACT | .46 |
| 2-03 | CANCELLATION OF AWARD | .46 |
| 2-04 | RETURN OF PROPOSAL GUARANTY | .46 |
| 2-05 | REQUIREMENT OF PERFORMANCE AND PAYMENT BONDS | .46 |
| 2-06 | EXECUTION OF CONTRACT | .46 |
| | APPROVAL OF CONTRACT | |
| 2-08 | FAILURE TO EXECUTE CONTRACT | .46 |

SECTION 1

PROPOSAL REQUIREMENTS AND CONDITIONS

1-01 ADVERTISEMENT (Notice to Bidders). The State of Illinois shall publish the advertisement at such places and at such times as are required by local law or ordinances. The published advertisement shall state the time and place for submitting sealed proposals; a description of the proposed work; instructions to bidders as to obtaining proposal forms, plans, and specifications; proposal guaranty required; and the Owner's right to reject any and all bids.

For Federally assisted contracts the advertisement shall conform to the requirements of local laws and ordinances pertaining to letting of contracts and, in addition, shall conform to the requirements of the appropriate parts of the Federal Aviation Regulations applicable to the particular contract being advertised.

1-02 PREQUALIFICATION OF BIDDERS.

(a) When the awarding authority is the State of Illinois, each prospective bidder, prior to being considered for issuance of any proposal forms will be required to file, on forms furnished by the Department, an experience questionnaire and a confidential financial statement in accordance with the Department's Instructions for Prequalification of Contractors. The Statement shall include a complete report of the prospective bidder's financial resources and liabilities, equipment, past record and personnel, and must be submitted at least thirty (30) days prior to the scheduled opening of bids in which the Contractor is interested.

After the Department has analyzed the submitted "Contractor's Statement of Experience and Financial Condition" and related information and has determined appropriate ratings, the Department will issue to the Contractor a "Certificate of Eligibility". The Certificate will permit the Contractor to obtain proposal forms and plans for any Department of Transportation letting on work which is within the limits of the Contractor's potential as indicated on his "Certificate of Eligibility", subject to any limitations due to present work under contract or pending award as determined from the Contractor's submitted "Affidavit of Availability". Bidders intending to consistently submit proposals shall submit a "Contractor's Statement of Experience and Financial Condition" at least once a year. However, prequalification may be changed during that period upon the submission of additional favorable reports or upon reports of unsatisfactory performance.

Before a proposal is issued, the prospective bidder will be required to furnish an "Affidavit of Availability" indicating the location and amount of all uncompleted work under contract, or pending award, either as principal or subcontractor, as well as a listing of all subcontractors and value of work sublet to others. The prospective bidder may be requested to file a statement showing the amount and condition of equipment which will be available.

Before an award is made, the bidder may be required to furnish an outline of his plans for conducting the work.

(b) When the awarding authority for contract construction work is the County Board of a county; the Council, the City Council, or the President and Board of Trustees of a city, village or town, each prospective bidder, in evidence of his competence, shall furnish the awarding authority as a prerequisite to the release of proposal forms by the awarding authority, a certified or photostatic copy of a "Certificate of Eligibility" issued by the Department of Transportation, in accordance with Section 1-02(a).

The two low bidders must file within 24 hours after the letting a sworn affidavit, in triplicate, showing all uncompleted contracts awarded to them and all low bids pending award for Federal, State, County, Municipal and private work, using the blank form made available for this affidavit. One copy shall be filed with the awarding authority and two copies with the District Highway Office.

1-03 CONTENTS OF PROPOSAL FORMS. Upon request, the Department will furnish the prequalified bidders a proposal form. This form will state the location and description of the contemplated construction and will show the estimate of the various quantities and kinds of work to be performed or materials to be furnished, and will have a schedule of items for which unit bid prices are invited. The proposal form will state the time in which work must be completed, the amount of the proposal guaranty, labor requirements, and date, time and place of the opening of proposals. The form will also include any special provisions or requirements which vary from or are not contained in these specifications.

All papers bound with or attached to the proposal form are considered a part thereof and must not be detached or altered when the proposal is submitted. Any addenda officially issued by the Department, will be considered a part of the proposal whether attached or not.

For Federally assisted contracts, the proposal shall conform to the requirements of local laws and ordinances pertaining to letting of contracts and, in addition, shall conform to the requirements of the appropriate parts of the Federal Aviation Regulations pertaining to the particular contract being let.

1-04 ISSUANCE OF PROPOSAL FORMS. The Department shall refuse to issue a proposal form for any of the following reasons:

- (a) Lack of competency and adequate machinery, plant and other equipment, as revealed by the financial statement and experience questionnaires required under Section 1-02(a).
- (b) Uncompleted work which, in the judgment of the Department, might hinder or prevent the prompt completion of additional work if awarded.
- (c) False information provided on a bidder's "Affidavit of Availability".
- (d) Failure to pay, or satisfactorily settle, all bills due for labor and material on former contracts in force at the time of issuance of proposal forms.
- (e) Failure to comply with any prequalification regulations of the Department.
- (f) Default under previous contracts.
- (g) Unsatisfactory performance record as shown by past work for the Department, judged from the standpoint of workmanship and progress.
- (h) When the Contractor is suspended from eligibility to bid at a public letting where the contract is awarded by, or require approval of, the Department.
- (i) When any agent, servant, or employee of the prospective bidder currently serves as a member, employee, or agent of a governmental body that is financially involved in the proposed work.
- (j) When any agent, servant, or employee of the prospective bidder has participated in the preparation of plans or specifications for the proposed work.

1-05 INTERPRETATION OF QUANTITIES IN BID SCHEDULE. An estimate of quantities of work to be done and materials to be furnished under these specifications is given in the proposal. It is the result of careful calculations and is believed to be correct. It is given only as a basis for comparison of proposals and the award of the contract. The Owner does not expressly or by implication agree that the actual quantities involved will correspond exactly therewith; nor shall the bidder plead misunderstanding or deception because of such estimates of quantities, or of the character, location, or other conditions pertaining to the work. Payment to the Contractor will be made only for the actual quantities of work performed or materials furnished in accordance with the plans and specifications. It is understood that the quantities may be increased or decreased as provided in the subsection titled ALTERATION OF WORK AND QUANTITIES of Section 20 of the Illinois Standard Specifications for Construction of Airports without in any way invalidating the unit bid prices.

1-06 EXAMINATION OF PLANS, SPECIFICATIONS, AND SITE. The bidder is expected to carefully examine the site of the proposed work, the proposal, plans, specifications, and contract forms. He shall satisfy himself as to the character, quality, and quantities of work to be performed, materials to be furnished, and as to the requirements of the proposed contract. The submission of a proposal shall be prima facie evidence that the bidder has made such examination and is satisfied as to the conditions to be encountered in performing the work and as to the requirements of the proposed contract, plans, and specifications.

Boring logs, underground utilities and other records of subsurface investigations and tests are available for inspection of bidders. It is understood and agreed that such subsurface information, whether included in the plans, specifications, or otherwise made available to the bidder, was obtained and is intended for the Owner's design and estimating purposes only. Such information has been made available for the convenience of all bidders. It is further understood and agreed that each bidder is solely responsible for all assumptions, deductions, or conclusions which he may make or obtain from his examination of the boring logs and other records of subsurface investigations and tests that are furnished by the Owner.

1-07 PREPARATION OF THE PROPOSAL. The bidder shall submit his proposal on the form furnished by the Department. The proposal shall be executed property, and bids shall be made for all items indicated in the proposal form, except that when alternate bids are asked, a bid on more than one alternate for each item is not required, unless otherwise provided. The bidder shall indicate, in figures, a unit price for each of the separate items called for in the proposal; he shall show the products of the respective quantities and unit prices in the column provided for that purpose, and the gross sum shown in the place indicated in the proposal shall be the summation of said products. All writing shall be with ink or typewriter, except the signature of the bidder which shall be written with ink.

If the proposal is made by an individual, his name and business address shall be shown. If made by a firm or partnership, the name and business address of each member of the firm or partnership shall be shown. If made by a corporation, the proposal shall show the names, titles, and business address of the president, secretary, and treasurer, and the seal of the corporation shall be affixed and attested by the secretary.

The proposal shall be issued to a prequalified bidder in the same name and style as the financial statement used for prequalification and shall be submitted in like manner.

1-08 REJECTION OF PROPOSALS. The Department reserves the right to reject proposals for any of the conditions in Article 1-04 or for any of the following reasons:

- (a) More than one proposal for the same work from an individual, firm, partnership, or corporation under the same or different names.
- (b) Evidence of collusion among bidders.
- (c) Unbalanced proposals in which the prices for some items are obviously out of proportion to the prices for other items.
- (d) If the proposal does not contain a unit price for each pay item listed except in the case of authorized alternate pay items or lump sum pay items.
- (e) If the proposal is other than that furnished by the Department; or if the form is altered or any part thereof is detached.
- (f) If there are omissions, erasures, alterations, unauthorized additions, conditional or alternate bids, or irregularities of any kind which may tend to make the proposal incomplete, indefinite, or ambiguous as to its meaning.
- (g) If the bidder adds any provisions reserving the right to accept or reject an award, or to enter into a contract pursuant to an award.
- (h) If the proposal is not accompanied by the proper proposal guaranty.
- (i) If the proposal is prepared with other than ink or typewriter.
- (j) If the proposal is submitted in any other name other than that to whom it was issued by the Department.

1-09 PROPOSAL GUARANTY. Each Proposal shall be accompanied by either a bid bond on the Department of Transportation, Division of Aeronautics form contained in the proposal, executed by a corporate surety company satisfactory to the Department or by a bank cashier's check or a properly certified check for not less than 5 percent of the amount bid.

Bank cashier's checks, or properly certified checks accompanying proposals shall be made payable to the Treasurer, State of Illinois.

- 1-10 DELIVERY OF PROPOSALS. Each proposal should be submitted in a special envelope furnished by the Department. The blank spaces on the envelope shall be filled in correctly to clearly indicate its contents. When an envelope other than the special one furnished by the Department is used, it shall be of the same general size and shape and be similarly marked to clearly indicate its contents. When sent by mail, the sealed proposal shall be addressed to the Department at the address and in care of the official in whose office the bids are to be received. All proposals shall be filed prior to the time and place specified in the Notice to Bidders. Proposals received after the time for opening of bids will be returned to the bidder unopened.
- 1-11 WITHDRAWAL OF PROPOSALS. Permission will be given a bidder to withdraw a proposal if he makes his request in writing or by telegram before the time for opening proposals. If a proposal is withdrawn, the bidder will not be permitted to resubmit this proposal at the same letting. With the approval of the Engineer, a bidder may withdraw a proposal and substitute a new proposal prior to the time of opening bids.
- 1-12 PUBLIC OPENING OF PROPOSALS. Proposals will be opened and read publicly at the time and place specified in the Notice to Bidders. Bidders, their authorized agents, and other interested parties are invited to be present.
- 1-13 DISQUALIFICATION OF BIDDERS. A bidder shall be considered disqualified for any of the following reasons:
 - (a) Submitting more than one proposal from the same partnership, firm, or corporation under the same or different name.
 - (b) Evidence of collusion among bidders. Bidders participating in such collusion shall be disqualified as bidders for any future work of the Owner.
 - (c) If the bidder is considered to be in "default" for any reason specified in the Subsection 1-04 titled ISSUANCE OF PROPOSAL FORMS of this section.
- 1-14 WORKER'S COMPENSATION INSURANCE. Prior to the approval of his contract by the Division, the Contractor shall furnish to the Division certificates of insurance covering Worker's Compensation, or satisfactory evidence that this liability is otherwise taken care of in accordance with Section 4.(a) of the "Worker's Compensation Act of the State of Illinois" as amended.

SECTION 2

AWARD AND EXECUTION OF CONTRACT

2-01 CONSIDERATION OF PROPOSALS. After the proposals are publicly opened and read, they will be compared on the basis of the summation of the products obtained by multiplying the estimated quantities shown in the proposal by the unit bid prices. In the event of a discrepancy between unit bid prices and extensions, the unit bid price shall govern.

Until the award of a contract is made, the Owner reserves the right to reject a bidder's proposal for any of the following reasons:

- (a) If the proposal is irregular as specified in the subsection titled REJECTION OF PROPOSALS of Section 1.
- (b) If the bidder is disqualified for any of the reasons specified in the subsection titled DISQUALIFICATION OF BIDDERS of Section 1.

In addition, until the award of a contract is made, the Owner reserves the right to reject any or all proposals; waive technicalities, if such waiver is in the best interest of the Owner and is in conformance with applicable State and Local laws or regulations pertaining to the letting of construction contracts; advertise for new proposals; or proceed with the work otherwise.

2-02 AWARD OF CONTRACT. The award of contract will be made within 60 calendar days after the opening of proposals to the lowest responsible and qualified bidder whose proposal complies with all the requirements prescribed. The successful bidder will be notified by letter, that his bid has been accepted, and that he has been awarded the contract.

If a contract is not awarded within 60 days after the opening of proposals, a bidder may file a written request with the Division for the withdrawal of his bid and the Division will permit such withdrawal.

For Federally assisted contracts, unless otherwise specified in this subsection, no award shall be made until the FAA has concurred in the Owner's recommendation to make such award and has approved the Owner's proposal contract to the extent that such concurrence and approval are required by Federal Regulations.

- 2-03 CANCELLATION OF AWARD. The Division reserves the right to cancel the award without liability to the bidder at any time before a contract has been fully executed by all parties and is approved by the Owner in accordance with the subsection titled APPROVAL OF CONTRACT of this section. The Division at the time of cancellation will return the proposal guaranty.
- 2-04 RETURN OF PROPOSAL GUARANTY. The proposal guaranties of all except the two lowest bidders will be returned promptly after the proposals have been checked, tabulated, and the relation of the proposals established. Proposal guaranties of the two lowest bidders will be returned as soon as the Construction Contract, Performance Bonds, and Payment Bonds of the successful bidder have been properly executed and approved.

If any other form of proposal guaranty is used, other than a bid bond, a bid bond may be substituted at the Contractor's option.

- 2-05 REQUIREMENT OF PERFORMANCE AND PAYMENT BONDS. The successful bidder for a contract, at the time of the execution of the contract, shall deposit with the Division separate performance and payment bonds each for the full amount of the contract. The form of the bonds shall be that furnished by the Division, and the sureties shall be acceptable to the Division.
- 2-06 EXECUTION OF CONTRACT. The successful bidder shall sign (execute) the Contract and shall return the signed Contract to the Owner (Sponsor) for signature (execution) and subsequently return all copies to the Division. The fully executed surety bonds specified in the subsection title REQUIREMENTS OF PERFORMANCE AND PAYMENT BONDS of this section will be forwarded to the Division within 15 days of the date mailed or otherwise delivered to the successful bidder. If the Contract and Bonds are mailed, special handling is recommended.

If the bidder to whom award is to be made is a corporation organized under the laws of a State other than Illinois, the bidder shall furnish the Division a copy of the corporation's certificate of authority to do business in the State of Illinois with the return of the executed contract and bond. Failure to furnish such evidence of a certificate of authority within the time required will be considered as just cause for the annulment of the award and the forfeiture of the proposal guaranty to the State, not as a penalty, but in payment of liquidated damages sustained as a result of such failure.

- 2-07 APPROVAL OF CONTRACT. Upon receipt of the contract and bonds that have been executed by the successful bidder, the Owner shall complete the execution of the contract in accordance with local laws or ordinances, and return the contract to the Division for approval and execution by the Division. Delivery of the fully executed contract to the Contractor shall constitute the Department's approval to be bound by the successful bidder's proposal and the terms of the contract.
- 2-08 FAILURE TO EXECUTE CONTRACT. If the contract is not executed by the Division within 15 days following receipt from the bidder of the properly executed contracts and bonds, the bidder shall have the right to withdraw his bid without penalty.

Failure of the successful bidder to execute the contract and file acceptable bonds within 15 days after the contract has been mailed to him shall be just cause for the cancellation of the award and the forfeiture of the proposal guaranty which shall become the property of the State, not as a penalty, but as liquidation of damages sustained.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DIVISION OF AERONAUTICS

The requirements of the following provisions written for Federally-assisted construction contracts, including all goals and timetables and affirmative action steps, shall also apply to all State-funded construction contracts awarded by the Illinois Department of Transportation.

NOTICE OF REQUIREMENT FOR AFFIRMATIVE ACTION TO ENSURE EQUAL EMPLOYMENT OPPORTUNITY (EXECUTIVE ORDER 11246)

- 1. The Offeror's or Bidder's attention is called to the "Equal Opportunity Clause" and the "Standard Federal Equal Employment Opportunity Construction Contract Specifications" set forth herein.
- 2. The goals and timetables for minority and female participation, expressed in percentage terms for the Contractor's aggregate workforce in each trade on all construction work in the covered area, are as follows:

APPENDIX A

The following goal for female utilization in each construction craft and trade shall apply to all Contractors holding Federal and federally assisted construction contracts and subcontracts in excess of \$10,000. The goal is applicable to the Contractor's total on-site construction workforce, regardless of whether or not part of that workforce is performing work on a Federal, federally assisted or nonfederally related construction contact or subcontract.

AREA COVERED (STATEWIDE)

Goals for Women apply nationwide.

GOAL

APPENDIX B

Until further notice, the following goals for minority utilization in each construction craft and trade shall apply to all Contractors holding Federal and federally-assisted construction contracts and subcontracts in excess of \$10,000. to be performed in the respective geographical areas. The goals are applicable to the Contractor's total on-site construction workforce, regardless of whether or not part of that workforce is performing work on a Federal, federally-assisted or nonfederally related construction contract or subcontract.

Goal

Economic Area

O56 Paducah, KY:

Non-SMSA Counties
IL - Hardin, Massac, Pope

KY - Ballard, Caldwell, Calloway, Carlisle, Crittenden,

Fulton, Graves, Hickman, Livingston, Lyon, McCracken, Marshall

| Economic Area | Goal (percent) |
|---|----------------|
| 080 Evansville, IN: Non-SMSA Counties - IL - Edwards, Gallatin, Hamilton, Lawrence, Saline, Wabash, White IN - Dubois, Knox, Perry, Pike, Spencer KY - Hancock, Hopkins, McLean, Mublenberg, Ohio, Union, Webster | 3.5 |
| 081 Terre Haute, IN: Non-SMSA Counties - IL - Clark, Crawford IN - Parke | 2.5 |
| 083 Chicago, IL: SMSA Counties: 1600 Chicago, IL - IL - Cook, DuPage, Kane, Lake, McHenry, Will | 19.6 |
| 3740 Kankakee, IL - IL - Kankakee | 9.1 |
| Non-SMSA Counties IL - Bureau, DeKalb, Grundy, Iroquois, Kendall, LaSalle, Livingston, Putnam IN - Jasper, Laporte, Newton, Pulaski, Starke | 18.4 |
| 084 Champaign - Urbana, IL: SMSA Counties: 1400 Champaign - Urbana - Rantoul, IL - IL - Champaign | 7.8 |
| Non-SMSA Counties - IL - Coles, Cumberland, Douglas, Edgar, Ford, Piatt, Vermilion | 4.8 |
| 085 Springfield - Decatur, IL: SMSA Counties: 2040 Decatur, IL - IL - Macon | 7.6 |
| 7880 Springfield, IL - IL - Mendard, Sangamon | 4.5 |
| Non-SMSA Counties IL - Cass, Christian, Dewitt, Logan, Morgan, Moultrie, Scott, Shelby | 4.0 |
| 086 Quincy, IL: Non-SMSA Counties | 3.1 |
| IL - Adams, Brown, Pike MO - Lewis, Marion, Pike, Ralls | |
| 087 Peoria, IL: SMSA Counties: 1040 Bloomington - Normal, IL - IL - McLean | 2.5 |

APPENDIX B (CONTINUED)

| Economic Area | Goal (percent) |
|---|----------------|
| 6120 Peoria, IL - IL - Peoria, Tazewell, Woodford | 4.4 |
| Non-SMSA Counties - IL - Fulton, Knox, McDonough, Marshall, Mason, Schuyler, Stark, Warren | 3.3 |
| 088 Rockford, IL: SMSA Counties: 6880 Rockford, IL - IL - Boone, Winnebago | 6.3 |
| Non-SMSA Counties - IL - Lee, Ogle, Stephenson | 4.6 |
| 098 Dubuque, IA: Non-SMSA Counties - IL - JoDaviess IA - Atlamakee, Clayton, Delaware, Jackson, Winnesheik WI - Crawford, Grant, Lafayette | 0.5 |
| 099 Davenport, Rock Island, Moline, IA - IL: SMSA Counties: 1960 Davenport, Rock Island, Moline, IA - IL - IL - Henry, Rock Island IA - Scott | 4.6 |
| Non-SMSA Counties - IL - Carroll, Hancock, Henderson, Mercer, Whiteside IA - Clinton, DesMoines, Henry, Lee, Louisa, Muscatine MO - Clark | 3.4 |
| 107 St. Louis, MO: SMSA Counties: 7040 St. Louis, MO - IL - IL - Clinton, Madison, Monroe, St. Clair MO - Franklin, Jefferson, St. Charles, St. Louis, St. Louis City | 14.7 |
| Non-SMSA Counties - IL - Alexander, Bond, Calhoun, Clay, Effingham, Fayette, Franklin, Greene, Jackson, Jasper, Jefferson, Jersey, Johnson, Macoupin, Marion, Montgomery, Perry, Pulaski, Randolph, Richland, Union, Washington, Wayne, Williamson MO - Bollinger, Butler, Cape Girardeau, Carter, Crawford, Dent, Gasconade, | 11.4 |
| Iron, Lincoln, Madison, Maries, Mississippi, Montgomery, Perry, Phelps, Reynolds, Ripley, St. Francois, St. Genevieve, Scott, Stoddard, Warren, Washington, Wayne | |

These goals are applicable to all the Contractor's construction work (whether or not it is Federal or federally assisted) performed in the covered area. If the Contractor performs construction work in a geographical area located outside of the covered area, it shall apply the goals established for such geographical area where the work is actually performed. With regard to this second area, the Contractor also is subject to the goals for both its federally involved and nonfederally involved construction.

The Contractor's compliance with Executive Order and the regulations in 41 CFR Part 60-4 shall be based on its implementation of the Equal Opportunity Clause, specific affirmative action obligations required by the provisions and specifications set forth in its federally assisted contracts, and its efforts to meet the goals established for the geographical area where the contract resulting from this solicitation is to be performed. The hours of minority and female employment and training must be substantially uniform throughout the length of the contract, and in each trade, and the Contractor shall make a good faith effort to employ minorities and women evenly on each of its projects. The transfer of minority or female employees or trainees from Contractor to Contractor or from project to project for the sole purpose of meeting the Contractor's goals shall be a violation of the contract, the Executive Order and the regulations in 41 CFR Part 60-4. Compliance with the goals will be measured against the total work hours performed.

- 3. The Illinois Division of Aeronautics will provide written notification to the Director of the Office of Federal Contract Compliance Programs within 10 working days of award of any construction contract and/or subcontract in excess of \$10,000 at any tier for construction work under the contract resulting from this solicitation. This notification will list the name, address and telephone number of the subcontractor; employer identification number; estimated dollar amount of the subcontract; estimated starting and completion dates of the subcontract; and the geographical area in which the contract is to be performed.
- 4. As used in this Notice, and in the contract resulting from this solicitation, the "covered area" is the entire State of Illinois for the goal set forth in APPENDIX A and the county or counties in which the work is located for the goals set forth in APPENDIX B.

STANDARD FEDERAL EQUAL EMPLOYMENT OPPORTUNITY CONSTRUCTION CONTRACT SPECIFICATIONS (EXECUTIVE ORDER 11246)

- 1. As used in these specifications:
 - a) "Covered area" means the geographical area described in the solicitation from which this contract resulted;
 - b) "Director" means Director, Office of Federal Contract Compliance Programs, United States Department of Labor, or any person to whom the Director delegates authority;
 - c) "Employer identification number" means the Federal Social Security number used on the Employer's Quarterly Federal Tax Return, U.S. Treasury Department Form 941;
 - d) "Minority" includes:
 - (i) Black (all persons having origins in any of the Black African racial groups not of Hispanic origin);
 - (ii) Hispanic (all persons of Mexican, Puerto Rican, Cuban, Central or South American or other Spanish Culture or origin, regardless of race);
 - (iii) Asian and Pacific Islander (all persons having origins in any of the original peoples of the Far East, Southeast Asia, the Indian Subcontinent, or the Pacific Islands); and
 - (iv) American Indian or Alaskan Native (all persons having origins in any of the original peoples of North America and maintaining identifiable tribal affiliations through membership and participation or community identification).
- 2. Whenever the Contractor, or any Subcontractor at any tier, subcontracts a portion of the work involving any construction trade, it shall physically include in each subcontract in excess of \$10,000. the provisions of these specifications and the Notice which contains the applicable goals for minority and female participation and which is set forth in the solicitations from which this contract resulted.

- 3. If the Contractor is participating (pursuant to 41 CFR 60-4.5) in a Hometown Plan approved by the U.S. Department of Labor in the covered area either individually or through an association, its affirmative action obligations on all work in the plan area (including goals and timetables) shall be in accordance with that Plan for those trades which have unions participating in the Plan. Contractors must be able to demonstrate their participation in and compliance with the provisions of any such Hometown Plan. Each Contractor or Subcontractor participating in an approved Plan is individually required to comply with its obligations under the EEO clause, and to make a good faith effort to achieve each goal under the Plan in each trade in which it has employees. The overall good faith performance by other Contractors or Subcontractors toward a goal in an approved Plan does not excuse any covered Contractor's or Subcontractor's failure to take good faith efforts to achieve the Plan goals and timetables.
- 4. The Contractor shall implement the specific affirmative action standards provided in paragraphs 7a through p of these specifications. The goals set forth in the solicitation from which this contract resulted are expressed as percentages of the total hours of employment and training of minority and female utilization the Contractor should reasonably be able to achieve in each construction trade in which it has employees in the covered area. Covered Construction Contractors performing construction work in geographical areas where they do not have a Federal or federally assisted construction contract shall apply the minority and female goals established for the geographical area where the work is being performed. Goals are published periodically in the Federal Register in notice form, and such notices may be obtained from any Office of Federal Contract Compliance Programs office or from Federal procurement contracting officers. The Contractor is expected to make substantially uniform progress toward its goals in each craft during the period specified.
- 5. Neither the provisions of any collective bargaining agreement, nor the failure by a union with whom the Contractor has a collective bargaining agreement, to refer either minorities or women shall excuse the Contractor's obligations under these specifications, Executive Order 11246, or the regulations promulgated pursuant thereto.
- 6. In order for the nonworking training hours of apprentices and trainees to be counted in meeting the goals, such apprentices and trainees must be employed by the Contractor during the training period, and the Contractor must have made a commitment to employ the apprentices and trainees at the completion of their training, subject to the availability of employment opportunities. Trainees must be trained pursuant to training programs approved by the U.S. Department of Labor.
- 7. The Contractor shall take specific affirmative actions to ensure equal employment opportunity. The evaluation of the Contractor's compliance with these specifications shall be based upon its effort to achieve maximum results from its actions. The Contractor shall document these efforts fully, and shall implement affirmative action steps at least as extensive as the following:
 - a) Ensure and maintain a working environment free of harassment, intimidation, and coercion at all sites, and in all facilities at which the Contractor's employees are assigned to work. The Contractor, where possible, will assign two or more women to each construction project. The Contractor shall specifically ensure that all foremen, superintendents, and other on-site supervisory personnel are aware of and carry out the Contractor's obligation to maintain such a working environment, with specific attention to minority or female individuals working as such sites or in such facilities.
 - b) Establish and maintain a current list of minority and female recruitment sources, provide written notification to minority and female recruitment sources and to community organizations when the Contractor or its unions have employment opportunities available, and maintain a record of the organizations' responses.
 - Maintain a current file of the names, addresses and telephone numbers of each minority and female off-the-street applicant and minority or female referral from a union, a recruitment source or community organization and of what action was taken with respect to each such individual. If such individual was sent to the union hiring hall for referral and was not referred back to the Contractor by the union or, if referred, not employed by the Contractor, this shall be documented in the file with the reason therefor, along with whatever additional actions the Contractors may have taken.

- d) Provide immediate written notification to the Director when the union or unions with which the Contractor has a collective bargaining agreement has not referred to the Contractor a minority person or woman sent by the Contractor, or when the Contractor has other information that the union referral process has impeded the Contractor's efforts to meet its obligations.
- e) Develop on-the-job training opportunities and/or participate in training programs for the area which expressly include minorities and women, including upgrading programs and apprenticeship and trainee programs relevant to the Contractor's employment needs, especially those programs funded or approved by the Department of Labor. The Contractor shall provide notice of these programs to the sources compiled under 7b above.
- f) Disseminate the Contractor's EEO policy by providing notice of the policy to unions and training programs and requesting their cooperation in assisting the Contractor in meeting its EEO obligations; by including it in any policy manual and collective bargaining agreements; by publicizing it in the company newspaper, annual report, etc.; by specific review of the policy with all management personnel and with all minority and female employees at least once a year; and by posting the company EEO policy on bulletin boards accessible to all employees at each location where construction work is performed.
- g) Review, at least annually, the company's EEO policy and affirmative action obligations under these specifications with all employees having any responsibility for hiring, assignment, layoff, termination or other employment decisions including specific review of these items with onsite supervisory personnel such as Superintendents, General Foreman, etc., prior to the initiation of construction work at any job site. A written record shall be made and maintained identifying the time and place of these meetings, persons attending, subject matter discussed, and disposition of the subject matter.
- h) Disseminate the Contractor's EEO policy externally by including it in any advertising in the news media, specifically including minority and female news media, and providing written notification to and discussing the Contractor's EEO policy with other Contractors and Subcontractors with whom the Contractor does or anticipates doing business.
- i) Direct its recruitment efforts, both oral and written, to minority, female and community organizations, to schools with minority and female students and to minority and female recruitment and training organizations serving the Contractor's recruitment area and employment needs. Not later than one month prior to the date for the acceptance of applications for apprenticeship of other training by any recruitment source, the Contractor shall send written notification to organizations such as the above, describing the openings, screening procedures, and tests to be used in the selection process.
- j) Encourage present minority and female employees to recruit other minority persons and women and, where reasonable, provide after school, summer and vacation employment to minority and female youth both on the site and in other areas of a Contractor's workforce.
- k) Validate all tests and other selection requirements where there is an obligation to do so under 41 CFR Part 60-3.
- Conduct, at least annually, an inventory and evaluation at least of all minority and female personnel for promotional opportunities and encourage these employees to seek or to prepare for, through appropriate training, etc., such opportunities.
- m) Ensure that seniority practices, job classifications, work assignments and other personnel practices, do not have a discriminatory effect by continually monitoring all personnel and employment related activities to ensure that the EEO policy and the Contractor's obligations under these specifications are being carried out.
- n) Ensure that all facilities and company activities are nonsegregated except that separate or single-user toilet and necessary changing facilities shall be provided to assure privacy between the sexes.
- Document and maintain a record of all solicitations of offers for subcontracts from minority and female construction Contractors and suppliers, including circulation of solicitations to minority and female Contractor associations and other business associations.

 Revised 08-31-83

- p) Conduct a review, at least annually, of all supervisors' adherence to and performance under the Contractor's EEO policies and affirmative action obligations.
- 8. Contractors are encouraged to participate in voluntary associations which assist in fulfilling one or more of their affirmative action obligations (7a through p). The efforts of a Contractor association, joint Contractor-union, Contractor-community, or other similar group of which the Contractor is a member and participant, may be asserted as fulfilling any one or more of its obligations under 7a through p of these Specifications provided that the Contractor actively participates in the group, makes every effort to assure that the group has a positive impact on the employment of minorities and women in the industry, ensures that the concrete benefits of the program are reflected in the Contractor's minority and female workforce participation makes a good faith effort to meet its individual goals and timetables, and can provide access to documentation which demonstrates the effectiveness of actions taken on behalf of the Contractor. The obligation to comply, however, is the Contractor's and failure of such a group to fulfill an obligation shall not be a defense for the Contractor's noncompliance.
- 9. A single goal for minorities and a separate single goal for women have been established. The Contractor, however, is required to provide equal employment opportunity and to take affirmative action for all minority groups, both male and female, and all women, both minority and non-minority. Consequently, the Contractor may be in violation of the Executive Order if a particular group is employed in a substantially disparate manner (for example, even though the Contractor has achieved its goals for women generally, the Contractor may be in violation of the Executive Order if a specified minority group of women is underutilized).
- 10. The Contractor shall not use the goals and timetables or affirmative action standards to discriminate against any person because of race, color, religion, sex, or national origin.
- 11. The Contractor shall not enter into any Subcontract with any person or firm debarred from Government contracts pursuant to Executive Order 11246.
- 12. The Contractor shall carry out such sanctions and penalties for violation of these specifications and of the Equal Opportunity Clause, including suspension, termination and cancellation of existing subcontracts as may be imposed or ordered pursuant to Executive Order 11246, as amended, and its implementing regulations, by the Office of Federal Contract Compliance Programs. Any Contractor who fails to carry out such sanctions and penalties shall be in violation of these specifications and Executive Order 11246, as amended.
- 13. The Contractor, in fulfilling its obligations under these specifications, shall implement specific affirmative action steps, at least as extensive as those standards prescribed in paragraph 7 of these specifications, so as to achieve maximum results from its efforts to ensure equal opportunity. If the Contractor fails to comply with the requirements of the Executive Order, the implementing regulations, or these specifications, the Director shall proceed in accordance with 41 CFR 60-4.8.
- 14. The Contractor shall designate a responsible official to monitor all employment related activity to ensure that the company EEO policy is being carried out, to submit reports relating to the provisions hereof as may be required by the Government and to keep records. Records shall at least include for each employee the name, address, telephone numbers, construction trade, union affiliation if any, employee identification number when assigned, social security number, race, sex, status (e.g., mechanic, apprentice, trainee, helper, or laborer), dates of changes in status, hours worked per week in the indicated trade, rate of pay, and locations at which the work was performed. Records shall be maintained in an easily understandable and retrievable form; however, to the degree that existing records satisfy his requirement, Contractors shall not be required to maintain separate records.
- 15. Nothing herein provided shall be construed as a limitation upon the application of other laws which establish different standards of compliance or upon the application of requirements for the hiring of local or other area residents (e.g., those under the Public Works Employment Act of 1977 and the Community Development Block Grant Program).

ANNUAL EEO-1 REPORT TO JOINT REPORTING COMMITTEE AS REQUIRED AT

41 CFR 60-1.7(a)

Any Contractor having a Federal contract of \$50,000 or more and 50 or more employees is required to file annual compliance reports on Standard Form 100 (EEO-1) with the Joint Reporting Committee in accordance with the instructions provided with the form. The Contractor will provide a copy of such a report to the contracting agency within 30 days after the award of a contract.

The Contractor shall require its subcontractors to file an SF 100 within 30 days after award of the subcontract if (1) it is not exempt from the provisions of these regulations in accordance with 60-1.5, (2) has 50 or more employees, (3) first tier subcontractor, and (4) has a subcontract amounting to \$50,000 or more.

Subcontractors below the first tier which perform construction work at the site of construction shall be required to file such a report if (1) it is not exempt from the provisions of these regulations in accordance with 60-1.5, (2) has 50 or more employees and has a subcontract amounting to \$50,000 or more.

The SF 100 is available at the following address:

Joint Reports Committee EEOC - Survey Division 1801 "L" Street N.W. Washington, D.C. 20750

Phone (202) 663-4968

DISADVANTAGED BUSINESS POLICY

I. NOTICE

This proposal contains the special provision entitled "Required Disadvantaged Business Participation." Inclusion of this Special Provision in this contract satisfies the obligations of the Department of Transportation under federal law as implemented by 49 CFR 23 and under the Illinois "Minority and Female Business Enterprise Act."

II. POLICY

It is public policy that the businesses defined in 49 CFR Part 23 shall have the maximum opportunity to participate in the performance of contracts financed in whole or in part with State or Federal funds. Consequently, the requirements of 49 CFR Part 23 apply to this contract.

III. OBLIGATION

The Contractor agrees to ensure that the businesses defined in 49 CFR Part 23 have the maximum opportunity to participate in the performance of this contract. In this regard, the Contractor shall take all necessary and reasonable steps, in accordance with 49 CFR Part 23, to ensure that the said businesses have the maximum opportunity to compete for and perform portions of this contract. The Contractor shall not discriminate on the basis of race, color, national origin, or sex in the selection and retention of subcontractors, including procurement of materials and leases of equipment.

The Contractor shall include the above Policy and Obligation statements of this Special Provision in every subcontract, including procurement of materials and leases of equipment.

IV. DBE/WBE CONTRACTOR FINANCE PROGRAM

On contracts where a loan has been obtained through the DBE/WBE Contractor Finance Program, the Contractor shall cooperate with the Department by making all payments due to the DBE/WBE Contractor by means of a two-payee check payable to the Lender (Bank) and the Borrower (DBE/WBE Contractor).

V. BREACH OF CONTRACT

Failure to carry out the requirements set forth above and in the Special Provision shall constitute a breach of contract and may result in termination of the contract or liquidated damages as provided in the special provision.

(Rev. 9/21/92)

State of Illinois Department of Transportation

SPECIAL PROVISION FOR DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION

- I. <u>FEDERAL OBLIGATION</u>: The Department of Transportation, as a recipient of federal financial assistance, is required to take all necessary and reasonable steps to ensure nondiscrimination in the award and administration of contracts. Consequently, the federal regulatory provisions of 49 CFR part 26 apply to this contract concerning the utilization of disadvantaged business enterprises. This Special Provision will also be used by the Department to satisfy the requirements of the Business Enterprise for Minorities, Females, and Persons with Disabilities Act, 30 ILCS 575. For the purposes of this Special Provision, a disadvantaged business enterprise (DBE) means a business certified by the Department in accordance with the requirements of 49 CFR part 26 and listed in the DBE Directory or most recent addendum.
- II. <u>CONTRACTOR ASSURANCE</u>: The Contractor makes the following assurance and agrees to include the assurance in each subcontract that the Contractor signs with a subcontractor:

The contractor, subrecipient or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The contractor shall carry out applicable requirements of 49 CFR part 26 in the award and administration of federally-assisted contracts. Failure by the contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy as the recipient deems appropriate.

- III. OVERALL GOAL SET FOR THE DEPARTMENT: As a requirement of compliance with 49 CFR part 26, the Department has set an overall goal for DBE participation in its federally assisted contracts. That goal is 22.77% of all federal-aid funds the Department will expend in its federally assisted contracts for the subject reporting fiscal year. The Department is required to make a good faith effort to achieve this goal. The dollar amount paid to all approved DBE firms performing work called for in this contract is eligible to be credited toward fulfillment of the Department's overall goal.
- IV. CONTRACT GOAL TO BE ACHIEVED BY THE CONTRACTOR: This contract includes a specific DBE utilization goal established by the Department. The goal has been included because the Department has determined that the work of this contract has subcontracting opportunities that may be suitable for performance by DBE companies. This determination is based on an assessment of the type of work, the location of the work, and the availability of DBE companies to do a part of the work. The assessment indicates that, in the absence of unlawful discrimination, and in an arena of fair and open competition, DBE companies can be expected to perform 6.0% of the work. This percentage is set as the DBE participation goal for this contract. Consequently, in addition to the other award criteria established for this contract, the Department will award this contract to a bidder who makes a good faith effort to meet this goal of DBE participation in the performance of the work. A bidder makes a good faith effort for award consideration if either of the following is done in accordance with the procedures set forth in this Special Provision:
 - A. The bidder documents that firmly committed DBE participation has been obtained to meet the goal; or
 - B. The bidder documents that a good faith effort has been made to meet the goal, even though the effort did not succeed in obtaining enough DBE participation to meet the goal.

- V. <u>DBE LOCATOR REFERENCES:</u> Bidders may consult the DBE Directory as a reference source for DBE companies certified by the Department. In addition, the Department maintains a letting and item specific DBE locator information system whereby DBE companies can register their interest in providing quotes on particular bid items advertised for letting. Information concerning DBE companies willing to quote work for particular contracts may be obtained by contacting the Department's Bureau of Small Business Enterprises at telephone number (217)785-4611, or by visiting the Department's web site at www.dot.state.il.us.
- VI. <u>BIDDING PROCEDURES:</u> Compliance with the bidding procedures of this Special Provision is required prior to the award of the contract and the failure of the as-read low bidder to comply will render the bid nonresponsive.
 - A. In order to assure the timely award of the contract, the as-read low bidder must submit a Disadvantaged Business Utilization Plan on Department form SBE 2026 within seven (7) working days after the date of letting. To meet the seven (7) day requirement, the bidder may send the Plan by certified mail or delivery service within the seven (7) working day period. If a question arises concerning the mailing date of a Plan, the mailing date will be established by the U.S. Postal Service postmark on the original certified mail receipt from the U.S. Postal Service or the receipt issued by a delivery service. It is the responsibility of the as-read low bidder to ensure that the postmark or receipt date is affixed within the seven (7) working days if the bidder intends to rely upon mailing or delivery to satisfy the submission day requirement. The Plan is to be submitted to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764 (Telefax: (217) 785-1524). It is the responsibility of the bidder to obtain confirmation of telefax delivery. The Department will not accept a Utilization Plan if it does not meet the seven (7) day submittal requirement, and the bid will be declared nonresponsive. In the event the bid is declared nonresponsive due to a failure to submit a Plan or failure to comply with the bidding procedures set forth herein, the Department may elect to cause the forfeiture of the penal sum of the bidder's proposal guaranty, and may deny authorization to bid the project if re-advertised for bids. The Department reserves the right to invite any other bidder to submit a Utilization Plan at any time for award consideration or to extend the time for award.
 - B. The Utilization Plan shall indicate that the bidder either has obtained sufficient DBE participation commitments to meet the contract goal or has not obtained enough DBE participation commitments in spite of a good faith effort to meet the goal. The Utilization Plan shall further provide the name, telephone number and telefax number of a responsible official of the bidder designated for purposes of notification of plan approval or disapproval under the procedures of this Special Provision.
 - C. The Utilization Plan shall include a DBE Participation Commitment Statement, Department form SBE 2025, for each DBE proposed for the performance of work to achieve the contract goal. The signatures on these forms must be original signatures. All elements of information indicated on the said form shall be provided, including but not limited to the following:
 - 1. The name and address of each DBE to be used;
 - 2. A description, including pay item numbers, of the commercially useful work to be done by each DBE;
 - 3. The price to be paid to each DBE for the identified work specifically stating the quantity, unit price and total subcontract price for the work to be completed by the DBE. If partial pay items are to be performed by the DBE, indicate the portion of each item, a unit price where appropriate and the subcontract price amount;
 - 4. A commitment statement signed by the bidder and each DBE evidencing availability and intent to perform commercially useful work on the project; and
 - 5. If the bidder is a joint venture comprised of DBE firms and non-DBE firms, the plan must also include a clear identification of the portion of the work to be performed by the DBE partner(s).

- D. The contract will not be awarded until the Utilization Plan submitted by the bidder is approved. The Utilization Plan will be approved by the Department if the Plan commits sufficient commercially useful DBE work performance to meet the contract goal. The Utilization Plan will not be approved by the Department if the Plan does not commit sufficient DBE performance to meet the contract goal unless the bidder documents that it made a good faith effort to meet the goal. The good faith procedures of Section VIII of this special provision apply. If the Utilization Plan is not approved because it is deficient in a technical matter, unless waived by the Department, the bidder will be notified and will be allowed no less than a five (5) working day period in order to cure the deficiency.
- VII. CALCULATING DBE PARTICIPATION: The Utilization Plan values represent work anticipated to be performed and paid for upon satisfactory completion. The Department is only able to count toward the achievement of the overall goal and the contract goal the value of payments made for the work actually performed by DBE companies. In addition, a DBE must perform a commercially useful function on the contract to be counted. A commercially useful function is generally performed when the DBE is responsible for the work and is carrying out its responsibilities by actually performing, managing, and supervising the work involved. The Department and Contractor are governed by the provisions of 49 CFR part 26.55(c) on questions of commercially useful functions as it affects the work. Specific counting guidelines are provided in 49 CFR part 26.55, the provisions of which govern over the summary contained herein.
 - A. DBE as the Contractor: 100% goal credit for that portion of the work performed by the DBE's own forces, including the cost of materials and supplies. Work that a DBE subcontracts to a non-DBE firm does not count toward the DBE goals.
 - B. DBE as a joint venture Contractor: 100% goal credit for that portion of the total dollar value of the contract equal to the distinct, clearly defined portion of the work performed by the DBE's own forces.
 - C. DBE as a subcontractor: 100% goal credit for the work of the subcontract performed by the DBE's own forces, including the cost of materials and supplies. Work that a DBE subcontractor in turn subcontracts to a non-DBE firm does not count toward the DBE goal.
 - D. DBE as a trucker: 100% goal credit for trucking participation provided the DBE is responsible for the management and supervision of the entire trucking operation for which it is responsible. At least one truck owned, operated, licensed and insured by the DBE must be used on the contact. Credit will be given for the full value of all such DBE trucks operated using DBE employed drivers. Goal credit will be limited to the value of the reasonable fee or commission received by the DBE if trucks are leased from a non-DBE company.
 - E. DBE as a material supplier:
 - 1. 60% goal credit for the cost of the materials or supplies purchased from a DBE regular dealer.
 - 2. 100% goal credit for the cost of materials or supplies obtained from a DBE manufacturer.
 - 3. 100% credit for the value of reasonable fees and commissions for the procurement of materials and supplies if not a regular dealer or manufacturer.
- VIII. GOOD FAITH EFFORT PROCEDURES: If the bidder cannot obtain sufficient DBE commitments to meet the contract goal, the bidder must document in the Utilization Plan the good faith efforts made in the attempt to meet the goal. This means that the bidder must show that all necessary and reasonable steps were taken to achieve the contract goal. Necessary and reasonable steps are those which could reasonably be expected to obtain sufficient DBE participation. The Department will consider the quality, quantity and intensity of the kinds of efforts that the bidder has made. Mere *pro forma* efforts are not good faith efforts; rather, the bidder is expected to have taken those efforts that would be reasonably expected of a bidder actively and aggressively trying to obtain DBE participation sufficient to meet the contract goal.

- A. The following is a list of types of action that the Department will consider as part of the evaluation of the bidder's good faith efforts to obtain participation. These listed factors are not intended to be a mandatory checklist and are not intended to be exhaustive. Other factors or efforts brought to the attention of the Department may be relevant in appropriate cases, and will be considered by the Department.
 - Soliciting through all reasonable and available means (e.g. attendance at pre-bid meetings, advertising and/or
 written notices) the interest of all certified DBE companies that have the capability to perform the work of the
 contract. The bidder must solicit this interest within sufficient time to allow the DBE companies to respond to
 the solicitation. The bidder must determine with certainty if the DBE companies are interested by taking
 appropriate steps to follow up initial solicitations.
 - 2. Selecting portions of the work to be performed by DBE companies in order to increase the likelihood that the DBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units to facilitate DBE participation, even when the prime contractor might otherwise prefer to perform these work items with its own forces.
 - 3. Providing interested DBE companies with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation.
 - 4. (a) Negotiating in good faith with interested DBE companies. It is the bidder's responsibility to make a portion of the work available to DBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available DBE subcontractors and suppliers, so as to facilitate DBE participation. Evidence of such negotiation includes the names, addresses, and telephone numbers of DBE companies that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional agreements could not be reached for DBE companies to perform the work.
 - (b) A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including DBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using DBE companies is not in itself sufficient reason for a bidder's failure to meet the contract DBE goal, as long as such costs are reasonable. Also, the ability or desire of a prime contractor to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts. Prime contractors are not, however, required to accept higher quotes from DBE companies if the price difference is excessive or unreasonable.
 - 5. Not rejecting DBE companies as being unqualified without sound reasons based on a thorough investigation of their capabilities. The contractor's standing within its industry, membership in specific groups, organizations, or associations and political or social affiliations (for example union vs. non-union employee status) are not legitimate causes for the rejection or non-solicitation of bids in the contractor's efforts to meet the project goal.
 - 6. Making efforts to assist interested DBE companies in obtaining bonding, lines of credit, or insurance as required by the recipient or contractor.
 - Making efforts to assist interested DBE companies in obtaining necessary equipment, supplies, materials, or related assistance or services.
 - 8. Effectively using the services of available minority/women community organizations; minority/women contractors' groups; local, state, and Federal minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of DBE companies.
- B. If the Department determines that the Contractor has made a good faith effort to secure the work commitment of DBE companies to meet the contract goal, the Department will award the contract provided that it is otherwise eligible for award. If the Department determines that a good faith effort has not been made, the Department will notify the bidder of that preliminary determination by contacting the responsible company official designated in the Utilization Plan. The preliminary determination shall include a statement of reasons why good faith efforts have not been found, and may include additional good faith efforts that the bidder could take. The notification will

designate a five (5) working day period during which the bidder shall take additional efforts. The bidder is not limited by a statement of additional efforts, but may take other action beyond any stated additional efforts in order to obtain additional DBE commitments. The bidder shall submit an amended Utilization Plan if additional DBE commitments to meet the contract goal are secured. If additional DBE commitments sufficient to meet the contract goal are not secured, the bidder shall report the final good faith efforts made in the time allotted. All additional efforts taken by the bidder will be considered as part of the bidder's good faith efforts. If the bidder is not able to meet the goal after taking additional efforts, the Department will make a pre-final determination of the good faith efforts of the bidder and will notify the designated responsible company official of the reasons for an adverse determination.

- C. The bidder may request administrative reconsideration of a pre-final determination adverse to the bidder within the five (5) working days after the notification date of the determination by delivering the request to the Department of Transportation, Division of Aeronautics, 1 Langhorne Bond Drive, Capital Airport, Springfield, IL 62707-8415 (Telefax: 217-785-4533). Deposit of the request in the United States mail on or before the fifth business day shall not be deemed delivery. The pre-final determination shall become final if a request is not made and delivered. A request may provide additional written documentation and/or argument concerning the issue of whether an adequate good faith effort was made to meet the contract goal. In addition, the request shall be considered a consent by the bidder to extend the time for award. The request will be forwarded to the Department's Reconsideration Officer. The Reconsideration Officer will extend an opportunity to the bidder to meet in person in order to consider all issues of whether the bidder made a good faith effort to meet the goal. After the review by the Reconsideration Officer, the bidder will be sent a written decision within ten (10) working days after receipt of the request for reconsideration, explaining the basis for finding that the bidder did or did not meet the goal or make adequate good faith efforts to do so. A final decision by the Reconsideration Officer that a good faith effort was made shall approve the Utilization Plan submitted by the bidder and shall clear the contract for award. A final decision that a good faith effort was not made shall render the bid nonresponsive.
- IX. CONTRACT COMPLIANCE: Compliance with this Special Provision is an essential part of the contract. The Department is prohibited by federal regulations from crediting the participation of a DBE included in the Utilization Plan toward either the contract goal or the Department's overall goal until the amount to be applied toward the goals has been paid to the DBE. The following administrative procedures and remedies govern the compliance by the Contractor with the contractual obligations established by the Utilization Plan. After approval of the Plan and award of the contract, the Utilization Plan and individual DBE Participation Statements become part of the contract. If the contractor did not succeed in obtaining enough DBE participation to achieve the advertised contract goal, and the Utilization Plan was approved and contract awarded based upon a determination of good faith, the total dollar value of DBE work calculated in the approved Utilization Plan as a percentage of the awarded contract value shall become the amended contract goal.
 - A. No amendment to the Utilization Plan may be made without prior written approval from the Division of Aeronautics. All requests for amendment to the Utilization Plan shall be submitted to the Department of Transportation, Division of Aeronautics, 1 Langhorne Bond Drive, Capital Airport, Springfield, IL 62707-8415. Telephone number (217) 785-8514. Telefax number (217) 785-4533.
 - B. All work indicated for performance by an approved DBE shall be performed, managed and supervised by the DBE executing the Participation Statement. The Contractor shall not terminate for convenience a DBE listed in the Utilization Plan and then perform the work of the terminated DBE with its own forces, those of an affiliate or those of another subcontractor, whether DBE or not, without first obtaining the written consent of the Bureau of Small Business Enterprises to amend the Utilization Plan. If a DBE listed in the Utilization Plan is terminated for reasons other than convenience, or fails to complete its work on the contract for any reason, the Contractor shall make good faith efforts to find another DBE to substitute for the terminated DBE. The good faith efforts shall be directed at finding another DBE to perform at least the same amount of work under the contract as the DBE that was terminated, but only to the extent needed to meet the contract goal or the amended contract goal. The Contractor shall notify the Division of Aeronautics of any termination for reasons other than convenience, and shall obtain approval for inclusion of the substitute DBE in the Utilization Plan. If good faith efforts following a termination of a DBE for cause are not successful, the Contractor shall contact the Division and provide a full accounting of the efforts undertaken to obtain substitute DBE participation. The Division will evaluate the good faith efforts in light of all circumstances surrounding the performance status of the contract, and determine whether the contract goal should be amended.

60

- C. The Contractor shall maintain a record of payments for work performed to the DBE participants. The records shall be made available to the Department for inspection upon request. After the performance of the final item of work or delivery of material by a DBE and final payment therefor to the DBE by the Contractor, but not later than thirty (30) calendar days after payment has been made by the Department to the Contractor for such work or material without regard to any retainage withheld by the Department, the Contractor shall submit a DBE Payment Report on Department form SBE 2115 to the Division's Chief Engineer. If full and final payment has not been made to the DBE, the Report shall indicate whether a disagreement as to the payment required exists between the Contractor and the DBE or if the Contractor believes that the work has not been satisfactorily completed. If the Contractor does not have the full amount of work indicated in the Utilization Plan performed by the DBE companies indicated in the Plan, the Department will deduct from contract payments to the Contractor the amount of the goal not achieved as liquidated and ascertained damages.
- D. The Department reserves the right to withhold payment to the Contractor to enforce the provisions of this Special Provision. Final payment shall not be made on the contract until such time as the Contractor submits sufficient documentation demonstrating achievement of the goal in accordance with this Special Provision or after liquidated damages have been determined and collected.

Certification of Nonsegregated Facilities - as Required by 41 CFR 60-1.8

(Applicable to (1) contracts, (2) subcontracts, and (3) agreements with applicants who are themselves performing federally assisted construction contracts, exceeding \$10,000.00 which are not exempt from the provisions of the Equal Opportunity clause).

By the submission of this bid, the bidder, offeror, applicant, or subcontractor certifies that he does not maintain or provide for his employees any segregated facilities at any of his establishments and that that he does not permit his employees to perform their services at any location, under his control, where segregated facilities are maintained. He certifies further that he will not maintain or provide for his employees any segregated facilities at any of his establishments and that he will not permit his employees to perform their services at any location, under his control, where segregated facilities are maintained. The bidder, offeror, applicant, or subcontractor agrees that a breach of his certification is a violation of the Equal opportunity clause in this contract. As used in this certification, the term "segregated facilities" means any waiting rooms, work areas, rest rooms and wash rooms, restaurants and other eating areas, time clocks, locker rooms and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing facilities provided for employees which are segregated by explicit directive or are in fact segregated on the basis of race, color, religion, or national origin, because of habit, local custom, or otherwise. He further agrees that (except where he has obtained identical certifications from proposed subcontractors for specific time periods) he will obtain identical certifications from proposed subcontractors prior to the award of subcontracts exceeding \$10,000.00 which are not exempt from the provisions of the Equal Opportunity clause; that he will retain such certifications in his files and that he will forward the following notice to such proposed subcontractors (except where the proposed subcontractors have submitted identical certifications for specific time periods):

NOTICE TO PROSPECTIVE SUBCONTRACTORS OF REQUIREMENT FOR CERTIFICATIONS OF NONSEGREGATED FACILITIES

A certification of Nonsegregated Facilities must be submitted prior to the award of a subcontract exceeding \$10,000.00 which is not exempt from the provisions of the Equal Opportunity clause. The certification may be submitted either for each subcontract or for all subcontracts during a period (i.e., quarterly, semiannually).

NOTE: The penalty for making false statements in offers is prescribed in 18 U.S.C 1001.

CERTIFICATION REGARDING DEBARMENT, SUSPENSION, AND OTHER RESPONSIBILITY MATTERS Instructions for Certification

- 1. By signing and submitting this proposal, the prospective primary participant is providing the certification set out below
- 2. The inability of a person to provide the certification required below will not necessarily result in denial of participation in this covered transaction. The prospective participant shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective primary participant to furnish a certification or an explanation shall disqualify such person from participation in this transaction.
- 3. The certification in this clause is a material representation of fact upon which reliance was placed when the department or agency determined to enter into this transaction. If it is later determined that the prospective primary participant knowingly rendered an erroneous certification in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause of default.
- 4. The prospective primary participant shall provide immediate written notice to the department or agency to whom this proposal is submitted if at any time the prospective primary participant learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.
- 5. The terms "covered transaction" "debarred" "suspended" "ineligible" "lower tier covered transaction" "participant" "person" "primary covered transaction" "principal" "proposal" and "voluntarily excluded" as used in this clause have the meaning set out in the Definitions and Coverage sections of the rules implementing Executive Order 12540. You may contact the department or agency to which this proposal is being submitted for assistance in obtaining a copy of those regulations.
- 6. The prospective primary participant agrees by submitting this proposal that should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction unless authorized by the department or agency entering into this transaction.
- 7. The prospective primary participant further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion Lower Tier Transaction", provided by the department or agency entering into this covered transaction without modification in all lower covered transactions and in all solicitations for lower covered transactions.
- 8. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that it is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not required to check the Nonprocurement List (Tel. #).
- 9. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of a participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.
- 10. Except for transactions authorized under paragraph 8 of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause or default.

<u>Certification Regarding Debarment, Suspension, and</u> <u>Other Responsibility Matters - Primary Covered Transactions</u>

- 1. The prospective primary participant certifies to the best of its knowledge and belief that it and its principals:
 - a. Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from covered transactions by an Federal department or agency;
 - b. Have not within a three-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain or performing a public (Federal, State or Local) transaction or contract under a public transaction: violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction or destruction of records, making false statements, or receiving stolen property;
 - c. Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offenses enumerated in paragraph (1)(b) of this certification; and
 - d. Have not within a three-period preceding this application/proposal had one or more public transactions (Federal, State or local) terminated for cause or default.
- 2. Where the prospective primary participant is unable to certify to any of the statements in this certification, such prospective participant shall attach an explanation to this proposal.

CERTIFICATION REGARDING LOBBYING (Applicable to contracts in excess of \$100,000):

Certification for Contracts, Grants, Loans and Cooperative Agreements.

The undersigned bidder certifies, to the best of his or her knowledge and belief, that:

- (1) No Federal appropriated funds have paid or will be paid, by or behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an Officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
- (2) If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying", in accordance with its instructions.
- (3) The undersigned shall require that the language of this certification be included in the award documents for all subawards at all tiers (including subcontracts, subgrants, and contracts under grants, loans, and cooperative agreements) and that all subrecipients shall certify and disclose accordingly.

This certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by Section 1352, title 31, U.S. Code. Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not more than \$100,000 for each such failure.

WORKERS' COMPENSATION INSURANCE

Prior to the execution of his construction contract by the Illinois Department of Transportation, Division of Aeronautics, hereinafter referred to as "Division", the Contractor shall furnish to the Division certificates of insurance covering Workers' Compensation, or satisfactory evidence that this liability is otherwise taken care of in accordance with Section 4.(a) of the "Workers' Compensation Act of the State of Illinois" as amended.

Such insurance, or other means of protection as herein provided, shall be kept in force until all work to be performed under the terms of the contract has been completed and accepted in accordance with the specifications, and it is hereby understood and agreed that the maintenance of such insurance or other protection, until acceptance of the work by the Division is a part of the contract. Failure to maintain such insurance, cancellation by the Industrial Commission of its approval of such other means of protection as might have been elected, or any other act which results in lack of protection under the said "Workers' Compensation Act" may be considered as a breach of the contract.

SPECIAL PROVISION FOR DOMESTIC SOURCE FOR STEEL

<u>Control of Materials</u>: All steel products, as defined by the Illinois Steel Products Procurement Act, incorporated into this project shall be manufactured or produced in the United States and, in addition, shall be domestically fabricated. The Contractor shall obtain from the steel producer and/or fabricator, in addition to the mill analysis, a certification that all steel products meet these domestic source requirements.

CLAUSE TO BE INCLUDED IN ALL SOLICITATIONS, CONTRACTS, AND SUBCONTRACTS RESULTING FROM PROJECTS FUNDED UNDER THE AIP

The Contractor or subcontractor, by submission of an offer and/or execution of a contract, certifies that it:

- a. is not owned or controlled by one or more citizens or nationals of a foreign country included in the list of countries that discriminate against U.S. firms published by the Office of the United States Trade Representative (USTR);
- b. has not knowingly entered into any contract or subcontract for this project with a Contractor that is a citizen or national of a foreign country on said list, or is owned or controlled directly or indirectly by one or more citizens or nationals of a foreign country on said list.
- c. has not procured any product nor subcontracted for the supply of any product for use on the project that is produced in a foreign country on said list.

Unless the restrictions of this clause are waived by the Secretary of Transportation in accordance with 49 CFR 30.17, no contract shall be awarded to a Contractor or subcontractor who is unable to certify to the above. If the Contractor knowingly procures or subcontracts for the supply of any product or service of a foreign country on the said list for use on the project, the Federal Aviation Administration may direct, through the sponsor, cancellation of the contract at no cost to the Government.

Further, the Contractor agrees that, if awarded a contract resulting from this solicitation, it will incorporate this provision for certification without modification in each contract and in all lower tier subcontracts. The Contractor may rely upon the certification of a prospective subcontractor unless it has knowledge that the certification is erroneous.

The Contractor shall provide immediate written notice to the sponsor if the Contractor learns that its certification or that of a subcontractor was erroneous when submitted or has become erroneous by reason of changed circumstances. The subcontractor agrees to provide immediate written notice to the Contractor, if at any time it learns that its certification was erroneous by reason of changed circumstances.

This certification is a material representation of fact upon which reliance was placed when making the award. If it is later determined that the Contractor or subcontractor knowingly rendered an erroneous certification, the Federal Aviation Administration may direct, through this sponsor, cancellation of the contract or subcontract for default at no cost to the Government.

Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render, in good faith, the certification required by this provision. The knowledge and information of a Contractor is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.

This certification concerns a matter within the jurisdiction of an agency of the United States of America and the making of false, fictitious, or fraudulent certification may render the maker subject to prosecution under Title 18, United States Code, Section 1001.

MINIMUM WAGES FOR FEDERAL AND FEDERALLY ASSISTED CONSTRUCTION CONTRACTS

This project is funded, in part, with Federal-aid funds and, as such, is subject to the provisions of the Davis-Bacon Act of March 3, 1931, as amended (46 Sta. 1494, as amended, 40 U.S.C. 276a) and of other Federal statutes referred to in a 29 CFR Part 1, Appendix A, as well as such additional statutes as may from time to time be enacted containing provisions for the payment of wages determined to be prevailing by the Secretary of Labor in accordance with the Davis-Bacon Act and pursuant to the provisions of 29 CFR Part 1. The prevailing rates and fringe benefits shown in the General Wage Determination Decisions issued by the U.S. Department of Labor shall, in accordance with the provisions of the foregoing statutes, constitute the minimum wages payable on Federal and federally assisted construction projects to laborers and mechanics of the specified classes engaged on contract work of the character and in the localities described therein.

General Wage Determination Decisions, modifications and supersedes decisions thereto are to be used in accordance with the provisions of 29 CFR Parts 1 and 5. Accordingly, the applicable decision, together with any modifications issued, must be made a part of every contract for performance of the described work within the geographic area indicated as required by an applicable DBRA Federal prevailing wage law and 29 CFR Part 5. The wage rates and fringe benefits contained in the General Wage Determination Decision shall be the minimum paid by contractors and subcontractors to laborers and mechanics.

NOTICE

The most current **General Wage Determination Decisions** (wage rates) are available on the IDOT web site. They are located on the Letting and Bidding page at http://www.dot.state.il.us/desenv/delett.html.

In addition, ten (10) days prior to the letting, the applicable Federal wage rates will be e-mailed to subscribers. It is recommended that all contractors subscribe to the Federal Wage Rates List or the Contractor's Packet through IDOT's subscription service.

PLEASE NOTE: if you have already subscribed to the Contractor's Packet you will automatically receive the Federal Wage Rates.

The instructions for subscribing are at http://www.dot.state.il.us/desenv/subsc.html.

If you have any questions concerning the wage rates, please contact IDOT's Chief Contract Official at 217-782-7806.

BITUMINOUS MATERIALS COST ADJUSTMENTS (BDE) (RETURN FORM WITH BID)

Effective: December 1, 2006

<u>Description.</u> For projects with at least 1200 tons of work involving applicable bituminous materials, cost adjustments will be made to provide additional compensation to the Contractor, or credit to the Department, for fluctuations in the cost of bituminous materials when optioned by the Contractor. The adjustments shall apply to permanent and temporary hot-mix asphalt (HMA) mixtures, bituminous surface treatments (cover and seal coats), and pavement preservation type surface treatments. The adjustments shall not apply to bituminous prime coats, tack coats, crack filling/sealing, or joint filling/sealing.

The bidder shall indicate on the attached form whether or not this special provision will be part of the contract and submit the completed form with his/her bid. Failure to submit the form, or failure to fill out the form completely, shall make this contract exempt of bituminous materials cost adjustments.

Method of Adjustment. Bituminous materials cost adjustments will be computed as follows.

 $CA = (BPI_p - BPI_L \times (\%AC_v / 100) \times Q$

Where: CA = Cost Adjustment, \$.

BPI_p = Bituminous Price Index, as published by the Department @ http://www.dot.il.gov/desenv/asphaltpi.html for the month the work is performed, \$/ton.

BPI_L = Bituminous Price Index, as published by the Department @

http://www.dot.il.gov/desenv/asphaltpi.html for the month prior to the letting, \$/ton.

%AC_v = Percent of virgin Asphalt Cement in the Quantity being adjusted. For HMA mixtures, the % AC_v will be determined from the adjusted job mix formula. For bituminous materials

applied, a performance graded or cutback asphalt will be considered to be 100% AC_v and undiluted emulsified asphalt will be considered to be 65% AC_v .

Q = Authorized construction Quantity, tons (see below).

For HMA mixtures measured in square yards: Q, tons = A x D x (G_{mb} x 46.8) / 2000. When computing adjustments for full-depth HMA pavement, separate calculations will be made for the base, leveling and surface courses to account for their different G_{mb} and % AC_{v} .

For bituminous materials measured in gallons: Q, tons = V x 8.33 lb/gal x SG / 2000

Where: A = Area of the HMA mixture, sq yd.

D = Depth of the HMA mixture, in.

 G_{mb} = Average bulk specific gravity of the mixture, from the approved mix design.

V = Volume of the bituminous material, gal.

SG = Specific Gravity of bituminous material as shown on the bill of lading.

Basis of Payment. Bituminous materials cost adjustments may be positive or negative but will only be made when there is a difference between the BPI_L and BPIp in excess of five percent, as calculated by:

Percent Difference = {(BPI_L - BPI_D) ÷ BPI_L} x 100

Bituminous materials cost adjustments will be calculated for each calendar month in which applicable bituminous material is placed; and will be paid or deducted when all other contract requirements for the items of work are satisfied. The adjustments shall not apply during contract time subject to liquidated damages for completion of the entire contract.

Added 12/01/2006

Return With Bid

ILLINOIS DEPARTMENT OF TRANSPORTATION

OPTION FOR BITUMINOUS MATERIALS COST ADJUSTMENTS

The bidder shall submit this completed form with his/her bid. Failure to submit the form, or failure to fill out the form completely, shall make this contract exempt of bituminous materials cost adjustments. After award, this form, when submitted, shall become part of the contract.

| Contract No.: | |
|--|------------------------------------|
| Company Name: | |
| Contractor's Option: | |
| Is your company opting to include this special | provision as part of the contract? |
| Yes 🗆 No | |
| Signature: | Date: |

Added 12/01/2006

14A CR003

SECTION III

CARMI MUNICIPAL AIRPORT

CARMI, ILLINOIS

EXTEND PARTIAL PARALLEL TAXIWAY

ILLINOIS PROJECT NO. CUL-3683 A.I.P. PROJECT NO. 3-17-0109-B7

Prepared By:



March 30, 2007

RECURRING SPECIAL PROVISIONS

The following RECURRING SPECIAL PROVISIONS indicated by an "X" are Applicable to this contract and are included by reference:

| T4 N. | | Dana Ma |
|-----------------|--|---|
| <u>item No.</u> | | Page No. |
| AR101580 | Refurbish 36" Beacon | 155 |
| AR106000 | Apron Lighting | 160 |
| AR119000 | Airport Obstruction Lighting (Not Included) | 166 |
| AR127000 | Airport Navaid Installation (Not Included) | 167 |
| AR150510 | Engineer's Field Office | 168 |
| AR150560 | Temporary Threshold | 170 |
| AR152540 | Soil Stabilization Fabric | 173 |
| AR156000 | Erosion Control | 175 |
| AR156513 | Separation Fabric | 180 |
| AR156540 | Riprap | 182 |
| AR201001 | Bituminous Base Course-Method I | 185 |
| AR201002 | Bituminous Base Course-Method II | 193 |
| AR201003 | Bituminous Base Course-Method I, Superpave | 209 |
| AR201004 | Bituminous Base Course-Method II, Superpave | 217 |
| AR201661 | Clean & Seal Bituminous Cracks | 230 |
| AR201663 | Sand Mix Crack Repair | 233 |
| AR201671 | Crack Control Fabric | 235 |
| AR302000 | Asphalt Treated Permeable Subbase | 237 |
| AR401001 | Bituminous Surface Course-Method I | 245 |
| AR401002 | Bituminous Surface Course-Method II | 253 |
| AR401002 | Bituminous Surface Course-Method I, Superpave | 269 |
| AR401002 | Bituminous Surface Course-Method II, Superpave | 277 |
| AR401640 | Bituminous Pavement Grooving | 290 |
| AR401650 | Bituminous Pavement Milling | 293 |
| AR401655 | Butt Joint Construction | 295 |
| AR401900 | Remove Bituminous Pavement | 297 |
| AR501001 | Portland Cement Concrete-Pavement Method I | 299 |
| AR501001 | Portland Cement Concrete-Pavement Method II | 316 |
| AR501001 | Portland Cement Concrete-Pavement Method III | 338 |
| AR501115 | Crack and Seat Pavement | 362 |
| AR501540 | PCC Pavement Grooving | 365 |
| AR501550 | PCC Pavement Milling | 368 |
| AR501900 | Remove PCC Pavement | 370 |
| AR501500 | Tie-down/Ground Rod | 372 |
| AR605000 | Silicone Joint Sealing Filler | 373 |
| | AR106000 AR119000 AR119000 AR127000 AR150510 AR150560 AR150560 AR152540 AR156000 AR156513 AR156540 AR201001 AR201002 AR201003 AR201004 AR201661 AR201663 AR201661 AR201663 AR201661 AR201663 AR401002 AR401002 AR401002 AR401002 AR401002 AR401650 AR401655 AR401650 AR401655 AR401900 AR501001 AR501001 AR501001 AR501115 AR501550 AR501500 | AR101580 Refurbish 36" Beacon AR106000 Apron Lighting AR119000 Airport Obstruction Lighting (Not Included) AR127000 Airport Navaid Installation (Not Included) AR150510 Engineer's Field Office AR150560 Temporary Threshold AR152540 Soil Stabilization Fabric AR156600 Erosion Control AR156513 Separation Fabric AR156540 Riprap AR201001 Bituminous Base Course-Method I AR201002 Bituminous Base Course-Method II, Superpave AR201004 Bituminous Base Course-Method II, Superpave AR201006 Clean & Seal Bituminous Cracks AR201661 Clean & Seal Bituminous Cracks AR201663 Sand Mix Crack Repair AR201671 Crack Control Fabric AR302000 Asphalt Treated Permeable Subbase AR401001 Bituminous Surface Course-Method II AR401002 Bituminous Surface Course-Method II BITUMINOUS Surface Course-Method II, Superpave AR401002 Bituminous Surface Course-Method II, Superpave AR401002 Bituminous Pavement Grooving AR401640 Bituminous Pavement Milling AR401655 Butt Joint Construction AR401900 Remove Bituminous Pavement AR501001 Portland Cement Concrete-Pavement Method II AR501001 Portland Cement Concrete-Pavement Method III AR501115 Crack and Seat Pavement AR501550 PCC Pavement Milling AR501900 Remove PCC Pavement AR501900 Remove PCC Pavement AR501900 Remove PCC Pavement AR501900 Remove PCC Pavement |

SUPPLEMENTAL SPECIFICATIONS

The following SUPPLEMENTAL SPECIFICATIONS are Applicable to this contract and are included by reference:

| Item No. | | Page No. |
|----------|--|----------|
| AR108 | Installation of Underground Cable for Airports | 134 |
| AR110 | Installation of Airport Underground Electrical Duct | 148 |
| AR125 | Installation of Airport Lighting Systems | 151 |
| AR152 | Excavation and Embankment | 25 |
| AR209 | Crushed Aggregate Base Course | 45 |
| AR602 | Bituminous Prime Coat | 58 |
| AR603 | Bituminous Tack Coat | 62 |
| AR610 | Structural Portland Cement Concrete | 72 |
| AR620 | Pavement Marking | 77 |
| AR701 | Pipe for Storm Sewers and Culverts | 105 |
| AR705 | Pipe Underdrains for Airports | 109 |
| AR752 | Concrete Culverts, Headwalls & Misc. Drainage Structures | 117 |
| AR901 | Seeding | 120 |
| AR908 | Mulching | 127 |

INDEX

| ITEM NO. | DESCRIPTION | PAGE |
|----------|---------------------------------|------|
| | Foreword | 4 |
| AR108158 | 1/C #8 5KV UG Cable in UD | 9 |
| AR109200 | Install Electrical Equipment | 14 |
| AR110502 | 2-Way Concrete Encased Duct | 13 |
| AR125410 | MITL-Stake Mounted | |
| AR125415 | MITL-Base Mounted | 30 |
| AR125443 | Taxi Guidance Sign, 3 Character | 30 |
| AR125444 | Taxi Guidance Sign, 4 Character | 30 |
| AR125901 | Remove Stake Mounted Light | 30 |
| AR125904 | Remove Taxi Guidance Sign | 30 |
| AR125964 | Relocate Taxiway Guidance Sign | 30 |
| AR125967 | Relocate REILS | |
| AR150540 | Haul Route | 42 |
| AR156510 | Silt Fence | 44 |
| AR156511 | Ditch Check | 46 |
| AR156513 | Separation Fabric | 47 |
| AR156521 | Headwall Protection | |
| AR156540 | RipRap | 52 |
| AR201610 | Bituminous Base Course | 53 |
| AR208540 | Oversize Aggregate | 55 |
| AR401610 | Bituminous Surface Course | 56 |
| | IDOT Standard 542301 | 58 |

FOREWORD

These Special Provisions, together with applicable Standard Specifications, Rules and Regulations, Contract Requirements for Airport Improvement Projects, Payroll Requirements, and Minimum Wage Rates, which are hereto attached or which by reference are herein incorporated, cover the requirements of the State of Illinois, Department of Transportation (IDOT), Division of Aeronautics (Division) for the following improvement project at the Carmi Municipal Airport, Carmi, Illinois including:

SCOPE OF WORK

This project shall consist of the completing the parallel taxiway to Runway 18-36. This taxiway will be constructed of 2" of Bituminous Surface Course, 3" of Bituminous Base Course, 6" Crushed Aggregate Base Course and 8" of Oversize Aggregate. Also included in this project are the installation of underground electric duct and cable, removal of several stake mounted medium-intensity taxiway lights, installation of medium-intensity taxiway stake and base mounted lights, taxiway guidance sign installation and associated drainage, earthwork and landscaping.

GOVERNING SPECIFICATIONS AND RULES AND REGULATIONS

The <u>Standard Specifications for Construction of Airport</u>, Illinois Department of Transportation, Division of Aeronautics, adopted January, 1985 and the <u>Supplemental Specifications and Recurring Special Provisions</u>, adopted July 1, 2004, shall govern the project, except as otherwise revised or noted in these Special Provisions. All references to IDOT Specifications refer to <u>Standard Specifications for Road and Bridge Construction</u>, Illinois Department of Transportation, adopted January 1, 2007, as revised. In the event of inconsistencies between the Standard Specifications and the Special Provisions, the Special Provisions shall govern.

DIVISION I SECTION 30 CONTROL OF WORK

<u>30-06 Construction Layout.</u> Delete this entire section and add the following:

"Construction Layout

The Contractor will be required to furnish and place all construction layout for this project."

30-08 Authority and Duties of the Resident Engineer. Revise this section as follows:

"As the direct representative of the Owner, the Resident Engineer has immediate charge of inspecting and monitoring the construction project. The Resident Engineer is authorized to inspect and/or perform tests to all or any part of the work and to the materials or manufacturer of materials to be used. The Resident Engineer is not authorized to revoke, alter, or waive any provision to the contract. The Resident Engineer is not authorized to issue instructions contrary to the Plans and Specifications. The Resident Engineer is not authorized to direct or supervise the Contractor or his Subcontractors.

The Resident Engineer is authorized to notify the Contractor or his representative of any failure of the work or materials to conform to the requirements of the contract documents and to recommend to the Engineer or Owner that nonconforming materials or work be rejected and to recommend to the Engineer or Owner suspension of any work in question until the Engineer can make a decision on its acceptability."

30-09 Duties of the Inspector. Revise this section to read as follows:

"The Resident Engineer and his staff will be authorized to inspect all work being performed and materials being incorporated into the project. Such observation may extend to all or any part of the work and to the preparation, fabrication, or manufacture of materials to be used. The Resident Engineer and his staff will not be authorized to alter or waiver the provisions of the contract nor will they be authorized to issue instructions contrary to the Plans and Specifications or to direct the Contractor's work."

<u>30-10 Inspection of the Work.</u> Revise the third paragraph to read as follows:

"Any work performed or materials incorporated without inspection by an authorized representative of the Engineer may be ordered removed and replaced by the Engineer at the Contractor's own expense."

"If upon delivery and incorporation of any materials, the Contractor has failed to provide the necessary submittals as required by Sections 30-18, 40-01, 40-03, and 40-11 of the Standard Specifications, Supplemental Specifications and Special Provisions, the pay item will not be included on the Contractor Progress Payment report until such submittals have been furnished."

SECTION 50 LEGAL RELATIONS AND RESPONSIBILITY TO PUBLIC

<u>50-10 Barricades, Warning Signs, and Hazard Markings.</u> Add the following paragraphs to this section:

"The Contractor will be responsible for placing barricades, as directed by the Resident Engineer. It will be the Contractor's responsibility to furnish and maintain the barricades, equipped with red, steady-burning, or flashing lights throughout the duration of this project. All barricades will be weighted to prevent them from blowing over. If necessary to avoid low wing aircraft, the barricades will be placed on the ground. At the close of the construction day, the Contractor will remove all barricades from the taxiways. All open trenches must be backfilled, and all equipment must be moved to the equipment parking area before the Contractor can open the taxiway."

50-12 Protection and Restoration of Property. Add the following paragraphs to this section:

"The Contractor shall take special precautions during construction so as not to damage the existing roads, parking lots, runways, aprons, taxiways, buildings, and other existing improvements. Any such existing improvements damaged by the Contractor during construction shall be repaired or replaced by him at his own expense.

The Contractor shall take special care when working in the vicinity of existing airport lighting systems so as not to damage them. Should the Contractor damage any of the lighting systems, he shall immediately repair or replace them and make any necessary repairs to place them in working order. The cost of equipment and making the repairs will be the responsibility of the Contractor. If during the course of construction it is necessary to interrupt any light circuits, temporary cables shall be installed, as needed, to make the circuit operational.

Active areas shall be kept broom clean at all times. The Contractor shall maintain the premises in reasonably clean condition and shall not allow any sizable accumulation of rubbish on the premises. He shall leave the premises in broom clean condition upon completion of the project. The Contractor shall take every precaution against fire."

SCHEDULING OF OPERATIONS

The Contractor will be required to submit a project work schedule to the State of Illinois, Division of Aeronautics, and to the Resident Engineer showing proposed sequences of work.

In the event that other construction projects are in progress at the Airport at the same time as this project, the Contractor will be required to cooperate with all other Contractors and the Airport Manager in the coordination of the work.

PROPOSED HAUL ROUTE

The Contractor will be allowed to use an existing gate located in the south perimeter fencing as his access to the construction site. The Contractor will construct his haul route through the existing gate. This haul route will be the only access the Contractor uses for access to the proposed construction site.

EMPLOYEE PARKING

The Contractors' employees will park their personal vehicles in the proposed equipment parking and material storage area. The proposed employee parking area is shown on the construction plans. No employee vehicles will be allowed onto the proposed construction site.

EQUIPMENT PARKING AND MATERIAL STORAGE

The Contractor will be allowed to park his equipment and store his material in the designated equipment parking and material storage area as shown on the Construction Plans.

AIRPORT SECURITY NOTES

Airport security will be maintained at all times. The Contractor will access the proposed job site through the existing gate. This gate will be closed during the construction day unless the Contractor is in a continuous hauling operation. At the end of the construction day the Contractor will close and lock this gate.

STAGING/COORDINATION NOTES

All runway closures will be coordinated with the airport manager. The Contractor will coordinate all closures at least 24 hours in advance of the closure. This will allow the airport personnel to contact the control tower and issue required NOTAMs. The day of the closure, the Contractor will not close the runway until the airport personnel have been contacted and they verify everything has been completed and the runway can be closed.

The Contractor will close a taxiway by placing barricades across the taxiway at a spacing of 8 ft. The barricades will be weighted to insure they will not be blown over. If necessary, the barricades will be placed on the ground to insure a low wing aircraft will not strike them. All barricades will be placed at least 85 ft from the crossing taxiway centerline.

All taxiway closures will be coordinated with the airport personnel.

SITE INSPECTION

The Contractor shall be responsible for an on-site inspection prior to submitting a bid on this project. <u>Upon receipt of a bid, it shall be assumed that the Contractor is fully familiar with the construction site.</u>

INSTALLATION OF UNDERGROUND CABLE FOR AIRPORTS

DESCRIPTION

<u>108-1.1</u>. Add the following to this section:

"This item of work shall consist of the installation (plowing, trenching, or directional boring) of cable for lighting circuits on the runways and taxiways and the associated homeruns at the locations shown on the Plans and in accordance with these Specifications. This item shall include cable-in-unit duct where noted on the Plans and specified herein."

MATERIAL

108-2.1 GENERAL. Add the following.

"All cable shall be UL-listed as suitable for installed application."

108-2.2 CABLE. Revise this section to read as follows:

"L-824 Cable – L-824 cable shall be FAA L-824, Type C and shall conform to the requirements of FAA Advisory Circular 150/5345-7E, (or latest edition) "SPECIFICATIONS FOR L-824 UNDERGROUND ELECTRICAL CABLE FOR AIRPORT LIGHTING CIRCUITS". Circuits for use with constant current regulator outputs (runway or taxiway lighting circuits) shall use 5000-Volt rated cable. Circuits for voltage applications of 600-Volts or less shall use 600-Volt or 5000-Volt rated cable.

<u>XLP-USE Wire</u> – Cable shall comply with UL Standard 44, UL Standard 854, and Federal Specification A-A-59544. Conductor shall be concentric, strand soft copper, conforming to ASTM B8 and Underwriters' Laboratories Standard UL44 for Rubber Insulated Wires. Insulation shall be rated for 600-Volts. Insulation shall be cross-linked polyethylene conforming to Underwriter's Laboratories Requirements for Type USE-2 insulation. Cable shall be UL-listed and marked USE-2. Cable shall be Service Wire Company Type USE-2, or approved equal.

Item AR108158, 1/C #8 5KV UG Cable in UD shall be one conductor No. 8, 5000-Volt, FAA L-824, Type C, stranded, in unit duct (3/4 in.).

Cable used from the respective splice location to the disconnect/safety switch for the relocated REIL units shall consist of 2-1/C #8 AWG, XLP-USE, 600-Volt cable in unit duct or Schedule 40 PVC conduit (1 in. or sized larger, as required per NEC). Cable insulation shall be color coded black for the 120 VAC phase conductor and white for

the neutral conductor. This cable will be considered an incidental item to the relocation of the REIL units and no additional compensation will be allowed. The routing of the proposed power cable shall be as shown on the Construction Plans.

Cable used from the respective safety switch/disconnect to the REIL Master Unit shall be 3-1/C #8 AWG XLP-USE, 600-Volt cable in unit duct or Schedule 40 PVC conduit. Cable between the REIL Master Unit and the REIL Slave unit shall be 3-1/C #8 AWG XLP-USE, 600-Volt cable with control cable in 2" Schedule 40 PVC conduit. Power Cable insulation shall be color coded black for the 120 VAC phase conductor, white for the neutral conductor, and green for the equipment ground wire. Control cable shall conform the REIL manufacturer's recommendations and instructions and shall be suitable for the respective installation. This cable will be considered an incidental item to the relocation of the REIL units and no additional compensation will be allowed.

<u>108-2.4 CABLE CONNECTIONS</u>. Add the following to this section:

"All below grade splices shall be installed in splice cans, handholes, or manholes. Splice cans shall be L-867, Class I, Size B (12 in. diameter), 24 in. deep, with 3/4 in. thick galvanized steel cover and stainless steel bolts. Larger size splice cans shall be provided, as applicable, for specific equipment applications or manufacturer's recommendations and/or where detailed on the Plans. Splice cans located in areas subject to heavy aircraft or vehicle loading shall be L-868 type. The Engineer shall approve all splice locations before work commences. The furnishing and installing of splice cans for new homerun cables shall be incidental to the respective cable pay item, and no additional compensation will be allowed."

<u>108-2.6 UNIT DUCT</u>. Standard sizes of smooth wall polyethylene duct shall conform to the dimensional requirements specified below:

| | Nominal | Nominal | Nominal |
|------------------|-----------|-----------|-----------|
| Nominal | Inside | Standard | Outside |
| Duct Size | Diameter | Wall | Diameter* |
| 3⁄4 in. | 0.910 in. | 0.070 in. | 1.050 in. |
| 1 in. | 1.145 in. | 0.085 in. | 1.315 in. |
| 1-1/4 in. | 1.440 in. | 0.110 in. | 1.660 in. |
| 1-1/2 in. | 1.650 in. | 0.125 in. | 1.900 in. |
| 1-1/2 in. | 2.065 in. | 0.155 in. | 2.375 in. |
| 2-1/2 in. | 2.449 in. | 0.213 in. | 2.875 in. |
| 3 in. | 3.048 in. | 0.226 in. | 3.500 in. |
| 4 in. | 4.000 in. | 0.250 in. | 4.500 in. |

^{*}Dimensions include allowance for duct eccentricity.

108-2.9 LINE MARKING TAPE. Delete this section.

CONSTRUCTION METHODS

<u>108-3.1 GENERAL</u>. Add the following to this section:

"At base-mounted lights, the unit duct will be inserted at least 3 in. inside each of the lights' two 6-in. conduit extensions, and then the end of the conduit will be sealed using a heat-shrink connection.

Only cable-in-unit duct may be plowed or directional bored.

The Contractor will identify all existing underground utilities located within the area where the proposed cables are being installed and will take all precautions to protect these utilities from damage. Any underground utility damaged will be repaired or replaced at the Contractor's own expense."

<u>108-3.2 INSTALLATION IN DUCT OR CONDUIT</u>. Add the following to this section:

"The unit duct will be run continuous through all ducts and conduits."

<u>108-3.3 TRENCHING.</u> Add the following to this section:

"(c) Cable installed in cultivated fields shall be installed a minimum of 42-in. below grade."

<u>108-3.4 INSTALLATION IN TRENCHES</u>. Add the following:

"Any and all trenches will be backfilled to a smooth grade to the satisfaction of the Resident Engineer. Areas disturbed during the installation of the proposed cable, which are not completed before the contract seeding operations, will be fertilized and seeded. The fertilizing and seeding will be completed in accordance with Items 901 and 908, but will be incidental to this pay item."

108-3.8 SPLICING. Add the following:

"In-line connections for existing cables cut during construction shall be repaired with the cast splice kit. The Contractor shall have a minimum of two splice kits on the job site at all times for emergency repairs. Cast splice kits shall be specified in paragraph (a) of Item 108-2.4. Splice cans shall be provided for existing cables cut and repaired for each splice in cables not to be abandoned. Where a splice can is not readily available at the time of the cable damage, splice markers shall be temporarily installed over each splice in cables not to be abandoned, then these splices shall later be replaced with new splices in an L-867 splice can.

There shall be no splices between series lighting circuit isolation transformers. In the event that a series lighting circuit cable is cut between isolation transformers, the entire length of cable between these isolation transformers shall be replaced."

108-3.9 BARE COUNTERPOISE WIRE INSTALLATION AND GROUNDING FOR LIGHTNING PROTECTION. Revise this section to read as follows:

"Bare copper, counterpoise wire will not be required on this project under Item 108."

108-3.12 LOCATING OF EXISTING CABLES. Add the following:

"The location, size, and type of material of existing underground utilities indicated on the Plans are not represented as being accurate, sufficient, or complete. Neither the Owner nor the Engineer assumes any responsibility whatever in respect to the accuracy, completeness, or sufficiency of the information. There is no guarantee, either expressed or implied, that the locations, size, and type of material of existing underground utilities indicated are representative of those to be encountered in the construction. It shall be the Contractor's responsibility to determine the actual location of all such facilities, including service connections to underground utilities. Prior to construction, the Contractor shall notify the utility companies of his operational plans and shall obtain from the respective utility companies detailed information and assistance relative to the location of their facilities and the working schedule of the companies for removal or adjustment, where required. In the event an unexpected utility interference is encountered during construction, the Contractor shall immediately notify the utility company of jurisdiction. The Engineer shall also be immediately notified. Any such mains and services shall be restored to service at once and paid for by the Contractor at no additional cost to the Contract.

It should be noted that all FAA control and communications cables shall be located by the FAA. All utility cables and lines shall be located by the respective utility. Contact the Joint Utility Location Information for Excavation (JULIE) for utility information, phone: 1-800-892-0123. Also contact the Airport Manager and/or respective airport personnel for assistance in locating underground airport cables and/or utilities.

Payment for locating and marking underground utilities and cables will not be paid for separately, but shall be considered incidental to the plowing/trenching/boring of unit duct."

108-3.14 SEPARATION OF HIGH-VOLTAGE AND LOW-VOLTAGE WIRING.

Low-voltage wiring shall maintain separation from high-voltage wiring. Low-voltage wiring and high-voltage wiring shall not be installed in the same raceway, handhole, or junction box.

BASIS OF PAYMENT

Illinois Project CUL-3683 AIP Project 3-17-0109-B7

<u>108-5.1</u>. Payment will be made at the contract unit price per lin. ft of cable completed and accepted by the Engineer. This price shall be full compensation for furnishing all materials and for all preparation, assembly, and installation of these materials; for all plowing, trenching, directional boring, coring of manholes, and for all excavation and backfilling; and for all labor, equipment, tools, and incidentals necessary to complete this item.

Payment will be made under:

Item AR108158 1/C #8 5KV UG Cable in UD - per lin. ft

ITEM AR109200 INSTALL ELECTRICAL EQUIPMENT

DESCRIPTION

109-1.1. Revise this section to read as follows:

"This item shall consist of furnishing and installing all electrical equipment in the vault to perform the vault modifications, as detailed on the Plans and specified herein. This item shall include all labor, materials, transportation, equipment, wiring, raceways, grounding, tools, utility coordination, relocations, operational instructions, labeling, testing, and all incidentals required to place the vault and associated equipment into proper working order as a completed unit to the satisfaction of the Owner and Engineer.

Included under this Item shall be the following:

- (a) Furnishing and installing all electrical equipment and support hardware in the vault, as detailed on the Plans and specified herein.
- (b) Furnishing and installing all raceways, conduits, and ducts in and adjacent to the vault.
- (c) Furnishing and installing all necessary cable and wiring within or at the vault, as detailed on the Plans and specified herein.
- (d) Furnishing and installing all grounding as detailed on the Plans and specified herein.
- (e) Field verification of existing power and control system wiring and furnishing and installing the necessary power and control circuit wiring and modifications to accommodate the new Taxiway constant current regulator. The new Taxiway constant current regulator shall operate the same as the existing Taxiway constant current regulator.
- (f) Testing, adjusting, and retesting (where applicable) all new equipment and modifications to existing systems for proper operation.
- (g) Labeling all electrical equipment and incidentals necessary to place all of the equipment in operation as a complete unit acceptable to the Owner and Engineer.
- (h) Furnishing operation, maintenance, and installation manuals for all new equipment.

EQUIPMENT AND MATERIALS

109-2.1 GENERAL. Add the following to this section:

"(c) FAA approval of airport lighting equipment and subsequent inclusion in Advisory Circular 150/5345-1 "Approved Airport Equipment", and/or Advisory Circular 150/5345-53 "Airport Lighting Equipment Certification Program" only

means that the test data satisfied the applicable Specification requirements. This does not insure that the approved equipment will satisfactorily operate when connected power-wise and/or control-wise to other approved airport lighting equipment or "off the shelf" equipment not requiring FAA approval.

- (d) The Contractor shall ascertain that all lighting system components furnished by him (including FAA-approved equipment) are compatible in all respects with each other and the remainder of the new system. Any non-compatible components furnished by the Contractor shall be replaced by him, at no additional cost to the Airport sponsor with a similar unit, approved by the Engineer (different model or different manufacturer) that is compatible with the remainder of the airport lighting system.
- (e) Except as specified otherwise, all new equipment shall be provided by the Contractor and shall be tested for Specification conformance as part of the Aviation Lighting Equipment Certification Program. Certification of conformance, as tested by the testing laboratory, shall be provided by the manufacturer for all items submitted for approval."

<u>109-2.4 BRICK</u>. Delete this section.

109-2.5 ASBESTOS CEMENT DUCT. Delete this section.

109-2.6 FIBER CONDUIT. Delete this section.

109-2.7 RIGID STEEL CONDUIT. Add the following:

"Galvanized, rigid steel conduit (GRSC) shall be heavy wall, hot-dipped, galvanized steel pipe bearing the UL label and conforming to UL-6 and ANSI Specification C80.1. Couplings, connectors, and fittings for rigid steel conduit shall be threaded galvanized steel or galvanized malleable iron specifically designed and manufactured for the purpose. Fittings shall conform to ANSI C80.4."

109-2.8 LIGHTING. Delete this section.

109-2.11 FLOOR DRAINS. Delete this section.

109-2.13 HIGH-VOLTAGE BUS. Delete this section.

109-2.14 BUS CONNECTORS. Delete this section.

109-2.15 BUS SUPPORTS. Delete this section.

109-2.16 GROUND BUS. Revise to read as follows:

"Vault ground bus shall be shall be ¼ in. thick by 2 in. wide by 20 in. overall length copper bus bar, as manufactured by Harger Lightning Protection Inc., 301 Ziegler Drive, Grayslake, IL 60030, Phone: 1-800-842-7437 or 847-548-8700, or approved

equivalent. Ground bus shall be UL-listed. Ground bus shall include standoff insulators, splices, bonding jumpers, mounting hardware, etc. as required for the respective application. Include an engraved phenolic or plastic legend plate 1/2-in. high white letters on a green background labeled "VAULT GROUND BUS". All cable connections to the ground bus shall be with two-hole, tongue, long barrel compression lugs bolted to the bus bar, as detailed on the Plans."

109-2.19 POTHEADS. Delete this section.

109-2.20 PREFABRICATED METAL HOUSING. Delete this section.

109-2.21 FAA-APPROVED EQUIPMENT. Add the following:

"Constant Current Regulator for Taxiway. Constant current regulator for Taxiway shall be a **7.5 KW**, L-828 constant current regulator, 240 VAC single-phase, 60 Hertz input, 6.6 Amps output, with 3 output brightness steps (4.8, 5.5 and 6.6 Amps). Constant current regulator shall comply with FAA AC 150/5345-10 (latest issue in force) for Type L-828 regulator. Constant current regulator shall be dry-type, saturable regulator. Constant current regulator shall not have solid state controls in the series circuit and shall be designed for no radio communication interference. Constant current regulator shall be magnetic design. Solid state electronic designs are not acceptable. Constant current regulator shall include open circuit protection, over current protection, output current ammeter, elapsed time meter, output volt meter and lightning and transient protection on input and output lines. Constant current regulators shall also include a remote/local control feature with selections for "Remote, Off, 10% Brightness, 30% Brightness, and 100% Brightness". Control voltage shall be 120 VAC (external). Constant current regulators shall be as manufactured by Flight Light/Hevi-Duty, Manairco, or approved equal."

109-2.22 OTHER ELECTRICAL EQUIPMENT. Add the following:

"Contractor shall confirm quantity for all electrical equipment with the Plans and as specified herein. Proposed electrical equipment for the vault shall be as follows:

Type S-1 Series Plug Cutout. Provide one series plug cutout for the new constant current regulator. Series plug cutout shall be Type S-1, rated 5KV, 20 Amp, and shall comply with FAA AC 150/5340-4C. Series plug cutouts shall be Crouse-Hinds Type S-1, #30775, or an approved equal. Note this is not an FAA-approved device included on the AC150/5345-53C, Appendix 3, Addendum listing. Note Crouse-Hinds Type S-1, Model 3, Catalog Number 30771 series plug cutouts are not acceptable because the handle is not removable. Note Siemens SCO series plug cutouts are not acceptable because they do not function the same as the Crouse-Hinds, Type S-1, Model 2, Catalog Number 30775 series plug cutout and do not match the existing cutouts located in the vault. Install each series plug cutout in a NEMA 1 or NEMA 12 enclosure sized as required to house the cutout, with a hinged cover and back panel to mount the cutout.

Circuit Breakers. Branch circuit breakers to be installed in the existing Cutler Hammer Type CC, Cat. No. CC2150, Issue No. KS602, 150 Amp, 120/240 VAC, 1-phase, 3-wire panelboard shall be compatible with the existing panelboard. Circuit breakers shall have an amp interrupting capacity of 10,000 Amps minimum at 240 VAC. Circuit breaker amperage trip settings and number of poles shall be as detailed on the Plans. Circuit breakers for new constant current regulators shall be sized, as detailed on the Plans, in accordance with the respective constant current regulator manufacturer's recommendations and per the requirements of National Electrical Code (NEC). Contractor shall adjust circuit breaker sizes for constant current regulators to conform to the manufacturer's requirements/recommendations and NEC, where applicable.

Junction and Pull Boxes. Junction and pull boxes shall be sized, as required for conductors and splices and per 2005 NEC Article 314. Boxes shall be UL-listed. Special boxes made to suit conditions shall be used to accommodate the respective application or where required by NEC, even though they might not be indicated on the Drawings. Surface-mounted, exterior junction and pull boxes located in non-hazardous, non-classified areas, shall be NEMA 4X stainless steel or aluminum, Crouse-Hinds, Killark, Hoffman, Hennessy, or equal. All junction and pull boxes installed in classified hazardous areas (Class 1, Division 1 or 2, Group D) shall be NEMA 7 and NEMA 4 and shall comply with applicable provisions of the NEC, including, but not limited to, Articles 500 and 501.

Schedule 40 PVC Conduit. Schedule 40 PVC conduit shall comply with Item 110 and the following: Conduit shall be Schedule 40 PVC, 90°C, UL-rated, or approved equal. Material shall comply with NEMA Specification TC-2 (Conduit), (Fittings UL-514), and UL-651 (Standard for rigid, non-metallic conduit). The conduit and fittings shall carry a UL label (on each 10 ft length of conduit and stamped or molded on every fitting). Conduit and fittings shall be identified for type and manufacturer and shall be traceable to location of plant and date manufactured. The markings shall be legible and permanent. The conduit shall be made from polyvinyl chloride C-300 compound that includes inert modifiers to improve weather ability, heat distortion. Clean, reworked material, generated by the manufacturer's own conduit production, may be used by the same manufacturer, provided the end products meet the requirements of this Specification. The conduit and fittings shall be homogenous plastic material free from visible cracks, holes, or foreign inclusions. The conduit bore shall be smooth and free of blisters, nicks, or other imperfections, which could mar conductors or cables. Conduit fittings and cement shall be produced by the same manufacturer to assure system integrity and shall be Carlon Plus 40 conduit or equal.

<u>Liquid-Tight, Flexible Metal Conduit.</u> Liquid-tight, flexible metal conduit shall consist of polyvinyl jacket over flexible, hot-dip, galvanized steel tubing. The flexible conduit shall be completely sealed from liquids, dust, dirt, and fumes and be resistant to oil, gasoline, grease, and abrasion. Jacket shall also be sunlight-resistant. Liquid-tight, flexible metal conduit shall be UL-listed, suitable for use as a grounding conductor, and

comply with Article 350 of the NEC. Liquid-tight, flexible metal conduit and associated fittings shall be UL-listed to meet the requirements of NEC 350.6. Liquid-tight, flexible metal conduit shall be Anaconda Sealtite Type UA, as manufactured by Anamet Electrical Inc., 1000 Broadway Avenue East, Mattoon, Illinois 61938-0039, (Phone: 217-234-8844), Liquatite Type LA, as manufactured by Electri-Flex Company, 222 W. Central Ave., Roselle, Illinois 60172, (Phone: 630-529-2920 or 1-800-323-6174), or approved equal.

Strut Support. Strut-type steel supports shall be provided to support all freestanding equipment enclosures and other equipment enclosures, as indicated on Plans. Supports shall be hot-dipped, galvanized steel strut, Unistrut P-1000HG, or approved equal. Steel supports shall be hot-dipped, galvanized finish, roll-formed from 12-gauge (.105 U.S.S. Gage) cold-rolled steel, galvanized material ASTM Des. A-446 Grade A. Material (cold-rolled steel) shall be hot-dipped, galvanized coating conforming to ASTM Specification A-525, Des. G-90. Zinc coating shall form an excellent bond with steel surface so as not to be affected by subsequent forming operations. Provide necessary hardware, such as floor flanges, etc., as required to install equipment. Provide materials, sizes, and types of anchors, fasteners, and supports necessary to carry the loads of equipment and conduits. Consider weights of conduit when selecting products. Fasteners and anchors shall be corrosion-resistant, stainless steel, or cadmium-plated.

<u>Legend Plates.</u> Legend plates shall be required for all constant current regulators, cutouts, panelboards, control panels, etc. Legend plates shall be provided to identify the equipment controlled, the power source, and the function of each device. Legend plates shall be weatherproof and abrasion-resistant, phenolic material. Lettering shall be black letters on a white background, unless otherwise noted."

<u>109-2.23 WIRE</u>. Delete paragraphs 1, 2, and 3 under section (b) <u>Power Circuits</u>. Add the following:

"<u>Power Cable (600V and Below)</u>. All power wiring, 600V and below, shall be the type, size, and number of conductors, as noted on the Plans.

<u>L-824 Cable.</u> L-824 cable shall be FAA-L-824, Type C cable complying with Item 108. Circuits for use with constant current regulator outputs (runway or taxiway lighting circuits) shall use 5000-Volt rated cable. Circuits for voltage applications of 600 Volts or less shall use 600-Volt or 5000-Volt rated cable.

<u>THWN Wire.</u> Cable shall comply with Underwriters' Laboratories Standard UL-83 and Federal Specification A-A-59544. Conductor shall be soft-annealed, uncoated copper and shall comply with ASTM B3 and B8. Insulation shall be rated for 600V. Insulation shall be polyvinyl-chloride conforming to Underwriters' Laboratories requirements for Type THW. The outer covering shall be nylon conforming to Underwriters' Laboratories for type THHN or THWN. Cable shall be UL-listed and

marked THWN. Power and control wiring shall be Superior Essex or Southwire Company Type THWN, or approved equal.

XLP-USE Wire. Cable shall comply with UL Standard 44, UL Standard 854, and Federal Specification A-A-59544. Conductor shall be concentric-strand, soft copper, conforming to ASTM B8 and Underwriters' Laboratories Standard UL44 for Rubber Insulated Wires. Insulation shall be rated for 600V. Insulation shall be cross-linked polyethylene conforming to Underwriter's Laboratories Requirements for Type USE-2 insulation. Cable shall be UL-listed and marked USE-2. Cable shall be Service Wire Company Type USE-2, or approved equal.

XHHW Wire. Cable shall comply with UL Standard 44, ICEA S-95-658/NEMA WC70 and Federal Specification A-A-59544. Conductors shall be Class B, stranded-annealed, uncoated copper per UL Standard 44. Insulation shall be rated for 600V. Insulation shall be cross-linked polyethylene complying with the physical and electrical requirements of UL Standard 44 for Type XHHW-2. Cable shall be UL-listed and marked XHHW-2. Service conductors shall be Service Wire Company or Southwire Company, Type XHHW-2, or approved equal.

Grounding electrode conductors and/or bonding jumpers shall be the size and type, as detailed on the Plans. Ground wire for bonding constant current regulator housings, cutout enclosures, and other vault equipment frames to the vault ground bus shall be #6 AWG (minimum), stranded copper bare or with green-colored insulation."

CONSTRUCTION METHODS

109-3.10 GENERAL. Add the following to this section:

"The Contractor shall furnish and install all materials necessary for complete and operational installation of the vault equipment, as specified herein and as shown on the Plans. The complete installation and wiring shall be done in a neat, workmanlike manner. All electrical work shall comply with the requirements of the NEC (most current issue in force) and all other applicable local codes, laws, ordinances, and requirements in force. Electrical equipment shall be installed in conformance with the respective manufacturer's directions and recommendations for the respective application. Any installations which void the UL listing, ETL listing (or other third party listing), and/or the manufacturer's warranty of a device will not be permitted.

Contractor shall keep a copy of the latest NEC in force on site at all times during construction for use as a reference.

Contractor shall coordinate work and any power outages with the Airport Manager and the Resident Engineer. Any shutdown of existing systems shall be scheduled with and approved by the Airport Manager, prior to shutdown.

All electrical equipment installed by the Contractor shall be properly labeled, and all cables must be tagged.

All changes to the vault wiring will be documented by the Contractor and provided to the Resident Engineer.

Locate Existing Underground Utilities and Cables. The location, size, and type of material of existing underground utilities indicated on the Plans are not represented as being accurate, sufficient, or complete. It shall be the Contractor's responsibility to determine the actual location of all such facilities, including service connections to underground utilities. Prior to construction, the Contractor shall notify the utility companies of his operational Plans, and shall obtain from the respective utility companies detailed information and assistance relative to the location of their facilities and the working schedule of the companies for removal or adjustment, where required. In the event an unexpected utility interference is encountered during construction, the Contractor shall immediately notify the utility company of jurisdiction. The Engineer shall also be immediately notified. Any such mains and services shall be restored to service at once and paid for by the Contractor at no additional cost to the Contract. It should be noted that all FAA control and communications cables shall be located by the FAA. All utility cables and lines shall be located by the respective utility. Contact JULIE for utility information, phone: 1-800-892-0123. Also contact the Airport Manager and/or respective airport personnel for assistance in locating underground airport cables and/or utilities."

<u>109-3.11 POWER SUPPLY EQUIPMENT</u>. Add the following to this section:

"Constant Current Regulators. Install constant current regulators in conformance with the manufacturer's recommendations, as detailed on the Plans and as specified herein. Confirm circuit breaker sizes for constant current regulators are sized in conformance with the respective manufacturer's recommendations and/or requirements and NEC. Where necessary to accommodate the respective constant current regulator input amperage requirements, circuit breakers, conductors, and conduits shall be adjusted to meet the manufacturer's recommendations and/or requirements and NEC. Conduit and wire sizes shown on the Plans are minimum sizes. Conduit connections to constant current regulators shall be with UL-listed, liquid-tight, flexible metal conduit. Furnish and install control wiring, as detailed on the Plans. Bond each constant current regulator enclosure frame to the vault ground bus with a #6 AWG (minimum), bare-stranded, copper bonding jumper."

<u>109-3.12 SWITCHGEAR AND PANELS</u>. Add the following to this section:

"Installation of S-1 Type Cutouts. Install plug cutouts in conformance with the manufacturer's recommendations, as detailed on the Plans and as specified herein. Provide NEMA 1 or NEMA 12 painted steel enclosures, adequately sized for the cutout and cables, with hinged cover and back panel to mount each plug cutout.

<u>Installation of Circuit Breakers in Panelboards.</u> Install circuit breakers in panelboards in conformance with the respective manufacturer's directions. Connect only one wire/cable to each breaker terminal. Update circuit directory to identify the respective device fed by each new circuit breaker."

<u>109-3.13 DUCT AND CONDUIT</u>. Add the following to this section:

- "(a) Conduit shall be installed in accordance with the following:
 - 1. All service, feeder, branch circuit, and control circuit conduits shall be galvanized, rigid steel.
 - 2. Schedule 40 PVC conduits shall be used for individual grounding electrode conductors and/or bonding jumpers.
 - 3. Liquid-tight, flexible metal conduit shall be used, as specified herein.

(b) Conduit Runs

- 1. All conduits shall be sized, as indicated on the Drawings, or if conduit sizes not shown, shall be in accordance with the NEC. All conduit systems shall be mechanically and electrically continuous from source of current to all outlets and grounded in accordance with the NEC.
- 2. Run all exposed conduit parallel to building walls using right angle bends. Exposed diagonal runs of conduit will not be permitted. Do not install conduit on roof surfaces unless specifically indicated on the Drawings.
- 3. Ream conduit after threads are cut. Cut ends square, and butt solidly into couplings.
- 4. Prevent the accumulation of water, foreign matter, or concrete in the conduits during the execution of the work. Temporarily plug conduit, blowout, and swab before wires are pulled.
- 5. Fasten conduits to all sheet metal boxes and cabinets with two locknuts in accordance with NEC, where insulated bushings are used and where bushings cannot be brought into firm contact with the metal enclosures; otherwise, use at least a single locknut and bushing.
- 6. Provide conduit expansion joints at building expansion joints for conduit runs 1½ in. and larger. Provide conduit expansion joints or flexible conduit connection at building expansion joints for conduits less than 1½ in.
- 7. Seal each underground joint and make water-tight.
- 8. Where building construction or other conditions make it impossible to use standard threaded couplings, install water-tight threaded unions.
- 9. Make changes in direction of runs with symmetrical bends or cast-metal fittings. Make field-made bends and offsets with conduit bending machine to avoid changing the internal diameter of the conduit and not damage its protective coating either inside or outside. Individual bends shall not exceed 90 degrees and not more than 270 degrees total bends

- will be allowed in any one conduit run. Where more bends are necessary, and conduit runs exceed 150 lin. ft, install a suitable pull box or junction box.
- 10. Provide empty conduits installed with a pull wire. Pull wire shall be No. 14 AWG, zinc-coated steel, or of plastic having not less than 200 pound tensile strength. Leave not less than 12 in. of slack at each end of the pull wire.
- 11. Use liquid-tight, flexible metal conduit for final connection to motors, constant current regulators, transformers, portable equipment, and for equipment subject to vibration and noise transmission. conduit, sizes up to 1-in. trade size, flexible conduit shall be minimum length of 12 in., and a maximum length of 36 in. and for conduit sizes above 1-in. trade size, flexible conduit shall be minimum length of 20 in. and maximum length of 48 in. Liquid-tight, flexible metal conduit shall be UL-listed and suitable for grounding.

(c) Raceway Support and Hangers:

1. Securely fasten raceways in place and support from ceiling or walls at spacing not exceeding:

| | <u>Material</u> <u>Ma</u> | ximum Spacing o | of Supports |
|----|-------------------------------|-----------------|-------------|
| a. | ½ in. thru 1 in. trade size | conduit | 6 ft |
| b. | 1¼ in. thru 1½ in. trade si | ze conduit | 8 ft |
| c. | 2 in. to 4 in. trade size cor | nduit | 10 ft |
| d. | Liquid-tight, flexible meta | al conduit | 4½ ft |
| e. | Metal wireway | | 10 ft |

- 2. Support rigid conduits within 3 ft of every outlet box, junction box, pull box, cabinet, or termination. Support flexible conduit within 12 in. on each side of every outlet box or fitting.
- 3. Support conduits by pipe straps, wall brackets, hangers, or ceiling trapeze. The use of perforated iron or wire for supporting conduits is prohibited. Fasten with wood screws or screw nails to wood; by toggle bolts on hollow masonry units, by concrete inserts, or expansion bolts on concrete or spring-tension or threaded C-clamps for rigid steel conduits on steel. Do not weld conduits or pipe straps to steel structures, unless specifically indicated.
- The load applied to fasteners shall not exceed one-third the proof test 4. load of the fasteners.
- 5. Fasteners attached to concrete shall be vibration-resistant and shockresistant.
- Where two or more conduits 1-in, trade size or larger run parallel, 6. trapeze hangers may be used consisting of threaded solid rods, washers, nuts, and galvanized "L" angle or channel iron. Individually fasten

conduits to the cross member of every other trapeze hanger with one hole straps or clamp backs with proper size bolts, washers, and nuts. When adjustable trapeze hangers are used, use U-bolt type clamps at end of conduit runs, at each elbow, and at each third intermediate hanger to fasten each conduit.

- 7. Make hangers of durable materials suitable for the application involved. Applied loads shall not exceed one-third of their loading capacity.
- 8. All screws, bolts, washers, and miscellaneous hardware used for conduit supports shall be fabricated from rust-resisting metal. Trapeze hangers shall have hanger assemblies protected with galvanized finish."

<u>109-3.15 WIRING AND CONNECTIONS.</u> Add the following to this section.

"Low-voltage wiring shall maintain separation from high-voltage wiring. Low-voltage and high-voltage wiring shall not be installed in the same raceway. Low-voltage and high-voltage wiring shall not be installed in the same handhole or junction box."

<u>109-3.16 MARKING AND LABELING</u>. Add the following to this section:

- "(c) Legend plates shall be provided for all equipment. Legend plates shall be provided to identify the equipment controlled, the power source, and the function of each device. Legend plates shall be weatherproof and abrasion-resistant, phenolic/plastic-engraved material and fastened with contact-type, permanent adhesive, screws, or rivets. Installation shall not break, crack, or deform the legend plate. Lettering shall be ¼ in. high, black on a white background, unless noted otherwise.
- (d) Each panelboard shall be furnished with a phenolic-engraved legend plate that identifies the panel designation, the power source, and the respective voltage, phase, and wire.
- (e) Each constant current regulator shall be furnished with a phenolic-engraved legend plate that identifies the regulator number designation and/or the runway or taxiway served.
- (f) Each plug cutout cabinet shall be furnished with a phenolic-engraved legend plate that identifies the respective runway or taxiway circuit or constant current regulator.
- (g) Each individual circuit breaker, control panel, terminal panel, safety switch, etc. shall be furnished with a phenolic-engraved legend plate that identifies the respective device, the power source, and the respective voltage, phase, and wire. Furnish additional phenolic-engraved legend plates, as detailed on the Plans and/or where required by code.
- (h) At electrical handholes, identify each cable originating in the vault with respect to the system or device served.
- (i) Color-code phase and neutral conductor insulation for No. 6 AWG or smaller. Provide colored marking tape for phase and neutral conductors for No. 4 AWG and larger. Insulated ground conductors shall have green-colored insulation for

all conductor AWG and/or KCMIL. Standard colors for power wiring and branch circuits shall be as follows:

| 120/240 VAC, 1 | PHASE, 3 Wire |
|----------------|---------------|
| Phase A | Black |
| Phase B | Red |
| Neutral | White |
| Ground | Green" |

<u>109-3.18 TESTING</u>. The installation shall be tested in operation and as a completed unit prior to acceptance. Contractor shall furnish all equipment, meters, instruments, cable connections, tools, manpower, and labor to perform the respective tests. Test all new equipment and all existing equipment where modifications take place and confirm proper operation. Coordinate tests with the respective airport personnel and the Engineer. Tests shall include resistance, voltage, and current reading, as applicable, for the respective equipment. When tests disclose any unsatisfactory workmanship, or equipment furnished under this Contract, correct defects and retest. Repeat tests until satisfactory results are obtained. When any wiring or equipment is damaged by tests, the wiring or equipment shall be repaired or replaced at no additional cost to the Contract. Test repaired or replaced items to ensure satisfactory operation. Submit three copies of all test reports to the Engineer. All test reports shall be assembled and bound in a folder or binder. Each test report shall include the following information:

- Project number,
- Project title and location,
- Device or system tested,
- Test performed,
- Date performed,
- Test equipment used,
- Respective Contractor's name, address, and telephone number,
- Testing firm's name, address, and telephone number, if other than the Contractor,
- Names of individuals performing tests,
- Names of individuals observing tests,
- Statement verifying each test,
- Nameplate data from respective equipment tested,
- Test results, and
- Retest results after correction of defective components or systems, where applicable.

109-3.19 GROUNDING REQUIREMENTS. Grounding shall conform to the following, as applicable: The Contractor shall furnish and install all grounding shown on the Plans and/or as may be necessary or required to make a complete grounding system, as required by the latest NEC (NFPA 70) in force. The reliability of the grounding system is dependent on careful, proper installation and choice of materials. Improper preparation of surfaces to be joined to make an electrical path, loose joints, or corrosion can introduce impedance that will seriously impair the ability of the ground path to protect personnel and equipment and to absorb

transients that can cause noise in communications circuits. The following functions are particularly important to ensure a reliable ground system:

- (a) All products associated with the grounding system shall be UL-listed and labeled.
- (b) All bolted or mechanical connections shall be coated with a corrosion-preventative compound before joining, Sanchem Inc. "NO-OX-ID "A-Special" compound or equal.
- (c) Metallic surfaces to be joined shall be prepared by the removal of all non-conductive material, per 2005 National Electrical Code, Article 250-12. All copper bus bars must be cleaned prior to making connections to remove surface oxidation.
- (d) Metallic raceway fittings shall be made up tight to provide a permanent low impedance path for all circuits. Metal conduit terminations in enclosures shall be bonded to the enclosure with UL-listed fittings suitable for grounding. Provide grounding bushings with bonding jumpers (from bushing to the respective ground connection/enclosure frame) for all metal conduits entering service equipment (meter bases, CT cabinet, service disconnects, service panelboards, main service breaker enclosure, etc.). Provide grounding bushings with bonding jumpers for all metal conduits entering an enclosure through concentric or eccentric knockouts that are punched or otherwise formed so as to impair the electrical connection to ground. Standard locknuts or bushings shall not be the sole means for bonding where a conduit enters an enclosure through a concentric or eccentric knockout.
- Furnish and install ground rings, ground fields, and/or ground rods at all (e) locations where shown on the Plans or specified herein. Ground rods shall be 3/4-in. diameter, 10-ft long, UL-listed, copper-clad with 10-mil minimum copper coating. Top of ground rods shall be a minimum of 30 in. below finish grade, unless otherwise noted on the Plans. Ground rods shall be spaced, as detailed on the Plans, and in no case spaced less than one-rod length apart. All connections to ground rods and/or ground rings shall be made with exothermic weld-type connectors, Cadweld by Erico Products, Inc., Solon, Ohio, (Phone 1-800-248-9353), Thermoweld by Continental Industries, Inc., Tulsa, Oklahoma (Phone 918-663-1440) or Ultraweld by Harger Lightning Protection Grounding Equipment, Grayslake, Illinois (Phone 1-800-842-7437). Exothermic-weld connections shall be installed in conformance with the respective manufacturer's directions using molds, as required for each respective application. Bolted connections will not be permitted at ground rods or at buried grounding electrode conductors. Grounding electrode conductors shall be bare-stranded copper sized, as detailed on the Plans. In addition to the grounding work described herein and shown on the Plans, the Contractor shall test the made electrode ground field/ground ring with an instrument specifically designed for testing ground field systems. If ground resistance exceeds 10 Ohms, contact the Resident Engineer for further direction. Copies of ground field/ground ring test results shall be furnished to the Resident Engineer, upon request, for review and record purposes.

- (f) Buried or concealed ground systems shall be observed by the Resident Engineer before backfilling or covering.
- (g) All connections located above grade between the different types of grounding conductors shall be made using UL-listed, double compression, crimp-type connectors, or UL-listed, bolted, ground connectors. For ground connections to enclosures, cases, and frames of electrical equipment not supplied with ground lugs, the Contractor shall drill required holes for mounting a bolted ground connector. All bolted ground connectors shall be Burndy, Thomas and Betts, or equal. Tighten connections to comply with tightening torques in UL Standard 486A to assure permanent and effective grounding.
- (h) All metal equipment enclosures, conduits, cabinets, boxes, receptacles, etc. shall be bonded to the respective grounding system.
- (i) Each feeder circuit and/or branch circuit shall include an equipment ground wire. Metal raceway or conduit shall not meet this requirement. The equipment ground wire from equipment shall not be smaller than allowed by 2005 NEC Table 250-122 "Minimum Size Conductors or Grounding Raceway and Equipment." When conductors are adjusted in size to compensate for voltage drop, equipment-grounding conductors shall be adjusted proportionately according to circular mil area. All equipment ground wires shall be copper, either bare or insulated, green in color. Where the equipment grounding conductors are insulated, they shall be identified by the color green and shall be the same insulation type as the phase conductors.
- (j) All utility transformer bank grounds shall be installed in accordance with the serving utility company's requirements and recommendations and in accordance with NEC.
- (k) Bond the main electrical service neutral to ground at the main service disconnect. Bond the service neutral to ground at one location only per the NEC. A grounding connection shall not be made to any neutral circuit conductor on the load side of the service disconnecting means, except as permitted by 2005 NEC, 250-24.
- (I) The secondary neutral of all transformers (separately derived system transformers) shall be grounded in accordance with the NEC. The respective grounding electrode conductor shall be connected to the neutral point of the transformer between the transformer and the output disconnecting means. Size of the grounding electrode conductor shall be in accordance with 2005 NEC, Article 250-66 and Table 250-66, unless shown larger on the Drawings. A bond shall be provided between the neutral and transformer case, or other metal that is part of the AC equipment grounding system, so as to complete a circuit for fault current to the transformer winding from the AC equipment grounding system. Size of the neutral bonding conductor shall be in accordance with 2005 NEC, Article 250-102.
- (m) All exterior metal conduits, where not electrically continuous because of manholes, handholes, non-metallic junction boxes, etc., shall be bonded to all other metal conduit in the respective duct run, and at each end, with a copper-bonding jumper sized in conformance with 2005 NEC, 250-102. Where metal conduits terminate in an enclosure (such as a motor control center, switchboard,

- etc) where there is not electrical continuity with the conduit and the respective enclosure, provide a bonding jumper from the respective enclosure ground bus to the conduit sized per 2005 NEC, 250-102.
- (n) Install grounding electrode conductors and/or individual ground conductors in Schedule 40 or Schedule 80 PVC conduit. Where grounding electrode conductors or individual ground conductors are run in PVC conduit, <u>Do Not completely encircle conduit with ferrous and/or magnetic materials</u>. Use non-metallic, reinforced, fiberglass, strut support. Where metal conduit clamps are installed, use nylon bolts, nuts, washers, and spacers to interrupt a complete metallic path from encircling the conduit.
- (o) Individual ground conductors and/or grounding electrode conductors shall not be run in metallic conduit and shall not be encircled by metallic clamps. If local codes dictate that grounding conductors must be run in metal conduit or raceway, then the conduit or raceway must be bonded to the grounding conductor at both ends with a bonding jumper sized in accordance with NEC 250.64(E). All such installations requiring individual grounding conduits to be run in metal conduit or raceway shall be verified and reviewed with the Resident Engineer. This does not apply to AC equipment ground wires run with AC circuits.

METHOD OF MEASUREMENT

109-4.3. Add the following to this section:

"The quantity of vault equipment to be paid for under Item AR109200 "Install Electrical Equipment" shall consist of furnishing and installing all electrical equipment at the vault, as detailed on the Plans and specified herein. This item shall include all labor, equipment, materials, tools, operational instructions, coordination, and testing required to place the vault and associated electrical equipment into proper working order. Conduits between the vault and handholes, splice cans, conduit to unit duct adapters, etc. located near the vault shall be considered incidental to this item, and no additional compensation will be allowed. New cables from the vault that interface/splice to existing cables (for airfield equipment and/or airfield lighting) at handholes, splice cans, junction boxes, etc. shall be considered incidental to this item, and no additional compensation will be allowed."

BASIS OF PAYMENT

Payment will be made under:

Item AR109200 Install Electrical Equipment - per lump sum

ITEM AR110 2-WAY CONCRETE-ENCASED DUCT

DESCRIPTION

This item of work shall consist of the installation of all proposed ducting, as shown on the Construction Plans.

<u>110-2.1 GENERAL.</u> Duct for constructing 2-way duct (concrete-encased) shall be Schedule 40 PVC. All materials for these items shall be in accordance with the FAA Standard Specification 110 "Equipment and Materials."

110-2.7 PLASTIC CONDUIT. Add to this section:

"Conduits for concrete encasement shall be Schedule 40 PVC, UL-listed, rated for 90°C cable-conforming to NEMA Standard TC-2 and UL 651, listed suitable for concrete encasement."

CONSTRUCTION METHODS

110-3.1 GENERAL. Add to this section:

"The proposed 2-way concrete-encased duct shall be constructed at the locations and in accordance with the details shown on the Construction Plans.

Ducts installed under paved areas and roadways shall extend a minimum of 3 ft beyond the respective pavement or roadway surface. A pull wire will be left in the conduit if it is to be left vacant. The ends of the conduit will be sealed with approved plugs.

The Contractor will determine if there is a conflict between the installation of the proposed electrical duct and any existing underground utilities, cables, drains, pipes, etc. He will make all necessary adjustments in depth of installation to avoid any and all proposed underground improvements."

110-3.7 LOCATING OF EXISTING UNDERGROUND UTILITIES AND CABLES. The location, size, and type of material of existing underground utilities indicated on the Plans are not represented as being accurate, sufficient, or complete. Neither the Owner nor the Engineer assumes any responsibility whatever in respect to the accuracy, completeness, or sufficiency of the information. There is no guarantee, either expressed or implied, that the locations, size, and type of material of existing underground utilities indicated are representative of those to be encountered in the construction. It shall be the Contractor's responsibility to determine the actual location of all such facilities, including service connections to underground utilities. Prior to construction, the Contractor shall notify the utility companies of his operational plans, and shall obtain from the respective utility companies detailed information and assistance

relative to the location of their facilities and the working schedule of the companies for removal or adjustment, where required. In the event an unexpected utility interference is encountered during construction, the Contractor shall immediately notify the utility company of jurisdiction. The Engineer shall also be immediately notified. Any such mains and services shall be restored to service at once and paid for by the Contractor at no additional cost to the Contract.

The Contractor shall coordinate the location of the FAA control and communication cables with the FAA and the Airport. All utility cables and lines shall be located by the respective utility. Contact JULIE for utility information, Phone: 800-892-0123. Also, contact the Airport Manager and/or respective Airport personnel for assistance in locating underground airport cables and/or utilities.

METHOD OF MEASUREMENT

<u>110-4.1.</u> The quantity of conduit to be paid for shall be the number of lin. ft of ducts of the particular type installed and measured in-place, complete, and accepted by the Resident Engineer.

BASIS OF PAYMENT

<u>110-5.1.</u> Payment will be made at the contract unit price per each type and size of conduit, completed and accepted. This price shall be full compensation for furnishing all materials and for all preparation, assembly, and installation of these materials; for all sawing and payment removal; and for all excavation and backfilling with aggregate backfill, earth backfill, and concrete; and for all labor, equipment, tools, and incidentals necessary to complete this item.

Payment will be made under:

Item AR110502 2-Way Concrete-Encased Duct - per lin. ft

ITEM AR125 INSTALLATION OF AIRPORT LIGHTING SYSTEMS

DESCRIPTION

<u>125-1.1.</u> Revise this paragraph to read as follows:

"This item of work shall consist of furnishing and installing taxi guidance signs, relocating and removing taxiway guidance signs, installing base mounted and stake mounted taxiway lights at the locations shown on the Construction Plans and in accordance with the details shown on the Plans. This item of work shall also include the removal of stake-mounted taxiway lights. Also included in this item will be the testing of the installation and all incidentals necessary to place the lighting systems into operation, completed, and to the satisfaction of the Resident Engineer."

EQUIPMENT AND MATERIALS

<u>125-2.1 General.</u> Add the following to this section:

"(d) Non-metallic light fixtures or plastic couplings will not be acceptable under this Contract. All proposed taxiway lights shall be Type L-861-T, with 30-Watt quartz lamps. All lights shall have an overall height of 24 in. All of the above lights shall be manufactured in accordance to FAA Specification AC No. 150/5345-46B, (or latest edition).

The concrete used in the construction of these items shall be in accordance with Item 610.

(e) The proposed taxi guidance signs will conform to Advisory Circular 150/5345-44G and be FAA approved. The signs will be Size 1, 18-in. sign face with a 12-in. legend; Style 2, powered from a 4.8 to 6.6 amp series lighting circuit; Class 2, for operation down to -55°C; medium-intensity, Mode 2, to withstand wind loads of 200 M.P.H., base-mounted, double-sided, as specified on the Plans.

The two existing lighted taxi guidance signs that are to be relocated are Lumacurve signs. For this reason, all modifications to these existing signs will be Lumacurve products. Lumacurve is a brand of Standard Sign, Inc.

The signs shall read as described on the Construction Plans. The proposed taxi guidance signs will be Type L-858-Y direction, destination and boundary signs (black legend on yellow background); Type L-858-R mandatory instruction sign (black outline on outside edge of white legend on red background); and Type L-858-L location sign (yellow legend and border on black background).

The concrete used in the construction of these items shall be in accordance with Item 610."

<u>125-2.8 LIGHT CANS.</u> Add the following to this section:

"Each light can shall include an internal and external ground lug."

- <u>125-2.14</u> Anti-Seize Compound. Prior to installing the proposed taxi guidance signs, the Contractor will apply an oxide-inhibiting, anti-seizing compound to all screws, nuts, breakable coupling, and all places where metal comes into contact with metal. The anti-seize compound will be as manufactured by I.T.T. brand name "Contax", or approved equal.
- <u>125-2.15</u> Stainless Steel Bolts. All base plate-mounting bolts and stake-mounting bolts shall be stainless steel.
- <u>125-2.16 GROUND RODS.</u> Furnish and install 5/8-inch diameter by 8-foot long (minimum) UL listed copper clad ground rod at each L-867 transformer base can and stake lights.

CONSTRUCTION METHODS

125-3.1 General. Add the following to this section:

"The proposed taxi guidance signs and taxiway lights will be installed in accordance with the details shown on the Construction Plans.

The existing taxiway lights designated for removal will be removed in their entirety. The Contractor will turn the light, stake, and isolation transformer over to the airport maintenance personnel. If they do not want any part of the existing light, the Contractor will dispose of it off the airport site at his own expense. The contractor is required to backfill the holes from the light removal with earth from the construction project.

All disturbed areas around the taxi guidance signs will be smooth graded to match the surrounding area, seeded, and mulched in accordance with Items 901 "Seeding" and 908 "Mulching". Liming and fertilizing of the disturbed areas will not be required.

Obtaining the required earth material, placing the earth material, grading, seeding, and mulching the disturbed areas will be considered as an incidental item to the proposed taxi guidance signs and lights, and no additional compensation will be allowed."

125-3.5 GROUNDING FOR AIRFIELD LIGHTS AND TAXI GUIDANCE SIGNS. Grounding for Runway Lights, Taxiway Lights, and Lighted Taxi Guidance Signs shall be as

detailed on the Plans and as specified herein. Per FAA AC 150/5340-30B DESIGN AND INSTALLTION DETAILS FOR AIRPORT VISUAL AIDS, Chapter 12, Part 12.6; a safety ground must be installed at each light fixture. The purpose of the safety ground is to protect personnel from possible contact with an energized light base or mounting stake as the result of a shorted cable or isolation transformer. A safety ground shall be installed at each transformer base/light can associated with runway lights, taxiway lights, and lighted taxi guidance signs. A safety ground shall also be installed at each stake mounted light fixture. The safety ground shall be a #6 AWG bare copper conductor connected to the ground lug on the respective L-867 transformer base/light can or mounting stake and a 5/8-inch diameter by 8-foot long (minimum) UL listed copper clad ground rod. Connections to ground lugs on the L-867 transformer base/light can or mounting stake shall be with a UL listed grounding connector. Connections to ground rods shall be made with exothermic weld type connectors, Cadweld by Erico Products, Inc., Solon, Ohio, (Phone: 800-248-9353), Thermoweld by Continental Industries, Inc., Tulsa, Oklahoma (Phone: 918-663-1440) or Ultraweld by Harger, Grayslake, Illinois (Phone: 800-842-7437). Exothermic weld connections shall be installed in conformance with the respective manufacturer's directions using molds as required for each respective application. Bolted connections will not be permitted at ground rods. Top of ground rods shall be buried 24 inches minimum below grade.

125-3.6 REMOVE TAXI GUIDANCE SIGN. There are two existing single module guidance signs on Taxiway "A1" that will be removed. These signs will be removed and turned over to the Airport Manager. If the Airport Manager doesn't want them, then the Contractor will disposed of the signs off the airport site. If a proposed sign is not designated to occupy the same location as the removed sign, then the Contractor will connect the cable connector back together and bury them. The concrete sign bases will be removed and earth material will be placed in the hole made from the sign base removal. The disturbed area will be seeded and mulched in accordance with Item 901 and 908. The seeding and mulching will be considered as an incidental item to the sign removal and no additional compensation will be allowed.

125-3.7 RELOCATE TAXI GUIDANCE SIGN. There are two existing taxi guidance signs that are located at the existing holding lines on Taxiway "A1" and "A2" that will be relocated to the proposed holding lines. The Contractor will remove these signs and modify the signs by attaching a single module to each guidance sign. This will make them large enough for the new legend. The Contactor will also furnish and install new sign panels on both sides of the two guidance signs. The sign panels will read as specified on the Construction Plans. These modified signs will then be placed on new concrete foundations located as shown on the Construction Plans. New electrical cable will be run to the relocated taxi guidance signs to place them into the taxiway lighting circuit. The existing concrete sign bases will be removed and disposed of off the airport site. The holes left from the sign base removal will be filled with earth material, compacted to prevent future settlement, seeded and mulched.

The removal and modification of the existing taxi guidance signs, removal of the concrete bases, furnishing and compacting of the earth material, seeding and mulching, construction of the new concrete taxi guidance sign bases will all be considered as an incidental item to the relocation of the existing taxi guidance signs and no additional compensation will be allowed.

BASIS OF PAYMENT

Add the following:

"If upon delivery and incorporation of any materials, the Contractor has failed to provide the necessary submittals as required by Sections 30-18, 40-01, 40-03, and 40-11 of the Standard Specifications, Supplemental Specifications and Special Provisions, the pay item will not be included on the Contractor Progress Payment report until such submittals have been furnished."

Payment will be made under:

Item AR125410 MITL – Stake Mounted – per each Item AR125415 MITL – Base Mounted – per each Item AR125443 Taxi Guidance Sign, 3 Character - per each Item AR125444 Taxi Guidance Sign, 4 Character per each Item AR125901 Remove Stake Mounted Light - per each Item AR125904 Remove Taxi Guidance Sign - per each Item AR125964 Relocate Taxi Guidance Sign – per each

ITEM AR125967 RELOCATE REILS

DESCRIPTION

This item of work shall consist of the relocation of the existing Runway End Identification Lights (REIL) units from the existing threshold of Runway End 36 to the proposed locations detailed on the Plans. The existing pair of REIL units are Godfrey Engineering Part No. GEA20-100F. The manufacturer is no longer in business and therefore installation instructions might not be readily available. Contractor shall field verify and record the existing wiring connections for the REIL units to assist with the relocation and rewiring of these units. The REIL are fed out of the vault from a boost transformer with a 120/240 VAC, 1 phase, 3 wire secondary. Based on information from airport maintenance personnel one of the cables feeding the REIL units was damaged and REIL units were reconnected to accept 120 VAC, 1 phase, 2 wire power in August 2004. The REIL units are powered by a 120 VAC cable fed from the electrical vault and are currently in working order.

EQUIPMENT AND MATERIALS

<u>Power and Control Cable:</u> Power cables from the respective power source splice location to the respective disconnecting means for the REILS shall be 2/C #8 XLP-USE, 600 Volt underground cable in unit duct or Schedule 40 PVC conduit as detailed on the Plans and in conformance with Item 108. Power and control cables between the REIL units shall be as recommended by the respective REIL manufacturer, per FAA AC 150/5345-51, and as detailed on the Plans. All cable that is direct buried in earth shall be listed suitable for direct burial in earth.

<u>Conduit:</u> Conduit for the REIL system shall conform to Item 110, per the REIL manufacturer's recommendations, and as detailed on the Plans.

<u>Strut Support:</u> Strut-type steel supports shall be provided to support all freestanding equipment enclosures and other equipment enclosures, as indicated on Plans. Supports shall be hot-dipped, galvanized steel strut, Unistrut P-1000HG, or approved equal. Provide necessary hardware, such as floor flanges, etc., as required to install equipment. Provide materials, sizes, and types of anchors, fasteners, and supports necessary to carry the loads of equipment and conduits. Consider weights of conduit when selecting products. Fasteners and anchors shall be corrosion-resistant, stainless steel, or cadmium-plated.

<u>Liquid-Tight Flexible Metal Conduit:</u> Liquid-tight, flexible metal conduit shall consist of polyvinyl jacket over flexible hot dip galvanized steel tubing. The flexible conduit shall be completely sealed from liquids, dust, dirt, and fumes and be resistant to oil, gasoline, grease, and abrasion. Jacket shall also be sunlight-resistant. Liquid-tight flexible metal conduit shall be UL-listed, suitable for use as a grounding conductor, and comply with Article 350 of the NEC. Liquid-tight flexible metal conduit and associated fittings shall be UL-listed to meet the requirements of NEC 350.6. Liquid-tight flexible metal conduit that is not UL

listed is not acceptable. Liquid-tight flexible metal conduit shall be Anaconda Sealtite Type UA as manufactured by Anamet Electrical Inc., 1000 Broadway Avenue East, Mattoon, Illinois 61938-0039, (Phone: 217-234-8844), Liquatite Type LA as manufactured by Electri-Flex Company, 222 W. Central Ave., Roselle, Illinois 60172, (Phone: 630-529-2920 or 1-800-323-6174), or approved equal.

<u>Safety Switches:</u> Furnish and install safety switches for the respective equipment as detailed on the Plans and specified herein. Safety switches shall be heavy duty, UL-listed, with amperage, voltage, number of poles, and type (fusible or not fusible), and accessories as detailed on the Plans. Safety switches shall be pad lockable in the off position. Include ground lugs or grounding kits with all safety switches. Safety switches located indoors in dry, non-corrosive, non-hazardous areas shall be in NEMA 1 or NEMA 12 enclosures. Safety switches located outdoors, or in damp areas shall be in NEMA 3R (rain-tight) and NEMA 12 (dust-tight) or NEMA 4X enclosures without knockouts. Safety switches located in hazardous classified areas shall be UL-listed or FM approved as suitable for the respective location. Safety switches shall be as manufactured by Square D, or equivalent.

REIL Base/Splice Cans: REIL bases shall be Type L-867 Base/Splice cans as detailed on the Plans and specified herein. REIL Base/Splice cans shall conform to the requirements of FAA AC 150/5345-42C (or most current issue in force) for Type L-867, Class IA, Size D (16-inch nominal diameter), 24-inch deep, and/or as detailed on the Plans. Splice cans shall have steel covers, 3/8 in. thick, or as recommended by the respective REIL manufacturer where the splice can is installed for use as the REIL base. Include internal and external ground lugs on the L-867 base can. Include breakable couplings for mounting REILS to the respective base/foundation.

<u>Anti-Seize Compound:</u> The Contractor will apply an oxide-inhibiting, anti-seizing compound to all screws, nuts, breakable coupling, and all places where metal comes into contact with metal. The anti-seize compound will be as manufactured by I.T.T. brand name "Contax" or an approved equal.

Stainless Steel Bolts: All base plate mounting bolts shall be stainless steel.

<u>Ground Rods:</u> Ground rods shall be 3/4-inch diameter by 10-foot long UL listed copper clad, with 10-mil minimum copper coating.

<u>Concrete</u>: Concrete associated with the each REIL foundation and/or splice can shall conform to Item 610 Portland Cement Concrete of the Standard Specifications for Construction of Airports.

<u>Legend Plates:</u> Legend plates shall be required for all REIL units, safety switches, circuit breakers, disconnects, etc. Legend plates shall be provided to identify the equipment controlled, the power source and voltage, and the function of each device. Legend plates shall be weatherproof and abrasion resistant phenolic material. Lettering shall be black letters on a white background, unless otherwise noted.

CONSTRUCTION

<u>Installation of REILS:</u> The Contractor will remove the existing REIL units after the existing Runway 36 is closed. The Contractor will store the units in a secure location of his choosing and will be responsible for replacing them in the same condition as noted prior to removal. Any damage to these units will be repaired by the Contractor at his own expense.

The Contractor will remove the existing REIL concrete bases and dispose of them off the airport site in a legal manner. The holes left from the base removal will be filled with earth material. The earth material will be compacted to prevent any future settlement. The earth material will be taken from the proposed construction site. The disturbed area will be limed, fertilized, and seeded in accordance with item 901. The liming, fertilizing, and seeding will be considered as an incidental item to the relocation of the REIL units.

The REILS shall be relocated and installed at the locations shown on the Plans. Installation of REILS systems shall conform to FAA AC No. 150/5345-51 titled "SPECIFICATION FOR DISCHARGE-TYPE FLASHING LIGHT EQUIPMENT" and the respective manufacturer's instructions. The Contractor shall install splice cans and construct concrete bases for the REIL units in accordance with the respective REIL manufacturer's installation instructions and recommendations and as detailed on the Construction Plans. All required trenching and cable between the master and slave units, associated hardware, mounting requirements, etc. shall be installed per the respective REIL manufacturer's installation instructions and recommendations, and shall be considered part of the installation with no additional compensation.

In the automatic mode of operation the REILS shall be activated by radio control corresponding to the 100% brightness level of the respective runway lights as follows:

3 clicks – Off

5 clicks – Off

7 clicks – 100% Brightness/On

The Contractor shall test the relocated units to assure that they are in proper working order. Contractor shall demonstrate proper operation and testing for the Resident Engineer.

<u>Electrical</u>: The Contractor shall furnish and install all electrical materials necessary for complete and operational installation of the REIL systems as shown on the plans and detailed herein. The complete installation and wiring shall be done in a neat, workmanlike manner. All electrical work shall comply with the requirements of the National Electrical Code (most current issue in force). Electrical equipment shall be installed in conformance with the respective manufacturer's directions and recommendations for the respective application. Any installations which void the UL listing, ETL listing, (or other third party listing), and/or the manufacturer's warranty of a device will not be permitted.

<u>Cable Installation for REILS:</u> Installation of cables shall conform to Item 108, the applicable sections of FAA AC 150/5345-51, per the respective equipment manufacturer's installation instructions and recommendations, and as detailed on the Plans.

The Contractor shall splice the existing power cables to new 2/C #8 AWG XLP-USE 600 Volt, underground cable in unit duct or schedule 40 PVC conduit inside an existing L-867 splice can at the location shown on the Construction Plans. The Contractor shall install new 2/C #8 AWG XLP-USE 600 Volt, underground cable in unit duct from the splice point to the proposed safety switch/disconnect located near the REIL master unit approximately 80 feet from the runway pavement edge as detailed on the Plans. Cable insulation shall be color coded black for the 120 VAC phase conductor and white for the neutral conductor. The new power cable from the respective splice point to the safety switch/disconnect will be considered incidental to the REIL relocation, and no additional compensation will be allowed. The routing of the proposed power cable shall be as shown on the Construction Plans.

The Contractor will furnish and install 3/C #8 AWG XLP-USE 600 Volt, underground cable in unit duct and/or conduit from the safety switch/disconnect to the REIL Master Unit. Cable insulation shall be color coded black for the 120 VAC phase conductor, white for the neutral conductor, and green for the equipment ground wire. These cables will be considered incidental to the REIL relocation, and no additional compensation will be allowed.

The Contractor will be responsible for installing all required power and control cables between the REIL units in accordance with the REIL unit manufacturer's installation instructions and recommendations and as detailed on the Plans. These cables will be considered incidental to the REIL relocation, and no additional compensation will be allowed.

<u>Conduit Installation for REILS:</u> Installation of conduit shall conform to Item 110 and the respective REIL manufacturer's installation instructions and/or recommendations.

Installation of Safety Switches: All safety switches shall be provided with appropriate mounting hardware and strut support. Strut support shall be hot dipped, galvanized steel strut support, Unistrut P-1000 HG, or approved equal. Provide zinc rich paint applied to field cuts of strut support to minimum the potential for corrosion per the respective strut support manufacturer's recommendation. All hardware shall be corrosion resistant. Mount safety switches securely in accordance with the manufacturer's recommendations/instructions and as required for the respective application. Inspect all safety switches for proper operation, tight and secure connections, and correctness. All safety switch enclosures shall be bonded to ground with a ground lug or bar and ground wire. Field cut holes in safety switch enclosures to accommodate conduit entrances. Where safety switches are provided with concentric knockouts, and the respective conduit does not use the largest knockout, install a grounding bushing with ground wire connections between the bushing and the ground bus. Do not use safety switch enclosures for a splice box or for a pull box. Do not route control wires or other circuit wiring through a safety switch. Where splices are required or other control circuit wires are installed in the respective conduit to a safety switch, provide a separate junction box to accommodate the splices and/or other circuit conductors. Provide weatherproof abrasion resistant, engraved legend plates for each safety switch noting the device served, the power

source, and the voltage system. The proposed mounting assembly will be considered as part of the relocation of the REIL units and no additional compensation will be allowed.

Grounding for REILS: Grounding for REILS shall conform to the respective REIL manufacturer's installation instructions, as detailed on the Plans, and as specified herein. The power circuit to Master REIL unit, and each slave unit, shall include an equipment ground wire of the same size and type as the phase conductors. The existing power feeder circuit is a 120 VAC, 2-wire circuit without an equipment ground wire. To comply with the requirements of National Electrical Code a safety switch/disconnect shall be installed at the relocated master REIL unit. The 120 VAC feeder conductors from the vault shall terminate on this safety switch/disconnect. Furnish and install a 3/4-inch diameter by 10-foot long copper clad ground rod at each REIL unit. Bond each REIL unit housing to the respective ground rod in accordance with the manufacturer's instructions with a #6 AWG bare solid or stranded (per REIL manufacturer requirements) copper grounding electrode conductor. Connect the safety switch enclosure frame/ground bar to the ground rod at the Master REIL unit with a #6 AWG stranded copper grounding electrode conductor. Bond the neutral to ground in this safety with a #8 AWG (minimum) stranded copper bonding jumper. From the load side of the safety switch install 1 #8 XLP-USE, 1 #8 XLP-USE Neutral, and 1 #8 equipment ground in 1" Schedule 40 PVC conduit to the Master REIL unit. Top of ground rods shall be buried approximately 30 inches below grade. All connections to ground rods shall be exothermic weld as manufactured by Cadweld, Thermoweld, or Ultraweld. Connections to REIL unit frames shall be as recommended by the manufacturer or with a UL listed grounding connectors. The REIL base cans shall also be bonded to the ground rods at each REIL unit. Contractor shall confirm counterpoise requirements and/or additional grounding requirements with the respective REIL manufacturer's installation instructions and/or recommendations and the details on the Plans.

Grounding Requirements: Grounding shall conform to the following as applicable: The Contractor shall furnish and install all grounding shown on the Plans and/or as may be necessary or required to make a complete grounding system, as required by the latest NEC (NFPA 70) in force. The reliability of the grounding system is dependent on careful, proper installation, and choice of materials. Improper preparation of surfaces to be joined to make an electrical path, loose joints, or corrosion can introduce impedance that will seriously impair the ability of the ground path to protect personnel and equipment and to absorb transients that can cause noise in communications circuits. The following functions are particularly important to ensure a reliable ground system:

- All products associated with the grounding system shall be UL-listed and labeled.
- All bolted or mechanical connections shall be coated with a corrosion preventative compound before joining, Sanchem Inc. "NO-OX-ID "A-Special" compound or equal
- Metallic surfaces to be joined shall be prepared by the removal of all non-conductive material, per 2005 NEC Article 250-12. All copper bus bars must be cleaned prior to making connections to remove surface oxidation.

- Metallic raceway fittings shall be made up tight to provide a permanent low impedance path for all circuits. Metal conduit terminations in enclosures shall be bonded to the enclosure with UL-listed fittings suitable for grounding. Provide grounding bushings with bonding jumpers for all metal conduits entering service equipment (meter base, CT cabinet, main service breaker enclosure, etc.), generator breaker enclosures, and automatic transfer switch enclosures. Provide grounding bushings with bonding jumpers for all metal conduits entering an enclosure through concentric or eccentric knockouts that are punched or otherwise formed so as to impair the electrical connection to ground. Standard locknuts or bushings shall not be the sole means for bonding where a conduit enters an enclosure through a concentric or eccentric knockout.
- Furnish and install ground rings, ground fields, and/or ground rods at all locations where shown on the Plans or specified herein. Ground rods shall be 3/4-in. diameter, 10 ft long, UL-listed, copper-clad with 10 mil. minimum copper coating. Top of ground rods shall be a minimum of 30 in. below finish grade unless otherwise noted on the Plans. Ground rods shall be spaced, as detailed on the Plans, and in no case spaced less than one-rod length apart. All connections to ground rods and/or ground rings shall be made with exothermic, weld-type connectors, Cadweld by Erico Products, Inc., Solon, Ohio, (Phone: 1-800-248-9353), Thermoweld by Continental Industries, Inc., Tulsa, Oklahoma (Phone: 918-663-1440), or approved equal. Exothermic weld connections shall be installed in conformance with the respective manufacturer's directions using molds, as required for each respective application. Bolted connections will not be permitted at ground rods or at buried grounding electrode conductors. Grounding electrode conductors shall be bare-stranded, copper-sized, as detailed on the Plans. In addition to the grounding work described herein and shown on the Plans, the Contractor shall test the made electrode ground field/ground ring with an instrument specifically designed for testing ground field systems. If ground resistance exceeds 10 Ohms, contact the Resident Engineer for further direction. Copies of ground field test results shall be furnished to the Resident Engineer, upon request, for review and record purposes.
- All connections, located above grade, between the different types of grounding conductors shall be made using UL-listed, double-compression, crimp-type connectors or UL-listed, bolted ground connectors. For ground connections to enclosures, cases, and frames of electrical equipment not supplied with ground lugs, the Contractor shall drill required holes for mounting a bolted, ground connector. All bolted, ground connectors shall be Burndy, Thomas and Betts, or equal. Tighten connections to comply with tightening torques in UL Standard 486A to assure permanent and effective grounding.
- All metal equipment enclosures, conduits, cabinets, boxes, receptacles, etc. shall be bonded to the respective grounding system.
- Each new feeder circuit and/or branch circuit shall include an equipment ground wire. Metal raceway or conduit shall not meet this requirement. The equipment ground wire from equipment shall not be smaller than allowed by 2005 NEC Table 250-122

"Minimum Size Conductors or Grounding Raceway and Equipment." When conductors are adjusted in size to compensate for voltage drop, equipment-grounding conductors shall be adjusted proportionately according to circular mil area. All equipment ground wires shall be copper, either bare or insulated green in color. Where the equipment grounding conductors are insulated, they shall be identified by the color green, and shall be the same insulation type as the phase conductors.

- Bond the main electrical service neutral to ground at the main service disconnect. Bond
 the service neutral to ground at one location only per the NEC. A grounding
 connection shall not be made to any neutral circuit conductor on the load side of the
 service disconnecting means, except as permitted by 2005 NEC 250-24.
- The secondary neutral of all transformers (separately derived system transformers) shall be grounded in accordance with the NEC. The respective grounding electrode conductor shall be connected to the neutral point of the transformer between the transformer and the output disconnecting means. Size of the grounding electrode conductor shall be in accordance with 2005 NEC Article 250-66 and Table 250-66 unless shown larger on the Drawings. A bond shall be provided between the neutral and transformer case, or other metal that is part of the AC equipment grounding system, so as to complete a circuit for fault current to the transformer winding from the AC equipment grounding system. Size of the neutral bonding conductor shall be in accordance with 2005 NEC Article 250-102.
- All exterior metal conduit, where not electrically continuous because of manholes, handholes, non-metallic junction boxes, etc., shall be bonded to all other metal conduit in the respective duct run, and at each end, with a copper-bonding jumper sized in conformance with 2005 NEC 250-102. Where metal conduits terminate in an enclosure (such as a motor control center, switchboard, etc) where there is not electrical continuity with the conduit and the respective enclosure, provide a bonding jumper from the respective enclosure ground bus to the conduit sized per 2005 NEC 250-102.
- Install grounding electrode conductors and/or individual ground conductors in Schedule 40 or Schedule 80 PVC conduit. Where grounding electrode conductors or individual ground conductors are run in PVC conduit, do not completely encircle conduit with ferrous and/or magnetic materials. Use non-metallic, reinforced fiberglass strut support. Where metal conduit clamps are installed, use nylon bolts, nuts, washers, and spacers to interrupt a complete metallic path from encircling the conduit.

BASIS OF PAYMENT

Payment shall be made at the contract unit price per pair for REIL Relocation. This price and payment shall be full compensation for removing the existing REIL units; storing the units; removal of the existing REIL bases and backfilling of the holes; furnishing, installing, and construction of the new REIL bases; for furnishing and installing safety switches, supports, conduits, ducts, and all other incidentals required to provide the electrical power to the

Illinois Project CUL-3683 AIP Project 3-17-0109-B7

relocated REIL units; for furnishing and installing all materials; for all excavating, labor, tools, testing, grounding, equipment and incidentals necessary to complete this item of work. All cable, wiring and splices associated with the REIL relocation shall be incidental to Item AR125967 Relocate REILS and no additional compensation will be allowed.

Payment will be made under:

Item AR125967 Relocate REILS - per pair

AR150540 HAUL ROUTE

DESCRIPTION

This item of work shall consist of construction, maintenance, and removal of the haul route at the location shown on the Construction Plans. The haul route will be constructed and maintained in accordance to these Specifications.

CONSTRUCTION METHODS

The Contractor shall construct the haul route to provide access to the construction site. The haul route will be maintained as not to cause delay to the proposed construction. The Contractor will be required to employ methods to control dust and tracking of mud on the grade of the construction site and paved areas.

The limits of the haul route will be delineated by the Contractor by placing ribbon lath at intervals of 100 ft on each side of the route.

The Contractor's access to the construction site will be through the perimeter fencing along the south side of the airport. There is a manual gate located in this perimeter fence that the contractor will use for his operations. During the hours of construction, the gate will remain closed and locked, unless the contractor is continuously hauling material to and from the site. At that time, the gate will remain open but the contractor will monitor the gate.

The Contractor is required to investigate for buried utilities that the haul road will cross. The Contractor is to provide sufficient protection for any buried utilities that the haul road crosses. Any utilities damaged by the Contractor will be repaired by him at no cost to the project. The Contractor will take special precautions during construction so as not to damage the existing roads, taxiways, buildings, and other existing improvements. Any damage to the existing improvements during construction shall be repaired or replaced by the Contractor at his own expense. All active pavement areas shall be kept broom clean at all times.

Restoration: The Contractor shall restore the haul route when it is no longer required. All materials used for the haul route will be removed from the airport site. The haul route location will be graded to its original elevations. The area disturbed by the haul route will be seeded and mulched in accordance with Item 901 - Seeding and Item 908 - Mulching. The turfing of the haul route is considered part of this item.

Safety: All traffic control, safety, and permitting requirements associated with the construction and use of the haul route are the responsibility of the Contractor.

BASIS OF PAYMENT

Payment will be made at the contract unit price per lump sum for constructing the haul routes as specified. This price shall be full compensation for furnishing and installation of all materials; restoration, and turfing; for all labor, equipment, and incidentals necessary to complete this item of work.

Payment will be made under:

Item AR150540 Haul Route - per lump sum

ITEM AR156510 SILT FENCE

DESCRIPTION

This item of work shall consist of a filter fence as partial implementation of a Stormwater Pollution Prevention Plan.

The measures of the Plan are shown on the Construction Plans, and shall be constructed in accordance with the Illinois Environmental Protection Agency (IEPA) Standards and Specifications for soil erosion and sediment control.

MATERIALS

<u>Silt Fence.</u> The proposed silt fence fabric shall consist of woven or nonwoven filaments of polypropylene, polyester, or polyethylene. Nonwoven fabric may be needle-punched, heat-bonded, resin-bonded, or combination thereof. The filaments in the silt fence fabric must be dimensionally stable (i.e., to each other), resistant to delamination, and must be free from any chemical treatment or coating that might significantly reduce porosity and permeability. The fabric shall be resistant to ultraviolet radiation. The fabric shall comply with the following physical properties:

| Physical Properties (English) | Ground Stabilization | Silt Filter Fence Fabric |
|---|--------------------------|---|
| Grab tensile strength (lbs) - ASTM D 4632 | 200 (min.) ^{1/} | 200 (min.) ^{1/} |
| Grab elongation @ break (%) – ASTM D 4632 | 12 (min.) ^{1/} | 12 (min.) ^{1/} |
| Burst strength (psi) - ASTM D 751 | 250 (min.) ^{2/} | 250 (min.) ^{2/} |
| Trapezoidal tear strength (lbs) ASTM D 4533 | 75 ^{2/} | |
| Width (ft.) | | 3.5 (min.) |
| Weight (oz/sq yd.) - ASTM D 3776 | 4.0 (min.) | 4.0 (min.) |
| Equivalent opening size (EOS) Sieve No Corps of Engrs. CS-02215 | | 30 (min.)(nonwoven) ^{2/} 50 (min.)(woven) ^{2/} |

| Physical Properties (Metric) | Ground Stabilization | Silt Filter Fence Fabric |
|---|---------------------------|---|
| (ivietile) | Stabilization | T effice T abric |
| Grab tensile strength (N) - ASTM D 4632 | 900 (min.) ^{1/} | 900 (min.) ^{1/} |
| Grab elongation @ break (%) - ASTM D 4632 | 12 (min.) ^{1/} | 12 (min.) ^{1/} |
| Burst strength (kPa) - ASTM D 751 | 1720 (min.) ^{2/} | 1720 (min.) ^{2/} |
| Trapezoidal tear strength (N) ASTM D 4533 | 335 ^{2/} | |
| Width (m) | | 1 (min.) |
| Weight (g/m ²) - ASTM D 3776 | 135 (min.) | 135 (min.) |
| Equivalent opening size (EOS) Sieve No Corps of Engrs. CS-02215 | | 600 μm (min.) (nonwov.) ^{2/} 300 μm (min.)(woven) ^{2/} |

^{1/} For woven fabric, test results shall be referenced to orientation with warp or weave, whichever the case may be. Both woven and nonwoven fabric shall be tested wet.

CONSTRUCTION METHODS

<u>Silt Fence.</u> The proposed erosion control fencing shall be constructed prior to start of grading operations at the locations shown on the plans. The erosion control fencing shall be constructed to intercept sheet flow of water borne silt and sediment, and prevent it from leaving the area of construction. The barrier shall be constructed according to manufacturer's specifications where appropriate.

The stakes for the fence barrier shall be a minimum of 48 in. long and made of 2 in. x 2 in. hardwood.

The silt fence will be removed once a stand of grass has been established on the site.

BASIS OF PAYMENT

Payment will be made at the contract unit bid price for Silt Fence. This price shall be full compensation for constructing all proposed erosion control measures, maintaining all erosion control structures for the duration of the project, and removal of all structures at the completion of the project. This price shall constitute full compensation for erosion control structures, and for furnishing all materials, labor, equipment, and other incidentals necessary to complete this item of work.

Payment will be made under:

Item AR156510 Silt Fence - per lin. ft

^{2/} Test results may be obtained by manufacturer's certification.

ITEM AR156511 DITCH CHECK

DESCRIPTION

This item of work shall consist of placing and maintaining straw bales to form ditch checks in accordance with the details shown on the Construction Drawings as partial implementation of a Stormwater Pollution Prevention Plan. The measures of the plan and locations of the ditch checks are shown on the Construction Drawings and shall be constructed in accordance with the Illinois Environmental Protection Agency (IEPA) Standards and Specifications for soil erosion and sediment control and these special provisions.

CONSTRUCTION METHODS

The Contractor shall furnish, install, and maintain the straw bales required for the ditch checks at the locations shown on the Construction Drawings. The ditch checks shall be inspected frequently and replaced or repaired, as needed, to the satisfaction of the Resident Engineer throughout the project duration. Replacement of a ditch check will not warrant compensation for an additional ditch check. Once a strand of grass is established and accepted by the Engineer, the Contractor shall remove the straw bale ditch checks and dispose them off the airport property.

METHOD OF MEASUREMENT

The quantity of ditch checks to be paid for shall be the number of ditch checks constructed as specified and accepted by the Resident Engineer.

BASIS OF PAYMENT

Payment will be made at the contract unit bid price for Ditch Checks. This price shall be full compensation for furnishing the required materials and constructing the ditch checks to the details shown and the specifications herein, for maintaining and replacing the ditch checks as needed for the duration of the project, and their removal once an acceptable stand of grass has been established on the site.

Payment will be made under:

Item AR156511 Ditch Check - each

ITEM AR156513 SEPARATION FABRIC

DESCRIPTION

This item of work shall consist of placing a geotech fabric on the prepared subgrade in the proposed taxiway construction areas.

MATERIALS

<u>156-2.2</u> Geotextile Fabric for Ground Stabilization. Fabric for Ground Stabilization shall consist of woven or nonwoven filaments of polypropylene, polyester, or polyethylene. Nonwoven fabric may be needle-punched, heat-bonded, resin-bonded, or combination thereof. The fabric shall be resistant to ultraviolet radiation. The fabric shall comply with the following physical properties:

| Physical Properties | Ground |
|---|--------------------------|
| (English) | Stabilization |
| Grab tensile strength (lbs.) – ASTM D | 200 (min.) 1/ |
| 4632 | |
| Grab elongation @ break (%) – ASTM D | 12 (min.) 1/ |
| 4632 | |
| Burst strength (psi) - ASTM D 751 | 250 (min.) ^{2/} |
| Trapezoidal tear strength (lbs.) ASTM D | 75 ^{2/} |
| 4533 | |
| Width (ft) | |
| Weight (oz/sq. yd) - ASTM D 3776 | 4.0 (min.) |
| Equivalent opening size | |
| (EOS) Sieve No Corps of Engrs. CS- | |
| 02215 | |

| Physical Properties (Metric) | Ground Stabilization |
|--|---------------------------|
| Grab tensile strength (N) - ASTM D 4632 | 900 (min.) 1/ |
| Grab elongation @ break (%) – ASTM D | 12 (min.) 1/ |
| 4632 | |
| Burst strength (kPa) - ASTM D 751 | 1720 (min.) ^{2/} |
| Trapezoidal tear strength (N) ASTM D | 335 2/ |
| 4533 | |
| Width (m) | |
| Weight (g/m ²) - ASTM D 3776 | 135 (min.) |
| Equivalent opening size | |
| (EOS) Sieve No Corps of Engrs. CS- | |
| 02215 | |

- 1/ For woven fabric, test results shall be referenced to orientation with warp or weave, whichever the case may be. Both woven and nonwoven fabric shall be tested wet.
- 2/ Test results may be obtained by manufacturer's certification.

CONSTRUCTION METHODS

<u>Installation Requirements.</u> Fabric shall be delivered to the job site in such a manner as to facilitate handling and incorporation into the work without damage. Material shall be stored in such a manner as to prevent exposure to direct sunlight and damage by other construction activities.

Prior to the installation of the fabric, the application surface shall be cleared of debris, sharp objects, and trees. Tree stumps shall be cut to the level of the ground surface. If the stumps cannot be cut to the ground level, they shall be completely removed. In the case of subgrades, all wheel tracks or ruts in excess of three in. in depth shall be graded smooth or otherwise filled with soil to provide a reasonably smooth surface.

Fabric may be installed on the application surface either by hand or by mechanical methods, provided that the fabric is not torn or the surface rutted.

Fabric of insufficient width or length to fully cover the specified area shall be lapped, or sewn. The minimum laps for lap only areas are 24 in. and for sewn areas are 4 in. If sewn, the seam strength shall be equal to or exceed the minimum grab tensile strength of the fabric when tested wet.

METHOD OF MEASUREMENT

The quantity of separation fabric to be paid for shall be the number of sq. yards placed and accepted by the Resident Engineer.

BASIS OF PAYMENT

This item of work will be paid for at the contract unit bid price per sq. yard for the separation fabric which price and payment shall constitute full compensation for furnishing and placement of all materials, labor, equipment, and incidentals necessary to complete this item of work.

Payment will be made under:

Item AR156513 Separation Fabric - per sq. yard

ITEM AR156521 HEADWALL PROTECTION

DESCRIPTION

This item of work shall consist of placing and maintaining straw bales and silt fence to protect end sections from silt in accordance with the details shown on the Construction Drawings as a partial implementation of a Stormwater Pollution Prevention Plan. The measures of the plan and the locations of the headwall protection are shown in the Construction Plans and shall be constructed in accordance with the Illinois Environmental Protection Agency (IEPA) Standards and Specifications for soil erosion and sediment control and these Special Provisions.

MATERIALS

Erosion Control Fence. The proposed silt fence fabric shall consist of woven or nonwoven filaments of polypropylene, polyester, or polyethylene. Nonwoven fabric may be needle-punched, heat-bonded, resin-bonded, or combination thereof. The filaments in the silt fence fabric must be dimensionally stable (i.e., to each other), resistant to delamination, and must be free from any chemical treatment or coating that might significantly reduce porosity and permeability. The fabric shall be resistant to ultraviolet radiation. The fabric shall comply with the following physical properties:

| Physical Properties | Ground | Silt Filter |
|---|--------------------------|---|
| (English) | Stabilization | Fence Fabric |
| Grab tensile strength (lbs) - ASTM D 4632 | 200 (min.) ^{1/} | 200 (min.) ^{1/} |
| Grab elongation @ break (%) – ASTM D 4632 | 12 (min.) ^{1/} | 12 (min.) ^{1/} |
| Burst strength (psi) - ASTM D 751 | 250 (min.) ^{2/} | 250 (min.) ^{2/} |
| Trapezoidal tear strength (lbs) ASTM D 4533 | 75 ^{2/} | |
| Width (ft.) | | 3.5 (min.) |
| Weight (oz/sq yd.) - ASTM D 3776 | 4.0 (min.) | 4.0 (min.) |
| Equivalent opening size (EOS) Sieve No Corps of Engrs. CS-02215 | | 30 (min.)(nonwoven) ^{2/} 50 (min.)(woven) ^{2/} |

| Physical Properties (Metric) | Ground Stabilization | Silt Filter Fence Fabric |
|---|---------------------------|---|
| Grab tensile strength (N) - ASTM D 4632 | 900 (min.) ^{1/} | 900 (min.) ^{1/} |
| Grab elongation @ break (%) – ASTM D 4632 | 12 (min.) ^{1/} | 12 (min.) ^{1/} |
| Burst strength (kPa) - ASTM D 751 | 1720 (min.) ^{2/} | 1720 (min.) ^{2/} |
| Trapezoidal tear strength (N) ASTM D 4533 | 335 ^{2/} | |
| Width (m) | | 1 (min.) |
| Weight (g/m ²) - ASTM D 3776 | 135 (min.) | 135 (min.) |
| Equivalent opening size (EOS) Sieve No Corps of Engrs. CS-02215 | | 600 μm (min.) (nonwov.) ^{2/} 300 μm (min.)(woven) ^{2/} |

- 1/ For woven fabric, test results shall be referenced to orientation with warp or weave, whichever the case may be. Both woven and nonwoven fabric shall be tested wet.
- 2/ Test results may be obtained by manufacturer's certification.

CONSTRUCTION METHODS

The Contractor shall furnish, install, and maintain the straw bales and silt fence required for the headwall protection at the locations shown on the Construction Drawings. The headwall protection shall be inspected frequently and straw bales replaced or repaired as needed to the satisfaction of the Resident Engineer throughout the duration of the project. Replacement of straw bales or silt fence is considered incidental the headwall protection and no additional compensation will be allowed. Once a strand of grass is established and accepted by the Engineer, the Contractor shall remove the straw bales and silt fence and remove them from the airport property.

METHOD OF MEASUREMENT

The quantity of headwall protection to be paid for shall be the number of headwall protection constructed as detailed and specified and accepted by the Resident Engineer.

BASIS OF PAYMENT

Payment will be made at the contract unit bid price for Headwall Protection. This price shall be full compensation for furnishing the required materials and constructing the headwall protection to the details shown and the specifications herein, for maintaining and replacing the straw bales and silt fence as needed for the duration of the project, and their removal, once an acceptable strand of grass has been established on the site.

Payment will be made under:

Item AR156521 Headwall Protection – per each

AR156540 RIPRAP

DESCRIPTION

This item shall consist of furnishing, transporting, and placing a protective course of stone or broken concrete laid as riprap in the areas designated on the Plans.

MATERIALS

The riprap material shall be RR #3 in accordance with the Illinois Department of Transportation Standard Specifications for Road and Bridge Construction, adopted January 1, 2007.

The filter fabric shall be in accordance with Article 1080.03 of the Illinois Department of Transportation Standard Specifications for Road and Bridge Construction, adopted January 1, 2007

CONSTRUCTION METHODS

Prior to placement of the riprap material, the Contractor will undercut the designated area 12 in. below finish grades. The undercut material will be used as embankment fill material. The riprap course will be 18 in. in total depth.

The riprap shall be placed in accordance with procedures set forth in the Illinois Department of Transportation Standard Specifications for Road and Bridge Construction, adopted January 1, 2007.

METHOD OF MEASUREMENT

The quantity of riprap to be paid for as required in the proposal shall be the number of sq. yds. of riprap material placed and accepted by the Resident Engineer.

BASIS OF PAYMENT

Payment shall be made at the contract unit price bid per sq. yd. for riprap. This price shall be full compensation for undercutting, furnishing, and placing of all materials, and for furnishing all labor, equipment, tools, and incidentals necessary to complete this item of work.

Payment will be made under:

Item AR156540 Riprap - per sq. yd.

ITEM AR201 BITUMINOUS BASE COURSE-METHOD I, SUPERPAVE (Central Plant Hot Mix)

Item 201 Bituminous Base Course shall meet the special provision for "Item AR201003 Bituminous Base Course-Method I, Superpave (Under 2,500 tons) and is modified as outlined below.

DESCRIPTION

<u>201-1.1.</u> Add the following to this section:

"This item of work shall consist of constructing a bituminous base course (3.0 in. depth) on the prepared proposed crushed aggregate base course."

<u>201-3.2</u>. Add the following to this section:

"The Traffic Mix will be as stated in TABLE 2 Superpave Design Criteria for Aircraft Under 60,000 lbs as a Runway or Taxiway"

CONSTRUCTION METHODS

<u>201-4.9. Transporting, Spreading, and Finishing.</u> Add the following paragraph after the fourth paragraph:

"The first lane of the first lift of the bituminous base course shall be started at the center of the pavement with a taut stringline (guide wire) set to grade at both sides of the paver. The automatic grade control system of the paver shall be used to control grade of both sides of the paver from these reference stringlines. The grade control for the adjacent lanes of pavement shall be maintained by using a matching shoe with the previous laid pavement and a stringline on the outer edge of the next lane. A stringline and matching shoe shall be used to pave all remaining lanes of the first lift of base course. If grade is established on the first lift, succeeding lifts shall be laid with a traveling ski on both sides of the paver for the center lane with matching shoe and traveling ski on adjacent lanes. If grade is not established on the first lift, the Resident Engineer shall require taut stringline references until satisfactory grade is established."

The grade control for the adjacent lanes of pavement through this stationing will be maintained by using a matching shoe with the previous laid pavement and a stringline on the outer edge of the next lane until the final lane, which will utilize two matching shoes.

<u>201-4.11 Joints.</u> Add the following as the fourth paragraph of this section:

"No core will be required on the longitudinal construction joint."

<u>201-4.12 Shaping Edges.</u> Add the following to this paragraph:

"All pavement edges (longitudinal, radius, and pavement ends) must be left in proper alignment as shown on the Plans. This may be accomplished by the trimming method outlined above or at the Contractor's option by sawing after the paving has been completed. The ends of Taxiway A and A3 will be sawed a minimum of 3 inches to provide a true square end to the pavement. No additional compensation will be made if the sawing method is used."

ITEM AR208540 OVERSIZE AGGREGATE

DESCRIPTION

This item of work shall consist of installing a layer of oversize aggregate to establish a stable subbase under the proposed pavement. The layer will be 8 in. thick and placed to the grades and locations as shown on the Construction Plans and cross-sections. The oversize aggregate shall be installed in accordance to the Standard Specifications for Construction of Airports, Item 208 procedures with the following exceptions as outlined below.

MATERIALS

The oversize aggregate material shall be a CA-2 course aggregate meeting the gradations as specified under Article 1004.01 in the Standard Specifications for Road and Bridge Construction, adopted January 1, 2007. A 3 in. top size will be allowed for the aggregate material. The Contractor will provide the Resident Engineer a proctor curve showing the optimum density and moisture for the supplied aggregate material before incorporating the material into the roadway subbase.

CONSTRUCTION METHODS

The oversize aggregate shall be constructed to the line and elevations as shown on the cross-sections. The oversize aggregate material may be placed in one lift. The material will be compacted to 95 percent density, as determined by compaction control tests specified in Division VII for aircraft weighing less than 60,000 lbs.

BASIS OF PAYMENT

Payment will be made at the contract unit bid price per ton of oversize aggregate, which price and payment will constitute full compensation for preparing subgrade, furnishing, hauling, and placing the materials; for spreading, compacting, and rolling; and for furnishing all labor, equipment, tools, and incidentals necessary to complete the work.

Payment will be made under:

Item AR208540 Oversize Aggregate - per ton

ITEM AR401 BITUMINOUS SURFACE COURSE (Central Plant Hot Mix)

Item 401 Bituminous Surface Course shall meet the special provision for "Item AR401003 Bituminous Surface Course-Method I, Superpave (Under 2,500 tons) and is modified as outlined below.

DESCRIPTION

<u>401-1.1.</u> Add the following to this section:

"This item of work shall consist of constructing a bituminous surface course (2 in. depth) on the prepared proposed bituminous base course for Taxiway A and A3.

401-3.2. Add the following to this section:

"The Traffic Mix will be as stated in TABLE 2 Superpave Design Criteria for Aircraft Under 60,000 lbs as a Runway or Taxiway"

CONSTRUCTION METHODS

<u>401-4.9</u> <u>Transporting, Spreading, and Finishing.</u> Add the following paragraph after the fourth paragraph:

""The first lane of the bituminous surface course shall be started at the high side of the pavement with a taut stringline (guide wire) set to grade at both sides of the paver. The automatic grade control system of the paver shall be used to control grade of both sides of the paver from these reference stringlines. The grade control for the adjacent lanes of pavement shall be maintained by using a matching shoe with the previous laid pavement and a stringline on the outer edge of the next lane.

A stringline and matching shoe shall be used to pave all remaining lanes of the first lift of the surface course. If grade is established on the final lift of bituminous base course, then the lift of bituminous surface course shall be laid with a traveling ski on both sides of the paver for the center lane with matching shoe and traveling ski on adjacent lanes. The maximum lift thickness shall be two (2) in. compacted unless otherwise authorized by the Resident Engineer."

401-4.11 Joints. Add the following as the fourth paragraph of this section:

"No core will be required on the longitudinal construction joint."

401-4.12 Shaping Edges. Add the following to this paragraph:

"All pavement edges (longitudinal, radius, and pavement ends) must be left in proper alignment as shown on the Plans. This may be accomplished by the trimming method outlined above or at the Contractor's option by sawing after the paving has been completed. The ends of taxiway A and A3 will be sawed a minimum of 3 inches to provide a true square end to the runway pavement. No additional compensation will be made if the sawing method is used."

IDOT Standard 542301

