

**GIRDER - 9**

Location	Station	Offset*	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. of W. Abut	16029+30.97	20.96	784.33	784.33
☉ Brg. W. Abut	16029+32.24	20.96	784.34	784.34
A	16029+42.24	20.96	784.43	784.45
B	16029+52.24	20.96	784.50	784.55
C	16029+62.24	20.96	784.58	784.64
D	16029+72.24	20.96	784.64	784.71
E	16029+82.24	20.96	784.70	784.77
F	16029+92.24	20.96	784.75	784.81
G	16030+02.24	20.96	784.79	784.84
H	16030+12.24	20.96	784.82	784.86
I	16030+22.24	20.96	784.85	784.87
J	16030+32.24	20.96	784.87	784.87
K	16030+42.24	20.96	784.88	784.88
☉ Pier	16030+52.47	20.96	784.89	784.89
L	16030+62.47	20.96	784.89	784.91
M	16030+72.47	20.96	784.88	784.93
N	16030+82.47	20.96	784.86	784.94
O	16030+92.47	20.96	784.84	784.96
P	16031+02.47	20.96	784.81	784.96
Q	16031+12.47	20.96	784.77	784.95
R	16031+22.47	20.96	784.72	784.92
S	16031+32.47	20.96	784.67	784.87
T	16031+42.47	20.96	784.61	784.80
U	16031+52.47	20.96	784.54	784.72
V	16031+62.47	20.96	784.47	784.61
W	16031+72.47	20.96	784.39	784.48
X	16031+82.47	20.96	784.30	784.35
☉ Brg. E. Abut	16031+91.46	20.96	784.21	784.21
Bk. E. Abut	16031+92.72	20.96	784.20	784.20

**GIRDER - 10**

Location	Station	Offset*	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. of W. Abut	16029+29.66	29.29	784.14	784.14
☉ Brg. W. Abut	16029+30.92	29.29	784.15	784.15
A	16029+40.92	29.29	784.24	784.27
B	16029+50.92	29.29	784.32	784.37
C	16029+60.92	29.29	784.39	784.45
D	16029+70.92	29.29	784.46	784.53
E	16029+80.92	29.29	784.52	784.58
F	16029+90.92	29.29	784.57	784.63
G	16030+00.92	29.29	784.61	784.66
H	16030+10.92	29.29	784.64	784.68
I	16030+20.92	29.29	784.67	784.69
J	16030+30.92	29.29	784.69	784.70
K	16030+40.92	29.29	784.71	784.70
☉ Pier	16030+51.16	29.29	784.71	784.71
L	16030+61.16	29.29	784.71	784.73
M	16030+71.16	29.29	784.71	784.75
N	16030+81.16	29.29	784.69	784.77
O	16030+91.16	29.29	784.67	784.79
P	16031+01.16	29.29	784.64	784.79
Q	16031+11.16	29.29	784.60	784.78
R	16031+21.16	29.29	784.56	784.75
S	16031+31.16	29.29	784.50	784.70
T	16031+41.16	29.29	784.44	784.64
U	16031+51.16	29.29	784.38	784.55
V	16031+61.16	29.29	784.30	784.45
W	16031+71.16	29.29	784.22	784.32
X	16031+81.16	29.29	784.14	784.18
☉ Brg. E. Abut	16031+90.14	29.29	784.05	784.05
Bk. E. Abut	16031+91.40	29.29	784.04	784.04

**GIRDER - 11**

Location	Station	Offset*	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. of W. Abut	16029+28.34	37.63	783.96	783.96
☉ Brg. W. Abut	16029+29.61	37.63	783.97	783.97
A	16029+39.61	37.63	784.06	784.08
B	16029+49.61	37.63	784.14	784.18
C	16029+59.61	37.63	784.21	784.27
D	16029+69.61	37.63	784.28	784.34
E	16029+79.61	37.63	784.33	784.40
F	16029+89.61	37.63	784.39	784.45
G	16029+99.61	37.63	784.43	784.48
H	16030+09.61	37.63	784.47	784.50
I	16030+19.61	37.63	784.50	784.51
J	16030+29.61	37.63	784.52	784.52
K	16030+39.61	37.63	784.53	784.53
☉ Pier	16030+49.84	37.63	784.54	784.54
L	16030+59.84	37.63	784.54	784.56
M	16030+69.84	37.63	784.53	784.58
N	16030+79.84	37.63	784.52	784.60
O	16030+89.84	37.63	784.50	784.62
P	16030+99.84	37.63	784.47	784.62
Q	16031+09.84	37.63	784.43	784.61
R	16031+19.84	37.63	784.39	784.59
S	16031+29.84	37.63	784.34	784.54
T	16031+39.84	37.63	784.28	784.47
U	16031+49.84	37.63	784.21	784.39
V	16031+59.84	37.63	784.14	784.28
W	16031+69.84	37.63	784.06	784.16
X	16031+79.84	37.63	783.97	784.02
☉ Brg. E. Abut	16031+88.83	37.63	783.89	783.89
Bk. E. Abut	16031+90.09	37.63	783.88	783.88

**GIRDER - 12**

Location	Station	Offset*	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. of W. Abut	16029+27.03	45.96	783.77	783.77
☉ Brg. W. Abut	16029+28.29	45.96	783.78	783.78
A	16029+38.29	45.96	783.87	783.90
B	16029+48.29	45.96	783.95	784.00
C	16029+58.29	45.96	784.03	784.09
D	16029+68.29	45.96	784.09	784.16
E	16029+78.29	45.96	784.15	784.22
F	16029+88.29	45.96	784.21	784.27
G	16029+98.29	45.96	784.25	784.30
H	16030+08.29	45.96	784.29	784.32
I	16030+18.29	45.96	784.32	784.34
J	16030+28.29	45.96	784.34	784.35
K	16030+38.29	45.96	784.36	784.35
☉ Pier	16030+48.53	45.96	784.37	784.37
L	16030+58.53	45.96	784.37	784.39
M	16030+68.53	45.96	784.36	784.41
N	16030+78.53	45.96	784.35	784.43
O	16030+88.53	45.96	784.33	784.45
P	16030+98.53	45.96	784.30	784.45
Q	16031+08.53	45.96	784.26	784.44
R	16031+18.53	45.96	784.22	784.42
S	16031+28.53	45.96	784.17	784.37
T	16031+38.53	45.96	784.11	784.31
U	16031+48.53	45.96	784.05	784.22
V	16031+58.53	45.96	783.98	784.12
W	16031+68.53	45.96	783.90	784.00
X	16031+78.53	45.96	783.81	783.86
☉ Brg. E. Abut	16031+87.51	45.96	783.73	783.73
Bk. E. Abut	16031+88.77	45.96	783.72	783.72

**GIRDER - 13**

Location	Station	Offset*	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. of W. Abut	16029+25.71	54.29	783.59	783.59
☉ Brg. W. Abut	16029+26.98	54.29	783.60	783.60
A	16029+36.98	54.29	783.69	783.71
B	16029+46.98	54.29	783.77	783.81
C	16029+56.98	54.29	783.84	783.90
D	16029+66.98	54.29	783.91	783.97
E	16029+76.98	54.29	783.97	784.04
F	16029+86.98	54.29	784.03	784.08
G	16029+96.98	54.29	784.07	784.12
H	16030+06.98	54.29	784.11	784.14
I	16030+16.98	54.29	784.14	784.16
J	16030+26.98	54.29	784.17	784.17
K	16030+36.98	54.29	784.18	784.18
☉ Pier	16030+47.21	54.29	784.19	784.19
L	16030+57.21	54.29	784.19	784.21
M	16030+67.21	54.29	784.19	784.23
N	16030+77.21	54.29	784.18	784.25
O	16030+87.21	54.29	784.16	784.27
P	16030+97.21	54.29	784.13	784.27
Q	16031+07.21	54.29	784.09	784.26
R	16031+17.21	54.29	784.05	784.23
S	16031+27.21	54.29	784.00	784.19
T	16031+37.21	54.29	783.95	784.12
U	16031+47.21	54.29	783.88	784.04
V	16031+57.21	54.29	783.81	783.94
W	16031+67.21	54.29	783.74	783.83
X	16031+77.21	54.29	783.65	783.69
☉ Brg. E. Abut	16031+86.20	54.29	783.57	783.57
Bk. E. Abut	16031+87.46	54.29	783.56	783.56

\* Offset measured from ☉ Stuenkel Rd.