

POROUS GRANULAR EMBANKMENT (FOR USE UNDER RIPRAP FOR SLOPE STABILIZATION)						
LOCATION	LENGTH	WIDTH	AVERAGE	SQ FT	SQ YD	CU YD
RT STA. 41+00		40.3				
	100		40.15	4015	446.11	37.18
RT STA. 42+00		40				
	100		41.35	4135	459.44	38.29
RT STA. 43+00		42.7				
	100		37.95	3795	421.67	35.14
RT STA. 44+00		33.2				
TOTAL				11945	1327	111

LOCATION	STABILIZED SUBBASE-HOT-MIX ASPHALT, 4"	AGGREGATE BASE COURSE TYPE A 12"	PORTLAND CEMENT CONCRETE PAVEMENT 10.25" (JOINTED)	PAVEMENT FABRIC	GEOTECHNICAL FABRIC FOR GROUND STABILIZATION
	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD
STA. 30+22 TO 40+61	2193	2193	1847		2193.0
STA. 40+61 TO 57+17	3496	3496	2944		3496.0
STA. 57+17 TO 68+45	1813	1813	1625	1625	1813
TOTAL	7502	7502	6416	1625	7502

STONE DUMPED RIPRAP, CLASS B3						
LOCATION	LENGTH	WIDTH	AVERAGE	SQ FT	CU YD	TON
RT STA. 37+00 TO 38+00	CROSS SECTION MEASURED IN CADD			2282	70	106
STA. 35+20	10	10		100	3	5
STA. 40+30	10	10		100	3	5
RT STA. 41+00		40				
	100		40	4015	260	390
RT STA. 42+00		40				
	100		41	4140	268	403
RT STA. 43+00		43				
	100		38	3785	245	368
RT STA. 44+00		33				
STA. 48+50	10	10	(x2)	200	6	9
FRONTAGE ROAD CULVERTS AT FRONTAGE STATIONS						
STA. 66+00	10	10	(x2)	200	6	9
STA. 72+00	10	10	(x2)	200	6	9
STA. 76+00	10	10	(x2)	200	6	9
TOTAL				15222	875	1313

FILTER FABRIC (NONWOVEN FOR USE UNDER RIPRAP FOR SLOPE STABILIZATION)					
LOCATION	LENGTH	WIDTH	AVERAGE	SQ FT	SQ YD
RT STA. 37+00 TO 38+00	100		23	2282	254
STA. 35+20	10	10		100	11
STA. 40+30	10	10		100	11
RT STA. 41+00		40			
	100		40	4015	446
RT STA. 42+00		40			
	100		41	4140	460
RT STA. 43+00		43			
	100		38	3785	421
RT STA. 44+00		33			
LT STA. 48+50	10	10	(x2)	200	22
WOVEN FABRIC FOR USE UNDER FRONTAGE ROAD RIPRAP AT CULVERTS (USING FRONTAGE STATIONING)					
STA. 66+00	10	10	(x2)	200	22
STA. 72+00	10	10	(x2)	200	22
STA. 76+00	10	10	(x2)	200	22
TOTAL				15222	1692

AGG SURFACE COURSE, TYPE A			
LOCATION	SQ FT	SQ YD	TON
PROPOSED FRONTAGE ROAD			
STA. 42+50 TO 83+72	49627	5514	2506
PROPOSED FRONTAGE ROAD ENTRANCE			
STA. 55+00	2053	228	104
STA. 64+00	2134	237	108
STA. 78+00	1020	113	52
TOTAL	54834	6093	2770

PERIMETER EROSION BARRIER	
LOCATION	FOOT
STA. 30+00 TO 68+45	4568
TOTAL	4568