

HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"

SHOULDER REMOVAL

HOT-MIX ASPHALT SURFACE REMOVAL, BUTT JOINT

SIDEWALK REMOVAL

MORRIS

ILLINOIS

PAVEMENT REMOVAL & DRIVEWAY PAVEMENT REMOVAL

PERU

COMBINATION CONCRETE CURB & GUTTER REMOVAL

A - MANHOLE OR INLET TO BE ADJUSTED

R — MANHOLE, INLET OR LIGHT POLE BASE TO BE REMOVED

RL — LIGHT POLE, LIGHTING CONTROLLER, FIRE HYDRANT,
AND WATER VALVE TO BE RELOCATED (SEE LIGHTING
AND WATER MAIN PLANS)

++++++++++ - STORM SEWER TO BE REMOVED

🗶 - TREE REMOVAL

NOTE: IN ADDITION TO THE ITEMS SHOWN TO BE REMOVED, RELOCATED OR ADJUSTED HERE, UTILITIES OWNED BY OTHERS MUST ALSO BE REMOVED, RELOCATED OR ADJUSTED. THE CONTRACTOR SHALL COORDINATE HIS WORK WITH THOSE UTILITIES.

DRAWN BY: NV CHECKED BY: JKC DATE: 02/12

CHAMLING

FAS 301 / FAU 383 SECTION 11-00007-00-WR VILLAGE OF DIAMOND **GRUNDY AND WILL COUNTIES**

REMOVAL PLAN - IL 113 STA. 154+00 TO STA. 158+00 CONSTRUCTION

CONTRACT NO. 87520 CURRENT AS OF: 02/12 SCALE: AS NOTED SHEET 12 FILE NO.: 66022.01 Y-