

LOCATION		LENGTH	WIDTH	AREA	42400100	42400300
STATION					PORTLAND CONCRETE CEMENT SIDEWALK 4 INCH	PORTLAND CONCRETE CEMENT SIDEWALK 6 INCH
FROM	TO	(FOOT)	(FOOT)	(SQ FT)	(SQ FT)	(SQ FT)
10+43.54	10+53.60	7.53	7.6		58	
10+82.00	10+87.00	5	5		25	
11+20.70	11+43.40			369	41	
11+72.07	12+65.80	94	5		469	
12+65.80	12+75.80	10	5			50
12+75.80	13+92.78	117	5		585	
14+16.65	15+13.21	102	5		508	
15+13.21	16+14.90	102	5		509	
16+23.50	16+71.85	48	5		242	
16+71.85	16+80.55	9	5			44
16+80.55	16+93.45	13	5		65	
17+03.35	18+54.27	151	5		755	
18+94.71	20+68.75	174	5		871	
20+83.65	22+55.21	172	5		858	
22+95.31	23+74.75	79	5		398	
23+82.95	24+13.95	31	5		155	
24+37.85	24+70.45	33	5		163	
24+70.45	24+80.35	10	5			50
24+80.35	26+55.22	175	5		875	
26+37.81	26+41.71	4	3.9		16	
26+96.07	27+78.90	83	5		415	
27+78.90	27+86.90	8	5			40
27+86.90	28+44.65	58	5		289	
28+61.95	28+69.60	8	5		39	
28+69.60	28+78.80	9	5			47
28+78.80	30+54.37	176	5		878	
30+36.86	30+40.89	4	4		17	
30+37.35	30+40.90	4	3.5		13	
30+97.14	31+13.81	17	5		84	
31+13.81	31+34.54	16	5		79	
31+73.38	31+91.89	19	5		93	
31+91.89	32+81.25	89	5		447	
32+92.75	33+68.40	76	5		379	
33+76.60	35+65.50	189	5		945	
35+96.89	36+87.19	90	5		452	
36+99.13	37+82.45	83	5		417	
36+87.19	37+90.35	103	5			516
37+90.35	38+78.50	88	5		441	
38+78.50	38+95.70	17	5			86
38+95.70	39+89.79	94	5		471	
200+05.00	200+19.00	14	5		70	
200+60.27	202+38.55	178	5		892	
202+38.55	202+59.95	21	5			108
202+59.95	203+20.80	61	5		305	
203+20.80	203+34.60	14	5			69
203+34.60	204+17.63	83	5		416	
TOTAL					13,735	1,010

LOCATION		LENGTH	WIDTH	AREA	44000600
STATION					SIDEWALK REMOVAL
FROM	TO	(FOOT)	(FOOT)	(SQ FT)	(SQ FT)
10+43.54	10+53.60	7.53	7.6		58
10+82.00	10+87.00	5	5		25
11+20.70	11+43.40			265	265
11+72.07	12+45.00	73	5		365
12+45.00	13+92.75	148	2.7		399
14+16.65	15+13.21	102	2.9		295
15+13.21	16+14.90	102	3.7		377
16+23.50	16+93.45	70	3.9		273
17+03.35	18+54.27	151	3.8		574
18+94.71	20+68.75	174	3.4		592
20+83.65	22+55.21	172	3.8		652
22+95.31	23+74.75	79	3.5		279
23+82.95	24+13.95	31	3.3		103
24+37.85	26+55.22	217	3.4		740
26+37.81	26+41.71	4	3.9		16
26+96.07	28+44.65	149	3.4		506
28+61.95	30+54.37	192	3.5		674
30+36.86	30+40.89	4	4		17
30+37.35	30+40.90	4	3.5		13
30+97.14	31+13.81	17	3.3		56
31+13.81	31+34.54	16	3.3		52
31+73.38	31+91.89	19	4		75
31+91.89	32+81.25	89	3.9		349
32+92.75	33+68.40	76	3.9		296
33+76.60	35+65.50	189	3.9		737
35+96.89	39+70.52	374	3.5		1,308
200+05.00	200+19.00	14	4.5		63
200+60.27	203+20.80	261	3.2		834
203+34.60	204+17.63	83	3.4		283
TOTAL					10,276

LOCATION		OFFSET	28000400
STATION			PERIMETER EROSION BARRIER
FROM	TO		(FOOT)
12+00.00	12+65.00	LT	85
12+75.00	13+93.00	LT	138
14+17.00	14+50.00	LT	53
16+32.00	16+70.00	LT	58
16+82.00	16+93.00	LT	31
17+03.00	18+00.00	LT	117
TOTAL			482

LOCATION	60255500
	MANHOLES TO BE ADJUSTED (EACH)
STA. 39+80	1
TOTAL	1

LOCATION	88000105
	FLASHING BEACON INSTALLATION (EACH)
STA. 11+39, 20' LT.	1
STA. 11+75, 6' RT.	1
TOTAL	2