

INDEX OF SHEETS

- 1 COVER SHEET
- 2 INDEX, GENERAL NOTES, & SIGNATURES
- 3 SUMMARY OF QUANTITIES
- 4 BRIDGE PLAN VIEW
- 5 TYPICAL BRIDGE CROSS SECTION
- 6 STAGING DETAIL
- 7-8 JOINT REPLACEMENT DETAILS
- 9 SILICONE JOINT DETAIL
- 10 BAR SPLICER DETAIL

STANDARDS

- 701101-01
- 701106-01
- 701400-02
- 701411-03
- 701446
- 702001-06

GENERAL NOTES

EPOXY CRACK SEALING SHALL BE USED FOR CRACKS IN THE POLYMER CONCRETE WHICH IS TO REMAIN IN PLACE. CRACK SEALING SHALL TAKE PLACE AFTER THE INSTALLATION OF THE NEW EXPANSION JOINT. ANY CRACKS THAT APPEAR IN THE POLYMER CONCRETE AS A RESULT OF REMOVAL OF THE EXISTING JOINT SHALL BE EPOXY SEALED AT THE CONTRACTOR'S EXPENSE.

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
DISTRICT 6

EXAMINED March 1 20 06

[Signature]
ENGINEER OF OPERATIONS

EXAMINED March 16 20 06

[Signature]
ENGINEER OF PROGRAM IMPLEMENTATION

EXAMINED MARCH 16 20 06

[Signature]
ENGINEER OF PROGRAM DEVELOPMENT

INDEX,
GENERAL NOTES,
& SIGNATURES
C-96-001-07
LOGAN COUNTY