

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
709	*	**	72	15

SCHEDULE OF QUANTITIES

* 113(RS-5,BR) & 114RS-2
 ** CHAMPAIGN AND VERMILION
 CONTRACT NO. 90864

#5000605 STORM SEWER REPAIR

VERMILION COUNTY

<u>STATION</u>	<u>FOOT</u>
119+00	30.0
128+00	30.0
<u>TOTAL</u>	<u>60.0</u>

EARTHWORK SCHEDULE

			20200100 EARTH EXCAVATION (CU YD)	ADJUSTED FOR SHRINKAGE (CU YD)	EMBANKMENT (CU YD)	*20400800 FURNISHED EXCAVATION (CU YD)
<u>STATION TO STATION</u>						
<u>CHAMPAIGN COUNTY</u>						
PARK AVE	LT 0+00	LT 0+27.5	2.1	1.6	0.8	0.8
PARK AVE	LT 0+27.5	LT 0+55	2.1	1.6	0.8	0.8
PARK AVE	RT 0+00	RT 0+27.5	2.9	2.2	1.9	0.3
PARK AVE	RT 0+27.5	RT 0+55	2.9	2.2	1.9	0.3
SN 010-8320	482+00	487+00	217.0	162.8	195.0	-32.3
PENNFIELD RD	LT 0+00	LT 0+76.3	2.9	2.2	0.0	2.2
PENNFIELD RD	RT 0+00	RT 0+66	2.5	1.9	0.0	1.9
AR CULVERT	5+99.90	6+00	0.0	0.0	0.0	0.0
AR CULVERT	6+00	7+00	4.1	3.1	9.1	-6.0
AR CULVERT	7+00	7+50	6.5	4.9	8.5	-3.6
AR CULVERT	7+50	7+90	9.7	7.3	12.8	-5.5
AR CULVERT	7+90	7+94.58	1.5	1.1	1.3	-0.2
AR CULVERT	7+94.58	8+00	1.8	1.4	1.0	0.4
AR CULVERT	8+00	8+50	14.5	10.9	7.3	3.6
AR CULVERT	8+50	9+00	13.6	10.2	2.5	7.7
AR CULVERT	9+00	9+50	9.7	7.3	2.4	4.9
AR CULVERT	9+50	9+50.1	0.0	0.0	0.0	0.0
<u>TOTAL</u>			293.8	220.4	245.3	-25.0
<u>USE</u>			294.0	220.0	245.0	-25.0

* FURNISHED EXCAVATION = EARTH EXCAVATION X ADJUSTMENT FOR SHRINKAGE (0.75) - EMBANKMENT

PLAN NOTES

THE INCIDENTAL BITUMINOUS SURFACE IS INTENDED TO RESURFACE THE EXISTING ENTRANCES, MAILBOX TURNOUTS AND SIDE ROADS IN THEIR ENTIRETY.

AGGREGATE SHOULDERS SHALL EXTEND 4' BEHIND INCIDENTAL BITUMINOUS SURFACE AREAS OR AS DIRECTED BY THE ENGINEER.

AGGREGATE SHOULDERS TYPE B WILL BE CARRIED AROUND THE RADII OF SIDE ROADS OR PLACED AS DIRECTED BY THE ENGINEER.

ALL BUTT JOINTS AND THEIR LOCATIONS ARE ILLUSTRATED BY DETAILS.

SCHEDULE OF INCIDENTAL ASPHALT SHALL BE USED IN ACCORDANCE WITH DETAILS SHOWN IN PLANS.

ALL TIE POINTS ASSOCIATED WITH PERMANENT SURVEY MARKERS TO BE ADJUSTED AND SHOWN HERE IN THE PLANS SHALL BE VERIFIED FOR ACCURACY IN THE FIELD BY ENGINEER.

LOCATIONS FOR SURVEY MARKER VAULTS SHALL BE LOCATED IN THE FIELD AND TIED OUT BY ENGINEER PRIOR TO RESURFACING.