

AGGREGATE SHOULDERS, TYPE B

STATION TO STATION	SIDE	LENGTH FT	CU. YD.	TON
10+21.59	11+03.85	LT	93.6	5.1
10+18.34	10+78.64	RT	74.5	4.1
11+55.80	11+80.81	RT	22.5	1.2
11+78.90	12+67.67	LT	88.8	4.9
12+16.22	12+69.20	RT	53.0	2.9
TOTAL				37.3
USE				38.0

AGGREGATE SURFACE COURSE, TYPE B

STATION	SIDE	AREA SQ. YD.	TON
12+05	RT	75.7	25.8
TOTAL			25.8
USE			26

BITUMINOUS BASE COURSE SUPERPAVE, 7"

STATION TO STATION	SQ. YD.
10+46.00	10+91.24
11+68.40	13+04.11
TOTAL	660

BITUMINOUS SURFACE REMOVAL - BUTT JOINT

STATION TO STATION	AREA SQ YD
10+19.98	10+29.99
TOTAL	65.1
USE	66

REMOVE EXISTING CULVERTS

STATION	SIDE	SIZE	TYPE	LIN FT
11+94.49	RT	12"	CMP	18.7
TOTAL				18.7
USE				19

COMBINATION CURB & GUTTER REMOVAL

STATION	STATION	SIDE	LENGTH (FEET)
12+86.42	13+02.59	LT	38.8
12+84.54	13+04.11	RT	39.3
TOTAL			78.1
USE			79

COMBINATION CONCRETE CURB & GUTTER, TYPE B-6.12

STATION TO STATION	SIDE	LENGTH (FEET)
12+67.7	13+02.66	LT
12+69.2	13+04.11	RT
TOTAL		98.7
USE		99

EROSION CONTROL SCHEDULE

STATION	SIDE	PERIMETER EROSION BARRIER FEET	TEMPORARY DITCH CHECKS EACH	INLET AND PIPE PROTECTION EACH
10+20 TO 10+70	RT	70		
10+95	LT		1	
11+20	RT		1	
11+30	LT		1	
11+04 TO 11+23	LT	30		
11+23 TO 11+54	RT	42		
11+70	RT		1	
11+77 TO 11+90	LT	23		
12+15	LT		1	
12+11.5	RT			1
12+50	RT		1	
TOTAL		165	6	1

PAVEMENT REMOVAL

STATION TO STATION	SIDE	PAVEMENT REMOVAL SQ YD
10+18.35	10+41.76	RT
10+81.69	10+89.23	LT & RT
12+85.48	13+03.40	LT & RT
TOTAL		75.4
USE		76

PORTLAND CEMENT CONCRETE SIDEWALK, 4 INCH

STATION TO STATION	SIDE	WIDTH FEET	LENGTH FEET	AREA SQ. FT.
12+84.85 TO 13+01.09	LT	5.0	26.4	132.0
12+84.35 TO 13+00.24	RT	5.0	27.1	136.0
TOTAL				268.0
USE				268

SIDEWALK REMOVAL

STATION	SIDE	WIDTH FEET	LENGTH FEET	AREA SQ. FT.
12+98.48	LT	5	26.0	130.0
12+97.65	RT	5	24.1	120.5
TOTAL				250.5
USE				251

SUBBASE GRANULAR MATERIAL, TYPE A

STATION TO STATION	THICK	SQ. YD.	TON
10+41.70	10+72.00	4"	19.8
10+59.00	10+72.00	0' TO 4"	33.5
10+72.00	10+91.24	4"	68.8
11+68.40	13+04.11	4"	538.6
TOTAL			146.7
USE			147

BITUMINOUS SURFACING SCHEDULE

STATION TO STATION	BITUMINOUS CONCRETE BINDER COURSE, IL-19.0 TONS	BITUMINOUS CONCRETE SURFACE COURSE, MIX "C" TONS	BITUMINOUS MATERIALS (PRIME COAT) GALLON
10+20 TO 10+91.2	39.8	25.6	12.7
10+91.2 TO 11+68.4		28.0	
11+68.4 TO 13+03.4	63.0	41.6	
TOTAL	102.8	95.2	12.7
USE	103	96	13

GUARDRAIL

STATION TO STATION	SIDE	TRAFFIC BARRIER TERMINAL		STEEL PLATE BEAM GUARDRAIL TYPE A FOOT	TERMINAL MARKER - DIRECT APPLIED EACH
		TYPE 5A EACH	TYPE 1 (SPECIAL) TANGENT EACH		
10+16.5	10+80.0	RT	2	87.5	
11+79.6	12+42.9	LT	1		1
CURLED END SECTION		RT			1
CURLED END SECTION		LT			1
TOTAL			3	87.5	3

SEEDING AND MULCH

LOCATION	SEEDING CLASS 1	NITROGEN FERTILIZER NUTRIENT	PHOSPHORUS FERTILIZER NUTRIENT	POTASSIUM FERTILIZER NUTRIENT	MULCH METHOD 2
	ACRE	POUND			ACRE
NW QUAD	0.05	5	5	5	0.05
SW QUAD	0.02	2	2	2	0.02
NE QUAD	0.08	8	8	8	0.08
SE QUAD	0.04	4	4	4	0.04
TOTAL	0.19	19	19	19	0.19
USE	0.25	22	22	22	0.25

PROTECTIVE COAT

ITEM	SQ YD
PCC SIDEWALK	29.8
C & G, TYPE B-6.12	22.0
TOTAL	51.8
USE	52

EARTHWORK

STATION TO STATION	EARTH EXCAVATION	ADJUSTED EXCAVATION (EXCAVATION X 0.75)	EMBANKMENT	BALANCE WASTE(+) OR SHORTAGE(-)
CU. YD.				
WEST CHAMBERS STREET				
10+20.00	13+03.40	127	95	274
TOTAL		127	95	274
USE		130	95	275

NOTE: QUANTITY FOR DRIVEWAY AT STATION 12+08 HAS BEEN INCLUDED

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

WEST CHAMBERS STREET SCHEDULE OF QUANTITIES

SCALE: VERT. HORIZ. DATE

DRAWN BY CHECKED BY