



SOIL BORING LOG

Page 1 of 2

Date 7/2/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AC

SECTION 60-1B-1 LOCATION SEC.29, TWP. 4N, RNG. 9W, PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for Depth (ft), Soil Description, and Test Results (B, U, M, O, S, I, T). Includes data for Forrest Soil, Brown SILT, Wet Density, Brown Fat CLAY, Brown CLAYEY SAND, and Brown Fine to Medium SAND.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 7/2/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AC

SECTION 60-1B-1 LOCATION SEC.29, TWP. 4N, RNG. 9W, PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for Depth (ft), Soil Description, and Test Results (B, U, M, O, S, I, T). Includes data for Gray Fine to Coarse SAND, Trace Gravel, and Gray Fine to Coarse SAND.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 2

Date 7/6/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AOT

SECTION 60-1B-1 LOCATION SEC.29, TWP. 4N, RNG. 9W, PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for Depth (ft), Soil Description, and Test Results (B, U, M, O, S, I, T). Includes data for Forrest Soil, Brown SANDY SILT, Brown Lean CLAY, Brown Fat CLAY, Brown SANDY SILT, Brown Fine to Medium SAND, Trace Silt, and Brown Fine SAND, Trace Silt.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 7/6/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AOT

SECTION 60-1B-1 LOCATION SEC.29, TWP. 4N, RNG. 9W, PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for Depth (ft), Soil Description, and Test Results (B, U, M, O, S, I, T). Includes data for Gray Fine to Coarse SAND, Trace Silt, Gray Medium to Coarse SAND, Trace Gravel, and Gray-brown Fine to Coarse SAND, Trace Gravel.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)

Table with columns: FILE NAME, USER NAME, DESIGNED, CHECKED, DRAWN, PLOT DATE, REVISED, CHECKED.

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

SOIL BORING LOGS STRUCTURE NO. 060-W008 SHEET NO. 14 OF 19 SHEETS

Table with columns: F.A.I. RTE., SECTION, COUNTY, TOTAL SHEETS, SHEET NO., CONTRACT NO.