



SOIL BORING LOG

Page 1 of 2

Date 7/14/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AQT

SECTION 60-1B-1 LOCATION SEC.29,TWP.4N,RNG.9W,PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for STRUCT. NO., Station, BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with depth and blow count data.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 7/14/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AQT

SECTION 60-1B-1 LOCATION SEC.29,TWP.4N,RNG.9W,PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for STRUCT. NO., Station, BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with depth and blow count data.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 2

Date 7/15/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AQT

SECTION 60-1B-1 LOCATION SEC.29,TWP.4N,RNG.9W,PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for STRUCT. NO., Station, BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with depth and blow count data.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 7/15/10

ROUTE I-270 DESCRIPTION I-270 CORC Retaining Wall LOGGED BY AQT

SECTION 60-1B-1 LOCATION SEC.29,TWP.4N,RNG.9W,PM

COUNTY Madison DRILLING METHOD HSA/Mud Rotary HAMMER TYPE Automatic

Table with columns for STRUCT. NO., Station, BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with depth and blow count data.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206) BBS, from 137 (Rev. 8-99)