

INDEX OF SHEETS	
SHEET NO.	DESCRIPTION
1	COVER SHEET
2	INDEX, GENERAL NOTES AND HIGHWAY STANDARDS
3	SUMMARY OF QUANTITIES
4	TYPICAL SECTION
5	DRAINAGE IMPROVEMENTS PLAN
6	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT (BD24)
7	ARTERIAL ROAD INFORMATION SIGN (TC22)

HIGHWAY STANDARDS	
STD. NO.	TITLE
602011-01	CATCH BASIN, TYPE C
602401-02	MANHOLE, TYPE A
604001-03	FRAME AND LIDS, TYPE 1
604091-02	FRAME AND GRATE, TYPE 24
606001-04	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
701606-06	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN
701701-06	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701801-04	LANE CLOSURE, MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
701901-01	TRAFFIC CONTROL DEVICES

- GENERAL NOTES**
- BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "J.U.L.I.E." AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES AND THE CITY OF LOCKPORT AT 815-838-0549 FOR FIELD LOCATIONS OF SANITARY SEWER AND WATER MAIN. (48 HOUR NOTIFICATION IS REQUIRED).
 - THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES.
 - THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.
 - WHEN ARTIFICIAL LIGHTING IS USED IN NIGHT OPERATIONS THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.
 - THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.
 - FOR PAVEMENT MARKING AND RAISED REFLECTIVE PAVEMENT MARKERS, REFER TO DISTRICT ONE TYPICAL MARKINGS FOR DETAILS NOT SHOWN.
 - MATCH EXISTING PAVEMENT MARKINGS AT PROJECT LIMITS.
 - EXCAVATED MATERIAL FROM THE JOB SITE WILL BE DISPOSED OF AT THE JOLIET MAINTENANCE YARD, LOCKPORT, ILLINOIS.

HOT-MIX ASPHALT MIXTURE REQUIREMENTS	
MIXTURE TYPE	AIR VOIDS
CLASS D PATCHES	
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70, 1 1/2"	4% @ 70 GYR
HOT-MIX ASPHALT BINDER COURSE, 19.0mm, N70, 12 1/2 INCH	4% @ 70 GYR

THE UNIT WEIGHT USED TO CALCULATE ALL HOT-MIX ASPHALT SURFACE MIXTURE A IS 112 LBS/SQ YD/IN.

THE "AC TYPE" FOR POLYMERIZED HMA MIXES SHALL BE "SBS/SBR PG 70-22" AND FOR NON-POLYMERIZED HMA THE "AC TYPE" SHALL BE "PG 64-22" UNLESS MODIFIED BY DISTRICT ONE SPECIAL PROVISIONS.

FILE NAME =	USER NAME = .USER.	DESIGNED - EF	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	IL 171 (STATE STREET) INDEX OF SHEETS, HIGHWAY STANDARDS AND GENERAL NOTES			F.A.P. RTE. 577	SECTION DY-T-1	COUNTY WILL	TOTAL SHEETS 7	SHEET NO. 2
#FILE#	PLOT SCALE = 20.0000' / IN.	DRAWN - EF	REVISED -		SCALE: 20	SHEET NO. 1 OF 1 SHEETS	STA.	TO STA.	CONTRACT NO. 60K74			
	PLOT DATE = 5/3/2010	CHECKED - RS	REVISED -		ILLINOIS FED. AID PROJECT							
		DATE - 04-26-2010	REVISED -									