

MAINLINE SCHEDULE															
LOCATION (MILE POST)(S)	Length	CENTERLINE		RIGHT EOP		LEFT EOP (1)		BIT MATERIALS PR CT	RAISED REFLECTIVE PVT MK REM	EPOXY PVT MK- LINE 4"	WET REFLECTIVE PREFORM. PLASTIC PVT MK-LINE 6"	EPOXY PVT MK- LINE 8" (2)	SHORT TERM PVT MARKINGS (4)	MIX CRACKS JTS & FLGWYS	
		PERCENT OF TOTAL LENGTH REQUIRED	MICROSURF SINGLE PASS TYPE II	PERCENT OF TOTAL LENGTH REQUIRED	MICROSURF SINGLE PASS TYPE II	PERCENT OF TOTAL LENGTH REQUIRED	MICROSURF SINGLE PASS TYPE II								
		FT	SQ YD	SQ YD	SQ YD	SQ YD	SQ YD								
<b>EASTBOUND</b>															
45.6	47.9	12144	5	134.9	100	2698.7	0	227	8	12144	3036		4008	7.7	
47.9	49.2	6864	5	76.3	5	76.3	0	12	5	6864	1716		2265	0.4	
49.2	55.5	33264	5	369.6	100	7392.0	0	621	21	33264	8316		10977	21.0	
55.5	58.0	13200	100	2933.3	100	2933.3	0	469	165	13200	3300		4356	15.8	
58.7	61.6	15312	100	3402.7	100	3402.7	0	544	192	15312	3828		5053	18.4	
<b>WESTBOUND</b>															
45.6	55.5	52272	10	1161.6	100	11616.0	0	1022	87	52272	13068		17250	34.5	
55.5	58.0	13200	100	2933.3	100	2933.3	0	469	165	13200	3300		4356	15.8	
58.7	61.6	15312	100	3402.7	100	3402.7	0	544	192	15312	3828		5053	18.4	
				14414		34455	0	450	3910	835	161568	40392	2000	53317	132

1. ALTHOUGH THE PRELIMINARY SURVEY INDICATED NO MICROSURFACING REQUIRED ON LEFT EOP, THE CONTRACTOR SHOULD BE PREPARED TO PERFORM A MINIMAL AMOUNT OF WORK ON THIS SIDE
2. TO BE USED AS NEEDED NEAR GORE AREA OF EXIST AND ENTRANCE RAMPS-SEE DETAIL
3. THE CENTERLINE AND RIGHT EDGE LINE INDICATED ABOVE SHALL ALL BE RESTRIPEDED
4. A 8' DIAGONAL STRIPE SHALL BE PLACED IN THE 10' SHOULDER EVERY 100'
5. OMIT MICROSURFACING FROM MM 58.0 TO MM 58.7. THIS AREA IS SCHEDULED FOR INTERMITTANT RESURFACING LATER IN THE YEAR