

INDEX OF SHEETS

1	COVER SHEET
2	INDEX OF SHEETS, HIGHWAY STANDARDS, GENERAL NOTES AND COMMITMENTS
3-5	SUMMARY OF QUANTITIES
6-9	SCHEDULES OF QUANTITIES
10-15	TYPICAL SECTIONS
16-33	PLAN SHEETS
34	STAGING PLAN (SN 086-0023/24)
35-42	STRUCTURAL DETAILS
43-48	MISCELLANEOUS DETAILS

GENERAL NOTES

- THE STANDARDS AND REVISION NUMBERS LISTED SHALL APPLY TO THIS PROJECT.
- THE THICKNESS OF THE HMA MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA MIXTURE IS PLACED.
- "ROAD CONSTRUCTION AHEAD" SIGNS SHALL BE PLACED AT THE BEGINNING AND END OF THE MAINLINE CONSTRUCTION SECTIONS AND THE CROSSOVER SIDE ROAD CONSTRUCTION LIMITS, AS DIRECTED BY THE RESIDENT ENGINEER. ALL CONSTRUCTION SIGNS SHALL BE FLUORESCENT ORANGE 48". THIS SHALL BE INCLUDED IN THE COST OF THE TRAFFIC CONTROL AND PROTECTION.
- THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

LOCATION	I-72 & US 67	I-72 & US 67	I-72	I-72 (2") & US 67 (1 1/2")	US 67 (2 1/4")	I-72 & US 67
MIXTURE USE	POLYMER HMA SURFACE COURSE	POLYMER HMA BINDER COURSE	HMA BASE COURSE	HMA SHOULDER (TOP LIFT)	HMA SHOULDER (BOTTOM LIFT)	INCIDENTAL SURFACE
PG	SBS PG 70-22	SBS PG 70-22	PG 64-22	PG 64-22	PG 58-22	PG 64-22
DESIGN AIR VOIDS	4.0% @ N DESIGN = 90	4.0% @ N DESIGN = 90	4.0% @ N DESIGN = 90	4.0% @ N DESIGN = 50	2.0% @ N DESIGN = 30	4.0% @ N DESIGN = 50
MIX COMPOSITION (GRADATION MIXTURE)	IL 9.5 OR 12.5	IL 19.0	IL 19.0	IL 9.5 OR 12.5	BAM	IL 9.5 OR 12.5
FRICTION AGGREGATE	MIX "D"	N/A	N/A	MIX "C"	N/A	MIX "C"

PLAN QUANTITIES FOR BITUMINOUS CONCRETE SURFACE COURSE ITEMS ARE CALCULATED USING A UNIT WEIGHT OF 112 LB/SQ YD/IN (59.8 KG/SO M/25 mm THICKNESS).

- THE ENGINEER WILL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE VARIOUS HMA LIFTS.
- THIS PROJECT CONTAINS ONE STATION EQUATION: PI STA. 443+19.48 BK= PI STA. 10+03.94 AH (I-72)
- ENGLISH UNITS OF MEASUREMENT SHALL GOVERN OVER AND SUPERSEDE ANY METRIC UNITS SHOWN IN THIS CONTRACT. WHERE INCLUDED, METRIC UNITS ARE FOR INFORMATION ONLY.
- THE NEW HMA PAVEMENT SHALL BE CONSTRUCTED WITH THE SAME SUPERELEVATION RATES AS THE EXISTING PAVEMENT AS SHOWN IN THESE PLANS.
- ALL TEMPORARY PAVEMENT MARKING WILL BE PLACED IN SUCH A MANNER SO AS NOT TO INTERFERE WITH THE PLACEMENT OF PERMANENT PAVEMENT MARKINGS.
- THE CONTRACTOR SHALL BE AWARE THAT EXISTING CONCRETE PATCHES SHALL BE MILLED AS PART OF THE PROPOSED HMA SURFACE REMOVAL AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED FOR THE MILLING OF THE CONCRETE.

11. THE FOLLOWING RATES OF APPLICATION HAVE BEEN USED IN CALCULATING PLAN QUANTITIES:

GRANULAR MATERIALS	2.05	TONS / CU YD
BITUMINOUS MAT PRIME COAT	0.00038	TON / SO YD (PAVEMENT) OR
	0.001425	TON / SO YD (AGG. SURFACE)
AGGREGATE PRIME COAT	0.002	TONS / SO YD
HMA RESURFACING	112	LBS / SO YD / IN
SHORT TERM PAVEMENT MARKING	4	FT / 40 FT OF APPLICATION

12. ONLY THOSE TREES DESIGNATED BY THE ENGINEER OR LISTED IN THE TREE REMOVAL SCHEDULE SHALL BE REMOVED. THE CONTRACTOR SHALL PROTECT ALL REMAINING TREES FROM DAMAGE DUE TO HIS OPERATIONS.

13. THE CONTRACTOR AND THE ENGINEER SHALL BE AWARE THAT NO SURVEY WAS PERFORMED FOR THIS PROJECT. THE STATIONING AND TOPO SHOWN IN THE PLANS WERE CREATED USING MICROFILM AND FIELD MEASUREMENTS MADE BY DESIGN PERSONAL. BOTH SHOULD BE CONSIDERED APPROXIMATE.

14. THE QUANTITY FOR OUTLET MARKERS IS BASED ON THE TOTAL LENGTH OF THE PROJECT (TIMES 4 PAVEMENT EDGES) DIVIDED BY 500 FEET AS PER ARTICLE 601.04 OF THE STANDARD SPECIFICATIONS FOR PIPE UNDERDRAIN OUTLETS.

HIGHWAY STANDARDS

000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
001001-02	AREAS OF REINFORCEMENT BARS
001006	DECIMAL OF AN INCH AND OF A FOOT
280001-05	TEMPORARY EROSION CONTROL SYSTEMS
442001-04	CLASS A PATCHES
630001-08	STEEL PLATE BEAM GUARDRAIL
630301-05	SHOULDER WIDENING FOR TYPE 1 (SPECIAL) GUARDRAIL TERMINALS
631011-06	TRAFFIC BARRIER TERMINAL, TYPE 2
635006-03	REFLECTOR AND TERMINAL MARKER PLACEMENT
635011-02	REFLECTOR MARKER AND MOUNTING DETAILS
642001-01	SHOULDER RUMBLE STRIPS
701101-02	OFF-RD OPERATIONS, MULTILANE, 15' (4.5 m) TO 24" (600 mm) FROM PAVEMENT EDGE
701106-02	OFF-RD OPERATIONS, MULTILANE, MORE THAN 15' (4.5 m) AWAY
701201-03	LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS ≥ 45 MPH
701400-04	APPROACH TO LANE CLOSURE, FREEWAY/EXPRESSWAY
701401-05	LANE CLOSURE, FREEWAY/EXPRESSWAY
701402-07	LANE CLOSURE, FREEWAY/EXPRESSWAY WITH BARRIER
701406-05	LANE CLOSURE, FREEWAY/EXPRESSWAY, DAY OPERATIONS ONLY
701411-06	LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT RAMP, FOR SPEEDS ≥ 45 MPH
701426-03	LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER., FOR SPEEDS ≥ 45 MPH
701901-01	TRAFFIC CONTROL DEVICES
704001-06	TEMPORARY CONCRETE BARRIER
720011-01	METAL POSTS FOR SIGNS, MARKERS & DELINEATORS
780001-02	TYPICAL PAVEMENT MARKINGS
781001-03	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

COMMITMENTS


1. THE FIELD/RESIDENT ENGINEER SHALL CONTACT STUDIES & PLANS CONCERNING ANY MAJOR PLAN CHANGES TO MAKE SURE NO PREVIOUS COMMITMENTS (NOT LISTED) WERE MADE AFFECTING THE DESIGN AND TO ALLOW IMPROVEMENT IN THE DESIGN FOR FUTURE PROJECTS.

2. INFORMATIONAL LETTER TO JACKSONVILLE.

DISTRICT SIX	
EXAMINED <u>APR 1</u> 20 <u>10</u>	
OPERATIONS ENGINEER	
EXAMINED <u>MARCH 25</u> 20 <u>10</u>	
PROGRAM IMPLEMENTATION ENGINEER	
EXAMINED <u>April 6</u> 20 <u>10</u>	
PROGRAM DEVELOPMENT ENGINEER	

• 86-10RS-3, 69-6RS-2, 69-1RS
•• SCOTT, MORGAN

FILE NAME =	USER NAME = SJS	DESIGNED -	REVISED -
...N0672C16-shr-gennote.dgn		DRAWN -	REVISED -
	PLOT SCALE = 100.0000 "/ IN.	CHECKED -	REVISED -
	PLOT DATE = 04/02/2010 08:48:41	DATE -	REVISED -



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

INDEX OF SHEETS, HIGHWAY STANDARDS,
GENERAL NOTES AND COMMITMENTS

SCALE: SHEET NO. OF SHEETS STA. TO STA.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
72			48	2
FED. ROAD DIST. NO.			ILLINOIS FED. AID PROJECT	
			CONTRACT NO. 72A16	