

PAVEMENT PATCHING SCHEDULE

STATION	LANE					LENGTH (FT)	WIDTH (FT)	PARTIAL DEPTH REMOVAL 3" (SQ YDS)	PARTIAL DEPTH (TON)
	EB		BI-DIR	WB					
	DL	PL		PL	DL				
129+80.				X		4	6	2.7	0.4
133+50.				X		4	4	1.8	0.3
133+50.				X		4	4	1.8	0.3
134+50.				X		4	4	1.8	0.3
134+50.				X		4	4	1.8	0.3
141+20.	X			X		4	20	8.9	1.5
141+20.				X		4	4	1.8	0.3
141+50.				X		4	4	1.8	0.3
141+80.				X		4	4	1.8	0.3
142+20.		X				4	12	5.3	0.9
142+50.				X		4	12	5.3	0.9
142+50.				X		4	12	5.3	0.9
142+60.			X			4	12	5.3	0.9
*143+90	X					3	70	23.3	3.9
*143+90				X		3	70	23.3	3.9
145+20.				X		4	4	1.8	0.3
145+30.				X		4	6	2.7	0.4
145+80.				X		4	8	3.6	0.6
146+10.				X		4	10	4.4	0.7
147+30.				X		4	6	2.7	0.4
147+40.				X		4	8	3.6	0.6
149+70.				X		4	10	4.4	0.7
149+90.				X		4	10	4.4	0.7
151+20.	X					4	6	2.7	0.4
151+20.				X		4	4	1.8	0.3
151+40.		X				4	6	2.7	0.4
151+40.			X			4	4	1.8	0.3
152+10.	X					4	6	2.7	0.4
152+10.				X		4	4	1.8	0.3
152+50.				X		4	4	1.8	0.3
153+10.			X			4	4	1.8	0.3
153+20.				X		4	4	1.8	0.3
153+50.				X		4	4	1.8	0.3
153+50.				X		4	4	1.8	0.3
154+10.		X				4	8	3.6	0.6
154+10.				X		4	6	2.7	0.4
155+20.				X		4	12	5.3	0.9
157+20.				X		4	6	2.7	0.4
157+24.				X		4	6	2.7	0.4
157+50.				X		4	6	2.7	0.4
157+50.				X		4	8	3.6	0.6
158+90.				X		4	6	2.7	0.4
159+10.			X			4	6	2.7	0.4
159+25.				X		4	6	2.7	0.4
159+90.				X		4	6	2.7	0.4
161+10.				X		4	6	2.7	0.4
161+30.			X			4	6	2.7	0.4
161+50.				X		4	6	2.7	0.4
161+90.				X		4	6	2.7	0.4
162+50.			X			4	6	2.7	0.4
162+90.				X		4	6	2.7	0.4
163+30.				X		4	6	2.7	0.4
165+25.				X		6	20	13.3	2.2
165+55.				X		6	20	13.3	2.2
166+20.	X					4	8	3.6	0.6
166+50.				X		6	12	8.0	1.3
168+20.				X		4	12	5.3	0.9
168+40.			X			4	10	4.4	0.7
168+50.				X		4	10	4.4	0.7
169+20.				X		4	6	2.7	0.4
169+50.				X		4	6	2.7	0.4
169+90.				X		4	6	2.7	0.4
170+20.				X		4	6	2.7	0.4
170+50.				X		4	12	5.3	0.9
172+50.				X		4	6	2.7	0.4
172+80.				X		4	6	2.7	0.4

PAVEMENT PATCHING SCHEDULE

STATION	LANE					LENGTH (FT)	WIDTH (FT)	PARTIAL DEPTH REMOVAL 3" (SQ YDS)	PARTIAL DEPTH (TON)
	EB		BI-DIR	WB					
	DL	PL		PL	DL				
173+10.				X		4	6	2.7	0.4
173+50.				X		4	6	2.7	0.4
174+50.				X		4	8	3.6	0.6
174+80.				X		4	8	3.6	0.6
175+20.				X		4	6	2.7	0.4
175+90.						4	6	2.7	0.4
*177+66					X	4	60	26.7	4.5
*177+66	X					4	60	26.7	4.5
181+20.	X					4	12	5.3	0.9
182+50.				X		4	6	2.7	0.4
182+80.			X			4	12	5.3	0.9
182+91.			X			4	12	5.3	0.9
183+20.				X		4	6	2.7	0.4
183+50.				X		4	6	2.7	0.4
183+80.				X		4	6	2.7	0.4
184+30.				X		4	6	2.7	0.4
185+50.	X					4	6	2.7	0.4
185+50.				X		4	8	3.6	0.6
185+70.	X					4	6	2.7	0.4
185+70.				X		4	8	3.6	0.6
186+35.				X		4	6	2.7	0.4
186+75.				X		4	6	2.7	0.4
187+50.	X					4	8	3.6	0.6
187+50.				X		4	8	3.6	0.6
188+50.				X		4	8	3.6	0.6
188+50.			X			4	6	2.7	0.4
189+50.			X			4	6	2.7	0.4
189+50.				X		4	6	2.7	0.4
189+50.	X					4	6	2.7	0.4
190+20.				X		4	6	2.7	0.4
190+50.				X		4	6	2.7	0.4
190+90.				X		4	6	2.7	0.4
191+30.	X					4	6	2.7	0.4
191+50.		X				4	6	2.7	0.4
193+50.				X		4	6	2.7	0.4
193+50.				X		4	6	2.7	0.4
194+20.				X		4	6	2.7	0.4
194+50.				X		4	6	2.7	0.4
194+50.	X					6	12	8.0	1.3
197+22.	X					6	12	8.0	1.3
198+30.			X			4	8	3.6	0.6
198+60.				X		4	8	3.6	0.6
199+30.				X		4	6	2.7	0.4
199+60.				X		4	6	2.7	0.4
202+30.				X		4	6	2.7	0.4
202+60.				X		4	6	2.7	0.4
202+90.				X		4	6	2.7	0.4
203+30.			X			4	6	2.7	0.4
204+30.				X		4	12	5.3	0.9
204+60.				X		4	8	3.6	0.6
204+90.				X		4	6	2.7	0.4
205+30.				X		4	6	2.7	0.4
205+31.	X					4	6	2.7	0.4
205+60.				X		4	6	2.7	0.4
205+90.				X		4	8	3.6	0.6
206+90.				X		4	6	2.7	0.4
207+30.				X		4	6	2.7	0.4
207+60.				X		4	4	1.8	0.3
211+30.				X		4	12	5.3	0.9
211+60.				X		4	4	1.8	0.3
211+90.				X		4	4	1.8	0.3
212+30.				X		4	4	1.8	0.3
212+60.				X		4	4	1.8	0.3
212+90.				X		4	6	2.7	0.4
213+30.	X					6	6	4.0	0.7
213+60.		X				6	6	4.0	0.7

PAVEMENT PATCHING SCHEDULE

STATION	LANE					LENGTH (FT)	WIDTH (FT)	PARTIAL DEPTH REMOVAL 3" (SQ YDS)	PARTIAL DEPTH (TON)
	EB		BI-DIR	WB					
	DL	PL		PL	DL				
216+50.				X		4	6	2.7	0.4
216+60.				X		4	6	2.7	0.4
216+90.				X		4	6	2.7	0.4
*217+32	X					3	75	25.0	4.2
218+30.				X		4	4	1.8	0.3
218+30.				X		4	4	1.8	0.3
218+80.				X		6	12	8.0	1.3
219+40.				X		6	12	8.0	1.3
219+80.				X		6	12	8.0	1.3
221+30.				X		4	6	2.7	0.4
221+60.				X		4	6	2.7	0.4
222+90.				X		4	4	1.8	0.3
224+50.				X		4	8	3.6	0.6
225+90.				X		4	20	8.9	1.5
226+90.				X		4	20	8.9	1.5
227+50.				X		4	4	1.8	0.3
227+80.				X		4	4	1.8	0.3
228+50.				X		4	12	5.3	0.9
229+30.				X		4	10	4.4	0.7
229+60.				X		4	12	5.3	0.9
229+90.				X		4	12	5.3	0.9
230+10.	X					4	6	2.7	0.4
230+90.				X		4	10	4.4	0.7
231+30.				X		4	4	1.8	0.3
231+60.				X		4	4	1.8	0.3
231+90.	X					4	6	2.7	0.4
232+30.		X				4	6	2.7	0.4
232+60.	X					4	6	2.7	0.4
233+30.			X			4	4	1.8	0.3
233+60.				X		4	4	1.8	0.3
233+90.				X		4	4	1.8	0.3
234+30.				X		4	8	3.6	0.6
234+60.	X					6	18	12.0	2.0
234+90.		X				6	18	12.0	2.0
236+30.			X			4	4	1.8	0.3
236+60.				X		4	4	1.8	0.3
236+90.				X		4	4	1.8	0.3
237+30.				X		4	4	1.8	0.3
237+90.			X			4	6	2.7	0.4
238+30.				X		4	4	1.8	0.3
238+60.				X		4	4	1.8	0.3
238+90.				X		4	4	1.8	0.3
240+45.				X		6	12	8.0	1.3
241+90.				X		4	4	1.8	0.3
242+30.				X		4	4	1.8	0.3
242+60.		</							