

LOCATION 1 SHOULDER SCHEDULE

LOCATION STATION TO STATION	LENGTH (FT)	SHOULDER WIDTH (FT)	AGG. SHLDRS., TY. A (1 1/2") (TON)	AGG. WEDGE SHLDRS., TY. B (See Note 1) (TON)
FAP 312 (IL 3) STA. 396+14.34 TO STA. 352+00				
396+14.34 TO 401+00.00	486	8.0	99	177
401+00.00 TO 424+32.12	2332	2.0		
Eq. Sta. 424+32.12 (bk) = Sta. 0+32.12 (ah)				
+32.12 TO 190+80.00	19048	2.0		1446
SN 039-2025 Omission - Sta. 193+56 to Sta. 194+51				
See Note 1				
Eq. Sta. 195+00 (bk) = Sta. 194+90.20 (ah)				
197+00.00 TO 225+85.96	2,886.0	2.0		219
Eq. Sta. 225+85.96 (bk) = Sta. 226+00.00 (ah)				
226+00.00 TO 271+72.54	4,572.5	2.0		347
Eq. Sta. 271+72.54 (bk) = Sta. 271+84.86 (ah)				
271+84.85 TO 352+00.00	8,015.2	2.0		609
LOCATION 1 TOTALS			99	2798

Note 1: Aggregate Wedge Shoulder, Ty. B shall be omitted left and right from Sta. 190+80 to Sta. 197+00 near SN 039-2025.

LOCATION 2 SHOULDER SCHEDULE

LOCATION STATION TO STATION	LENGTH (FT)	SHOULDER WIDTH (FT)	BIT. MAT. (PRIME COAT) (GAL)	AGG. (PRIME COAT) (TON)	HMA SHOULDRS (2.5") (TON)	AGG. WEDGE SHLDRS., TY. B (See Note 1) (TON)	NOTES
FAP 312 (IL 3) STA. 195+00 TO STA. 434+55							
Lt & Rt 195+00.00 TO 244+77.00	4977	10.0	995	16.6	1548		
SN 039-0048 Omission - Sta. 244+77 to Sta. 249+90							
Lt 249+90.00 TO 266+69.60	1680	10.0	168	2.8	261		
Rt 249+90.00 TO 266+69.60	1480	10.0	148	2.5	230		200' SRR
Eq. Sta. 266+69.6 (bk) = Sta. 283+92.2 (ah)							
Lt & Rt 283+92.20 TO 286+00.00	207.8	10.0	42	0.7	65		
Ex. PCC Pvt ends/ Bit. Surfaced Pvt begins - Sta. 286+00							
286+00.00 TO 327+37.00	4,137.0	2.0				314	
SN 039-0067 Omission - Sta. 327+37 to Sta. 333+96							
333+96.00 TO 434+55.00	10,059.0	2.0				764	
LOCATION 2 TOTALS			1353	22.6	2104	1078	

Note 1: The AGGREGATE WEDGE SHOULDERS are calculated at 3" depth due to erosion along existing edge of pavement.