



SOIL BORING LOG

Page 1 of 1

Date 10/4/05

ROUTE FAP 327 (IL 250) DESCRIPTION Un-named Stream LOGGED BY E. Sandschafer

SECTION 5B-1 LOCATION W 1/2, SEC. 6, TWP. 3 N, RNG. 10 E, 3 PM

COUNTY Richland DRILLING METHOD Hollow stem auger & split spoon HAMMER TYPE Auto 140#

Table with columns for STRUCT. NO., BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with associated elevations and SPT values.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 1 of 2

Date 10/4/05

ROUTE FAP 327 (IL 250) DESCRIPTION Un-named Stream LOGGED BY E. Sandschafer

SECTION 5B-1 LOCATION W 1/2, SEC. 6, TWP. 3 N, RNG. 10 E, 3 PM

COUNTY Richland DRILLING METHOD Hollow stem auger & split spoon HAMMER TYPE Auto 140#

Table with columns for STRUCT. NO., BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with associated elevations and SPT values.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)



SOIL BORING LOG

Page 2 of 2

Date 10/4/05

ROUTE FAP 327 (IL 250) DESCRIPTION Un-named Stream LOGGED BY E. Sandschafer

SECTION 5B-1 LOCATION W 1/2, SEC. 6, TWP. 3 N, RNG. 10 E, 3 PM

COUNTY Richland DRILLING METHOD Hollow stem auger & split spoon HAMMER TYPE Auto 140#

Table with columns for STRUCT. NO., BORING NO., Station, Offset, Ground Surface Elev., and soil descriptions with associated elevations and SPT values.

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer) The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)

BBS, from 137 (Rev. 8-99)