



OPTION 1



OPTION 2 TYPICAL TEMPORARY RAMP

(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)




TYPICAL BUTT JOINT AND HMA TAPER FOR MILLING AND RESURFACING


REVISED - R. SHAH 10-25-94 USER NAME = gaglianobt DESIGNED - M. DE YONG CHECKED -REVISED - A. ABBAS 03-21-97 PLOT SCALE = 50.0000 '/ IN. DRAWN REVISED - M. GOMEZ 04-06-01 PLOT DATE = 1/4/2008 CHECKED -- 06-13-90 REVISED -- R. BORO 01-01-07

FILE NAME = 08564-DTLS-05 - BD-32

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**

COUNTY **BUTT JOINT AND** 09-00117-00-RS COOK 10 10 HMA TAPER DETAILS BD400-05 BD32 CONTRACT NO. 63159 SHEET NO. 10 OF 10 SHEETS STA. TO STA. FED. ROAD DIST, NO. 1 ILLINOIS FED. AID PROJECT M-9003(219)





TYPICAL BUTT JOINT AND HMA TAPER FOR RESURFACING ONLY

* * PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT.

NOTES

- A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS.
- B: MINOR SIDE ROADS.
- C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE.
- D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES.
- E: TAPER THE TEMP. RAMP AT A RATE OF 3'-0" (900 mm) PER 1 INCH (25 mm) OF MILLING THICKNESS.
- F: INSTALLATION AND REMOVAL OF THE 4'-6" (1.35 m) TEMP. RAMP IS INCLUDED IN COST OF HMA SURFACE REMOVAL - BUTT JOINT
- G: SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".
- * SEE TYPICAL SECTIONS FOR MILLING THICKNESS.
- * * * 20'-0" (6.1 m) PER 1 (25) RESURFACING (NOTE "A") 10'-0" (3.0 m) PER 1 (25) RESURFACING (NOTE "B")

BASIS OF PAYMENT:

THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SQUARE YARD (SQUARE METER) FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT".

SCALE:

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN.