

GENERAL NOTES

THE WORK UNDER THIS CONTRACT CONSISTS OF THE FOLLOWING:

- DATUM USED FOR SURVEY IS U.S.G.S.
- ALL STATIONING IS ALONG CENTERLINE OF ROADWAY, EXCEPT AS OTHERWISE NOTED.
- ACCESS TO ENTRANCES - ACCESS TO ENTRANCES SHALL BE MAINTAINED BY THE USE OF TEMPORARY SURFACE AGGREGATE IN ACCORDANCE WITH ARTICLE 107.09 OF THE STANDARD SPECIFICATIONS. HOWEVER THE COST OF FURNISHING, PLACING AND REMOVING THE TEMPORARY SURFACE AGGREGATE WILL BE PAID FOR AT THE CONTRACT PRICE PER TON FOR AGGREGATE SURFACE COURSE TYPE B AND NO OTHER COMPENSATION WILL BE ALLOWED, AN ESTIMATED QUANTITY OF 400 TONS OF AGGREGATE SURFACE COURSE, TYPE B HAS BEEN INCLUDED IN THE PLANS FOR ACCESS PURPOSES.
- THE THICKNESS OF BITUMINOUS MIXTURES SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATION FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE BITUMINOUS MIXTURE IS PLACED.
- EXCEPT AS NOTED IN THE PLANS, PAVEMENT GRADES SHOWN ARE AT THE TOP OF PAVEMENT SURFACES.
- ALL EXCAVATION UNDER PAVEMENT, SIDEWALK, AND CURB & GUTTER SHALL BE BACKFILLED AND COMPACTED WITH MATERIAL MEETING THE REQUIREMENTS OF SECTION 209. SEPARATE PAYMENT FOR TRENCH BACKFILL SHALL BE MADE ONLY WHEN SPECIFIED IN THE PLANS.
- THE ENGINEER SHALL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE VARIOUS BITUMINOUS LIFTS.
- TEMPORARY MARKING TAPE SHALL BE USED FOR ALL TEMPORARY PAVEMENT MARKING ON FINAL SURFACE.
- ONLY THOSE TREES DESIGNATED BY THE ENGINEER OR LISTED IN THE TREE REMOVAL SCHEDULE SHALL BE REMOVED. THE CONTRACTOR WILL PROTECT ALL REMAINING TREES FROM DAMAGE DUE TO HIS OPERATIONS.
- ALL SAWCUTTING OF EXISTING PAVEMENT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT. THE MINIMUM SAW CUT DEPTH IN THE PAVEMENT SHALL BE 2 INCHES, UNLESS OTHERWISE SPECIFIED IN A DETAIL IN THE PLANS.
- THE CONTRACTOR SHALL PROVIDE TEMPORARY DRAINAGE.
- ALL REQUIRED SAW CUTTING SHALL BE INCIDENTAL TO THE REMOVAL PAY ITEM INVOLVED.
- FOR NEW CONSTRUCTION, PLACE SIDEWALK RAMPS FOR THE HANDICAPPED (STD 2356) AT ALL LOCATIONS WHERE PROPOSED SIDEWALK ABUTS CURB AT STREET ENTRANCES.
- THE EXISTING ROAD SIGNS THAT INTERFERE WITH CONSTRUCTION SHALL BE REMOVED OR RELOCATED AS DIRECTED BY THE ENGINEER. AFTER THE CONSTRUCTION IS COMPLETED, THE CONTRACTOR SHALL REPLACE THE SIGNS AS DIRECTED BY THE ENGINEER, THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO THE CONTRACT AND NO COMPENSATION WILL BE ALLOWED.
- ABANDONED UNDERGROUND UTILITY ITEMS WHICH CONFLICT WITH CONSTRUCTION SHALL BE DISPOSED OUTSIDE THE LIMITS OF THE RIGHT OF WAY ACCORDING TO ARTICLE 202.03 OF THE STANDARD SPECIFICATIONS, AND AS DIRECTED BY THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE CONSIDERED INCIDENTAL TO EARTH EXCAVATION AND NO ADDITIONAL COMPENSATION WILL BE ALLOWED.
- ANY REFERENCE TO A STANDARD IN THESE PLANS SHALL BE INTERPRETED TO MEAN THE EDITION AS INDICATED BY THE SUB-NUMBER LISTED IN THE INDEX OF SHEETS, OR THE COPY OF THE STANDARD INCLUDED IN THESE PLANS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING UTILITY PROPERTY FROM CONSTRUCTION OPERATIONS AS OUTLINED IN ARTICLE 107.31 OF THE STANDARD SPECIFICATIONS. THE JULIE NUMBER IS 1-800-892-0123. A MINIMUM OF FORTY EIGHT (48) HOURS ADVANCE NOTICE IS REQUIRED.
- ALL WATER MAINS SHALL BE PROTECTED FROM CONTAMINATION. STATE CODE SECTION 653.119 EXPLAINS THE METHODS OF PROTECTION AND WHEN THEY ARE REQUIRED.
- PROTECTIVE COAT SHALL BE APPLIED TO THE SURFACES OF NEW CONCRETE ACCORDING TO ARTICLES 420.21 AND/OR 503.21 OF THE STANDARD SPECIFICATIONS.
- THERMOPLASTIC PAVEMENT MARKINGS AND PAINT STRIPING QUANTITIES ARE APPROXIMATE ONLY. PAYMENT WILL BE MADE FOR ACTUAL QUANTITIES USED AS MEASURED IN THE FIELD.
- THE FOLLOWING UTILITY COMPANIES HAVE UTILITIES WITHIN THE LIMITS OF CONSTRUCTION. ADJUSTMENT OF UTILITY LOCATIONS WILL BE MADE BY THE OWNER, UNLESS OTHERWISE NOTED ON THE PLANS.

LEGEND

- IRON ROD RECOVERED
- ⊗ RIGHT-OF-WAY MARKER
- IRON PIPE RECOVERED
- ⊗ PK NAIL RECOVERED
- ⊗ EXIST. MAILBOX
- ⊗ EXIST. FLAG POLE
- ⊗ EXIST. GUY WIRE
- ⊗ EXIST. POWER POLE
- ⊗ EXIST. STREET LIGHT
- ⊗ EXIST. LIGHT POLE
- ⊗ EXIST. TELEPHONE PEDESTAL
- ⊗ EXIST. GAS VALVE
- ⊗ EXIST. FIRE HYDRANT
- ⊗ EXIST. WATER VALVE
- ⊗ EXIST. BUFFALO BOX
- ⊗ EXIST. WATER METER
- ⊗ EXIST. FLARED END SECTION
- ⊗ EXIST. INLET
- ⊗ EXIST. MANHOLE
- ⊗ EXIST. STOP SIGN
- ⊗ EXIST. SIGN
- ⊗ EXIST. DITCH FLOW LINE
- ⊗ GRADE
- ⊗ EXIST. SWALE FLOW LINE
- ⊗ TREE/BUSH
- ⊗ EXIST. TREE STUMP, SIZE
- ⊗ EXIST. CULVERT
- ⊗ EXIST. WATER
- ⊗ EXIST. STORM SEWER
- ⊗ EXIST. SANITARY SEWER
- ⊗ EXIST. FENCE
- ⊗ EXIST. EDGE OF PAVEMENT & SIDEWALK
- ⊗ EXIST. CURB & GUTTER
- ⊗ RIGHT OF WAY
- ⊗ (680.70) NEW SPOT ELEVATION
- ⊗ NEW STREET LIGHT
- ⊗ NEW FIRE HYDRANT
- ⊗ NEW WATER VALVE
- ⊗ NEW MANHOLE
- ⊗ NEW INLET
- ⊗ NEW FLARED END SECTION
- ⊗ NEW STORM SEWER
- ⊗ NEW EASEMENT
- ⊗ NEW AGGREGATE
- ⊗ NEW CURB & GUTTER
- ⊗ SURFACE REMOVAL
- ⊗ DETECTABLE WARNINGS FOR CURB RAMPS ON SIDEWALKS
- ⊗ REMOVE OBJECT

PAVEMENT DESIGN

BURNS ROAD
STA. 33+67 to STA. 53+33

Class II, 2-lane pavement
D.P. - 20 years
Design Traffic
Existing ADT: 0 1% growth
Proposed ADT: 6600
PV (85%): 5610 SU (10%): 660 MU (5%): 330
73,280 pound load limit
Critical subgrade Eri: 3ksi
T.F. = D.P. (0.073PV+44.53SU+156.403MU)
1,000,000


T.F. = 1.628
Subgrade support rating: fair
PG Binder grade for slow traffic: PG 64-22
mixture temperature: 78.5
Eac: 580
design strain: 90
Pavement thickness required: 10.25"

USE: 10.25"

UTILITY	STATUS OF RELOCATION		
	DATE		
POWER COMMONWEALTH EDISON CO. 2500 SOUTH GOVERNORS HIGHWAY UNIVERSITY PARK, IL 60466	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	
TELEPHONE AT&T 65 WEST WEBSTER JOLIET, IL 60431	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	
CABLE TV COMCAST 17700 HOFFMAN WAY HOMEWOOD, IL 60430	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	
GAS NORTHERN ILLINOIS GAS CO. 1844 FERRY ROAD NAPERVILLE, IL 60563	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO/ DURING CONSTRUCTION
	FINAL PLAN SET	4/13/07	
WATER AQUA ILLINOIS 1000 SOUTH SCHUYLER AVE. KANKAKEE, IL 60901	PRELIMINARY PLANS SET	1/27/06	RELOCATION PRIOR TO CONSTRUCTION
	FINAL PLAN SET	4/13/07	

	HMA Binder Burns Road	HMA Level Binder	HMA Surface Burns Road	HMA Surface US 45/52	HMA Base Course	HMA Shoulder
PG Grade	PG58-22	SBS/ PG70-22	PG64-22	SBS/ PG70-22	PG58-22	PG58-22
Max % RAP Allowable**	25%	10%	15%	10%	25%	40%
Design Air Voids	4.0% @ N50	4.0% @ N70	4.0% @ N50	4.0% @ N70	4.0% @ N50	2.0% @ N50
Mixture Composition	IL 19.0	IL 9.5	IL 12.5 or IL 9.5	IL 12.5 or IL 9.5	IL 19.0	BAM
Friction Aggregate	-	-	Mixture D	Mixture D	-	-
Density Test Method	Correlation	Satisfaction of Engineer	Correlation	Cores/ Nuclear	***	*

* Material shall be compacted to 93.0-97.4 percent of the maximum theoretical density, except that when placed as first lift on an unimproved subgrade the minimum percent compaction shall be 92.0 percent. The maximum theoretical density shall be determined from the moving average as specified in the QC/QA Specification.
** If RAP option is selected, the asphalt cement grade may need to be adjusted. This will be determined by the Engineer.
*** See standard specifications adopted January 1, 2007.

FAU. NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
*	**	KANKAKEE	41	2
CONTRACT NO. 87414				
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				
* BURNS ROAD WEST - FAU 6212				
** 03-00058-00-FP				
				
TYSON ENGINEERING, INC. CONSULTING CIVIL ENGINEERS LAND SURVEYORS DESIGN FIRM LICENSE #184-001136 367 SOUTH SCHUYLER AVENUE KANKAKEE, ILLINOIS 60901 PHONE (815) 932-7406				
This document and the ideas and designs incorporated herein, as an instrument of professional service, is the property of Tyson Engineering Inc. and is not to be used in whole or in part, for any other project without written authorization of Tyson Engineering Inc. Do not scale drawings. Use dimensions only. Contractor shall be responsible for verifying all dimensions. Information herein and herein is confidential.				
REVISIONS				
NO.	DATE	BY	DESCRIPTION	
1	3/12/07	MRG	PER IDOT REVIEW	
2	4/13/07	MRG	PER IDOT REVIEW	
3	4/9/09	MRG	PHASING	
COVER SHEET				
PROPOSED IMPROVEMENTS FOR BURNS ROAD WEST FROM BURNING BUSH DRIVE TO U.S. ROUTE 45/52				
SECTION 03-00058-00-FP				
DATE:	1/29/07	JOB NO.	E05055	
SCALE:	N/A	FILE NO.		
DRAWN BY:	MRG	SHEET	2	
CHECKED BY:	SRM		41	