


**SECTION THRU STRIP SEAL JOINT  
FOR OVERLAY OVER DECK BEAMS**



**LOCKING EDGE RAIL**



**LOCKING EDGE RAIL SPLICE**

**NOTES**

The strip seal shall be made continuous and shall have a minimum thickness of 1/4". The configuration of the strip seal shall match the configuration of the Locking Edge Rails.

The height and thickness of the Locking Edge Rails shown are minimum dimensions. The actual configuration of the Locking Edge Rails and matching strip seal may vary from manufacturer to manufacturer. Flanged edge rails will not be allowed.

The inside of the Locking Edge Rail groove shall be free of weld residue. Locking Edge Rails may be spliced at slope discontinuities and stage construction joints.

The manufacturer's recommended installation methods shall be followed. All steel components shall be galvanized after fabrication according to Article 520.03 of the Standard Specifications.

**BILL OF MATERIAL**

Item	Unit	Quantity
Preformed Joint Strip Seal	Foot	68

**PREFORMED JOINT STRIP SEAL  
F.A. RT. 782 SECTION 11BR-1  
GALLATIN COUNTY  
STATION 355+95.00  
STRUCTURE NO. 030-0018**

<b>COOMBE-BLOXDORF P.C.</b> Engineers / Land Surveyors Springfield, Illinois Design Firm License No. 184-002703	PROJECT NO.	07056-4
	DATE	4/17/08
	DRAWN BY	TFG
	CHECKED BY	GB/BD/MCB