DETAIL NO.	DESCRIPTION
------------	-------------

DRIVEWAY DETAILS - DISTANCE BETWEEN ROW AND FACE OF CURB & EDGE OF SHOULDER >= 15' (4.5 m)
DRIVEWAY DETAILS - DISTANCE BETWEEN ROW AND FACE OF CURB & EDGE OF SHOULDER < 15' (4.5 m)
OUTLET FOR CONCRETE CURB AND GUTTER
DETAIL OF STORM SEWER CONNECTION TO EXISTING SEWER
DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING 8007 BUTT JOINT AND HMA TAPER DETAILS BD36 FIRE HYDRANT TO BE MOVED PCC PAVEMENT ROUNDOUTS AT CURB & GUTTER BENCHING DETAIL FOR EMBANKMENT WIDENING DETAIL OF PAVEMENT SEPARATION JOINT FOR JOINTED PCC PAVEMENTS AT INTERSECTIONS TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS
TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
DISTRICT ONE TYPICAL PAVEMENT MARKINGS
TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING

ARTERIAL ROAD INFORMATION SIGN

DRIVEWAY ENTRANCE SIGNING STANDARD TRAFFIC SIGNAL DESIGN DETAILS

SHEET NO.	DESCRIPTION	REV.NO.	STD. NO.	DESCRIPTION
*	COVER SHEET	-04	000001	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
2	INDEX OF SHEETS & STATE STANDARDS	-07		TEMPORARY EROSION CONTROL SYSTEMS
3	GENERAL NOTES / COMMITMENTS	-07		PAYEMENT JOINTS
4 - 14	SUMMARY OF QUANTITIES	-04		24' (7.2 m) JOINTED PCC PAVEMENT 36' (10.8 m) JOINTED PCC PAVEMENT
15 - 27 28 - 40	TYPICAL SECTIONS SCHEDULE OF QUANTITIES	- 04		PCC PAVEMENT ROUNDOUTS
41 - 43	ALIGNMENT, TIES, AND BENCHMARKS	-07		PERPENDICULAR CURB RAMPS FOR SIDEWALKS
44 - 54	EXISTING ROADWAY AND REMOVAL PLANS	-01		MEDIAN PEDESTRIAN CROSSINGS
55 - 73	PROPOSED ROADWAY PLANS AND PROFILES	-03 -02		CLASS C AND D PATCHES HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT
74 - 80	ROADWAY DETAILS	-03		HMA SHOULDER ADJACENT TO RIGID PAVEMENT
81 ~ 144 145 ~ 207	STAGING AND TRAFFIC CONTROL FLANS STAGING AND TRAFFIC CONTROL CROSS SECTIONS	-03 -04 -03		PCC SHOULDER
208 - 249	EROSION CONTROL AND SEDIMENT CONTROL PLANS	-03		PRECAST REINFORCED CONCRETE FLARED END SECTION
250 - 269	DRAINAGE AND UTILITY PLANS AND PROFILES	-02		PRECAST REINFORCED CONCRETE ELLIPTICAL FLARED END SECTION SUB-SURFACE DRAINS
270 - 280	DRAINAGE SCHEDULE	-01		CONCRETE HEADWALL FOR PIPE DRAIN
281 - 285	DRAINAGE DETAILS			CATCH BASIN TYPE A
286 - 293 294 - 381	UTILITY PLANS BY SUE (SUBSURFACE UTILITY EXPLORATION PLAT OF HIGHWAYS			CATCH BASIN TYPE C
382 - 386		-04		INLET-TYPE A
387 - 412		-03 -03		INLET-TYPE B MANHOLE TYPE A
413 - 422	LANDSCAPING PLANS	-06		MANHOLE TYPE A 6' (1.8 m) DIAMETER
423 - 457	TRAFFIC SIGNAL PLANS	-04		MANHOLE TYPE A 8' (2.4 m) DIAMETER
	CITY OF WOODSTOCK EXISTING AND PROPOSED UTILITY PL	~ ~		VALVE VAULT TYPE A
472 - 488 489 - 673	DISTRICT ONE STANDARD DETAILS CROSS SECTIONS	U U		PRECAST REINFORCED CONCRETE FLAT SLAB TOP MANHOLE STEPS
103	0,1003 360,10113	- 02 - 03		FRAME AND LIDS TYPE 1
		~04		FRAME AND GRATE TYPE 3
		-02		GRATE TYPE 8
		- 02		FRAME AND GRATE TYPE 24 CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
		- 05 - 02		OUTLETS FOR CONCRETE CURB AND GUTTER TYPE 8-6.24 (8-15.60)
		-04		PC CONCRETE ISLANDS AND MEDIANS
		-03		CORRUGATED PC CONCRETE MEDIANS
		-01		PAVED DITCH REFLECTOR MARKER AND MOUNTING DETAILS
		- 01 - 01		SHOULDER RUMBLE STRIPS, 8 IN.
		-02		OFF-RD OPERATIONS, 2L. 2W, MORE THAN 15' (4.5 m) AWAY
		- 05		OFF-RO OPERATIONS, 2L, 2W, (15') 4.5 M TO 24" (600mm) FROM PAVEMENT EDGE
		-04		OFF-RD MOVING OPERATIONS, 2L, 2W, DAY ONLY OFF-RD OPERATIONS, MULTILANE, 15' (4.5m) TO 24" (600 mm) FROM PAVEMENT EDGE
		-04 -02		OFF-RD OPERATIONS, MULTILANE, MORE THAN 15' (4.5m) AWAY
		- 04		LANE CLOSURE, 2L, 2W, DAY ONLY, FOR SPEEDS >= 45 MPH
		-03		LANE CLOSURE, 2L, 2W, NIGHT ONLY FOR SPEEDS >= 45 MPH
		- 04		LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS LANE CLOSURE, 2L, 2W, SLOW MOVING OPERATIONS DAY ONLY, FOR SPEEDS >= 45 MPH
		- 03 - 03		LANE CLOSURE 2L, 2W MOVING OPERATIONS DAY ONLY
		-04		LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS >= 45 MPH
		-04		LANE CLOSURE. 2L, 2W, WITH RUN-AROUND, FOR SPEEDS >= 45 MPH
		-06		LANE CLOSURE, 2L. 2W, WORK AREAS IN SERIES, FOR SPEEDS >= 45 MPH LANE CLOSURE, MULTILANE, DAY OPERATIONS ONLY FOR SPEEDS >= 45 MPH TO 55 MPH
		-06		LANE CLOSURE, MULTILANE, DAT OPERATIONS ONLY FOR SPEEDS 2= 45 MPH TO 55 MPH LANE CLOSURE, MULTILANE, FOR SPEEDS 2= 45 MPH TO 55 MPH
		-06 -06		LANE CLOSURE, MULTILANE, INTERMITTENT OR MOVING OPER., FOR SPEEDS >= 45 MPH
		-06		URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
		-09		URBAN LANE CLOSURE, MULTILANE INTERSECTION
		- 03 - 07		TRAFFIC CONTROL DEVICES TEMPORARY CONCRETE BARRIER
		-01		SIGN PANEL MOUNTING DETAILS
		-04	720006	SIGN PANEL ERECTION DETAILS
		-03		MAST ARM MOUNTED STREET NAME SIGNS
		-01		TELESCOPING STEEL SIGN SUPPORT BASE FOR TELESCOPING STEEL SIGN SUPPORT
		-04		TYPICAL PAVEMENT MARKINGS
		-01	805001	ELECTRICAL SERVICE INSTALLATION DETAILS
		-02		HANDHOLES ,
	•	. 02		DOUBLE HANDHOLES STANDARD PHASE DESIGNATION DIAGRAMS AND PHASE SEQUENCES
		-01		UNINTERRUPTABLE POWER SUPPLY (UPS)
		-02	873001	TRAFFIC SIGNAL GROUNDING & BONDING
		- 05		STEEL MAST ARM ASSEMBLY AND POLE 16' THROUGH 55'
		- 02		SEETL MAST ARM ASSEMBLY AND POLE 56' THROUGH 75' CONCRETE FOUNDATION DETAILS
		- 09 - 01		SPAN WIRE MOUNTED SIGNALS AND FLASHING BEACON INSTALLATION
		-01	880006	TRAFFIC SIGNAL MOUNTING DETAILS
		-01	886001	DETECTOR LOOP INSTALLATIONS

R	o	V	
	-		٠

6117	FILE NAME -	USER NAME * HECHTER	DESIGNED -	REVISED -	STATE OF ILLINOIS	INDEX OF SHEETS &	F.A.P. SECTION	COUNTY TOTAL SH
-2813,	expU.S. Services Inc.	PLOT SCALE > #SCALE*	DRAWN - RJS CHECKED - BRH	REVISED -	DEPARTMENT OF TRANSPORTATION	HIGHWAY STANDARDS	305 27R-2	MCHENRY 673
SUDMISS EASTH & ENVIRONMENT - DIERGY SHOULTHAN - MERASTRUCTURE - SUSTAINABLITY	PLOT DATE = #CATES	DATE - 11/01/13	REVISED -	U.S. ROUTE 14	SCALE: N.T.S. SHEET NO. OF SHEETS STA. TO STA.	FED. ROAD DIST. NO. 1 HLINOIS FED. A	CONTRACT NO. 622	