

RESURFACING SCHEDULE

LOCATION		LENGTH	HOT-MIX ASPHALT SURFACE REMOVAL, 1 1/2"	HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"	BITUMINOUS MATERIALS (PRIME COAT)	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N70	LEVELING BINDER (MACHINE METHOD), IL-9.5FG, N70	HOT-MIX ASPHALT SHOULDERS	HOT-MIX ASPHALT SHOULDERS, 8"	AGGREGATE WEDGE SHOULDER, TYPE B	STRIP REFLECTIVE CRACK CONTROL TREATMENT
STA.	TO STA.	FOOT	SQ YD	SQ YD	POUNDS	TON	TON	TON	SQ YD	TON	FOOT
941+10.00	TO 943+56.00	246.0		710.7	479.7	59.7	29.8				492
943+56.00	TO 945+10.00	154.0		684.4	300.3	57.5	28.7				616
945+10.00	TO 949+35.00	425.0	1227.8		828.8	103.2	51.6			26.3	850
949+35.00	TO 1042+84.00	9349.0	27008.4		18230.6	2268.9	1134.4			346.4	18698
1042+84.00	TO 1053+40.00	1056.0	3050.7		2059.2	256.3	128.2		352.0	39.2	2112
1053+40.00	TO 1061+75.00	835.0	2412.3		1628.3	202.7	101.4			31.0	1670
1061+75.00	TO 1073+47.00	1172.0	3385.8		2285.4	284.5	142.3		390.7	43.5	2344
1073+47.00	TO 1097+86.00	2439.0	7046.1		4756.1	591.9	296.0			90.4	4878
1097+86.00	TO 1106+92.00	906.0	2617.4		1766.7	219.9	110.0		302.0	33.6	1812
STATION EQUATION: STA. 1106+92.0 (AHEAD) = STA. 1104+28.9 (BACK)											
1104+28.90	TO 1111+74.00	745.1	2152.6		1452.9	180.9	90.5		248.3	27.6	1490
1111+74.00	TO 1112+75.00	101.0	291.8		197	24.6	12.3			3.8	202
1112+75.00	TO 1116+91.00	416.0	1386.7		936	101	50.5		23.2	7.8	832
1116+91.00	TO 1116+98.50	7.5	25.0		16.9	1.9			0.5	0.2	15
BRIDGE OMISSION (SN 014-0078)											
1116+98.50	TO 1121+11.50	413.0									
1121+11.50	TO 1121+19.00	7.5	25.0		16.9	1.9			0.5	0.2	15
1121+19.00	TO 1124+75.00	356.0	1186.7		801	86.4	43.2		19.8	6.6	712
1124+75.00	TO 1132+60.00	785.0	2267.8		1530.8	190.5	95.3			29.1	1570
1132+60.00	TO 1134+99.00	239.0	690.5		466.1	58.1	29.0			8.9	478
1134+99.00	TO 1135+90.00	91.0	313.5		211.6	26.4	13.2				
1135+90.00	TO 1138+30.00	240.0	693.4		468	58.3	29.1			8.9	480
1138+30.00	TO 1141+06.50	276.5	798.8		539.2	67.1	33.5			10.3	553
1141+06.50	TO 1141+14.00	7.5	21.7		14.6	1.9				0.2	15
TOTAL		20004	56602	1395.1	38986.1	4843.6	2419	44	1293	714	39834

PATCHING SCHEDULE

LOCATION	EB OR WB	LENGTH	WIDTH	PAVEMENT PATCHING,		
				TYPE II, 14 INCH	TYPE III, 14 INCH	TYPE IV, 14 INCH
STATION		FOOT	FOOT	SQ YD	SQ YD	SQ YD
953+67	EB	6	13	8.7		
954+67	EB	10	13	14.5		
955+20	EB	40	13			57.7
956+94	EB	30	13			43.3
967+39	EB	10	13	14.5		
967+39	WB	10	13	14.5		
970+72	EB	6	13	8.7		
981+39	EB	12	13		17.3	
1001+24	EB	20	13			28.8
1014+97	WB	12	13		17.3	
1016+92	WB	6	13	8.7		
1025+26	EB	20	6	13.4		
1029+38	EB	60	6			40
1038+15	EB	20	6	13.4		
1092+37	WB	20	13			28.8
STATION EQUATION: STA. 1106+92.0 (AHEAD) = STA. 1104+28.9 (BACK)						
1117+44	EB	12	13		17.3	
1117+44	WB	12	13		17.3	
SUBTOTAL				96.4	69.2	198.6
ANTICIPATED FAILURES (±15%)				14.6	10.8	30.4
TOTAL				111	80	229