

MIXTURE REQUIREMENTS SHALL BE PREPARED AS DIRECTED BELOW:

MAINLINE SURFACE COURSE

Location (s):	Hot-Mix Asphalt Surface Course
Mixture Use(s):	Polymerized Hot-Mix Asphalt Surface Course, Mtx D, N90
AC/PG:	SBS PG76-22
RAP % (Max):	0
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-9.5 mm or IL 12.5mm
Friction Aggregate:	D Surface

PATCHING SPECS

Location (s):	Class D Patching
Mixture Use(s):	Hot-Mix Asphalt Binder Course, N90, IL-19.0
AC/PG:	PG64-22
RAP % (Max):	10
Design Air Voids:	4.0 %, 90 Gyration Design
Mixture Composition: (Gradation Mixture)	IL-19.0
Friction Aggregate:	None

STRUCTURE INFORMATION SCHEDULE

STRUCTURE NO.	STATION	INV. RATING	OPR. RATING	SUFF. RATING
SN 028-0084	45+65.88	27.6	46.0	93.6
SN 028-7024	52+45	0.0	0.0	99.8
SN 028-7025	66+29	0.0	0.0	99.8

SN 028-0084 MTD ALLOWANCE: A LOADED MTD IS ALLOWED OVER THIS STRUCTURE.
 SN 028-7024 MTD ALLOWANCE: ONLY AN EMPTIED MTD IS ALLOWED OVER THIS STRUCTURE.
 SN 028-7025 MTD ALLOWANCE: ONLY AN EMPTIED MTD IS ALLOWED OVER THIS STRUCTURE.