

MATCHLINE STA. 628+00

MATCHLINE STA. 643+00

FOREST PRESERVE ENTRANCE

PROP. THERMO. PVT. MARKING (WHITE) - 12"
LONGITUDINAL CROSSWALK - RT. 45° 6'
DIAGONAL LINE @ 2' APART - (TYP.)

PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"
PROP. POLYMERIZED LEVELING BINDER
(MACHINE METHOD), IL-4.75, N50, 3/4"
PROP. HOT-MIX ASPHALT SURFACE COURSE,
MIX "D", N70, 1 1/2"

IL. 68 (DUNDEE RD.)

DOE RD.

PAVEMENT MARKING KEY NOTE LEGEND:

- (A) PROP. THERMO. PVT. MARKING (YELLOW) - 4"
SOLID CENTERLINE (2 LINES @ 11" C-C) - (TYP.)
- (B) PROP. THERMO. PVT. MARKING (YELLOW) - 4"
SOLID EDGELINE - (TYP.)
- (C) PROP. THERMO. PVT. MARKING (YELLOW) - 4"
SKIP-DASH CENTERLINE (10' LINE - 30' SPACE) - (TYP.)
- (D) PROP. THERMO. PVT. MARKING (YELLOW) - 4"
SOLID NO PASSING ZONE LINE (5-1/2" C-C FROM SKIP-DASH) - (TYP.)
- (E) PROP. THERMO. PVT. MARKING (WHITE) - 4"
SOLID EDGELINE - (TYP.)
- (F) PROP. THERMO. PVT. MARKING (WHITE) - 4"
SKIP-DASH LANE LINE (10' LINE - 30' SPACE) - (TYP.)
- (G) PROP. THERMO. PVT. MARKING (YELLOW) - 4"
TWO-WAY LEFT TURN LANE LINE (2 LINES @ 5-1/2" C-C) - (TYP.)
- (H) PROP. THERMO. PVT. MARKING (WHITE) - 6"
SOLID TURN LANE LINE - (TYP.)
- (I) PROP. THERMO. PVT. MARKING (WHITE) - 6"
SKIP-DASH TURN LANE LINE (2' LINE - 6' SPACE) - (TYP.)
- (J) PROP. THERMO. PVT. MARKING (WHITE) - 6"
SOLID PEDESTRIAN CROSSWALK - (TYP.)
- (K) PROP. THERMO. PVT. MARKING (WHITE) - 8"
SOLID CHANNELIZATION LINE - (TYP.)
- (L) PROP. THERMO. PVT. MARKING (YELLOW) - 12"
SOLID PAINTED MEDIAN DIAGONAL LINE - RT. 45°
DIAGONAL @ 75' C-C - (TYP.)
- (LI) PROP. THERMO. PVT. MARKING (WHITE) - 12"
SOLID SHOULDER DIAGONAL LINE - RT. 45°
DIAGONAL @ 75' C-C - (TYP.)
- (M) PROP. THERMO. PVT. MARKING (YELLOW) - 12"
SOLID PAINTED MEDIAN DIAGONAL LINE - RT. 45°
DIAGONAL @ 150' C-C - (TYP.)
- (MI) PROP. THERMO. PVT. MARKING (WHITE) - 12"
SOLID SHOULDER DIAGONAL LINE - RT. 45°
DIAGONAL @ 150' C-C - (TYP.)
- (N) PROP. THERMO. PVT. MARKING (WHITE) - 12"
SOLID CHANNELIZATION LINE - RT. 45°
CHEVRON @ 20' C-C - (TYP.)
- (O) PROP. THERMO. PVT. MARKING (YELLOW) - 12"
SOLID PAINTED MEDIAN DIAGONAL LINE - RT. 45°
DIAGONAL 5 EQUALLY SPACED
- (P) PROP. THERMO. PVT. MARKING (WHITE) - 24"
SOLID STOP BAR - (TYP.)
- (Q) PROP. THERMO. PVT. MARKING (WHITE)
LETTERS AND SYMBOLS - (TYP.)

IL. 68 (DUNDEE RD.)

MATCHLINE STA. 643+00

MATCHLINE STA. 658+00

N. ARBOR RD.

N. CRABTREE DR.

PORTAGE AVE.

PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2 1/4"
PROP. POLYMERIZED LEVELING BINDER
(MACHINE METHOD), IL-4.75, N50, 3/4"
PROP. HOT-MIX ASPHALT SURFACE COURSE,
MIX "D", N70, 1 1/2"

FILE NAME =	USER NAME = steedp	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	ROADWAY AND PAVEMENT MARKING PLANS				F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
c:\pw\work\p\dot\stedp\0293334\0127	12-shr-plan.dgn	DRAWN -	REVISED -		F.A.P. 343/ IL 68 (DUNDEE RD.)-IL 59 (HAWTHORNE RD.) TO US 12				343	(70 & 3045)RS-2	COOK	57	23
	PLOT SCALE = 100.0000 1" = 100'	CHECKED -	REVISED -		SCALE: 1"=50'				SHEET OF SHEETS STA. 628+00 TO STA. 658+00				
	PLOT DATE = 6/13/2014	DATE -	REVISED -		CONTRACT NO. 60T02				ILLINOIS FED. AID PROJECT				