

MATCHLINE STA. 748+00

MATCHLINE STA. 762+00

PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2 3/4"  
PROP. POLYMERIZED LEVELING BINDER  
(MACHINE METHOD), IL-4.75, N50, 3/4"  
PROP. POLYMERIZED HOT-MIX ASPHALT SURFACE  
COURSE, STONE MATRIX ASPHALT, N80, 2"

IL. RTE 68 (DUNDEE RD.)

PEPPER TREE DR.

N. KING EDWARD CT.

PAVEMENT MARKING KEY NOTE LEGEND:

- (A) PROP. THERMO. PVT. MARKING (YELLOW) - 4"  
SOLID CENTERLINE (2 LINES @ 11" C-C) - (TYP.)
- (B) PROP. THERMO. PVT. MARKING (YELLOW) - 4"  
SOLID EDGELINE - (TYP.)
- (C) PROP. THERMO. PVT. MARKING (YELLOW) - 4"  
SKIP-DASH CENTERLINE (10' LINE - 30' SPACE) - (TYP.)
- (D) PROP. THERMO. PVT. MARKING (YELLOW) - 4"  
SOLID NO PASSING ZONE LINE (5-1/2" C-C FROM SKIP-DASH) - (TYP.)
- (E) PROP. THERMO. PVT. MARKING (WHITE) - 4"  
SOLID EDGELINE - (TYP.)
- (F) PROP. THERMO. PVT. MARKING (WHITE) - 4"  
SKIP-DASH LANE LINE (10' LINE - 30' SPACE) - (TYP.)
- (G) PROP. THERMO. PVT. MARKING (YELLOW) - 4"  
TWO-WAY LEFT TURN LANE LINE (2 LINES @ 5-1/2" C-C) - (TYP.)
- (H) PROP. THERMO. PVT. MARKING (WHITE) - 6"  
SOLID TURN LANE LINE - (TYP.)
- (I) PROP. THERMO. PVT. MARKING (WHITE) - 6"  
SKIP-DASH TURN LANE LINE (2' LINE - 6' SPACE) - (TYP.)
- (J) PROP. THERMO. PVT. MARKING (WHITE) - 6"  
SOLID PEDESTRIAN CROSSWALK - (TYP.)
- (K) PROP. THERMO. PVT. MARKING (WHITE) - 8"  
SOLID CHANNELIZATION LINE - (TYP.)
- (L) PROP. THERMO. PVT. MARKING (YELLOW) - 12"  
SOLID PAINTED MEDIAN DIAGONAL LINE - RT.  
45° DIAGONAL @ 75' C-C - (TYP.)
- (LI) PROP. THERMO. PVT. MARKING (WHITE) - 12"  
SOLID SHOULDER DIAGONAL LINE - RT. 45°  
DIAGONAL @ 75' C-C - (TYP.)
- (M) PROP. THERMO. PVT. MARKING (YELLOW) - 12"  
SOLID PAINTED MEDIAN DIAGONAL LINE - RT.  
45° DIAGONAL @ 150' C-C - (TYP.)
- (MI) PROP. THERMO. PVT. MARKING (WHITE) - 12"  
SOLID SHOULDER DIAGONAL LINE - RT. 45°  
DIAGONAL @ 150' C-C - (TYP.)
- (N) PROP. THERMO. PVT. MARKING (WHITE) - 12"  
SOLID CHANNELIZATION LINE - RT. 45°  
CHEVRON @ 20' C-C - (TYP.)
- (O) PROP. THERMO. PVT. MARKING (YELLOW) - 12"  
SOLID PAINTED MEDIAN DIAGONAL LINE - RT.  
45° DIAGONAL 5 EQUALLY SPACED
- (P) PROP. THERMO. PVT. MARKING (WHITE) - 24"  
SOLID STOP BAR - (TYP.)
- (Q) PROP. THERMO. PVT. MARKING (WHITE)  
LETTERS AND SYMBOLS - (TYP.)

IL. RTE 68 (DUNDEE RD.)

N. OAK ST.

PROP. HOT-MIX ASPHALT SURFACE REMOVAL, 2 3/4"  
PROP. POLYMERIZED LEVELING BINDER  
(MACHINE METHOD), IL-4.75, N50, 3/4"  
PROP. POLYMERIZED HOT-MIX ASPHALT SURFACE  
COURSE, STONE MATRIX ASPHALT, N80, 2"

MATCHLINE STA. 762+00

MATCHLINE STA. 777+00



FILE NAME =	USER NAME = steedpa	DESIGNED -	REVISED -	<b>STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION</b>	<b>ROADWAY AND PAVEMENT MARKING PLANS</b>			F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
as\pw\work\p\dot\stedpa\d8293334\0127	12-sh1-plan.dgn	DRAWN -	REVISED -		F.A.P. 343/ IL 68 (DUNDEE RD.)--IL 59 (HAWTHORNE RD.) TO US 12			343	(70 & 3045)RS-2	COOK	57	27
	PLOT SCALE = 100.0000' / in.	CHECKED -	REVISED -		SCALE: 1"=50'			SHEET OF SHEETS STA. 748+00 TO STA. 777+00		CONTRACT NO. 60T02		
	PLOT DATE = 8/12/2014	DATE -	REVISED -		ILLINOIS FED. AID PROJECT							