

SCHEDULE OF QUANTITIES

HOT-MIX ASPHALT (SHEET 3 OF 3)

LOCATION	DIRECTION	STATION	TO	STATION	WIDTH OF INSIDE SHOULDER (FOOT)	WIDTH OF OUTSIDE SHOULDER (FOOT)	THICKNESS (INCHES)	(A) LENGTH (FOOT)	(B) WIDTH (FOOT)	(C) AREA (SQ YD)	BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	HOT-MIX ASPHALT SHOULDERS 8" 48203029 (SQ YD)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)
NW RAMP:	RT.	11+00.00		11+56.00		3.0	2.5	56.00	3.0	18.7	1.9		2.6
	RT.	11+00.00		11+56.00		2.0	2.0	56.00	2.0	12.4	1.2		1.4
	RT.	11+56.00		17+36.00		6.0	2.5	580.00	6.0	386.7	38.7		54.1
	RT.	11+56.00		17+36.00		2.0	2.0	580.00	2.0	128.9	12.9		14.4
	RT.	17+36.00		17+51.00		6.0	2.125	15.00	6.0	10.0	1.0		1.2
	RT.	17+36.00		17+51.00		2.0	1.8125	15.00	2.0	3.3	0.3		0.3
	RT.	17+51.00		25+82.40		6.0	1.75	831.40	6.0	554.3	55.4		54.3
	RT.	17+51.00		25+24.50		2.0	1.625	773.50	2.0	171.9	17.2		15.6
	RT.	25+17		OUTLET		2.0	0.875	20.00	2.0	4.4	0.4		0.2
	LT.	11+29.00		16+49.00		4.0	2.5	520.00	4.0	231.1	23.1		32.4
	LT.	15+26.00		16+49.00		2.0	2.0	123.00	2.0	27.3	2.7		3.1
	LT.	17+51.00		19+54.00		4.5	1.75	203.00	4.5	101.5	10.2		9.9
SW RAMP:	RT.	10+00.00		15+27.00		6.0	1.75	527.00	6.0	351.3	35.1		34.4
	RT.	11+75.00		15+27.00		2.0	1.625	352.00	2.0	78.2	7.8		7.1
	RT.	15+27.00		15+42.00		6.0	2.125	15.00	6.0	10.0	1.0		1.2
	RT.	15+27.00		16+18.00		2.0	1.8125	91.00	2.0	20.2	2.0		2.1
	RT.	15+42.00		22+43.00		6.0	2.5	701.00	6.0	467.3	46.7		65.4
	LT.	15+27.00		15+42.00		5.0	2.125	15.00	5.0	8.3	0.8		1.0
	LT.	15+42.00		16+62.00		8.0	2.5	120.00	8.0	106.7	10.7		14.9
SE RAMP:	RT.	11+39.00		17+59.00		6.0	2.5	620.00	6.0	413.3	41.3		57.9
	RT.	17+59.00		17+74.00		6.0	2.125	15.00	6.0	10.0	1.0		1.2
	RT.	17+74.00		28+53.77		6.0	1.75	1079.77	6.0	719.8	72.0		70.5
	LT.	10+96.00		17+55.00		4.0	2.5	659.00	4.0	292.9	29.3		41.0
NE RAMP:	LT.	17+55.00		17+74.00		12.5	2.125	19.00	12.5	26.4	2.6		3.1
	RT.	10+00.00		16+55.00		8.0	1.75	655.00	8.0	582.2	58.2		57.1
	RT.	16+55.00		16+80.00		5.5	2.125	25.00	5.5	15.3	1.5		1.8
	RT.	16+80.00		17+20.00		4.75	2.5	40.00	4.75	21.1	2.1		3.0
	RT.	17+20.00		21+86.00		2.0	2.0	466.00	2.0	103.6	10.4		11.6
	LT.	15+30.00		16+55.00		4.0	1.75	125.00	4.0	55.6	5.6		5.4
	LT.	16+55.00		16+92.00		6.0	1.75	37.00	6.0	24.7	2.5		2.4
	LT.	16+92.00		17+07.00		5.5	1.75	15.00	5.5	9.2	0.9		0.9
LT.	17+07.00		21+86.00		2.0	2.0	479.00	2.0	106.4	10.6		11.9	
SUB-TOTAL =											536.6	0.0	624.6
FROM HMA PAVING SCHEDULE:											13188.3		
TOTAL =											15063.7	5217.3	1422.7
ROUND TO:											15070.0	5220.0	1430.0

HOT-MIX ASPHALT & SHOULDER SUMMARY

LOCATION:	BITUMINOUS MATERIALS (PRIME COAT) 40600100 (GALLON)	AGGREGATE (PRIME COAT) 40600300 (TON)	POLYMERIZED LEVEL BINDER MACHINE METHOD, IL-9.5, FG, N90 40600909 (TON)	POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "E", N90 40603570 (TON)	HOT-MIX ASPHALT SHOULDERS, 8" 48203029 (SQ YD)	HOT-MIX ASPHALT SHOULDERS 48203100 (TON)
LEG "A":	6,538.2	57.1	2,000.2	3200.1	4,814.4	335.3
LEG "C":	5,929.2	54.2	1,894.9	3,031.7	402.9	462.9
SW RAMP:	566.4	4.3	121.3	181.9		167.0
NW RAMP:	623.0	4.7	128.3	192.4		189.6
NE RAMP:	696.5	5.9	169.3	254.0		94.1
SE RAMP:	710.6	5.6	158.1	237.1		173.7
TOTAL =	15,063.9	131.8	4,472.1	7,097.2	5,217.3	1,422.6
ROUND TO	15,070.0	135.0	4,480.0	7,100.0	5,220.0	1,430.0