

Girder 1				
Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. A but.	2599+33.00	-20.33	387.54	387.54
CL Brg. S. Abut.	2599+34.25	-20.33	387.53	387.53
A	2599+44.25	-20.33	387.53	387.56
B	2599+54.25	-20.33	387.52	387.57
C	2599+64.25	-20.33	387.51	387.57
D	2599+74.25	-20.33	387.51	387.57
E	2599+84.25	-20.33	387.50	387.55
F	2599+94.25	-20.33	387.49	387.52
G	2600+04.25	-20.33	387.49	387.50
H	2600+14.25	-20.33	387.48	387.48
CL Pier 1	2600+21.00	-20.33	387.48	387.48
I	2600+31.00	-20.33	387.47	387.48
J	2600+41.00	-20.33	387.46	387.50
K	2600+51.00	-20.33	387.46	387.53
L	2600+61.00	-20.33	387.45	387.55
M	2600+71.00	-20.33	387.44	387.56
N	2600+81.00	-20.33	387.44	387.56
O	2600+91.00	-20.33	387.43	387.54
P	2601+01.00	-20.33	387.42	387.52
Q	2601+11.00	-20.33	387.42	387.48
R	2601+21.00	-20.33	387.41	387.45
S	2601+31.00	-20.33	387.40	387.42
CL Pier 2	2601+44.00	-20.33	387.40	387.40
T	2601+54.00	-20.33	387.39	387.40
U	2601+64.00	-20.33	387.38	387.41
V	2601+74.00	-20.33	387.38	387.43
W	2601+84.00	-20.33	387.37	387.45
X	2601+94.00	-20.33	387.36	387.47
Y	2602+04.00	-20.33	387.36	387.47
Z	2602+14.00	-20.33	387.35	387.47
AA	2602+24.00	-20.33	387.34	387.44
BB	2602+34.00	-20.33	387.34	387.41
CC	2602+44.00	-20.33	387.33	387.38
DD	2602+54.00	-20.33	387.32	387.34
CL Pier 3	2602+67.00	-20.33	387.31	387.31
EE	2602+77.00	-20.33	387.31	387.31
FF	2602+87.00	-20.33	387.30	387.32
GG	2602+97.00	-20.33	387.29	387.33
HH	2603+07.00	-20.33	387.29	387.34
II	2603+17.00	-20.33	387.28	387.34
JJ	2603+27.00	-20.33	387.28	387.33
KK	2603+37.00	-20.33	387.27	387.31
LL	2603+47.00	-20.33	387.26	387.28
CL Brg. N. Abut.	2603+53.75	-20.33	387.26	387.26
Bk. N. A but.	2603+55.00	-20.33	387.26	387.26

Girder 2				
Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. A but.	2599+33.00	-13.00	387.69	387.69
CL Brg. S. Abut.	2599+34.25	-13.00	387.69	387.69
A	2599+44.25	-13.00	387.68	387.71
B	2599+54.25	-13.00	387.67	387.72
C	2599+64.25	-13.00	387.67	387.73
D	2599+74.25	-13.00	387.66	387.72
E	2599+84.25	-13.00	387.65	387.70
F	2599+94.25	-13.00	387.65	387.68
G	2600+04.25	-13.00	387.64	387.65
H	2600+14.25	-13.00	387.63	387.63
CL Pier 1	2600+21.00	-13.00	387.63	387.63
I	2600+31.00	-13.00	387.62	387.64
J	2600+41.00	-13.00	387.62	387.66
K	2600+51.00	-13.00	387.61	387.68
L	2600+61.00	-13.00	387.60	387.70
M	2600+71.00	-13.00	387.60	387.71
N	2600+81.00	-13.00	387.59	387.71
O	2600+91.00	-13.00	387.58	387.70
P	2601+01.00	-13.00	387.58	387.67
Q	2601+11.00	-13.00	387.57	387.64
R	2601+21.00	-13.00	387.56	387.60
S	2601+31.00	-13.00	387.56	387.57
CL Pier 2	2601+44.00	-13.00	387.55	387.55
T	2601+54.00	-13.00	387.54	387.55
U	2601+64.00	-13.00	387.54	387.57
V	2601+74.00	-13.00	387.53	387.59
W	2601+84.00	-13.00	387.52	387.61
X	2601+94.00	-13.00	387.52	387.62
Y	2602+04.00	-13.00	387.51	387.63
Z	2602+14.00	-13.00	387.50	387.62
AA	2602+24.00	-13.00	387.50	387.60
BB	2602+34.00	-13.00	387.49	387.57
CC	2602+44.00	-13.00	387.48	387.53
DD	2602+54.00	-13.00	387.48	387.50
CL Pier 3	2602+67.00	-13.00	387.47	387.47
EE	2602+77.00	-13.00	387.46	387.46
FF	2602+87.00	-13.00	387.45	387.47
GG	2602+97.00	-13.00	387.45	387.48
HH	2603+07.00	-13.00	387.44	387.49
II	2603+17.00	-13.00	387.43	387.49
JJ	2603+27.00	-13.00	387.43	387.48
KK	2603+37.00	-13.00	387.42	387.46
LL	2603+47.00	-13.00	387.41	387.43
CL Brg. N. Abut.	2603+53.75	-13.00	387.41	387.41
Bk. N. A but.	2603+55.00	-13.00	387.41	387.41

Girder 3				
Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. A but.	2599+33.00	-5.67	387.81	387.81
CL Brg. S. Abut.	2599+34.25	-5.67	387.81	387.81
A	2599+44.25	-5.67	387.80	387.83
B	2599+54.25	-5.67	387.79	387.84
C	2599+64.25	-5.67	387.79	387.85
D	2599+74.25	-5.67	387.78	387.84
E	2599+84.25	-5.67	387.77	387.82
F	2599+94.25	-5.67	387.77	387.80
G	2600+04.25	-5.67	387.76	387.77
H	2600+14.25	-5.67	387.75	387.75
CL Pier 1	2600+21.00	-5.67	387.75	387.75
I	2600+31.00	-5.67	387.74	387.76
J	2600+41.00	-5.67	387.74	387.78
K	2600+51.00	-5.67	387.73	387.80
L	2600+61.00	-5.67	387.72	387.82
M	2600+71.00	-5.67	387.72	387.83
N	2600+81.00	-5.67	387.71	387.83
O	2600+91.00	-5.67	387.70	387.82
P	2601+01.00	-5.67	387.70	387.79
Q	2601+11.00	-5.67	387.69	387.76
R	2601+21.00	-5.67	387.68	387.72
S	2601+31.00	-5.67	387.68	387.69
CL Pier 2	2601+44.00	-5.67	387.67	387.67
T	2601+54.00	-5.67	387.66	387.67
U	2601+64.00	-5.67	387.66	387.69
V	2601+74.00	-5.67	387.65	387.71
W	2601+84.00	-5.67	387.64	387.73
X	2601+94.00	-5.67	387.64	387.74
Y	2602+04.00	-5.67	387.63	387.75
Z	2602+14.00	-5.67	387.62	387.74
AA	2602+24.00	-5.67	387.62	387.72
BB	2602+34.00	-5.67	387.61	387.69
CC	2602+44.00	-5.67	387.60	387.65
DD	2602+54.00	-5.67	387.60	387.62
CL Pier 3	2602+67.00	-5.67	387.59	387.59
EE	2602+77.00	-5.67	387.58	387.58
FF	2602+87.00	-5.67	387.57	387.59
GG	2602+97.00	-5.67	387.57	387.60
HH	2603+07.00	-5.67	387.56	387.61
II	2603+17.00	-5.67	387.55	387.61
JJ	2603+27.00	-5.67	387.55	387.60
KK	2603+37.00	-5.67	387.54	387.58
LL	2603+47.00	-5.67	387.53	387.55
CL Brg. N. Abut.	2603+53.75	-5.67	387.53	387.53
Bk. N. A but.	2603+55.00	-5.67	387.53	387.53