

Girder 6				
Location	Station	Offset	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
Bk. S. Abut.	2599+33.00	16.33	387.62	387.62
CL Brg. S. Abut.	2599+34.25	16.33	387.62	387.62
A	2599+44.25	16.33	387.61	387.64
B	2599+54.25	16.33	387.60	387.65
C	2599+64.25	16.33	387.60	387.66
D	2599+74.25	16.33	387.59	387.65
E	2599+84.25	16.33	387.58	387.63
F	2599+94.25	16.33	387.58	387.61
G	2600+04.25	16.33	387.57	387.58
H	2600+14.25	16.33	387.56	387.56
CL Pier 1	2600+21.00	16.33	387.56	387.56
I	2600+31.00	16.33	387.55	387.57
J	2600+41.00	16.33	387.55	387.59
K	2600+51.00	16.33	387.54	387.61
L	2600+61.00	16.33	387.53	387.63
M	2600+71.00	16.33	387.53	387.64
N	2600+81.00	16.33	387.52	387.64
O	2600+91.00	16.33	387.51	387.63
P	2601+01.00	16.33	387.51	387.60
Q	2601+11.00	16.33	387.50	387.57
R	2601+21.00	16.33	387.49	387.53
S	2601+31.00	16.33	387.49	387.50
CL Pier 2	2601+44.00	16.33	387.48	387.48
T	2601+54.00	16.33	387.47	387.48
U	2601+64.00	16.33	387.47	387.50
V	2601+74.00	16.33	387.46	387.52
W	2601+84.00	16.33	387.45	387.54
X	2601+94.00	16.33	387.45	387.55
Y	2602+04.00	16.33	387.44	387.56
Z	2602+14.00	16.33	387.43	387.55
AA	2602+24.00	16.33	387.43	387.53
BB	2602+34.00	16.33	387.42	387.50
CC	2602+44.00	16.33	387.41	387.46
DD	2602+54.00	16.33	387.41	387.43
CL Pier 3	2602+67.00	16.33	387.40	387.40
EE	2602+77.00	16.33	387.39	387.39
FF	2602+87.00	16.33	387.38	387.40
GG	2602+97.00	16.33	387.38	387.41
HH	2603+07.00	16.33	387.37	387.42
II	2603+17.00	16.33	387.37	387.43
JJ	2603+27.00	16.33	387.36	387.42
KK	2603+37.00	16.33	387.35	387.39
LL	2603+47.00	16.33	387.35	387.36
CL Brg. N. Abut.	2603+53.75	16.33	387.34	387.34
Bk. N. Abut.	2603+55.00	16.33	387.34	387.34