

INDEX OF SHEETS

STATE STANDARDS

GENERAL NOTES

1	COVER SHEET	000001-05
2	INDEX OF SHEETS, LIST OF ILLINOIS DOT HIGHWAY STANDARDS, GENERAL NOTES, COMMITMENTS	001001-02 001006
3-7	SUMMARY OF QUANTITIES	420001-07
8	TYPICAL SECTIONS	420401-08
9-12	SCHEDULE OF QUANTITIES	421001-02 424001-05 442201-03
13-14	HORIZONTAL AND VERTICAL CONTROL	515001-03
15	PLAN I-94	601001-03
16	PLAN AND PROFILE (ELSTON AVE)	604051-03
16A.	GRADING PLAN	606001-04
17-30	MAINTENANCE OF TRAFFIC	630001-08 635001-01 635006-03
31-34	DETOUR PLANS	635011-02
35	DRAINAGE PLANS	637001-04
36-39	DETAILS	642001-01
40-43	PAVEMENT MARKING PLANS	701301-03
*44-50	TRAFFIC SIGNAL PLANS	701311-03
50A-50C	LIGHTING PLANS	701400-04 701401-05 701406-05 701411-06
74-76	TRAFFIC SURVEILLANCE PLAN	
77-118	STRUCTURE PLANS	701456
119	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (BD-22)	701701-06
120	CITY OF CHICAGO CATCH BASIN, INLET AND MANHOLE DETAILS (BD 47)	701801-04
121	LIGHT POLE, FOUNDATION INTEGRAL WITH DOUBLE FACE BARRIER WALL (BE322)	701901-01 704001-06
122	LIGHT POLE, FOUNDATION ON CONCRETE PARAPET WALL 11.5" BOLT CIRCLE	720001-01 720006-02
123	PIER/ABUTMENT MOUNTED UNDERPASS LUMINAIRE INSTALLATION DETAILS (BE902)	780001-02 781001-03
124-127	REMOVE AND REERECT GUARDRAIL (BM21)	
128	ENTRANCE AND EXIT CLOSURE RAMP DETAILS (TC08)	
129	FREEWAY SINGLE AND MULTI LANE WEAVE (TC09)	
130	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS (TC-10)	
131-132	MULTI-LANE FREEWAY PAVEMENT MARKING (TC12)	
133	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TC-14)	
134	TRAFFIC CONTROL FOR SHOULDER CLOSURES AND PARTIAL RAMP CLOSURES (TC17)	
135	TYPICAL MARKING FOR CLOSING STATE HIGHWAYS (TC21)	
136	ARTERIAL ROAD INFORMATION SIGNS (TC-22)	
137-138	CITY OF CHICAGO TYPICAL PAVEMENT MARKINGS (TC24)	
139	DRIVEWAY ENTRANCE SIGNING (TC26)	

STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
AREAS OF REINFORCEMENT BARS
DECIMAL OF AN INCH AND OF A FOOT
PAVEMENT JOINTS
BRIDGE APPROACH PAVEMENT CONNECTOR
BAR REINFORCEMENT FOR CRC PAVEMENT
CURB RAMPS FOR SIDEWALKS
CLASS C AND D PATCHES
NAME PLATE FOR BRIDGES
SUB-SURFACE DRAINS
FRAME AND GRATE, TYPE 11
CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
STEEL PLATE BEAM GUARDRAIL
DELINEATORS
REFLECTOR AND TERMINAL MARKER PLACEMENT
REFLECTOR MARKER AND MOUNTING DETAILS
CONCRETE BARRIER 815 MM (32 IN.) HEIGHT
SHOULDER RUMBLE STRIPS
LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
LANE CLOSURE, 2L, 2W, MOVING OPERATIONS - DAY ONLY
APPROACH TO LANE CLOSURE, FREEWAY/EXPRESSWAY
LANE CLOSURE, FREEWAY/EXPRESSWAY
LANE CLOSURE, FREEWAY/EXPRESSWAY, DAY OPERATIONS ONLY
LANE CLOSURE, MULTILANE, AT ENTRANCE OR EXIT RAMP, FOR SPEEDS > 45 MPH
PARTIAL EXIT RAMP CLOSURE FREEWAY/EXPRESSWAY
URBAN LANE CLOSURE, MULTILANE INTERSECTION
LANE CLOSURE, MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
TRAFFIC CONTROL DEVICES
TEMPORARY CONCRETE BARRIER
SIGN PANEL MOUNTING DETAILS
SIGN PANEL ERECTION DETAILS
TYPICAL PAVEMENT MARKINGS
TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS

10 ft (3 m) TRANSITIONS SHALL BE USED TO MATCH PROPOSED ITEMS OF WORK TO EXISTING ITEMS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEM OF WORK SPECIFIED.

WHERE ARTIFICIAL LIGHTING IS UTILIZED IN NIGHT OPERATIONS, THE CONTRACTOR SHALL EXERCISE THE UTMOST PRECAUTIONS IN PREVENTING ADVERSE VISIBILITY TO THE MOTORING PUBLIC AND ADJOINING RESIDENTIAL AREAS.

THE ENGINEER SHALL BE THE SOLE JUDGE CONCERNING CURING TIME FOR THE VARIOUS BITUMINOUS LIFTS.

FOR STABILIZATION, ALL TYPE III BARRICADES SHALL REQUIRE A MINIMUM OF FOUR SANDBAGS PER BARRICADE.

STORM SEWER WATER MAIN IS TO BE USED AT LOCATIONS WHERE LATERAL SEPARATION BETWEEN THE SEWER AND WATER MAIN IS LESS THAN 10 ft (3.0 m) AND THE WATER MAIN INVERT IS LESS THAN 1.5 ft (0.45 m) ABOVE THE STORM SEWER CROWN.

STORM SEWER, RUBBER GASKET IS TO BE USED AT LOCATIONS WHERE THE WATER MAIN CROSSES BELOW THE SEWER, REGARDLESS OF VERTICAL SEPARATION OR WHERE THE BOTTOM OF THE WATER MAIN IS LESS THAN 1.5 ft (0.45 m) ABOVE THE TOP OF THE SEWER.

THE BITUMINOUS MATERIAL PRIME COAT QUANTITIES HAVE BEEN DETERMINED USING A RATE OF 0.44 gal/yd² (2.0 L/m²).

THE RESIDENT ENGINEER SHALL CONTACT THE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO THE PLACEMENT OF ANY TEMPORARY TRAFFIC CONTROL DEVICES.

ANY SIGNS, PAVEMENT MARKINGS OR REFLECTORS DAMAGED DURING CONSTRUCTION BY THE CONTRACTOR NOT INCLUDED FOR REPLACEMENT IN THE PLANS SHALL BE REPLACED IN KIND BY THE CONTRACTOR AND NO COMPENSATION WILL BE ALLOWED.

COMMITMENTS

THIS PROJECT HAS BEEN SIGNED OFF IN-HOUSE FOR SPECIAL WASTE. IF THE PROPOSED SCOPE OF WORK CHANGES OR IF ADDITIONAL ROW/TEMPORARY EASEMENTS ARE REQUIRED, PLEASE CONTACT THE ENVIRONMENTAL STUDIES UNIT AT EXTENSION 4101 TO DISCUSS ANY POTENTIAL IMPACTS.

SPECIAL WASTE

THE PROPOSED SCOPE OF WORK INCLUDES EXCAVATION AND DISPOSAL OF BACKFILL MATERIAL FROM BEHIND THE EXISTING BRIDGE ABUTMENTS OF S.N. 016-0610

EXCAVATED MATERIAL IS LOCATED WITHIN EXISTING ROADWAY LIMITS AND SHALL BE DISPOSED OF WITHIN IDOT RIGHT-OF-WAY AT THE LOCATION SHOWN ON THE PLANS.

THIS PROJECT HAS BEEN SIGNED OFF IN-HOUSE FOR SPECIAL WASTE. IF THE PROPOSED SCOPE OF WORK CHANGES OR IF ADDITIONAL ROW/TEMPORARY EASEMENTS ARE REQUIRED, PLEASE CONTACT THE ENVIRONMENTAL STUDIES UNIT AT EXTENSION 4101 TO DISCUSS ANY POTENTIAL IMPACTS.

COST OF GRADING AND COMPACTING EXCAVATED MATERIAL IS INCLUDED IN THE COST OF STRUCTURE EXCAVATION. SEE STRUCTURE PLANS.

Rev. 9-2-10

FILE NAME =	USER NAME = #USER#	DESIGNED -	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	INDEX OF SHEETS, IDOT HIGHWAY STANDARDS, GENERAL NOTES & COMMITMENTS	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
#FILE#		DRAWN -	REVISED -			94	0101.8B	COOK	139	2	
		CHECKED -	REVISED -			CONTRACT NO. 60C18					
		DATE -	REVISED -			ILLINOIS FED. AID PROJECT					
		PLOT SCALE = #SCALE#			SCALE:	SHEET NO.	OF	SHEETS	STA.	TO STA.	