

PORTLAND CEMENT CONCRETE
SIDEWALK, 5 INCH

LOCATION	QUANTITY
STATION	(SQ FT)
98+41 TO 99+76 RT	690
100+66 TO 102+23 RT	775
98+00 TO 99+64 LT	815
100+24 TO 101+00 LT	380
TOTAL	2660

SIDEWALK REMOVAL

LOCATION		QUANTITY
STATION	OFFSET	(SQ FT)
98+41 TO 99+76	RT	643
100+37 TO 102+23	RT	903
98+00 TO 99+62	LT	778
100+24 TO 101+00	LT	363
TOTAL		2687

STORM SEWER REMOVAL 24"

LOCATION		QUANTITY
STATION	OFFSET	(FOOT)
99+38 TO 99+68	LT	30
TOTAL		30

DETECTABLE WARNINGS

LOCATION		QUANTITY
STATION	OFFSET	(SQ FT)
98+45	RT	15
TOTAL		15

APPROACH SLAB REMOVAL

LOCATION		QUANTITY
STATION	(SQ YD)	
99+40.21 TO 99+70.95		183
100+28.89 TO 100+61.18		191
TOTAL		374

FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)

LOCATION		QUANTITY
STATION	OFFSET	(EACH)
98+06.78	17.3 RT	1
98+07.03	17.7 LT	1
98+14.43	0.4 RT	1
98+56.72	33.4 RT	1
98+69.31	47.3 RT	1
98+79.15	32.6 LT	1
99+33.96	19.1 RT	1
99+38.03	18.5 LT	1
100+64.26	34.0 RT	1
100+68.39	0.5 RT	1
100+69.00	34.8 LT	1
101+93.34	33.4 LT	1
101+94.54	33.5 RT	1
102+07.00	37.8 LT	1
TOTAL		14

PAVEMENT REMOVAL

LOCATION	QUANTITY
STATION	(SQ YD)
97+76.50 TO 99+45.25	1196
100+58.09 TO 102+22.50	1166
TOTAL	2362

MEDIAN REMOVAL

LOCATION		QUANTITY
STATION	(SQ FT)	
99+45.29 TO 99+70.95		344
100+28.89 TO 100+61.18		374
101+92.32 TO 102+74.75		228
TOTAL		946

HOT-MIX ASPHALT SURFACE REMOVAL, 2"

LOCATION	QUANTITY
STATION	(SQ YD)
102+22.50 TO 102+72.44	342
TOTAL	342

HOT-MIX ASPHALT SHOULDERS, 6"

LOCATION		QUANTITY
STATION	OFFSET	(SQ. YD.)
98+47 TO 99+75	RT	27
94+95 TO 98+00	LT	98
100+37 TO 102+01	RT	37
101+00 TO 102+73	LT	53
TOTAL		215

COMBINATION CONCRETE CURB
AND GUTTER, TYPE B-6.24

LOCATION		QUANTITY
STATION	OFFSET	(FOOT)
97+76.43 TO 99+44.66	RT	168
97+76.58 TO 98+00.00	LT	23
100+66.11 TO 102+22.48	RT	156
101+00.00 TO 102+22.52	LT	123
TOTAL		470

DRIVEWAY PAVEMENT REMOVAL

LOCATION	QUANTITY
STATION	(SQ. YD.)
COMMERCIAL ENTRANCE	58
98+05.15 TO 98+52.69	
TOTAL	58

STORM SEWERS, CLASS A, TYPE 2, 24"

LOCATION		QUANTITY
STATION	OFFSET	(FOOT)
99+38 TO 99+68	LT	30
TOTAL		30

STEEL PLATE BEAM GUARD RAIL, TYPE A, 6 FOOT POSTS

LOCATION		QUANTITY
STATION	OFFSET	(FOOT)
95+69.59 TO 97+56.85	LT	187.5
99+04.16 TO 99+16.66	RT	12.5
101+09.80 TO 101+22.30	RT	12.5
101+43.15 TO 101+93.05	LT	50.0
TOTAL		262.5

COMBINATION CURB AND
GUTTER REMOVAL

LOCATION		QUANTITY
STATION	OFFSET	(FOOT)
97+76.50 TO 99+39.94	LT	164
97+76.50 TO 99+45.45	RT	169
100+24.98 TO 102+22.50	LT	198
100+61.74 TO 102+22.50	RT	161
TOTAL		692