

# GENERAL NOTES


5. THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

MIXTURE USE	POLY SURFACE	LEVEL BINDER	POLY BINDER	SHOULDERS	INCIDENTAL SURF
AC/PG	SBS PG 76-22	PG 64-22	SBS PG 76-22	PG 64-22	PG 64-22
RAP % (MAX)	0%	10%	10%	30%	10%
DESIGN AIR Voids	4.0% @ Ndes=80	4.0% @ Ndes=90	4.0% @ Ndes=90	2.0% @ Ndes=30	4.0% @ Ndes=90
MIX COMPOSITION (GRADATION MIXTURE)		IL 9.5	IL 19.0		
FRICION AGGREGATE	SMA	MIXTURE "C"	MIXTURE "B"	BAM	MIXTURE "C"


TOP LIFT SHOULDERS - DESIGN THIS MIX AT 2.0% VOIDS AND ADD ASPHALT TO REDUCE VOIDS TO 1.5%.

PLAN QUANTITIES FOR BITUMINOUS CONCRETE SURFACE COURSE ITEMS ARE CALCULATED USING A UNIT WEIGHT OF 112 LB/SQ YD/IN (59.8 KG/SQ M/25 mm THICKNESS).

## WESTBOUND WORK SCHEDULE



## EASTBOUND WORK SCHEDULE



26. IT IS THE CONTRACTOR'S OPTION TO USE THE MATERIAL TRANSFER DEVICE (MTD) ON ANY LIFT. THE PAY ITEM FOR THE MTD WILL NOT BE INCLUDED IN THIS CONTRACT.

*Rev. Sheet 8-31-09*

\* 60-(7,8,9,10)RS, 60-(8,9,10)BR

